

Industrial Ethernet

Let's connect.

Version 2021



Weidmüller 

Orange Selection

Quick and easy planning

As a planning engineer, do you want to select products easily and receive them quickly? From a partner you can rely on? Then plan with the Orange Selection from Weidmüller in the future. The Orange Selection items are always available, carefully selected and the portfolio consists of more than 1,500 items to fully cover your standard needs.

If your order is placed before 3:00 pm, we guarantee that your order will be on its way the very next working day.

For even more efficient planning and production processes, we will of course provide all articles in digital form. CAD, ETIM and eClass data are available in our online product catalogue catalog.weidmueller.com

We have summarised all the advantages of the Orange Selection on our website.

Check it out: www.weidmueller.com/orange-selection



Dear Customers,

The PDF versions of our catalogues offer practical additional functions, helping you to find your way around our product range and simplifying the ordering process.

In addition to the catalogue, the PDF also contains:

- Internal page links
- Links to the online catalogue

Try it out for yourself. Click the order number to obtain more detailed information and close-up images via your web browser. The links in the PDF file also enable you to go directly to the next desired catalogue page.

Further Weidmüller product catalogues can be accessed by clicking the following:



Industrial Ethernet – Active components

Catalogue 9

A

Active components

Introduction – Active components

B

Unmanaged Switches

C

Managed Switches

D

Industrial Security Router

E

u-link Remote Access Service

F

Media converter and protocol gateways

G

IoT-Gateways

H

Industrial WLAN

I

Accessories – Active components

Industrial Ethernet – Passive components

Catalogue 9

Passive components

Introduction – Passive components

Single Pair Ethernet

IP20 plug-in connectors and mounting rail outlets

FrontCom® IP65 service interfaces

IP67 plug-in connectors

IP65 connection components / FreeCon connecting components

Contactless Transmission

Copper cabling solutions

Fibre-optic cabling solutions

Accessories – Passive components

Appendix

Service and support

Index

Search according to type or order number

Active components

An overview of our portfolio

Unmanaged Switches

Fast Ethernet, Fast / Gigabit Ethernet, Gigabit Ethernet
Page B.4, B.11



Managed Power over Ethernet Switches

Gigabit Ethernet
Page C.13



Media interface modules for modular switches

Fast Ethernet, Gigabit Ethernet, 10-Gigabit Ethernet
Page C.20



Ethernet media converters (copper/fiber-optic)

Page F.4



Unmanaged Power over Ethernet

Switches / Injectors – Fast Ethernet, Gigabit Ethernet
Page B.9, B.14



Managed Switches IEC 61850-3

Fast / Gigabit Ethernet, Gigabit Ethernet
Page C.14



Industrial Security Routers

Page D.4



Serial / Ethernet converters and Modbus TCP / RTU gateway

Page F.5



Managed Switches

Fast Ethernet, Fast / Gigabit Ethernet, Gigabit Ethernet
Page C.4



Modular Managed Switches IEC 61850-3

Fast Ethernet, Gigabit Ethernet, 10-Gigabit Ethernet
Page C.18



u-link Remote Access Service

Page E.6



IoT-Gateways

Page G.4



Active components

An overview of our portfolio

Industrial WLAN

Page H.4



SFP transceiver

Fast Ethernet, Gigabit Ethernet, 10-Gigabit Ethernet

Page I.4



Configuration backup and restore module

Page I.8



Mounting kits for 19" rack and wall

Page I.10



Passive components

An overview of our portfolio

Single Pair Ethernet

Page K.2



IP65 service interface FrontCom®

Page M.2



IP65 FreeCon Active PROFINET

Page O.9



IP20 plug-in connectors

Page L.5



IP67 plug-in connectors

Page N.2



IP65 Contactless Power Transmission FreeCon Contactless Power

Page P.2



IP20 mounting rail outlets

Page L.13



IP65 connection components / connectivity components FreeCon

Page O.2



Cabling solutions

An overview of our portfolio

Installation cables

Page Q.6



Connecting cables

Page Q.8



Dragline cables

Page Q.14



RJ45 patch cables

Page Q.18



System cables assembled

Page Q.30



FO connecting cables

Page R.4



FO patch cables

Page R.5



FO system cables

Page R.11



Passive components

Accessories from a single source

Cable connector

Page S.3



Tools Copper cabling

Page S.4



Tools Fibre-optic cabling

Page S.10



General tools

Page S.16



Protective caps

Page S.24



Cabtite®

Page S.18



Inkjet printer

Page S.25



Cable Bender

Page S.23



Markers

Page S.27




Intended use for Industrial Ethernet

A complete range of products for industrial communications infrastructure

The trend to network industrial plant components using Ethernet protocols was already apparent several years ago. Ethernet communication is now well established in all market segments; including automotive, general machine construction, process industry, transportation, energy and even Maritime. The requirements of these differ in terms of protocols, environmental conditions, certifications and standards. As well as being a leading provider of industrial connection and network products, Weidmüller embraces solutions for these differing requirements with a comprehensive and highquality product range of active and passive components for Ethernet communications.

The basic requirements of these industrial markets are high reliability, availability and safeguarding against failure. These are met by extremely high MTBF times of our network components. Using Weidmüller's high-quality STEADYTEC® connector system means that maximum reliability and simple operation is ensured. Indeed, Weidmüller's network components create a complete communications infrastructure for industrial applications in machine construction, process and plant engineering and energy.





Automotive

The automotive manufacturers of AIDA (Automation Initiative of the German Automotive Industry) are the drivers behind the use of the Industrial Ethernet in manufacturing. Extremely harsh environmental conditions place high demands on the components used: Cabling must be torsion-resistant and there are increased EMC requirements for connectors and active devices. For these areas of application, Weidmüller offers a complete product range consisting of copper and fibre optic connectors that are designed to meet the special needs of robot cabling.



Machinery & Plant Engineering

Machinery has to stand out from the competition with special services and a stronger customer focus. This results in a dynamic change in machinery and plant construction, demanding greater economic efficiency, quality, flexibility and performance from machines. The networking of machine segments and plant parts and their connection to higher-level office networks is playing an increasingly important role in this. Our products are perfectly adapted to these requirements and offer not only robustness and reliability, but are also easy to configure.



Ships

The shipbuilding industry is also experiencing disruptive market development in the face of rapidly advancing technological developments. Autonomous shipping, sustainability, networking, digitalisation concepts and advanced data analytics are the key topics in this respect. To meet the requirements of this industry, the various products in our portfolio include variants with a marine approval according to DNV GL



Transmission & Distribution

The energy market is booming – especially in the field of renewable energies. The products used here must often be able to withstand harsh environmental conditions. To ensure that power grids function reliably and stably, intelligent solutions are being integrated more and more in order to minimise downtimes and to reduce maintenance work. This requires uninterrupted communication. We support the energy sector with reliable components that are approved according to IEC 61850-3 and IEEE 1613 standards.



Process industry

In large-scale process plants, fibre optic media are often used for communication over long distances. However, for reliable data transmission in the field, the components used must be protected from harmful environmental influences. These include high temperature fluctuations, vibrations, dust exposure and electromagnetic influences. Our active and passive Ethernet components have ATEX approval and can reliably withstand these influences.

Active components

Introduction

Active components

Introduction - Active components

A.2

Transfer data between devices in the network flexibly and reliably

Active Industrial Ethernet – the perfect solution for countless applications

A


The Industrial Ethernet has proved itself in many areas of automation. With its high performance and flexibility, it opens up a multitude of design options for the network infrastructure. Our Industrial Ethernet components are the perfect connection solution for data communication between Ethernet-capable devices in industrial automation. They have various features and approvals, which is why they are ideally suited to many industrial applications.

As a complete supplier of industrial network infrastructures, we are active in machinery and plant engineering, shipbuilding, the process industry and energy, including traditional/renewable power generation, as well as transmission and distribution.

Our broad product range includes a variety of products with a wide range of approvals for individual requirements. These include Fast/Gigabit switches (unmanaged/managed including Power over Ethernet variants), routers, WLAN devices, IoT gateways, media converters and protocol gateways, as well as u-link, our remote maintenance solution. All our Ethernet components meet the highest demands and enable reliable, flexible Ethernet communication.

Thanks to the highly differentiated Eco, Basic, Value, Advanced, Premium and SubstationLine product lines, our switches are suitable for meeting a wide range of requirements. This allows us to guarantee optimal data transmission at all times – from simple communication structures to the complex data meshes of extensive systems.

As an ideal complement to this, we offer you a comprehensive passive product portfolio of RJ45 and fibre optic connectors and cables. This makes Weidmüller your perfect partner for Industrial Ethernet solutions.





Always the best choice for your requirements

Our switch product lines for all-round application-oriented solutions

A

Ethernet networks must allow the exchange of data packets between specific participants. For this purpose, the participants are connected to each other via Ethernet switches. Ethernet switches thus collect all data streams and distribute them to the respective participants to enable communication to take place. Since Ethernet switches have to meet very different requirements depending on the area of application, we offer a variety of product lines. They differ in terms of their properties, special features and technical highlights.



EcoLine:

Our unmanaged EcoLine switches are characterised by a rich variety of different models and high economic efficiency. They can be used in a uniquely wide temperature range of -40 to +75 °C, which enables them to be operated both inside production plants and in the field. The robust devices have 5 to 24 ports as well as a redundant voltage input. Their SFP ports allow especially flexible use, regardless of the available communication media and/or the required distance. Power over Ethernet switches are also available within the EcoLine in order to reduce the required cabling work.



BasicLine:

The BasicLine series consists of an extensive range of unmanaged plug and play switches. All devices were developed for use in harsh industrial environments and have numerous international approvals, such as cULus, Class I, Div. 2, ATEX and DNV/GL. This makes them ideal for use in many different industries. The devices are available with Fast Ethernet and Gigabit Ethernet ports. In addition, the series also includes individual variants with Power over Ethernet ports.



ValueLine:

Our ValueLine series features unmanaged and managed switches available with Fast Ethernet and Gigabit Ethernet ports. Our ValueLine managed switches support various industrial communication protocols, e.g. MODBUS/TCP, PROFINET/RT and ETHERNET/IP. This enables optimal integration into the most common automation networks. They also support a variety of helpful management functions, such as port mirroring and error messaging via e-mail or relay. All of these functions can be set up with ease via the web-based management interface. ValueLine switches also have numerous international approvals to ensure proper operation in a variety of industries (cULus, Class I Div. 2 / ATEX Zone 2, DNV GL).



AdvancedLine:

The managed switches of our AdvancedLine are characterised by a wide assortment of variants and economic efficiency. The different model variants designed for Fast Ethernet and Gigabit as well as integrating 5 to 24 ports and SFP slots ensure a high degree of flexibility. Their especially wide temperature range of -40 to +75 °C allows them to be used both in production plants and in the field. All switches in the series can be intuitively configured via a browser-based web interface. The comprehensive management tool can be used to set up various redundancy, monitoring, traffic filtering and security functions. The AdvancedLine ranges from full-managed switches for demanding applications to lite-managed switches for simpler requirements within a network and offers an excellent price-performance ratio. Power over Ethernet switches are also available in the AdvancedLine in order to reduce cabling work.



PremiumLine:

The managed switches of our PremiumLine are true high-end products. They are especially suitable for ambitious network solutions with high data volumes. The devices are available in a wide variety of versions. For example, customers can select the number of ports, transmission rate (Fast/Gigabit Ethernet) and connection variant. PremiumLine switches support various industrial application protocols, e.g. MODBUS/TCP, PROFINET RT and ETHERNET / IP. They also have numerous international approvals, such as cULus, Class I Div.2 / ATEX Zone 2 and DNV GL, making them a perfect choice for many different industries and applications.



SubstationLine:

The SubstationLine comprises managed Ethernet switches that comply with the IEC 61850-3 standard, making them robust enough for operation in harsh environments. All switches include a redundant power supply, and the series also includes variants with Fast Ethernet, Gigabit, all the way up to 10 Gigabit Ethernet, as well as sophisticated features like PTPv2 time synchronisation. All devices were designed for use in substations and other energy (T&D) systems, where electromagnetic interference is higher than in other industries.

Unmanaged Switches

Overview

Unmanaged Switches	
Introduction – Unmanaged Switches	B.2
Unmanaged Switches Fast Ethernet	B.4
Unmanaged Power over Ethernet Switches Fast Ethernet	B.9
Unmanaged Switches Fast/Gigabit Ethernet	B.11
Unmanaged Switches Gigabit Ethernet	B.12
Unmanaged Power over Ethernet Switches Gigabit Ethernet	B.14
Power over Ethernet Injector Gigabit Ethernet	B.16

The proven standard for active network components

Unmanaged switches – adaptable and economical

B
Unmanaged switches require no configuration and are nevertheless adaptable. They use basic standardised protocols, such as autonegotiation, autocrossing and flow control, allowing them to adapt automatically to widely varying transmission speeds or connector assignments. In addition, the switches are protocol-transparent. Each port of a switch forms its own collision domain. All switches support the use of twisted pair cabling with RJ45 interface or fibre optic cable based on the interfaces specified in IEEE 802.3.

Our unmanaged switches are the simple and economical standard start-up solution for the Industrial Ethernet. We offer different versions with different features. In addition to the unmanaged switches of the EcoLine, BasicLine and ValueLine, we can also offer you Power over Ethernet variants within all lines that can significantly reduce your wiring work. This means you can also operate Ethernet devices in areas that are difficult to access – without a separate power supply cable.

Your special advantage:

- Wide variety of ports in terms of number and features to meet individual requirements
- Fast Ethernet and Gigabit versions available, including Power over Ethernet variants
- Rapid fault diagnosis thanks to the clearly visible LED display
- Robust housing for reliable long-term use in different environments



See chapter A for details about the product lines



Variety of versions

Variety of port numbers and media types for a wide range of applications (up to 24 ports)

**Variety of models**

Numerous international approvals, such as cULus, KC, EAC, Class 1 Div. 2 / ATEX Zone 2 and DNV GL

Design advantage

Space-saving design for high economic efficiency

**Variety of models**

Fast Ethernet | Gigabit and Power over Ethernet versions

Unmanaged Switches Fast Ethernet – EcoLine

5 and 8-Port unmanaged Fast Ethernet Switches

- Suitable for use in harsh industrial environment thanks to rugged design and wide operating temperature range of -40°C up to 75°C



Technical data

Technology			Physical characteristics		
Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX and 100BASE-FX IEEE 802.3x for flow control		Weight	IE-SW-EL05-5TX: 205 g IE-SW-EL08-8TX: 334 g IE-SW-EL08-6TX-2SC: 328 g IE-SW-EL08-6TX-2SCS: 328 g	
Processing type	Store and Forward		Environmental conditions		
Flow control	IEEE 802.3x flow control		Operating temperature	-40 to 75 °C (-40 to 167 °F)	
Switch characteristics			Storage temperature	-40 to 85 °C (40 to 185 °F)	
MAC table size	1K		Humidity	5 to 95 % (non-condensing)	
Packet buffer Size	448 Kbit		Operating altitude	≤ 2000 m	
Interfaces			EMC conformity and approvals		
RJ45 ports	10/100BASE-T(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port		EMC	EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz bis 1 Ghz: 3 V/m IEC 61000-4-4 EFT: Power: 0.5 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 0.5 kV; Signal: 1 kV IEC 61000-4-6 CS: 3 Vrms	
Fibre optic ports	100BASE-FX (SC-Duplex connector)		Safety	UL 61010-1, UL 61010-2-201	
Fibre optic transceiver characteristics			Shock	IEC 60068-2-27	
Transmission rate	100 Mbps		Vibration	IEC 60068-2-6	
Connector type	SC-Duplex		Free fall	IEC 60068-2-31	
Transceiver type	Multimode	Singlemode	MTBF		
Fiber cable type	50/125 µm 62.5/125 µm	9/125 µm	Time	IE-SW-EL05-5TX: 2,638,236 hrs IE-SW-EL08-8TX: 1,390,019 hrs IE-SW-EL08-6TX-2SC: 595,597 hrs IE-SW-EL08-6TX-2SCS: 609,551 hrs	
Transmission distance, typical	2 km	30 km	Database	Telcordia SR332	
Wavelength, typical	1310 nm		Guarantee		
Optical power RX range	-31 to 0 dBm	-34 to 0 dBm	Time interval	5 years	
Optical power TX range	-23.5 to -14 dBm	-15 to -8 dBm	Ordering Information		
Link-budget	7.5 dB	19 dB	Version	Model Type	Order No.
Power supply			5x RJ45 10/100 Mbit/s	IE-SW-EL05-5TX	2682130000
Connection type	IE-SW-EL05-5TX: 1 removable 4-pin terminal block IE-SW-EL08-8TX: 1 removable 4-pin terminal block IE-SW-EL08-6TX-2SC: 1 removable 3-pin terminal block IE-SW-EL08-6TX-2SCS: 1 removable 3-pin terminal block		8x RJ45 10/100 Mbit/s	IE-SW-EL08-8TX	2682140000
Input voltage	IE-SW-EL05-5TX: 24 V DC (12 - 48 V), 24 V AC (18 - 36 V), 2 redundant inputs IE-SW-EL08-8TX: 24 V DC (12 - 48 V), 24 V AC (18 - 36 V), 2 redundant inputs IE-SW-EL08-6TX-2SC: 24 V DC (10 - 30 V DC), 1 single input IE-SW-EL08-6TX-2SCS: 24 V DC (10 - 30 V DC), 1 single input		6x RJ45 10/100 Mbit/s, 2x SC Multimode 100 Mbit/s	IE-SW-EL08-6TX-2SC	2682170000
Current consumption at 24 V	IE-SW-EL05-5TX: 0.1 A IE-SW-EL08-8TX: 0.14 A IE-SW-EL08-6TX-2SC: 0.14 A IE-SW-EL08-6TX-2SCS: 0.14 A		6x RJ45 10/100/Mbit/s, 2x SC Singlemode 100 Mbit/s	IE-SW-EL08-6TX-2SCS	2682180000
Overload current protection	yes		Accessories		
Reverse polarity protection	yes		19" Rack Mounting Kit	RM-KIT	1241440000
Physical characteristics					
Housing main material	Metal				
Protection degree	IP30				
Type of mounting	DIN rail				
Dimensions (W x H x D)	IE-SW-EL05-5TX: 26.1 x 95 x 70 mm (1.03 x 3.74 x 2.76 in) IE-SW-EL08-8TX: 41 x 95 x 90 mm (1.61 x 3.74 x 3.54 in) IE-SW-EL08-6TX-2SC: 41 x 115 x 84 mm (1.61 x 4.52 x 3.31 in) IE-SW-EL08-6TX-2SCS: 41 x 115 x 84 mm (1.61 x 4.52 x 3.31 in)				

16 and 24-Port unmanaged Fast Ethernet Switches

- Suitable for use in harsh industrial environment thanks to rugged design and wide operating temperature range of -40°C up to 75°C
- Reliable operation due to redundant voltage inputs, fault relay and LED diagnostics
- SFP-ports for fiber optic transmission over long distances

**Technical data****Technology**

Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX and 100BASE-FX IEEE 802.3x for flow control
Processing type	Store and Forward
Flow control	IEEE 802.3x flow control
Switch characteristics	
MAC table size	IE-SW-EL16-14TX-2FESFP: 4K IE-SW-EL16-16TX: 8K IE-SW-EL24-24TX: 8K
Packet buffer Size	IE-SW-EL16-14TX-2FESFP: 2.75 Mbit IE-SW-EL16-16TX: 1 Mbit IE-SW-EL24-24TX: 1 Mbit

Interfaces

RJ45 ports	10/100BASE-T(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port
Fibre optic ports	100BaseSFP-slot
Relay Contact	1 relay output with a current capacity of 1 A at 24 V DC
Power supply	
Connection type	1 removable 6-pin terminal block
Input voltage	24 V DC (12 - 48 V), 2 redundant inputs
Current consumption at 24 V	IE-SW-EL16-14TX-2FESFP: 0.34 A IE-SW-EL16-16TX: 0.27 A IE-SW-EL24-24TX: 0.39 A
Overload current protection	yes
Reverse polarity protection	yes

Physical characteristics

Housing main material	Metal
Protection degree	IP30
Type of mounting	DIN rail
Dimensions (W x H x D)	IE-SW-EL16-14TX-2FESFP: 74 x 170 x 140 mm (2.91 x 6.69 x 5.51 in) IE-SW-EL16-16TX: 74.3 x 153.6 x 107.5 mm (2.93 x 6.05 x 4.2 in) IE-SW-EL24-24TX: 96.4 x 154 x 108.5 mm (3.8 x 6.06 x 4.27 in)
Weight	IE-SW-EL16-14TX-2FESFP: 931 g IE-SW-EL16-16TX: 931 g IE-SW-EL24-24TX: 1056 g

Environmental conditions

Operating temperature	-40 to 75 °C (-40 to 167 °F)
Storage temperature	-40 to 85 °C (-40 to 185 °F)
Humidity	5 to 95 % (non-condensing)
Operating altitude	≤ 2000 m
EMC conformity and approvals	
EMC	EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz bis 1 Ghz: 3 V/m IEC 61000-4-4 EFT: Power: 0.5 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 0.5 kV; Signal: 1 kV IEC 61000-4-6 CS: 3 Vrms
Safety	UL 61010-1, UL 61010-2-201
Shock	IEC 60068-2-27
Vibration	IEC 60068-2-6

EMC conformity and approvals

Free fall IEC 60068-2-31

MTBF

Time IIE-SW-EL16-14TX-2FESFP: 719,800 hrs
IE-SW-EL16-16TX: 1,160,204 hrs
IE-SW-EL24-24TX: 959,803 hrs

Database Telcordia SR332

Guarantee

Type interval 5 years

Ordering Information

Version	Model Type	Order No.
14x RJ45 10/100 Mbit/s, 2x SFP 100 Mbit/s	IE-SW-EL16-14TX-2FESFP	2682160000
16x RJ45 10/100 Mbit/s	IE-SW-EL16-16TX	2682150000
24x RJ45 10/100 Mbit/s	IE-SW-EL24-24TX	2682190000

Accessories

	Model Type	Order No.
19" Rack Mounting Kit	RM-KIT	1241440000

Note

Corresponding SFP modules for EcoLine switches, see page I.4.

Unmanaged Switches Fast Ethernet – BasicLine

5 and 8-Port unmanaged Fast Ethernet Switches

- Two redundant voltage inputs 12/24/48 V DC (9.6 to 60 V DC)
- IP30 aluminium housing
- Rugged hardware design well suited for hazardous locations (Class I Div. 2 / ATEX Zone 2) and maritime environments (DNV-GL)
- -40°C to 75°C operating temperature range (T models)



Technical data

Technology		
Standards		IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT (X) and 100BaseFX IEEE 802.3x for Flow Control
Processing Type		Store and Forward
Flow Control		IEEE 802.3x flow control, back pressure flow control
Switch Properties		
MAC Table Size		IE-SW-BL05-Series: 1K IE-SW-BL08-Series: 2K
Packet Buffer Size		IE-SW-BL05-Series: 384 kbit IE-SW-BL08-Series: 768 kbit
Interface		
Fibre Ports		100BaseFX (SC/ST-duplex connection)
RJ45 Ports		10/100BaseT(X) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection
DIP Switches		Enable/Disable broadcast storm protection
Specification optical fiber		
Transceiver Type		
100Base FX		
Multi-Mode		
Fiber Cable Type	OM1	50/125 µm
		800 MHz·km
G.652		
Typical Distance		4 km 5 km 40 km
Wave-length	Typical (nm)	1300 1310
	TX Range (nm)	1260 to 1360 1280 to 1340
	RX Range (nm)	1100 to 1600 1100 to 1600
Optical Power	TX Range (dBm)	-10 to -20 0 to -5
	RX Range (dBm)	-3 to -32 3 to -34
	Link-Budget (dB)	12 29
Dispersion Penalty (dB)		3 1
Note: When connecting a single-mode fiber transceiver over a short distance, we recommend using an attenuator to prevent the transceiver from being damaged by excessive optical power.		
Power Requirements		
Input Voltage		12/24/48 V DC (9.6 to 60 V DC), two redundant inputs
Input Current		IE-SW-BL05-5TX: 0.09 A at 24 V IE-SW-BL05-4TX-1SC/1ST/1SCS: 0.1 A at 24 V IE-SW-BL08-8TX: 0.11 A at 24 V IE-SW-BL08-6TX-2SC/2ST/2SCS: 0.15 A at 24 V IE-SW-BL08-7TX-1SC: 0.11 A at 24 V
Overload current protection		1.1 A
Connection		1 removable 4-contact terminal block
Reverse Polarity Protection		Present
Physical Characteristics		
Housing		Aluminum, IP30 protection
Dimensions (W x H x D)		IE-SW-BL05-Series: 30 x 115 x 70 mm (1.18 x 4.52 x 2.76 in) IE-SW-BL08-Series: 50 x 114 x 70 mm (1.96 x 4.52 x 2.76 in)
Weight		IE-SW-BL05-5TX: 175 g IE-SW-BL08-8TX: 275 g
Type of mounting		DIN rail, wall (with optional mounting kit)
Environmental Limits		
Operating Temperature		Standard Models: -10 to 60 °C (14 to 140 °F) Wide Temp. Models: -40 to 75 °C (-40 to 167 °F)
Storage Temperature		-40 to 85 °C (-40 to 185 °F)
Ambient Relative Humidity		5 to 95 % (non-condensing)
Regulatory Approvals		
Safety		UL 508

Regulatory Approvals			
Hazardous Location			UL/cUL Class I, Division 2, Groups A, B, C and D; ATEX Zone 2 Ex nA IIC T4 Gc
EMV			EN 55032/24 / CISPR 32 FCC Part 15B Class A IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-8 CS: 10 V IEC 61000-4-8
Maritime			
Shock			DNV-GL (not for 1412110000, 1412120000, 1412070000, 1412080000)
Freefall			IEC 60068-2-32
Vibration			IEC 60068-2-6
MTBF (meantime between failures)			
Time			IE-SW-BL05-Series: 3,040,784 hrs, IE-SW-BL08-Series: 2,701,531 hrs
Database			Telcordia (Bellcore), GB
Warranty			
Warranty Period			5 years
Ordering Information			
Version	Model Type	Operating Temperature	Order No.
5 * RJ45	IE-SW-BL05-5TX IE-SW-BL05T-5TX	-10 to +60 °C -40 to +75 °C	1240840000 1240850000
4 * RJ45, 1 * SC-Multimode	IE-SW-BL05-4TX-1SC IE-SW-BL05T-4TX-1SC	-10 to +60 °C -40 to +75 °C	1240890000 1286550000
4 * RJ45, 1 * ST-Multimode	IE-SW-BL05-4TX-1ST IE-SW-BL05T-4TX-1ST	-10 to +60 °C -40 to +75 °C	1240880000 1286540000
4 * RJ45, 1 * SC-Singlemode	IE-SW-BL05-4TX-1SCS IE-SW-BL05T-4TX-1SCS	-10 to +60 °C -40 to +75 °C	1240870000 1286530000
8 * RJ45	IE-SW-BL08-8TX IE-SW-BL08T-8TX	-10 to +60 °C -40 to +75 °C	1240900000 1286560000
6 * RJ45, 2 * SC-Multimode	IE-SW-BL08-6TX-2SC IE-SW-BL08T-6TX-2SC	-10 to +60 °C -40 to +75 °C	1240910000 1240920000
6 * RJ45, 2 * ST-Multimode	IE-SW-BL08-6TX-2ST IE-SW-BL08T-6TX-2ST	-10 to +60 °C -40 to +75 °C	1240930000 1286570000
6 * RJ45, 2 * SC-Singlemode	IE-SW-BL08-6TX-2SCS IE-SW-BL08T-6TX-2SCS	-10 to +60 °C -40 to +75 °C	1412110000 1412120000
7 * RJ45, 1 * SC-Multimode	IE-SW-BL08-7TX-1SC IE-SW-BL08T-7TX-1SC	-10 to +60 °C -40 to +75 °C	1412070000 1412080000
Accessories			
	Model Type	Order No.	
19" Rack Mounting Kit	RM-KIT	1241440000	
Wall mounting kit for IE-SW-BL05 series	IE-WALLMOUNT-KIT-30M	1504450000	

16-Port unmanaged Fast Ethernet Switches

- Two redundant voltage inputs 12/24/48 V DC (9.6 to 60 V DC)
- Warning of relay output in the event of power failure and port error
- Broadcast storm protection
- -40 °C to 75 °C operating temperature range (T models)

**Technical data**

Technology	
Standards	IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT(X) IEEE 802.3x for Flow Control
Processing Type	Store and Forward
Flow Control	IEEE 802.3x flow control, back pressure flow control
Switch Properties	
MAC Table Size	4K
Packet Buffer Size	1.25 Mbit
Interface	
RJ45 Ports	10/100BaseT(X) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection
DIP Switches	Port fault alarm Broadcast storm protection enable/disable
Alarm Contact	1 relay output with current carrying capacity of 1 A at 24 V DC
Power Requirements	
Input Voltage	12/24/48 V DC (9.6 to 60 V DC), two redundant inputs
Input Current	0.26 A at 24 V
Overload Current Protection	1.6 A
Connection	1 removable 6-pin terminal blocks
Reverse Polarity Protection	Present
Physical Characteristics	
Housing	Metal, IP30 protection
Dimensions (W x H x D)	80.5 x 135 x 105 mm (3.16 x 5.31 x 4.13 in)
Weight	1140 g
Type of mounting	DIN-Rail
Environmental Limits	
Operating Temperature	Standard Models: 0 to 60 °C (32 to 140 °F) Wide Temp. Models: -40 to 75 °C (-40 to 167 °F)
Storage Temperature	-40 to 85 °C (-40 to 185 °F)
Ambient Relative Humidity	5 to 95 % (non-condensing)
Regulatory Approvals	
Safety	UL 508, UL 60950-1, EN 60950-1
Hazardous Location	UL/cUL Class I, Division 2, Groups A, B, C and D; ATEX Zone 2 Ex nA nC IIC T4 Gc
EMC	EN 55032/24 CISPR 32, FCC Part 15B Class A IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8
Maritime	DNV-GL
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-32
Vibration	IEC 60068-2-6

MTBF (mean time between failures)

Time	2,290,506 hrs
Database	Telcordia (Bellcore), GB

Warranty

Warranty Period	5 years
-----------------	---------

Ordering Information

Version	Model Type	Operating Temperature	Order No.
16 * RJ45	IE-SW-VL16-16TX IE-SW-VL16T-16TX	0 to +60 °C -40 to +75 °C	1241000000 1286590000

Accessories

19" Rack Mounting Kit	Model Type	Order No.
RM-KIT		1241440000

5-Port IP67 unmanaged Fast Ethernet Switches

- M12 connection system and IP67 protected housing
- 10/100BaseT (X), 4-pin M12 (D-coded)
- Full/half duplex mode and auto MDI/MDI-X
- Input voltage 12 to 45 V DC, 18 to 30 V AC



B

**Technical data**

Technology	
Standards	IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT (X) IEEE 802.3x for Flow Control
Processing Type	Store and Forward
Flow Control	IEEE 802.3x flow control, back pressure flow control
Switch Properties	
MAC Table Size	2 K
Packet Buffer Size	384 Kbit
Interface	
M12-Ports	10/100BaseT (X) auto negotiation, full/half duplex mode and auto MDI/MDI-X connection, 4-pin, D-coded
Power Requirements	
Input Voltage	24/36 V DC (12 to 45 V DC), 18 to 30 V AC (47 to 63 Hz), one input
Input Current	0.28 A to 24 V AC 0.10 A to 24 V DC 0.08 A to 36 V DC
Overload Current Protection	1.1 A
Connection	1 x M12 socket, A-coded
Reverse Polarity Protection	Present
Physical Characteristics	
Housing	Plastic, IP67 protection, encapsulated
Dimensions (W x H x D)	60 x 125 x 29.6 mm (2.36 x 4.92 x 1.09 Zoll)
Weight	270 g
Type of mounting	Wall mounting, screwed
Environmental Limits	
Operating Temperature	Standard Models: -25 to 60 °C (-13 to 140 °F) Wide Temp. Models: -40 to 75 °C (40 to 167 °F)
Storage Temperature	-40 to 85 °C (-40 to 185 °F)
Ambient Relative Humidity	5 to 95 % (non-condensing)

Regulatory Approvals

Safety	UL 508		
EMC	FCC Part 15B Class A EN 55032 Class A IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8		
Shock	IEC 60068-2-27		
Freefall	IEC 60068-2-32		
Vibration	IEC 60068-2-6		
MTBF (mean time between failures)			
Time	3,451,678 hrs		
Database	Telcordia (Bellcore), GB		
Warranty			
Warranty Period	5 years		
Ordering data			
Version	Model Type	Operating Temperature	Order No.
5 * M12 10/100BaseT(X)	IE-SW-IP67-5M12 IE-SW-IP67T-5M12	-25 to +60 °C -40 to +75 °C	1504410000 1504420000

6 and 8-Port unmanaged PoE+ Fast Ethernet Switches

- IEEE 802.3af/at compliant PoE ports
- Fiber optic ports for communication links over long distances
- Reliable operation due to redundant voltage inputs, fault relay and LED diagnostics

**Technical data**

Technology		
Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX and 100BASE-FX IEEE 802.3x for flow control IEEE 802.3at/af for Power-over-Ethernet	
Processing type	Store and Forward	
Flow control	IEEE 802.3x flow control	
Switch characteristics		
MAC table size	1K	
Packet buffer Size	448 Kbit	
Interfaces		
RJ45 ports	10/100BASE-T(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port	
Fibre optic ports	100BASE-FX (SC-Duplex connector)	
Relay Contact	1 relay output with a current capacity of 1 A at 24 V DC	
DIP switches	2x enabling/disabling power fault alarm via relay	
Fibre optic transceiver characteristics		
Transmission rate	100 Mbps	
Connector type	SC-Duplex	
Transceiver type	Multimode	
Fiber cable type	50/125 µm 62.5/125 µm	
Transmission distance, typical	2 km	
Wavelength, typical	1310 nm	
Optical power RX range	-31 to 0 dBm	
Optical power TX range	-23.5 to -14 dBm	
Link-budget	7.5 dB	
Power supply		
Connection type	1 removable 6-pin terminal block	
Input voltage	IE-SW-EL08-8PoE: 12/24/48 V DC (12 - 57 V), 2 redundant inputs IE-SW-EL06-4PoE-2SC: 24/48 V DC (24 - 57 V), 2 redundant inputs	
Current consumption at 24 V (with PD consumption)	IE-SW-EL06-4PoE-2SC: 2.8 A IE-SW-EL08-8PoE: 5.74 A	
Overload current protection	yes	
Reverse polarity protection	yes	
Power over Ethernet (PoE)		
PoE pin assignment	Mode A: Pin 1, 2 (V+); Pin 3, 6 (V-); Alternative A; MDI	
Total PoE power budget	IE-SW-EL06-4PoE-2SC: 60 W at 24 - 50 V DC; 120 W at 50-57 V DC IE-SW-EL08-8PoE: 60 W at 12 - 23 V DC; 120 W at 24-57 V DC	
Physical characteristics		
Housing main material	Metal	
Protection degree	IP30	
Type of mounting	DIN rail	
Dimensions (W x H x D)	41 x 144.3 x 94.9 mm (1.61 x 5.68 x 3.74 in)	
Weight	IE-SW-EL06-4PoE-2SC: 435 g IE-SW-EL08-8PoE: 580 g	
Environmental conditions		
Operating temperature	-40 to 75 °C (-40 to 167 °F)	
Storage temperature	-40 to 85 °C (-40 to 185 °F)	
Humidity	5 to 95 % (non-condensing)	
Operating altitude	≤ 2000 m	

Unmanaged Power over Ethernet Switches Fast Ethernet - BasicLine

6-Port unmanaged Fast Ethernet PoE+ Switches

- 4x IEEE 802.3af/at konforme PoE-Ports
- Up to 30 watts per PoE port
- 12/24/48 V DC redundant wide-range power supply
- Integrated DC/DC converter can supply 48 V-PoE devices across the entire input voltage range of 12-57 V DC
- Intelligent power consumption detection and classification
- Broadcast Storm Protection

**Technical data**

Technology		Regulatory Approvals	
Standards	IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT(X) IEEE 802.3x for Flow Control IEEE 802.3af for PoE IEEE 802.3at for PoE+	EMC	EN 55032/24 CISPR 32, FCC Part 15B Class A IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8
Processing Type	Store and Forward	Shock	IEC 60068-2-27
Flow Control	IEEE 802.3x flow control, back pressure flow control	Freefall	IEC 60068-2-32
Switch Properties		Vibration	IEC 60068-2-6
MAC table size	2 K	MTBF (mean time between failures)	
Packet buffer size	768 KB	Time	1,398,743 hrs
Interface		Datenbase	Telcordia (Bellcore), GB
RJ45 Ports	10/100BaseT(X) auto negotiation speed, Full/Half duplex mode and auto MDI/MDI-X connection	Warranty	
DIP Switches	Enable/disable broadcast storm protection	Warranty Period	5 years
Power Requirements		Ordering data	
Input Voltage	12/24/48 V DC (12 to 57 V DC), two redundant inputs	Version	Type
Current consumption (with PD consumption)	6.19 A at 12 VDC 5.55 A at 24 VDC 2.71 A at 48 VDC	2 * RJ45 10/100 BaseT(X), 4 * RJ45 10/100 BaseT(X) PoE+	Operating Temperature
Inrush current	64.56 A at 48 VDC (0.1 - 1 ms)	IE-SW-BL06-2TX-4PoE	-10 to +60 °C
Power loss	36.4 BTU/h	IE-SW-BL06T-2TX-4PoE	-40 to +75 °C
Connection	1 removable 4-pole terminal block	Accessories	
Reverse polarity protection	Present	19" Rack Mounting Kit	Type
Overcurrent protection	Present	RM-KIT	
PoE		Order No.	
PoE power budget total	62 W at 12 V DC (12-17 V DC) 120 W at 24/48 V DC (18-57 V DC)	1241380000	
PoE output voltage	50 V DC at 12/24/48 V DC input voltage	1286920000	
PoE output power	15.4 W at 802.3af, 30 W at 802.3at		
PoE output current	350 mA at 802.3af, 600 mA at 802.3at		
PoE pinout	Mode A: wire pair 1, 2 (V+); wire pair 3, 6 (V-)		
Physical Characteristics			
Housing	Aluminium, IP30 protection		
Dimensions (W x H x D)	50 x 114 x 70 mm (1.96 x 4.53 x 2.76 in)		
Weight	375 g		
Type of mounting	DIN-Rail		
Environmental Limits			
Operating Temperature	Standard models: -10 to 60°C (14 to 140°F), models with extended temperature range: -40 to 75 °C (-40 to 167 °F)		
Storage Temperature	-40 to 85 °C (-40 to 185 °F)		
Ambient Relative Humidity	5 to 95 % (non-condensing)		
Regulatory Approvals			
Safety	UL 508		

18-Port unmanaged Fast/Gigabit Ethernet Switches

- Suitable for use in harsh industrial environment thanks to rugged design and wide operating temperature range of -40°C up to 75°C
- Reliable operation due to redundant voltage inputs, fault relay and LED diagnostics
- SFP-ports for fiber optic transmission over long distances

**Technical data****Technology**

Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX IEEE 802.3ab for 1000BASE-T IEEE 802.3z for 1000BASE-X IEEE 802.3x for flow control
Processing type	Store and Forward
Flow control	IEEE 802.3x flow control
Switch characteristics	
MAC table size	8K
Packet buffer Size	1 Mbit
Interfaces	
RJ45 ports	10/100BASE-T(X) or 10/100/1000BASE-T(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port
Fibre optic ports	1000BaseSFP-slot
Relay Contact	1 relay output with a current capacity of 1 A at 24 V DC
Power supply	
Connection type	1 removable 6-pin terminal block
Input voltage	24 V DC (12 - 48 V), 2 redundant inputs
Current consumption at 24 V	0.35 A
Overload current protection	yes
Reverse polarity protection	yes
Physical characteristics	
Housing main material	Metal
Protection degree	IP30
Type of mounting	DIN rail
Dimensions (W x H x D)	96.4 x 154 x 108.5 mm (3.8 x 6.06 x 4.27 in)
Weight	1044 g
Environmental conditions	
Operating temperature	-40 to 75 °C (-40 to 167 °F)
Storage temperature	-40 to 85 °C (-40 to 185 °F)
Humidity	5 to 95 % (non-condensing)
Operating altitude	≤ 2000 m
EMC conformity and approvals	
EMC	EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz bis 1 Ghz: 3 V/m IEC 61000-4-4 EFT: Power: 0.5 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 0.5 kV; Signal: 1 kV IEC 61000-4-6 CS: 3 Vrms
Safety	UL 61010-1, UL 61010-2-201
Shock	IEC 60068-2-27
Vibration	IEC 60068-2-6
Free fall	IEC 60068-2-31

MTBF

Time 748,087 hrs

Database Telcordia SR332

Guarantee

Time interval 5 years

Ordering Information

Version	Model Type	Order No.
16x RJ45 10/100 Mbit/s, 2x combo-ports usable as RJ45 10/100/1000 Mbit/s or SFP 1000Mbit/s)	IE-SW-EL18-16TX-2GC	2682200000

Accessories

	Model Type	Order No.
19" Rack Mounting Kit	RM-KIT	1241440000

Note

Corresponding SFP modules for EcoLine switches, see page I.5.

Unmanaged Switches Gigabit Ethernet – EcoLine

5 to 10-Port unmanaged Gigabit Ethernet Switches

- Gigabit Ethernet on all ports including Jumbo Frame support for applications with high demand on bandwidth and latency
- Reliable operation due to redundant voltage inputs, fault relay and LED diagnostics
- SFP-ports for fiber optic transmission over long distances



Technical data

Technology		Physical characteristics
Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX and 100BASE-FX IEEE 802.3ab for 1000BASE-T IEEE 802.3z for 1000BASE-X IEEE 802.3x for flow control	Dimensions (W x H x D) IE-SW-EL05-5GT: 26.1 x 95 x 70 mm (1.03 x 3.74 x 2.76 in) IE-SW-EL05-4GT-1GESFP: 26.1 x 144.3 x 94.9 mm (1.03 x 5.68 x 3.74 in) IE-SW-EL08-8GT-MINI: 41 x 95 x 90 mm (1.61 x 3.74 x 3.54 in) IE-SW-EL08-8GT: 26.1 x 144.3 x 94.9 mm (1.03 x 5.68 x 3.74 in) IE-SW-EL10-8GT-2GESFP: 96.4 x 154 x 108.5 mm (3.8 x 6.06 x 4.27 in)
Processing type	Store and Forward	Weight IE-SW-EL05-5GT: 218 g IE-SW-EL05-4GT-1GESFP: 305 g IE-SW-EL08-8GT-MINI: 330 g IE-SW-EL08-8GT: 335 g IE-SW-EL10-8GT-2GESFP: 410 g
Flow control	IEEE 802.3x flow control	Environmental conditions Operating temperature: -40 to 75 °C (-40 to 167 °F) Storage temperature: -40 to 85 °C (-40 to 185 °F) Humidity: 5 to 95% (non-condensing) Operating altitude: ≤ 2000 m
Switch characteristics		EMC conformity and approvals
MAC table size	IE-SW-EL05-5GT: 4K IE-SW-EL05-4GT-1GESFP: 1K IE-SW-EL08-8GT-MINI: 4K IE-SW-EL08-8GT: 4K IE-SW-EL10-8GT-2GESFP: 4K	EMC EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz bis 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 0.5 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 0.5 kV; Signal: 1 kV IEC 61000-4-6 CS: 3 Vrms
Packet buffer Size	IE-SW-EL05-5GT: 1 Mbit IE-SW-EL05-4GT-1GESFP: 1 Mbit IE-SW-EL08-8GT-MINI: 1.5 Mbit IE-SW-EL08-8GT: 1.5 Mbit IE-SW-EL10-8GT-2GESFP: 1.5 Mbit	Safety UL 61010-1, UL 61010-2-201
Jumbo frame support	IE-SW-EL05-5GT: up to 9.72 KB IE-SW-EL05-4GT-1GESFP: up to 10 KB IE-SW-EL08-8GT-MINI: up to 9 KB IE-SW-EL08-8GT: up to 9.2 KB IE-SW-EL10-8GT-2GESFP: up to 9 KB	Shock IEC 60068-2-27
Interfaces		Vibration IEC 60068-2-6
RJ45 ports	10/100/1000BASE-T(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port	Free fall IEC 60068-2-31
Fibre optic ports	100/1000BaseSFP-slot or 1000BaseSFP-slot	MTBF
Relay Contact	IE-SW-EL05-4GT-1GESFP: 1 relay output with a current capacity of 1 A at 24 V DC IE-SW-EL08-8GT-MINI: 1 relay output with a current capacity of 1 A at 24 V DC	Time IE-SW-EL05-5GT: 2,556,319 hrs IE-SW-EL05-4GT-1GESFP: 1,861,840 hrs IE-SW-EL08-8GT-MINI: 1,742,238 hrs IE-SW-EL08-8GT: 926,332 hrs IE-SW-EL10-8GT-2GESFP: 748,087 hrs
DIP switches	IE-SW-EL05-4GT-1GESFP: 2x enabling/disabling power fault alarm via relay IE-SW-EL08-8GT-MINI: 2x enabling/disabling power fault alarm via relay	Database Telcordia SR332
Power supply		Guarantee
Connection type	IE-SW-EL05-5GT: 1 removable 4-pin terminal block IE-SW-EL05-4GT-1GESFP: 1 removable 6-pin terminal block IE-SW-EL08-8GT-MINI: 1 removable 4-pin terminal block IE-SW-EL08-8GT: 1 removable 6-pin terminal block IE-SW-EL10-8GT-2GESFP: 1 removable 6-pin terminal block	Time interval 5 years
Input voltage	24 V DC (12 - 48 V), 2 redundant inputs	Ordering Information
Current consumption at 24 V	IE-SW-EL05-5GT: 0.14 A IE-SW-EL05-4GT-1GESFP: 0.18 A IE-SW-EL08-8GT-MINI: 0.17 A IE-SW-EL08-8GT: 0.20 A IE-SW-EL10-8GT-2GESFP: 0.20 A	Version 5x RJ45 10/100/1000 Mbit/s 4x RJ45 10/100/1000 Mbit/s, 1x SFP 1000 Mbit/s 8x RJ45 10/100/1000 Mbit/s 8x RJ45 10/100/1000 Mbit/s 8x RJ45 10/100/1000 Mbit/s, 2x SFP 100/1000 Mbit/s
Overload current protection	yes	Model Type IE-SW-EL05-5GT IE-SW-EL05-4GT-1GESFP IE-SW-EL08-8GT-MINI IE-SW-EL08-8GT IE-SW-EL10-8GT-2GESFP
Reverse polarity protection	yes	Order No. 2682210000 2682220000 2705000000 2682230000 2682240000
Physical characteristics		Accessories
Housing main material	Metal	Model Type RM-KIT
Protection degree	IP30	Note Corresponding SFP modules for EcoLine switches, see page I.4 - I.5.
Type of mounting	DIN rail	

5 and 8-Port unmanaged Gigabit Ethernet Switches

- Gigabit Ethernet on all ports
- Variants with slots for SFP transceivers
- Redundant dual 12/24/48 V DC power inputs
- Relay output warning for power failure and port break alarm
- Broadcast storm protection
- Supports jumbo frame transmission

**Technical data**

Technology		Regulatory Approvals	
Standards	IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT (X) and 100BaseFX IEEE 802.3ab for 1000BaseT(X) IEEE 802.3z for 1000BaseX IEEE 802.3x for flow control IEEE 802.3az for energy-efficient Ethernet	EMC	EN 55032/24 CISPR 32, FCC Part 15B Class A IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 4 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8
Processing Type	Store and Forward	Maritime	DNV-GL
Flow Control	IEEE 802.3x flow control, back pressure flow control	Shock	IEC 60068-2-27
Switch Properties		Freefall	IEC 60068-2-32
MAC Table Size	8 K	Vibration	IEC 60068-2-6
Packet Buffer Size	IE-SW-BL05-4GT-Series: 1 Mbit IE-SW-VL08-Series: 4 Mbit	MTBF (mean time between failures)	IE-SW-BL05-4GT-Serie: 2,823,446 hrs IE-SW-VL08-Serie: 2,424,649 hrs
Jumbo frame support	IE-SW-BL05-4GT-Series: 10 KByte IE-SW-VL08-Series: 9.6 KByte	Database	Telcordia (Bellcore), GB
Interface		Warranty	Warranty Period
Fibre Ports	100/1000BaseSFP		5 years
RJ45 Ports	10/100/1000BaseT(X) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection	Ordering Information	
DIP Switches	Port fault alarm enable/disable Broadcast storm protection enable/disable Jumbo frame support enable/disable IEEE 802.3az energy saving enable/disable Switching between 100BaseSFP and 1000BaseSFP at SFP slot	Version	Model Type
Alarm Contact	1 relay output with current carrying capacity of 1 A at 24 V DC		Operating Temperature
Power Requirements			Order No.
Input Voltage	12/24/48 V DC (9.6 to 60 V DC), redundant dual inputs	4 * RJ45 10/100/1000BaseT(X)	IE-SW-BL05-4GT-1GS -10 to +60 °C 243540000
Input Current	IE-SW-BL05-4GT-1GS: 0.14 A at 24 V IE-SW-VL08-8GT: 0.29 A at 24 V IE-SW-VL08-6GT-2GS: 0.31 A at 24 V	1 * Combo Port (10/100/1000 BaseT(X) or 100/1000BaseSFP)	IE-SW-BL05T-4GT-1GS -40 to +75 °C 243541000
Connection	1 removable 6-contact terminal block	8 * RJ45 10/100/1000BaseT(X)	IE-SW-VL08-8GT -10 to +60 °C 124127000
Reverse Polarity Protection	Present	IE-SW-VL08T-8GT	IE-SW-VL08T-8GT -40 to +75 °C 1286860000
Physical Characteristics		6 * RJ45 10/100/1000BaseT(X), 2 * Combo Port (10/100/1000 BaseT(X) or 100/1000BaseSFP)	IE-SW-VL08-6GT-2GS -10 to +60 °C 1241280000
Housing	Metal, IP30 protection	IE-SW-VL08T-6GT-2GS	IE-SW-VL08T-6GT-2GS -40 to +75 °C 1286870000
Dimensions (W x H x D)	IE-SW-BL05-4GT-Series: 29 x 135 x 105 mm (1.14 x 5.31 x 4.13 in) IE-SW-VL08-xGT: 53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in)		
Weight	IE-SW-BL05-4GT-Series: 290 g IE-SW-VL08-Series: 630 g		
Type of mounting	DIN-Rail, wall (with optional mounting kit)		
Environmental Limits			
Operating Temperature	Standard Models: -10 to 60 °C (14 to 140 °F) Wide Temp. Models: -40 to 75 °C (-40 to 167 °F) (on request)		
Storage Temperature	-40 to 85 °C (-40 to 185 °F)		
Ambient Relative Humidity	5 to 95 % (non-condensing)		
Regulatory Approvals			
Safety	UL 508		
Hazardous Location	UL/cUL Class I, Division 2, Groups A, B, C, and D; ATEX Zone 2 Ex nA nC IIC T4 Gc		

Hinweis

Corresponding SFP modules for Basic/ValueLine switches, see page I.7

Unmanaged Power over Ethernet Switches Gigabit Ethernet – EcoLine

8 and 10-Port unmanaged PoE+ Gigabit Ethernet Switches

- IEEE 802.3af/at compliant PoE ports
- Integrated DC/DC converter for providing PoE voltage to PDs over the entire PSE input voltage range from 12 to 57 V DC
- Gigabit Ethernet on all ports including Jumbo Frame support for applications with high demand on bandwidth and latency
- Reliable operation due to redundant voltage inputs, fault relay and LED diagnostics

**Technical data****Technology**

Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX and 100BASE-FX IEEE 802.3ab for 1000BASE-T IEEE 802.3z for 1000BASE-X IEEE 802.3x for flow control IEEE 802.3at/af for Power-over-Ethernet
-----------	--

Processing type

Processing type	Store and Forward
-----------------	-------------------

Flow control

Flow control	IEEE 802.3x flow control
--------------	--------------------------

Switch characteristics

MAC table size	IE-SW-EL08-8GTPoE: 4K IE-SW-EL10-8GTPoE-2GESFP: 8K
Packet buffer Size	IE-SW-EL08-8GTPoE: 1.5 Mbit IE-SW-EL10-8GTPoE-2GESFP: 4 Mbit

Jumbo frame support

Jumbo frame support	IE-SW-EL08-8GTPoE: up to 9.72 KB IE-SW-EL10-8GTPoE-2GESFP: up to 9.6 KB
---------------------	--

Interfaces

RJ45 ports	10/100/1000BASE-T(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port
Fibre optic ports	100/1000BaseSFP-slot
Relay Contact	1 relay output with a current capacity of 1 A at 24 V DC
DIP switches	IE-SW-EL08-8GTPoE: 2x enabling/disabling power fault alarm via relay IE-SW-EL10-8GTPoE-2GESFP: 2x enabling/disabling power fault alarm via relay, 2x for Switching between 100BaseSFP and 1000BaseSFP on SFP port

Power supply

Connection type	1 removable 6-pin terminal block
Input voltage	12/24/48 V DC (12 - 57 V), 2 redundant inputs
Current consumption at 24 V (with PD consumption)	IE-SW-EL08-8GTPoE: 5.86 A IE-SW-EL10-8GTPoE-2GESFP: 6.13 A
Overload current protection	yes
Reverse polarity protection	yes

Power over Ethernet (PoE)

PoE pin assignment	Mode A: Pin 1, 2 (V+); Pin 3, 6 (V-); Alternative A; MDI
Total PoE power budget	60 W at 12 - 23 V DC; 120 W at 24 - 57 V DC

Physical characteristics

Housing main material	Metal
Protection degree	IP30
Type of mounting	DIN rail
Dimensions (W x H x D)	IE-SW-EL08-8GTPoE: 41 x 144.3 x 94.9 mm (1.62 x 5.68 x 3.74 in) IE-SW-EL10-8GTPoE-2GESFP: 54.3 x 145.1 x 108.3 mm (2.13 x 5.71 x 4.26 in)
Weight	IE-SW-EL08-8GTPoE: 590 g IE-SW-EL10-8GTPoE-2GESFP: 729 g

Environmental conditions

Operating temperature	-40 to 75 °C (-40 to 167 °F)
Storage temperature	-40 to 85 °C (-40 to 185 °F)
Humidity	5 to 95 % (non-condensing)
Operating altitude	≤ 2000 m

EMC conformity and approvals

EMC	EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz bis 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 0.5 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 0.5 kV; Signal: 1 kV IEC 61000-4-6 CS: 3 Vrms
-----	---

Safety

Safety	UL 61010-1, UL 61010-2-201
--------	----------------------------

Shock	IEC 60068-2-27
-------	----------------

Vibration	IEC 60068-2-6
-----------	---------------

Free fall

Free fall	IEC 60068-2-31
-----------	----------------

MTBF

Time	IE-SW-EL08-8GTPoE: 532,527 hrs IE-SW-EL10-8GTPoE-2GESFP: 537,330 hrs
------	---

Database	Telcordia SR322
----------	-----------------

Guarantee

Time interval	5 years
---------------	---------

Ordering Information

Version	Model Type	Order No.
8x RJ45 PoE+ 10/100/1000 Mbit/s	IE-SW-EL08-8GTPoE	2682400000
8x RJ45 PoE+ 10/100/1000 Mbit/s, 2x SFP 100/1000 Mbit/s	IE-SW-EL10-8GTPoE-2GESFP	2682410000

Accessories

	Model Type	Order No.
19" Rack Mounting Kit	RM-KIT	1241440000

Note

Corresponding SFP modules for EcoLine switches, see page I.4 - I.5.

5-Port unmanaged Gigabit Ethernet PoE+ Switches

- Gigabit Ethernet at all ports
- 4x IEEE 802.3af/at conform PoE ports
- Up to 36 Watt per PoE port
- 12/24/48 V DC redundant wide-range power supply
- Support for jumbo frames
- Intelligent power consumption detection and classification
- Intelligent PoE surge voltage and short-circuit protection

**Technical data**

Technology		Regulatory Approvals	
Standards	IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT(X) IEEE 802.3ab for 1000BaseT IEEE 802.3x for Flow Control IEEE 802.3af for PoE IEEE 802.3at for PoE+ IEEE 802.3az for Energy-Efficient Ethernet	Safety	UL 508
Processing Type	Store and Forward	EMC	EN 55032/24 CISPR 32, FCC Part 15B Class A IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8
Switch Properties		Shock	IEC 60068-2-27
MAC table size	8 K	Freefall	IEC 60068-2-32
Packet buffer size	1 Mbit	Vibration	IEC 60068-2-6
Jumbo Frame support	10 KB	MTBF (mean time between failures)	
RJ45 Ports	10/100/1000BaseT(X) auto negotiation speed, Full/Half duplex mode and auto MDI/MDI-X connection	Time	1,564,608 hrs
DIP Switches	Broadcast storm protection enable/disable Jumbo Frame support enable/disable IEEE 802.3az energy saving enable/disable PoE High Power enable/disable	Database	Telcordia (Bellcore), GB
Power Requirements		Warranty	
Input voltage	12/24/48 V DC 12 to 57 V DC, two redundant inputs	Warranty Period	5 years
Current consumption (with PD consumption)	5.92 A at 12 VDC 5.65 A at 24 VDC 3.21 A at 48 VDC	Ordering data	
Inrush current	17.4 A at 24 VDC (0.1 - 1 ms)	Version	Type
Power loss	36.4 BTU/h		Operating Temperature
Connection	2 removable 2-pole terminal blocks	1 * RJ45 10/100/1000 BaseT(X), 4 * RJ45 10/100/1000 BaseT(X) PoE+	0 to +60 °C
Reverse polarity protection	Present	IE-SW-BL05-1GT-4GTPoE	1504320000
Overcurrent current protection	Present	IE-SW-BL05T-1GT-4GTPoE	1504340000
PoE		Accessories	
PoE power budget total	62 W at 12 V DC (12-17 V DC) 120 W at 24 V DC (18-35 V DC) 144 W at 48 V DC (36 to 57 VDC)	Type	Order No.
PoE output voltage	53 V DC at 12/24/48 V DC input voltage	RM-KIT	1241440000
PoE output power	15.4 W at 802.3af, 30 W at 802.3at, 36 W in high power mode	IE-WALLMOUNT-KIT-30MM	1504450000
PoE output current	350 mA at 802.3af, 600 mA at 802.3at, 720 mA in high power mode		
PoE pinout	Mode A: wire pair 1, 2 (V+); wire pair 3, 6 (V-)		
Physical Characteristics			
Housing	Aluminium, IP30 protection		
Dimensions (W x H x D)	29 x 135 x 105 mm (1.14 x 5.31 x 4.13 Zoll)		
Weight	300 g		
Type of mounting	DIN-Rail, wall (with optional mounting kit)		
Environmental Limits			
Operating Temperature	Standard Models: 0 to 60 °C (32 to 140 °F) Wide Temp. Models: -40 to 75 °C (-40 to 167 °F)		
Storage Temperature	-40 to 85 °C (-40 to 185 °F)		
Ambient Relative Humidity	5 to 95 % (non-condensing)		

Power over Ethernet Injector Gigabit Ethernet – EcoLine

PoE+ Gigabit Ethernet Injector

- IEEE 802.3af/at compliant PoE ports
- Integrated DC/DC converter for providing PoE voltage to PDs over the entire PSE input voltage range from 12 to 57 V DC



Technical data

Technology		Guarantee	
		Time interval	5 years
Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-T(X) IEEE 802.3ab for 1000BASE-T IEEE 802.3at/af for Power-over-Ethernet		
Interfaces	RJ45 ports	10/100/1000BASE-T(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port	
Power supply	Connection type	1 removable 4-pin terminal block	
	Input voltage	12/24/48 V DC (12 - 57 V), 1 single input	
	Current consumption at 24 V (with PD consumption)	2.81 A	
	Overload current protection	yes	
	Reverse polarity protection	yes	
Power over Ethernet (PoE)	PoE pin assignment	Mode A: Pin 1, 2 (V+); Pin 3, 6 (V-); Alternative A: MDI-X	
	Total PoE power budget	30 W at 12 - 23 V DC; 60 W at 24 - 57 V DC	
Physical characteristics	Housing main material	Metal	
	Protection degree	IP30	
	Type of mounting	DIN rail	
	Dimensions (W x H x D)	41 x 95 x 70 mm (1.61 x 2.75 x 3.74 in)	
	Weight	370 g	
Environmental conditions	Operating temperature	-40 to 75 °C (-40 to 167 °F)	
	Storage temperature	-40 to 85 °C (-40 to 185 °F)	
	Humidity	5 to 95 % (non-condensing)	
	Operating altitude	≤ 2000 m	
EMC conformity and approvals	EMC	EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz bis 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 0.5 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 0.5 kV; Signal: 1 kV IEC 61000-4-6 CS: 3 Vrms	
Safety	UL 61010-1, UL 61010-2-201		
Shock	IEC 60068-2-27		
Vibration	IEC 60068-2-6		
Free fall	IEC 60068-2-31		
MTBF	Time	3,165,390 hrs	
	Database	Telcordia SR332	

Managed Switches

Overview

Managed Switches	
Introduction – Managed Switches	C.2
Managed Switches Fast Ethernet	C.4
Managed Switches Fast / Gigabit Ethernet	C.9
Managed Switches Gigabit Ethernet	C.12
Managed Power over Ethernet Switches Gigabit Ethernet	C.13
Managed Switches, IEC 61850-3, DIN-rail mounting Fast/Gigabit Ethernet	C.14
Managed Switches, IEC 61850-3, DIN-rail mounting Gigabit Ethernet	C.15
Managed Switches, IEC 61850-3, 19" rack mounting Fast/Gigabit Ethernet	C.16
Managed Switches, IEC 61850-3, 19" rack mounting, modular Fast/Gigabit / 10-Gigabit Ethernet	C.18
Media interface modules for modular switch Fast/Gigabit Ethernet	C.20
Media interface modules for modular switch Gigabit / 10-Gigabit Ethernet	C.21

Increased productivity through uninterrupted operation

Managed switches – for optimal control and effective redundancy

In order to coordinate the different requirements of communication participants within an industrial network, managed switches feature extensive control mechanisms for data distribution and bandwidth management. Different configuration options are supported, e.g. web-based configuration, SNMP, Telnet console, command-line interface (CLI) and serial console connection.

C In the industrial Ethernet infrastructures of today, system availability must be ensured through network redundancy. This prevents machine downtimes and production losses due to connection errors in the highly integrated systems. Weidmüller managed switches feature high-performance redundancy mechanisms in order to increase the availability of managed Ethernet networks.


In order to satisfy all the requirements of industrial networks, our managed switches are available in four different lines: ValueLine, AdvancedLine, PremiumLine and SubstationLine. This selection ensures the availability of the right product regardless of application-specific and industrial requirements. The lines offer both DIN rail and 19" rack models, Fast, Gigabit and up to 10 Gigabit interfaces, a broad selection of port numbers and types, Power over Ethernet variants, support for the most important industrial automation protocols and the necessary approvals for use in such demanding sectors as the process industry, transmission and distribution, and shipbuilding.

Your special advantage:

- Wide variety of ports in terms of number and features to meet individual requirements
- Models available with Fast Ethernet, Gigabit and up to 10 Gigabit interfaces
- Lite- to full-managed models, including Power over Ethernet variants
- Support of industrial protocols for optimal integration into the most common automation networks

See
chapter A for
details about
the product
lines





Managed Switches Fast Ethernet – AdvancedLine

5 and 6-Port managed Fast Ethernet Switches

- Extensive set of management features enable the set-up of various redundancy, monitoring, traffic filter and security functions
- Suitable for use in harsh industrial environment thanks to rugged design and wide operating temperature range of -40°C up to 75°C



Technical data

Technology		
Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX and 100BASE-FX IEEE 802.3x for flow control IEEE 802.1D for the Spanning Tree protocol (STP) IEEE 802.1w for Rapid Spanning Tree protocol (RSTP) IEEE 802.1AB for Link Layer Discovery Protocol (LLDP)	
Processing type	Store and Forward	
Flow control	IEEE 802.3x flow control	
Switch characteristics		
MAC table size	2K	
Packet buffer Size	1 Mbit	
Management features		
Device configuration	Webbrowser (HTTP/HTTPS), SNMP v1/v2c/v3, Telnet console, CLI, Local serial console port, Upload of a configuration file via web-interface or TFTP-Server	
Monitoring function	SNMP v1/v2c/v3, LLDP, Port mirroring, Port statistics, Port monitoring, Syslog, RMON, Event based warning via E-Mail, relay, SNMP trap	
Network redundancy	STP, RSTP, MSTP, LACP, O-Ring, O-Chain, Fast recovery	
Network traffic filter	Quality of Service (QoS), Differentiated Services Code Point (DSCP), Port based VLAN, Tag based VLAN, IGMP v2/v3, Multicast VLAN Registration (MVR), Traffic Rate Limiting	
IP-address management	Static, DHCP-Client, DHCP-Server (port based, pool-based), DHCP-Relay	
Security functions	VLAN segmentation, Enable/disable ports, TACACS+ and IEEE 802.1X, User Authentication, Access control (Port based via IEEE 802.1X), Access Control List (IP-based, MAC-based), Management access security via secure IP-list and configuration of allowed access methods (web-interface, telnet, SSH), Loop protection	
Time synchronization management	SNTP client	
Industrial protocol support	Modbus/TCP slave	
Interfaces		
RJ45 ports	10/100BASE-T(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port	
Fibre optic ports	100BASE-FX (SC-Duplex connector)	
Relay Contact	1 relay output with a current capacity of 1 A at 24 V DC	
DIP switches	1x enabling/disabling power fault alarm via relay 3x for ring redundancy settings	
Reset button	< 5 sec: System reboot ; > 5 sec: Factory default	
Fibre optic transceiver characteristics		
Transmission rate	100 Mbps	
Connector type	SC-Duplex	
Transceiver type	Multimode	Singlemode
Fiber cable type	50/125 µm 62.5/125 µm	9/125 µm
Transmission distance, typical	2 km	30 km
Wavelength, typical	1310 nm	
Optical power RX rangey	-31 to 0 dBm	-34 to 0 dBm
Optical power TX range	-23.5 to -14 dBm	-15 to -8 dBm
Link-budget	7.5 dB	19 dB
Power supply		
Connection type	IE-SW-AL05LM-5TX: 1 removable 6-pin terminal block IE-SW-AL06LM-4TX-2SC: 1 removable 7-pin terminal block IE-SW-AL06LM-4TX-2SCS: 1 removable 7-pin terminal block	
Input voltage		
Current consumption at 24 V	24 V DC (12 - 48 V), 2 redundant inputs IE-SW-AL05LM-5TX: 0.25 A IE-SW-AL06LM-4TX-2SC: 0.24 A IE-SW-AL06LM-4TX-2SCS: 0.24 A	
Overload current protection		
	yes	
Reverse polarity protection		
	yes	
Physical characteristics		
Housing main material	Metal	
Protection degree	IP30	
Type of mounting	DIN rail	
Dimensions (W x H x D)	IE-SW-AL05LM-5TX: 26.1 x 144.3 x 94.9 mm (1.03 x 5.68 x 3.74 in) IE-SW-AL06LM-4TX-2SC: 54.2 x 145.4 x 107.1 mm (2.13 x 5.72 x 4.22 in) IE-SW-AL06LM-4TX-2SCS: 54.2 x 145.4 x 107.1 mm (2.13 x 5.72 x 4.22 in)	
Weight	IE-SW-AL05LM-5TX: 335 g IE-SW-AL06LM-4TX-2SC: 649 g IE-SW-AL06LM-4TX-2SCS: 649 g	
Environmental conditions		
Operating temperature	-40 to 75 °C (-40 to 167 °F)	
Storage temperature	-40 to 85 °C (-40 to 185 °F)	
Humidity	5 to 95 % (non-condensing)	
Operating altitude	≤ 2000 m	
EMC conformity and approvals		
EMC	EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz bis 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 0.5 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 0.5 kV; Signal: 1 kV IEC 61000-4-6 CS: 3 Vrms	
Safety	UL 61010-1, UL 61010-2-201	
Shock	IEC 60068-2-27	
Vibration	IEC 60068-2-6	
Free fall	IEC 60068-2-31	
MTBF		
Time	IE-SW-AL05LM-5TX: 1,796,601 hrs IE-SW-AL06LM-4TX-2SC: 595,597 hrs IE-SW-AL06LM-4TX-2SCS: 609,551 hrs	
Database	Telcordia SR332	
Guarantee		
Time interval	5 years	
Ordering Information		
Version	Model Type	Order No.
5x RJ45 10/100 Mbit/s	IE-SW-AL05LM-5TX	2682250000
4x RJ45 10/100 Mbit/s, 2x SC Multimode 100 Mbit/s	IE-SW-AL06LM-4TX-2SC	2682260000
4x RJ45 10/100 Mbit/s, 2x SC Singlemode 100 Mbit/s	IE-SW-AL06LM-4TX-2SCS	2682270000
Accessories		
19" Rack Mounting Kit	Model Type	Order No.
19" Rack Mounting Kit	RM-KIT	1241440000

8 to 24-Port managed Fast Ethernet Switches

- Extensive set of management features enable the set-up of various redundancy, monitoring, traffic filter and security functions
- Suitable for use in harsh industrial environment thanks to rugged design and wide operating temperature range of -40°C up to 75°C

**Technical data**

Technology		
Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX IEEE 802.3x for flow control IEEE 802.3ad for port trunk with LACP IEEE 802.1D for the Spanning Tree protocol (STP) IEEE 802.1w for Rapid Spanning Tree protocol (RSTP) IEEE 802.1s for Multiple Spanning Tree Protocol (MSTP) IEEE 802.1p for Class of Service IEEE 802.1Q for VLAN Tagging IEEE 802.1X for Authentication IEEE 802.1AB for Link Layer Discovery Protocol (LLDP)	
Processing type	Store and Forward	
Flow control	IEEE 802.3x flow control	
Switch characteristics		
MAC table size	8K	
Packet buffer Size	1 Mbit	
Priority queues	4	
Number of available VLANs	4095 (1 to 4094)	
IGMP groups	IE-SW-AL08M-8TX: 1024 IE-SW-AL16M-16TX: 256 per VLAN IE-SW-AL24M-24TX: 256 per VLAN	
Management features		
Device configuration	Webbrowser (HTTP/HTTPS), SNMP v1/v2c/v3, Telnet console, CLI, Local serial console port, Upload of a configuration file via web-interface or TFTP-Server	
Monitoring function	SNMP v1/v2c/v3, Link Layer Discovery Protocol (LLDP), Port mirroring, Port statistics, Port monitoring, Syslog, RMON (Remote monitoring), Event based warning via E-Mail, Event based warning via relay, Event based warning via SNMP trap	
Network redundancy	SNMP v1/v2c/v3, LLDP, Port mirroring, Port statistics, Port monitoring, Syslog, RMON, Event based warning via E-Mail, relay, SNMP trap	
Network traffic filter	Quality of Service (QoS), Differentiated Services Code Point (DSCP), Port based VLAN, Tag based VLAN, IGMP v2/v3, Multicast VLAN Registration (MVR), Traffic Rate Limiting	
IP-address management	Static, DHCP-Client, DHCP-Server (port based, pool-based), DHCP Option 82, DHCP-Relay	
Security functions	VLAN segmentation, Enable/disable ports, TACACS+ and IEEE 802.1X, User Authentication, Access control (Port based via IEEE 802.1X), Access Control List (IP-based, MAC-based), Management access security via secure IP-list and configuration of allowed access methods (web-interface, telnet, SSH), Loop protection	
Time synchronization management	NTP server SNTP client	
Industrial protocol support	PROFINET device acc. to conformance class A, Modbus/TCP slave	
Interfaces		
RJ45 ports	10/100BASE-T(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port	
Serial console port	RS-232 (RJ45 connector)	
Relay Contact	1 relay output with a current capacity of 1 A at 24 V DC	
Reset button	< 5 sec: System reboot; > 5 sec: Factory default	
Power supply		
Connection type	IE-SW-AL08M-8TX: 1 removable 7-pin terminal block IE-SW-AL16M-16TX: 1 removable 6-pin terminal block IE-SW-AL24M-24TX: 1 removable 6-pin terminal block	
Power supply		
Input voltage	24 V DC (12 - 48 V), 2 redundant inputs	
Current consumption at 24 V	IE-SW-AL08M-8TX: 0.24 A IE-SW-AL16M-16TX: 0.6 A IE-SW-AL24M-24TX: 0.6A	
Overload current protection	yes	
Reverse polarity protection	yes	
Physical characteristics		
Housing main material	Metal	
Protection degree	IP30	
Type of mounting	DIN rail	
Dimensions (W x H x D)	IE-SW-AL08M-8TX: 54.2 x 145.4 x 107.1 mm (2.13 x 5.72 x 4.21 in) IE-SW-AL16M-16TX: 74.3 x 153.6 x 107.5 mm (2.93 x 6.05 x 4.2 in) IE-SW-AL24M-24TX: 96.4 x 154 x 108.5 mm (3.8 x 6.06 x 4.27 in)	
Weight	IE-SW-AL08M-8TX: 789 g IE-SW-AL16M-16TX: 1148 g IE-SW-AL24M-24TX: 1281 g	
Environmental conditions		
Operating temperature	-40 to 75 °C (-40 to 167 °F)	
Storage temperature	-40 to 85 °C (-40 to 185 °F)	
Humidity	5 to 95 % (non-condensing)	
Operating altitude	≤ 2000 m	
EMC conformity and approvals		
EMC	EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz bis 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 0.5 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 0.5 kV; Signal: 1 kV IEC 61000-4-6 CS: 3 Vrms	
Safety	UL 61010-1, UL 61010-2-201	
Shock	IEC 60068-2-27	
Vibration	IEC 60068-2-6	
Free fall	IEC 60068-2-31	
MTBF		
Time	IE-SW-AL08M-8TX: 841,599 hrs IE-SW-AL16M-16TX: 886,987 hrs IE-SW-AL24M-24TX: 731,289 hrs	
Database	Telcordia SR332	
Guarantee		
Time interval	5 years	
Ordering Information		
Version	Model Type	Order No.
8x RJ45 10/100 Mbit/s	IE-SW-AL08M-8TX	2682280000
16x RJ45 10/100 Mbit/s	IE-SW-AL16M-16TX	2682310000
24x RJ45 10/100 Mbit/s	IE-SW-AL24M-24TX	2682320000
Accessories		
Model Type	Order No.	
19" Rack Mounting Kit	RM-KIT	1241440000

5-Port managed Fast Ethernet Switches

- Supports the automation protocols Modbus/TCP, PROFINET RT and EtherNet/IP
- Turbo Ring and Turbo Chain with fast recovery time (<20 ms for up to 250 switches)
- IGMP snooping, QoS, port- and tag-based VLAN
- Configurable error messages via SNMP trap, e-mail or relay output
- User-friendly, web-based configuration and management



EtherNet/IP™ **ModbusTCP**

Technical data**Standards**

- IEEE 802.3 for 10BaseT ■ IEEE 802.3u for 100BaseT(X) ■ IEEE 802.3x for Flow Control
- IEEE 802.1D-2004 for Spanning Tree Protocol ■ IEEE 802.1w for Rapid STP ■ IEEE 802.1p for Class of Service
- IEEE 802.1Q for VLAN Tagging

Protocols

- IGMPv1/v2 ■ GMRP ■ GVRP ■ SNMIPv1/v2c/v3 ■ DHCP Server/Client ■ TFTP ■ SNTP ■ SMTP ■ RARP
- RMON ■ HTTP ■ Telnet ■ Syslog ■ DHCP Option 66/67/82 ■ BootP ■ LLDP ■ Modbus/TCP ■ PROFINET RT (PROFINET-IO device in compliance with Conformance Class B) ■ EtherNet/IP (CIP support) ■ IPv6

MIB

- MIB-II ■ Ethernet-like MIB ■ P-BRIDGE MIB ■ Bridge MIB ■ RSTP MIB

- RMON MIB Group 1, 2, 3, 9 ■ Private MIB

Flow Control

- IEEE 802.3x flow control ■ back pressure flow control

Switch Properties

MAC Table Size	2 K
Packet Buffer Size	1 MBit

Interface

RJ45 Ports	10/100BaseT(X) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection
Console Port	RS 232 (RJ45 connector)

DIP Switches

- Turbo Ring, Master, Coupler, Reserve

Alarm Contact

- 1 relay output with current carrying capacity of 1 A at 24 V DC

Power Requirements

Input Voltage	12/24/48 V DC (9.6 to 60 V DC), two redundant inputs
Input Current	0.24 A at 24 V
Overload Current Protection	Present
Connection	1 removable 6-contact terminal block
Reverse Polarity Protection	Present

Physical Characteristics

Housing	Metal, IP30 protection
Dimensions (W x H x D)	53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in)
Weight	650 g
Type of mounting	DIN-Rail

Environmental Limits

Operating Temperature	Standard models: -10 to 60 °C (14 to 140 °F) Models with extended temperature range: -40 to 75 °C (-40 to 167 °F)
-----------------------	--

Storage Temperature	-40 to 85 °C (-40 to 185 °F)
---------------------	------------------------------

Ambient Relative Humidity	5 to 95 % (non-condensing)
---------------------------	----------------------------

Regulatory Approvals

Safety	UL 508, UL 60950-1, CSA C22.2 No. 60950-1, EN60950-1
Hazardous Location	UL/cUL Class I, Division 2, Groups A, B, C and D
EMC	EN 55032/24 CISPR 32, FCC Part 15B Class A IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8
Maritime	DNV GL
Shock	IEC 60068-2-27

Regulatory Approvals

Freefall	IEC 60068-2-32
Vibration	IEC 60068-2-6

MTBF (mean time between failures)

Time	1,547,941 hrs
Database	Telcordia (Bellcore), GB

Warranty

Warranty Period	5 years
-----------------	---------

Ordering data

Version	Model Type	Operating Temperature	Order No.
5 * RJ45	IE-SW-VL05M-5TX	-10 to +60 °C	1504280000
5 * RJ45	IE-SW-VL05MT-5TX	-40 to +75 °C	1504310000

Accessories

	Model Type	Order No.
External Backup and Restore Module	EBR-Module RS232	1241430000
19" Rack Mounting Kit	RM-KIT	1241440000

8-Port managed Fast Ethernet Switches

- Supports the automation protocols Modbus/TCP, PROFINET RT and EtherNet/IP
- Turbo Ring and Turbo Chain with fast recovery time (<20 ms for up to 250 switches)
- IGMP snooping, QoS, port- and tag-based VLAN
- Configurable error messages via SNMP trap, e-mail or relay output
- User-friendly, web-based configuration and management



EtherNet/IP™

ModbusTCP

C

Technical data**Standards**

IEEE 802.3 for 10BaseT ■ IEEE 802.3u for 100BaseT(X) and 100BaseFX ■ IEEE 802.3x for Flow Control
 ■ IEEE 802.1D-2004 for Spanning Tree Protocol ■ IEEE 802.1w for Rapid STP ■ IEEE 802.1p for Class of Service
 ■ IEEE 802.1Q for VLAN Tagging

Protocols

IGMPv1/v2 ■ GMRP ■ GVRP ■ SNMPPv1/v2c/v3 ■ DHCP Server/Client ■ TFTP ■ SNTP ■ SMTP ■ RARP
 ■ RMON ■ HTTP ■ Telnet ■ Syslog ■ DHCP Option 66/67/82 ■ BootP ■ LLDP ■ Modbus/TCP ■ PROFINET RT
 (PROFINET-Io device in compliance with Conformance Class B) ■ EtherNet/IP (CIP support) ■ IPv6

MIB

MIB-II ■ Ethernet-like MIB ■ P-BRIDGE MIB ■ Bridge MIB ■ RSTP MIB ■ RMON MIB Group 1, 2, 3, 9
 ■ Private MIB

Flow Control

IEEE 802.3x flow control ■ back pressure flow control

Switch Properties

MAC Table Size	8K
Packet Buffer Size	1 MBit

Interface

Fibre Ports	100BaseFX (SC/ST-duplex connection)		
RJ45 Ports	10/100BaseT(X) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection		
Console Port	RS 232 (RJ45 connector)		
DIP Switches	Turbo Ring, Master, Coupler, Reserve		
Alarm Contact	1 relay output with current carrying capacity of 1 A at 24 V DC		

Specification optical fiber

Transceiver Type	100Base FX		
	Multi-Mode	Single-Mode	
Fiber Cable Type	OM1	50/125 µm 800 MHz•km	G.652
Typical Distance	4 km	5 km	40 km
Wave-length	Typical (nm)	1300	1310
	TX Range (nm)	1260 to 1360	1280 to 1340
	RX Range (nm)	1100 to 1600	1100 to 1600
Optical Power	TX Range (dBm)	-10 to -20	0 to -5
	RX Range (dBm)	-3 to -32	-3 to -34
	Link-Budget (dB)	12	29
	Dispersion Penalty (dB)	3	1

Note: When connecting a single-mode fiber transceiver over a short distance, we recommend using an attenuator to prevent the transceiver from being damaged by excessive optical power.

Power Requirements

Input Voltage	12/24/48 V DC (9.6 to 60 V DC), two redundant inputs		
Input Current	IE-SW-VL08M-8TX: 0.18 A at 24 V IE-SW-VL08M-6TX-2ST/2SC/2SCS: 0.30 A at 24 V IE-SW-VL08MT-5TX-1SC-2SCS: 0.35 A at 24 V		
Overload Current Protection	Present		
Connection	1 removable 6-contact terminal block		

Reverse Polarity Protection Present

Physical Characteristics

Housing	Metal, IP30 protection		
Dimensions (W x H x D)	53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in)		
Weight	IE-SW-VL08MT-8TX/6TX-2SC/6TX-2ST/6TX-2SCS: 650 g IE-SW-VL08MT-5TX-1SC-2SCS: 890 g		

Physical Characteristics

Type of mounting DIN-Rail

Environmental Limits

Operating Temperature -40 to 75 °C (-40 to 167 °F)

Storage Temperature -40 to 85 °C (-40 to 185 °F)

Ambient Relative Humidity 5 to 95 % (non-condensing)

Regulatory Approvals

Safety UL 508, UL 60950-1*

Hazardous Location UL/cUL Class I, Division 2, Groups A, B, C and D*;
ATEX Zone 2 Ex nA nC IIC T4 Gc*

EMC EN 55032/24

CISPR 32, FCC Part 15B Class A

IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV

IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m

IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV

IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV

IEC 61000-4-6 CS: 10 V

IEC 61000-4-8

Maritime DNV-GL*

Shock IEC 60068-2-27

Freefall IEC 60068-2-32

Vibration IEC 60068-2-6

MTBF (mean time between failures)

Time 1,339,439 hrs / 1,253,072 hrs model IE-SW-VL08MT-5TX-1SC-2SCS

Database Telcordia (Bellcore), GB

Warranty

Warranty Period 5 years

Ordering data

Version	Model Type	Operating Temperature	Order No.
8 * RJ45	IE-SW-VL08MT-8TX	-40 to +75 °C	1240940000
5 * RJ45, 1 * SC-Multimode, 2 * SC-Singlemode	IE-SW-VL08MT-5TX-1SC-2SCS	-40 to +75 °C	1345240000
6 * RJ45, 2 * ST-Multimode	IE-SW-VL08MT-6TX-2ST	-40 to +75 °C	1240990000
6 * RJ45, 2 * SC-Multimode	IE-SW-VL08MT-6TX-2SC	-40 to +75 °C	1344770000
6 * RJ45, 2 * SC-Singlemode	IE-SW-VL08MT-6TX-2SCS	-40 to +75 °C	1241020000

Accessories

Model Type	Order No.
External Backup and Restore Module	1241430000
19" Rack Mounting Kit	1241440000

Note

* does not apply to model IE-SW-VL08MT-5TX-1SC-2SCS

16-Port managed Fast Ethernet Switches

- Supports the automation protocols Modbus/TCP, PROFINET RT and EtherNet/IP
- Plug-n-play Turbo Ring and Turbo Chain (<20 ms for up to 250 switches)
- IEEE 1588 PTP, Modbus/TCP, LLDP, SNMP Inform, QoS, IGMP snooping, VLAN, IEEE 802.1X, HTTPS, SNMPv3, and SSH supported



EtherNet/IP™ **ModbusTCP**

Technical data**Standards**

- IEEE 802.3 for 10BaseT ■ IEEE 802.3u for 100BaseT (X) ■ IEEE 802.3x for Flow Control
- IEEE 802.1D-2004 for Spanning Tree Protocol ■ IEEE 802.1w for Rapid STP
- IEEE 802.1Q for VLAN Tagging ■ IEEE 802.1p for Class of Service ■ IEEE 802.1X for Authentication
- IEEE 802.3ad for Port Trunk with LACP

Protocols

- IGMPv1/v2 ■ GVRP ■ SNMPv1/v2c/v3 ■ DHCP Server/Client ■ BootP ■ TFTP ■ SNTP ■ SMTP ■ RARP
- GMRP ■ LACP ■ RMON ■ HTTP ■ HTTPS ■ Telnet ■ Syslog ■ DHCP Option 66/67/82 ■ SSH ■ SNMP Inform
- Modbus/TCP ■ PROFINET RT (PROFINET-IO device in compliance with Conformance Class B)
- EtherNet/IP (CIP support) ■ LLDP ■ IEEE 1588 PTP ■ IPv6

MIB

- MIB-II ■ Ethernet-Like MIB ■ P-BRIDGE MIB ■ Q-BRIDGE MIB ■ Bridge MIB ■ RSTP MIB
- RMON MIB Group 1, 2, 3, 9 ■ Private MIB

Flow Control

- IEEE 802.3x flow control ■ back pressure flow control

Switch Properties

Priority Queues	4
Max. Number of Available VLANs	64
VLAN ID Range	VID 1 to 4094
IGMP Groups	256
MAC Table Size	8 K
Packet Buffer Size	2 Mbit
Interface	
RJ45 Ports	10/100BaseT(X) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection
Console Port	RS 232 (RJ45 connector)
Alarm Contact	2 relay outputs with a current carrying capacity from 1 A at 24 V DC
Digital Inputs	2 inputs with the same ground, electrically isolated <ul style="list-style-type: none"> +13 to +30 V for state "1" -30 to +3 V for state "0" Max. input current: 8 mA

Power Requirements

Input Voltage	24 V DC (12 to 45 V DC), two redundant inputs
Input Current	0.41 A at 24 V
Overload Current Protection	Present
Connection	2 removable 6-contact terminal blocks
Reverse Polarity Protection	Present

Physical Characteristics

Housing	Metal, IP30 protection
Dimensions (W x H x D)	94 x 135 x 142.7 mm (3.7 x 5.31 x 5.62 in)
Weight	1586 g
Type of mounting	DIN-Rail

Environmental Limits

Operating Temperature	Standard Models: 0 to 60 °C (32 to 140 °F) Wide Temp. Models: -40 to 75 °C (-40 to 167 °F)
Storage Temperature	-40 to 85 °C (-40 to 185 °F)
Ambient Relative Humidity	5 to 95 % (non-condensing)
Regulatory Approvals	

Safety UL 508, UL 60950-1, CSA C22.2 No. 60950-1, EN60950-1

Regulatory Approvals

Hazardous Location	UL/cUL Class I, Division 2, Groups A, B, C and D; ATEX Zone 2 Ex nA nC IIC T4 Gc
--------------------	---

EMI FCC Part 15, CISPR (EN55022) class A

EMC EN61000-4-2 (ESD) level 2;

EN61000-4-3 (RS) level 3;

EN61000-4-4 (EFT) level 3;

EN61000-4-5 (Surge) level 3;

EN61000-4-6 (CS) level 3;

EN61000-4-8

Maritime DNV-GL

Shock IEC 60068-2-27

Freefall IEC 60068-2-32

Vibration IEC 60068-2-6

MTBF (mean time between failures)

Time 247,000 hrs

Database Telcordia (Bellcore), GB

Warranty

Warranty Period 5 years

Ordering data

Version	Model Type	Operating Temperature	Order No.
16 * RJ45	IE-SW-PL16M-16TX	0 to 60 °C	1241100000
	IE-SW-PL16MT-16TX	-40 to +75 °C	1286820000

8 to 18-Port managed Fast/Gigabit Ethernet Switches

- Extensive set of management features enable the set-up of various redundancy, monitoring, traffic filter and security functions
- Suitable for use in harsh industrial environment thanks to rugged design and wide operating temperature range of -40°C up to 75°C
- SFP-ports for fiber optic transmission over long distances

**Technical data****Technology**

Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX and 100BASE-FX IEEE 802.3ab for 1000BASE-T IEEE 802.3z for 1000BASE-X IEEE 802.3x for flow control IEEE 802.3ad for port trunk with LACP IEEE 802.1D for the Spanning Tree protocol (STP) IEEE 802.1w for Rapid Spanning Tree protocol (RSTP) IEEE 802.1s for Multiple Spanning Tree Protocol (MSTP) IEEE 802.1p for Class of Service IEEE 802.1Q for VLAN Tagging IEEE 802.1X for Authentication IEEE 802.1AB for Link Layer Discovery Protocol (LLDP)
-----------	--

Processing type

Store and Forward

Flow control

IEEE 802.3x flow control

Switch characteristics

MAC table size	8K
Packet buffer Size	1 Mbit
Priority queues	4
Number of available VLANs	4095 (1 to 4094)

IGMP groups

1024

Management features

Device configuration	Webbrowser (HTTP/HTTPS), SNMP v1/v2c/v3, Telnet console, CLI, Local serial console port, Upload of a configuration file via web-interface or TFTP-Server
Monitoring function	SNMP v1/v2c/v3, LLDP, Port mirroring, Port statistics, Port monitoring, Syslog, RMON, Event based warning via E-Mail, relay, SNMP trap
Network redundancy	STP, RSTP, MSTP, LACP, O-Ring, O-Chain, Fast recovery
Network traffic filter	Quality of Service (QoS), Differentiated Services Code Point (DSCP), Port based VLAN, Tag based VLAN, IGMP v2/v3, Multicast VLAN Registration (MVR), Traffic Rate Limiting
IP-address management	Static, DHCP-Client, DHCP-Server (port based, pool-based), DHCP Option 82, DHCP-Relay
Security functions	VLAN segmentation, Enable/disable ports, TACACS+ and IEEE 802.1X, User Authentication, Access control (Port based via IEEE 802.1X), Access Control List (IP-based, MAC-based), Management access security via secure IP-list and configuration of allowed access methods (web-interface, telnet, SSH), Loop protection
Time synchronization management	NTP server, SNTP client

Industrial protocol support	PROFINET device acc. to conformance class A, Modbus/TCP slave
-----------------------------	---

Interfaces

RJ45 ports	10/100BaseT(X) or 10/100/1000BaseT(X), auto negotiation, Full/half-duplex mode, Auto MDI/MDI-X port
Fibre optic ports	100/1000BaseSFP-slot

Serial console port	RS-232 (RJ45 connector)
Relay Contact	1 relay output with a current capacity of 1 A at 24 V DC

Reset button	< 5 sec: System reboot ; > 5 sec: Factory default
--------------	---

Power supply

Connection type	IE-SW-AL08M-6TX-2GT: 1 removable 7-pin terminal block IE-SW-AL10M-8TX-2GC: 1 removable 6-pin terminal block IE-SW-AL18M-16TX-2GC: 1 removable 6-pin terminal block
-----------------	--

Input voltage	24 V DC (12 - 48 V), 2 redundant inputs
Current consumption at 24 V	IE-SW-AL08M-6TX-2GT: 0.41 A IE-SW-AL10M-8TX-2GC: 0.45 A IE-SW-AL18M-16TX-2GC: 0.6 A

Power supply

Overload current protection	yes
Reverse polarity protection	yes

Physical characteristics

Housing main material	Metal
Protection degree	IP30

Type of mounting	DIN rail
Dimensions (W x H x D)	IE-SW-AL08M-6TX-2GT: 54.2 x 145.4 x 107.1 mm (2.13 x 5.72 x 4.21 in) IE-SW-AL10M-8TX-2GC: 74.3 x 153.6 x 107.5 mm (2.93 x 6.05 x 4.2 in) IE-SW-AL18M-16TX-2GC: 96.4 x 154 x 108.5 mm (3.8 x 6.06 x 4.27 in)

Weight	IE-SW-AL08M-6TX-2GT: 789 g IE-SW-AL10M-8TX-2GC: 1140 g IE-SW-AL18M-16TX-2GC: 1281 g
--------	---

Environmental conditions

Operating temperature	-40 to 75 °C (-40 to 167 °F)
Storage temperature	-40 to 85 °C (-40 to 185 °F)

Humidity	5 to 95 % (non-condensing)
----------	----------------------------

Operating altitude	≤ 2000 m
--------------------	----------

EMC conformity and approvals

EMC	EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 4 kV, Air: 8 kV IEC 61000-4-3 RS: 80 MHz bis 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 0.5 kV, Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 0.5 kV, Signal: 1 kV IEC 61000-4-6 CS: 3 Vrms
-----	---

Safety	UL 61010-1, UL 61010-2-201
--------	----------------------------

Shock	IEC 60068-2-27
-------	----------------

Vibration	IEC 60068-2-6
-----------	---------------

Free fall	IEC 60068-2-31
-----------	----------------

MTBF

Time	IE-SW-AL08M-6TX-2GT: 798,350 hrs IE-SW-AL10M-8TX-2GC: 366,529 hrs IE-SW-AL18M-16TX-2GC: 600,504 hrs
------	---

Database	Telcordia SR332
----------	-----------------

Guarantee	5 years
-----------	---------

Ordering Information

Version	Model Type	Order No.
6x RJ45 10/100 Mbit/s, 2x RJ45 10/100/1000 Mbit/s	IE-SW-AL08M-6TX-2GT	2682290000
8x RJ45 10/100 Mbit/s, 2x combo-ports usable as RJ45 10/100/1000 Mbit/s	IE-SW-AL10M-8TX-2GC	2740420000
16x RJ45 10/100 Mbit/s, 2x combo-ports usable as RJ45 10/100/1000 Mbit/s	IE-SW-AL18M-16TX-2GC	2682330000

Accessories

	Model Type	Order No.
19" Rack Mounting Kit	RM-KIT	1241440000

Note

Corresponding SFP modules for AdvancedLine switches, see page I.4 - I.5.

10-Port managed Fast/Gigabit Ethernet Switches

- Supports the automation protocols Modbus/TCP, PROFINET RT and EtherNet/IP
- 2 Gigabit Ethernet ports for redundant ring and 1 Gigabit Ethernet port for uplink solution
- Ring redundancy with fast recovery time (< 20 ms for up to 250 switches)
- IEEE 1588 PTP, LLDP, SNMP Inform, QoS, IGMP snooping, VLAN, IEEE 802.1X, HTTPS, SNMPv3, and SSH supported



EtherNet/IP™ ModbusTCP

Technical data**Standards**

- IEEE 802.3 for 10BaseT ■ IEEE 802.3u for 100BaseT (X) ■ IEEE 802.3ab for 1000BaseT(X)
- IEEE 802.3x for Flow Control ■ IEEE 802.1D-2004 for Spanning Tree Protocol ■ IEEE 802.1w for Rapid STP
- IEEE 802.1Q for VLAN Tagging ■ IEEE 802.1p for Class of Service ■ IEEE 802.1X for Authentication
- IEEE 802.3ad for Port Trunk with LACP

Protocols

- IGMPv1/v2 ■ GMRP ■ GVRP ■ SNMPv1/v2c/v3 ■ DHCP Server/Client ■ BootP ■ TFTP ■ SNTP ■ SMTP
- RARP ■ RMON ■ HTTP ■ HTTPS ■ Telnet ■ Syslog ■ DHCP Option 66/67/82 ■ SSH ■ SNMP Inform
- Modbus/TCP ■ PROFINET RT (PROFINET-IO device in compliance with Conformance Class B)
- EtherNet/IP (CIP support) ■ LLDP ■ IEEE 1588 PTP ■ IPv6

MIB

- MIB-II ■ Ethernet-Like MIB ■ P-BRIDGE MIB ■ Q-BRIDGE MIB ■ Bridge MIB ■ RSTP MIB
- RMON MIB Group 1, 2, 3, 9 ■ Private MIB

Flow Control

- IEEE 802.3x flow control ■ back pressure flow control

Switch Properties

Priority Queues	4
Max. Number of Available VLANs	64
VLAN ID Range	VID 1 to 4094
IGMP Groups	256
MAC Table Size	8 K
Packet Buffer Size	1 MBit
Interface	
RJ45 Ports	10/100BaseT(X) oder 10/100/1000BaseT(X) auto negotiation
Console Port	RS 232 (RJ45 connector)
DIP Switches	Turbo-Ring, Master, Coupler, Reserve
Alarm Contact	2 relay outputs with a current carrying capacity from 1 A at 24 V DC
Digital Inputs	2 inputs with the same ground, but electrically isolated from the electronics <ul style="list-style-type: none"> +13 to +30 V for state "1" -30 to +3 V for state "0" Max. input current: 8 mA

Power Requirements

Input Voltage	24 V DC (12 to 45 V DC), two redundant inputs
Input Current	0.48 A at 24 V
Overload Current Protection	Present
Connection	2 removable 6-contact terminal blocks
Reverse Polarity Protection	Present
Physical Characteristics	
Housing	Metal, IP30 protection
Dimensions (W x H x D)	80.2 x 135 x 105 mm (3.16 x 5.31 x 4.13 in)
Weight	1170 g
Type of mounting	DIN-Rail

Environmental Limits

Operating Temperature	Standard Models: -10 to 60 °C (32 to 140 °F); Wide Temp. Models: -40 to 75 °C (-40 to 167 °F)
Storage Temperature	-40 to 85 °C (-40 to 185 °F)
Ambient Relative Humidity	5 to 95 % (non-condensing)

Regulatory Approvals

Safety	UL 508, UL 60950-1, CSA C22.2 No. 60950-1, EN 60950-1
Hazardous Location	UL/cUL Class I, Division 2, Groups A, B, C and D; ATEX Zone 2 Ex nA nC IIC T4 Gc
EMC	EN 55032/24 CISPR 32, FCC Part 15B Class A IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-32
Vibration	IEC 60068-2-6

MTBF (mean time between failures)

Time	977,099 hrs
Database	Telcordia (Bellcore), GB

Warranty

Warranty Period	5 years
-----------------	---------

Ordering data

Version	Model Type	Operating Temperature	Order No.
3 * RJ45 10/100/1000BaseT(X), 7 * RJ45 10/100BaseT(X)	IE-SW-PL10M-3GT-7TX IE-SW-PL10MT-3GT-7TX	-10 to 60 °C -40 to +75 °C	1241290000 1286930000

Accessories

	Model Type	Order No.
External Backup and Restore Module	EBR-Modul RS232	1241430000
19" Rack Mounting Kit	RM-KIT	1241440000

18-Port managed Fast/Gigabit Ethernet Switches

- Supports the automation protocols Modbus/TCP, PROFINET RT and EtherNet/IP
- 2 Gigabit Ethernet ports plus 16 Fast Ethernet ports for copper and fibre
- Ring redundancy with rapid recovery time (< 20 ms for up to 250 switches)
- IEEE 1588 PTP, LLDP, SNMP Inform, QoS, IGMP snooping, VLAN, IEEE 802.1X, HTTPS, SNMPv3, and SSH supported



EtherNet/IP™ **ModbusTCP**

Technical data**Standards**

- IEEE 802.3 for 10BaseT • IEEE 802.3u for 100BaseT(X) • IEEE 802.3ab for 1000BaseT(X)
- IEEE 802.3z for 1000BaseX IEEE 802.3x for Flow Control • IEEE 802.1D-2004 for Spanning Tree Protocol
- IEEE 802.1w for Rapid STP • IEEE 802.1Q for VLAN Tagging • IEEE 802.1p for Class of Service
- IEEE 802.1X for Authentication • IEEE 802.3ad for Port-Trunk mit LACP

Protocols

- IGMPv1/v2 • GMRP, GVRP • SNMPv1/v2c/v3 • DHCP Server/Client • BootP • TFTP • SNTP • SMTP • RARP
- RMON • HTTP • HTTPS • Telnet • Syslog • DHCP-Option 66/67/82 • SSH • SNMP Inform • Modbus/TCP
- PROFINET RT (PROFINET-Io device in compliance with Conformance Class B) • EtherNet/IP (CIP support)
- LLDP • IEEE 1588 PTP • IPv6

MIB

- MIB-II • Ethernet-like MIB • P-BRIDGE MIB • Q-BRIDGE MIB • Bridge MIB • RSTP MIB
- RMON MIB Group 1, 2, 3, 9 • Private MIB

Flow Control

- IEEE 802.3x flow control • back pressure flow control

Switch Properties

Priority Queues	4
Max. Number of Available VLANs	64
VLAN ID Range	VID 1 to 4094
IGMP Groups	256
MAC Table Size	8 K
Packet Buffer Size	2 MBit
Interface	
Fibre Ports	1000BaseSFP (100BaseSFP modules are not supported)
RJ45 Ports	10/100BaseT(X) or 10/100/1000BaseT(X) auto negotiation
Console Port	RS 232 (RJ45 connector)
Alarm Contact	2 relay outputs with a current carrying capacity from 1 A at 24 V DC
Digital Inputs	2 inputs with the same ground, but electrically isolated from the electronics.
	<ul style="list-style-type: none"> +13 to +30 V for state "1" -30 to +3 V for state "0" Max. input current: 8 mA

Power Requirements

Input Voltage	24 V DC (12 to 45 V DC), redundant dual inputs
Input Current	0.51 A at 24 V
Overload Current Protection	Present
Connection	2 removable 6-contact terminal blocks
Reverse Polarity Protection	Present
Physical Characteristics	
Housing	Metal, IP30 protection
Dimensions (W x H x D)	94 x 135 x 142.7 mm (3.7 x 5.31 x 5.62 in)
Weight	1630 g
Type of mounting	DIN-Rail

Environmental Limits

Operating Temperature	Standard Models: 0 to 60 °C (32 to 140 °F) Wide Temp. Models: -40 to 75 °C (-40 to 167 °F)
Storage Temperature	-40 to 85 °C (-40 to 185 °F)
Ambient Relative Humidity	5 to 95 % (non-condensing)

Regulatory Approvals

Safety	UL 508, UL 60950-1, CSA C22.2 No. 60950-1, EN 60950-1
Hazardous Location	UL/cUL Class I, Division 2, Groups A, B, C and D; ATEX Zone 2 Ex nA nC IIC T4 Gc
EMC	FCC Part 15, CISPR (EN55022) Class A EN61000-4-2 (ESD), level 2; EN61000-4-3 (RS), level 3; EN61000-4-4 (EFT), level 2; EN61000-4-5 (Surge), level 3; EN61000-4-6 (CS), level 3; EN61000-4-8; EN61000-4-12
Maritime	DNV-GL
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-32
Vibration	IEC 60068-2-6
MTBF (mean time between failures)	
Time	240,000 hrs
Database	Telcordia (Bellcore), GB
Warranty	
Warranty Period	5 years

Ordering data

Version	Model Type	Operating Temperature	Order No.
16 * RJ45 10/100BaseT(X), 2 * Combo Port (10/100/1000BaseT(X) or 1000BaseSFP)	IE-SW-PL18M-2GC-16TX IE-SW-PL18MT-2GC-16TX	0 to +60 °C -40 to +75 °C	1241320000 1286970000
14 * RJ45 10/100BaseT(X), 2 * SC-Singlemode 100BaseFX, 2 * Combo Port (10/100/1000BaseT(X) or 1000BaseSFP)	IE-SW-PL18M-2GC14TX2SCS IE-SW-PL18MT-2GC14TX2SCS	0 to +60 °C -40 to +75 °C	1241350000 1287010000

Note

Corresponding SFP modules for PremiumLine switches, see page I.7

Managed Switches Gigabit Ethernet – AdvancedLine

8 to 24-Port managed Gigabit Ethernet Switches

- Extensive set of management features enable the set-up of various redundancy, monitoring, traffic filter and security functions
- Suitable for use in harsh industrial environment thanks to rugged design and wide operating temperature range of -40°C up to 75°C
- SFP-ports for fiber optic transmission over long distances
- Gigabit Ethernet including Jumbo Frame support for applications with high demand on bandwidth and latency

available
Q3 2021

Technical data

Technology

Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX and 100BASE-FX IEEE 802.3ab for 1000BASE-T IEEE 802.3z for 1000BASE-X IEEE 802.3x for flow control IEEE 802.3ad for port trunk with LACP IEEE 802.1D for the Spanning Tree protocol (STP) IEEE 802.1w for Rapid Spanning Tree protocol (RSTP) IEEE 802.1s for Multiple Spanning Tree Protocol (MSTP) IEEE 802.1p for Class of Service IEEE 802.1Q for VLAN Tagging IEEE 802.1X for Authentication IEEE 802.1AB for Link Layer Discovery Protocol (LLDP) IEEE 1588 PTPv2 for time synchronization
Processing type	Store and Forward

Switch characteristics

MAC table size	8K
Packet buffer Size	4 Mbit
Jumbo frame support	up to 9.6 KB
Priority queues	8
Number of available VLANs	4096 (1 to 4095)
IGMP groups	256 per VLAN
Management features	
Device configuration	Webbrowser (HTTP/HTTPS), SNMP v1/v2c/v3, Telnet console, CLI, Local serial console port, Upload of a configuration file via web-interface, TFTP-Server or external backup module
Monitoring function	SNMP v1/v2c/v3, LLDP, Port mirroring, Port statistics, Port monitoring, Syslog, RMON, Event based warning via E-Mail, relay, SNMP trap, Ethernet cable diagnostics on RJ-45 ports
Network redundancy	STP, RSTP, MSTP, LACP, O-Ring, O-Chain, Fast recovery
Network traffic filter	Quality of Service (QoS), Tag based VLAN, IGMP v2/v3, Traffic Rate Limiting
IP-address management	Static, DHCP-Client, DHCP-Server (port based, pool-based), DHCP Option 82, DHCP-Relay
Security functions	VLAN segmentation, Enable/disable ports, TACACS+ and IEEE 802.1X User Authentication, DoS/DDoS auto prevention, Access Control List (IP-based, MAC-based), Loop protection, Management access security via privilege level configuration for different user roles
Time synchronization management	SNTP server, SNTP client, PTPv2 (for IE-SW-AL14M-12GT-2GESFP and IE-SW-AL24M-16GT-8GESFP only)
Industrial protocol support	PROFINET device acc. to conformance class A, Modbus/TCP slave, EtherNet/IP

Interfaces

RJ45 ports	10/100/1000BaseT(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port
Fibre optic ports	100/1000BaseSFP-slot
Serial console port	RS-232 (RJ45 connector)
Relay Contact	1 relay output with a current capacity of 1 A at 24 V DC
Reset button	< 5 sec: System reboot ; > 5 sec: Factory default
Power supply	
Connection type	1 removable 6-pin terminal block
Input voltage	24 V DC (12 - 48 V), 2 redundant inputs
Current consumption at 24 V	IE-SW-AL08M-8GT: 0.55 A IE-SW-AL12M-8GT-4GESFP: 0.54 A IE-SW-AL14M-12GT-2GESFP: 0.53 A IE-SW-AL24M-16GT-8GESFP: 0.84 A



Power supply

Overload current protection	yes
Reverse polarity protection	yes

Physical characteristics

Housing main material	Metal
Protection degree	IP30
Type of mounting	DIN rail
Dimensions (W x H x D)	IE-SW-AL08M-8GT: 54.3 x 145.1 x 108.3 mm (2.13 x 5.71 x 4.26 in) IE-SW-AL12M-8GT-4GESFP: 54.3 x 145.1 x 108.3 mm (2.13 x 5.71 x 4.26 in) IE-SW-AL14M-12GT-2GESFP: 74.3 x 153.6 x 109.2 mm (2.93 x 6.05 x 4.3 in) IE-SW-AL24M-16GT-8GESFP: 96.4 x 154.0 x 108.5 mm (3.8 x 6.06 x 4.27 in)
Weight	IE-SW-AL08M-8GT: 810 g IE-SW-AL12M-8GT-4GESFP: 779 g IE-SW-AL14M-12GT-2GESFP: 1039 g IE-SW-AL24M-16GT-8GESFP: 1319 g

Environmental conditions

Operating temperature	-40 to 75 °C (-40 to 167 °F)
Storage temperature	-40 to 85 °C (-40 to 185 °F)
Humidity	5 to 95 % (non-condensing)
Operating altitude	≤ 2000 m

EMC conformity and approvals

EMC	EN 55023, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz bis 1 Ghz: 3 V/m IEC 61000-4-4 EFT: Power: 0.5 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 0.5 kV; Signal: 1 kV IEC 61000-4-6 CS: 3 Vrms
Safety	UL 61010-1, UL 61010-2-201
Shock	IEC 60068-2-27
Vibration	IEC 60068-2-6
Free fall	IEC 60068-2-31

MTBF

Time	IE-SW-AL08M-8GT: 508,672 hrs IE-SW-AL12M-8GT-4GESFP: 551,478 hrs IE-SW-AL14M-12GT-2GESFP: 713,154 hrs IE-SW-AL24M-16GT-8GESFP: 507,660 hrs
Database	Telcordia SR332

Guarantee

Time interval	5 years
---------------	---------

Ordering Information

Version	Model Type	Order No.
8x RJ45 10/100/1000 Mbit/s	IE-SW-AL08M-8GT	2682350000
8x RJ45 10/100/1000 Mbit/s, 4x SFP 100/1000 Mbit/s	IE-SW-AL12M-8GT-4GESFP	2682340000
12x RJ45 10/100/1000 Mbit/s, 2x SFP 100/1000 Mbit/s	IE-SW-AL14M-12GT-2GESFP	2682360000
16x RJ45 10/100/1000 Mbit/s, 8x SFP 100/1000 Mbit/s	IE-SW-AL24M-16GT-8GESFP	2682370000

Accessories

	Model Type	Order No.
19" Rack Mounting Kit	RM-KIT	1241440000
Configuration backup and restore module	IE-EBR-MODULE-RS232-ALM	2682610000

Note

Corresponding SFP modules for AdvancedLine switches, see page I.4 – I.5.

6 and 8-Port managed PoE+ Gigabit Ethernet Switches

- IEEE 802.3af/at compliant PoE ports
- Integrated DC/DC converter for providing PoE voltage to PDs over the entire PSE input voltage range from 12 to 57 V DC
- Gigabit Ethernet on all ports including Jumbo Frame support for applications with high demand on bandwidth and latency
- SFP-ports for fiber optic transmission over long distances
- Gigabit Ethernet including Jumbo Frame support for applications with high demand on bandwidth and latency



similar to illustration

**Technical data****Technology**

Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX and 100BASE-FX IEEE 802.3ab for 1000BASE-T IEEE 802.3z for 1000BASE-X IEEE 802.3x for flow control IEEE 802.3ad for port trunk with LACP IEEE 802.1D for the Spanning Tree protocol (STP) IEEE 802.1w for Rapid Spanning Tree protocol (RSTP) IEEE 802.1s for Multiple Spanning Tree Protocol (MSTP) IEEE 802.1p for Class of Service IEEE 802.1Q for VLAN Tagging IEEE 802.1X for Authentication IEEE 802.1AB for Link Layer Discovery Protocol (LLDP) IEEE 802.3at/af for Power-over-Ethernet
Processing type	Store and Forward
Flow control	IEEE 802.3x flow control
Switch characteristics	
MAC table size	8K
Packet buffer Size	4 Mbit
Jumbo frame support	up to 9.6 KB
Priority queues	8
Number of available VLANs	4096 (1 to 4095)
IGMP groups	256 per VLAN
Management features	
Device configuration	Webbrowser (HTTP/HTTPS), SNMP v1/v2c/v3, Telnet console, CLI, Local serial console port, Upload of a configuration file via web-interface, TFTP-Server or external backup module
Monitoring function	SNMP v1/v2c/v3, LLDP, Port mirroring, Port statistics, Port monitoring, Syslog, RMON, Event based warning via E-Mail, relay, SNMP trap, Ethernet cable diagnostics on RJ-45 ports
Network redundancy	STP, RSTP, MSTP, LACP, O-Ring, O-Chain, Fast recovery
Network traffic filter	Quality of Service (QoS), Tag based VLAN, IGMP v2/v3, Traffic Rate Limiting
IP-address management	Static, DHCP-Client, DHCP-Server (port based, pool-based), DHCP Option 82, DHCP-Relay
Security functions	VLAN segmentation, Enable/disable ports, TACACS+ and IEEE 802.1X User Authentication, DoS/DDoS auto prevention, Access Control List (IP-based, MAC-based), Loop protection, Management access security via privilege level configuration for different user roles
Time synchronization management	SNTP server, SNTP client
Industrial protocol support	PROFINET device acc. to conformance class A, Modbus/TCP slave, EtherNet/IP
Interfaces	
RJ45 ports	10/100/1000BaseT(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port
Fibre optic ports	100/1000BaseSFP-slot
Serial console port	RS-232 (RJ45 connector)
Relay Contact	1 relay output with a current capacity of 1 A at 24 V DC
Reset button	< 5 sec: System reboot; > 5 sec: Factory default
Power supply	
Connection type	1 removable 6-pin terminal block
Input voltage	12/24/48 V DC (12 - 57 V), 2 redundant inputs

Power supply

Current consumption at 24 V (with PD consumption)	IE-SW-AL06M-4GTPoE-2GESFP: 5.4 A IE-SW-AL08M-8GTPoE: 5.32 A
Overload current protection	yes
Reverse polarity protection	yes

Power over Ethernet (PoE)

PoE pin assignment	Mode A: Pin 1, 2 (V+); Pin 3, 6 (V-); Alternative A; MDI
Total PoE power budget	60 W at 12 - 23 V DC; 120 W at 24 - 57 V DC

Physical characteristics

Housing main material	Metal
Protection degree	IP30
Type of mounting	DIN rail
Dimensions (W x H x D)	54.3 x 145.1 x 108.5 (2.13 x 5.71 x 4.27 in)
Weight	IE-SW-AL06M-4GTPoE-2GESFP: 975 g IE-SW-AL08M-8GTPoE: 985 g

Environmental conditions

Operating temperature	-40 to 75 °C (-40 to 167 °F)
Storage temperature	-40 to 85 °C (-40 to 185 °F)
Humidity	5 to 95 % (non-condensing)
Operating altitude	≤ 2000 m

EMC conformity and approvals

EMC	EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 4 kV, Air: 8 kV IEC 61000-4-3 RS: 80 MHz bis 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 0.5 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 0.5 kV; Signal: 1 kV IEC 61000-4-6 CS: 3 Vrms
Safety	UL 61010-1, UL 61010-2-201
Shock	IEC 60068-2-27
Vibration	IEC 60068-2-6
Free fall	IEC 60068-2-31

MTBF

Time	IE-SW-AL06M-4GTPoE-2GESFP: 495,624 hrs IE-SW-AL08M-8GTPoE: 495,670 hrs
Database	Telcordia SR332

Guarantee

Time interval	5 years
---------------	---------

Ordering Information

Version	Model Type	Order No.
4x RJ45 PoE+ 10/100/1000 Mbit/s, 2x SFP 100/1000 Mbit/s	IE-SW-AL06M-4GTPoE-2GESFP	2682430000
8x RJ45 PoE+ 10/100/1000 Mbit/s	IE-SW-AL08M-8GTPoE	2682420000

Accessories

19" Rack Mounting Kit	Model Type	Order No.
RM-KIT		1241440000

Configuration backup and restore module	IE-EBR-MODULE-RS232-ALM
	2682610000

Note

Corresponding SFP modules for AdvancedLine switches, see page I.4 - I.5.

10-Port managed Fast/Gigabit Ethernet Switches

- Meets IEC 61850-3 / IEEE 1613 standards
- Redundant power supply modules
- Extensive set of management features enable the set-up of various redundancy, monitoring, traffic filter and security functions
- Suitable for use in harsh industrial environment thanks to rugged design and wide operating temperature range of -40°C up to 85°C
- SFP-ports for fiber optic transmission over long distances

**available
Q3 2021**

**Technical data**

Technology		
Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX and 100BASE-FX IEEE 802.3ab for 1000BASE-T IEEE 802.3z for 1000BASE-X IEEE 802.3x for flow control IEEE 802.3ad for port trunk with LACP IEEE 802.1D for the Spanning Tree protocol (STP) IEEE 802.1w for Rapid Spanning Tree protocol (RSTP) IEEE 802.1D-2004 for Rapid Spanning Tree Protocol 2004 (RSTP-2004) IEEE 802.1s for MSTP (Multiple Spanning Tree Protocol) IEEE 802.1p for Class of Service IEEE 802.1Q for VLAN Tagging IEEE 802.1X for Authentication IEEE 802.1AB for LLDP (Link Layer Discovery Protocol)	
Processing type	Store and Forward	
Flow control	IEEE 802.3x flow control	
Switch characteristics		
MAC table size	8K	
Packet buffer size	1 Mbit	
Priority queues	4	
Number of available VLANs	4095 (1 to 4094)	
IGMP groups	1024	
Management features		
Device configuration	Webbrowser (HTTP/HTTPS), SNMP v1/v2c/v3, Telnet console, CLI, Local serial console port, Upload of a configuration file via web-interface or TFTP-Server	
Monitoring function	SNMP v1/v2c/v3, LLDP, Port mirroring, Port statistics, Port monitoring, Syslog, RMON, Event based warning via E-Mail, relay, SNMP trap	
Network redundancy	STP, RSTP, MSTP, LACP, O-Ring, O-Chain, Fast recovery	
Network traffic filter	Quality of Service (QoS), Differentiated Services Code Point (DSCP), Port based VLAN, Tag based VLAN, IGMP v2/v3, Multicast VLAN Registration (MVR), Traffic Rate Limiting	
IP-address management	Static, DHCP-Client, DHCP-Server (port based, pool-based), DHCP Option 82, DHCP-Relay	
Security functions	VLAN segmentation, Enable/disable ports, TACACS+ and IEEE 802.1X, User Authentication, Access control (Port based via IEEE 802.1X), Access Control List (IP-based, MAC-based), Management access security via secure IP-list and configuration of allowed access methods (web-interface, telnet, SSH), Loop protection	
Time synchronization management	NTP server, SNTP client	
Industrial protocol support	PROFINET device acc. to conformance class A, Modbus/TCP slave	
Interfaces		
RJ45 ports	10/100BASE-T(X) or 10/100/1000BASE-T(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port	
Fibre optic ports	100/1000BaseSFP-slot	
Serial console port	RS-232 (RJ45 connector)	
Relay Contact	1 relay output with a current capacity of 1 A at 24 V DC	
Reset button	< 5 sec: System reboot ; > 5 sec: Factory default	
Power supply		
Connection type	IE-SW-SL10M-7TX-3GC-HV: 2x 3-pin fork/ring lug connection IE-SW-SL10M-7TX-3GC-LV: 2 removable 2-pin terminal blocks	
Power supply		
Input voltage	IE-SW-SL10M-7TX-3GC-HV: 110/220 V DC (88 - 373 V), 110/220 V AC (85 - 264 V), 2 redundant isolated inputs IE-SW-SL10M-7TX-3GC-LV: 48 V DC (12 - 52 V), 2 redundant inputs	
Power consumption	12 W (max.)	
Overload current protection	yes	
Reverse polarity protection	yes	
Physical characteristics		
Housing main material	Metal	
Protection degree	IP30	
Type of mounting	DIN rail	
Dimensions (W x H x D)	96.4 x 154 x 148.5 mm (3.8 x 6.06 x 5.85 in)	
Weight	IE-SW-SL10M-7TX-3GC-HV: 1935 g IE-SW-SL10M-7TX-3GC-LV: 1415 g	
Environmental conditions		
Operating temperature	-40 to 85 °C (-40 to 185 °F)	
Storage temperature	-40 to 85 °C (-40 to 185 °F)	
Humidity	5 to 95 % (non-condensing)	
Operating altitude	≤ 2000 m	
EMC conformity and approvals		
EMC	EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 4 kV; Signal: 4 kV IEC 61000-4-5 Surge: Power: 4 kV; Signal: 4 kV IEC 61000-4-6 CS: 10 Vrms	
Safety	EN 62368-1	
Substation compliance	IEC 61850-3, IEEE 1613	
Shock	IEC 60870-2-2 class Cm	
Vibration	IEC 60870-2-2 class Cm and Class Bm	
Free fall	IEC 60870-2-2 class Cm	
MTBF		
Time	IE-SW-SL10M-7TX-3GC-HV: 599,113 hrs IE-SW-SL10M-7TX-3GC-LV: 528,570 hrs	
Database	Telcordia SR332	
Guarantee		
Time interval	5 years	
Ordering Information		
Version	Model Type	Order No.
7x RJ45 10/100 Mbit/s, 3x combo-ports usable as RJ45 10/100/1000 Mbit/s or SFP 100/1000Mbit/s,	IE-SW-SL10M-7TX-3GC-HV	2778950000
High Voltage		
7x RJ45 10/100 Mbit/s, 3x combo-ports usable as RJ45 10/100/1000 Mbit/s or SFP 100/1000Mbit/s,	IE-SW-SL10M-7TX-3GC-LV	2778960000
Low Voltage		
Accessories	Model Type	Order No.
19" Rack Mounting Kit	RM-KIT	1241440000
Note		
Corresponding SFP modules for SubstationLine switches, see page I.4 - I.5.		

20-Port managed Gigabit Ethernet Switches

- Meets IEC 61850-3 / IEEE 1613 standards
- Redundant power supply modules
- Extensive set of management features enable the set-up of various redundancy, monitoring, traffic filter and security functions
- Suitable for use in harsh industrial environment thanks to rugged design and wide operating temperature range of -40°C up to 85°C
- SFP-ports for fiber optic transmission over long distances



**available
Q3 2021**

**Technical data****Technology**

Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX and 100BASE-FX IEEE 802.3ab for 1000BASE-T IEEE 802.3z for 1000BASE-X IEEE 802.3x for flow control IEEE 802.3ad for port trunk with LACP IEEE 802.1D for the Spanning Tree protocol (STP) IEEE 802.1w for Rapid Spanning Tree protocol (RSTP) IEEE 802.1s for Multiple Spanning Tree Protocol (MSTP) IEEE 802.1p for Class of Service IEEE 802.1Q for VLAN Tagging IEEE 802.1X for Authentication IEEE 802.1AB for LLDP (Link Layer Discovery Protocol) IEEE 1588 PTPv2 for time synchronization
-----------	--

Processing type

Flow control	Store and Forward
--------------	-------------------

Switch characteristics

MAC table size	8K
Packet buffer Size	4 Mbit
Jumbo frame support	up to 9.6 KB
Priority queues	8
Number of available VLANs	4096 (1 to 4095)
IGMP groups	256 per VLAN

Management features

Device configuration	Webbrowser (HTTP/HTTPS), SNMP v1/v2c/v3, Telnet console, CLI, Local serial console port, Upload of a configuration file via web-interface, TFTP-Server or external backup module
Monitoring function	SNMP v1/v2c/v3, LLDP, Port mirroring, Port statistics, Port monitoring, Syslog, RMON, Event based warning via E-Mail, relay, SNMP trap, Ethernet cable diagnostics on RJ-45 ports
Network redundancy	STP, RSTP, MSTP, LACP, O-Ring, O-Chain, Fast recovery
Network traffic filter	Quality of Service (QoS), Tag based VLAN, IGMP v2/v3, Traffic Rate Limiting
IP-address management	Static, DHCP-Client, DHCP-Server (port based, pool-based), DHCP Option 82, DHCP-Relay
Security functions	VLAN segmentation, Enable/disable ports, TACACS+ and IEEE 802.1X User Authentication, DoS/DDoS auto prevention, Access Control List (IP-based, MAC-based), Loop protection, Management access security via privilege level configuration for different user roles

Time synchronization management

SNTP server, SNTP client, PTPv2

Industrial protocol support

PROFINET device acc. to conformance class A, Modbus/TCP slave, EtherNet/IP
--

Interfaces

RJ45 ports	10/100/1000BASE-T(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port
Fibre optic ports	100/1000BaseSFP-slot
Serial console port	RS-232 (RJ45 connector)
Relay Contact	1 relay output with a current capacity of 1 A at 24 V DC
Reset button	< 5 sec: System reboot ; > 5 sec: Factory default

Power supply

Connection type	IE-SW-SL20M-8GT-12GESFP-HV: 2x 3-pin fork/ring lug connection IE-SW-SL20M-8GT-12GESFP-LV: 2 removable 2-pin terminal blocks
-----------------	--

Power supply

Input voltage	IE-SW-SL20M-8GT-12GESFP-HV: 110/220 V DC (88 - 373 V), 110/220 V AC (85 - 264 V), 2 redundant isolated inputs IE-SW-SL20M-8GT-12GESFP-LV: 48 V DC (12 - 52 V), 2 redundant isolated inputs
Power consumption	23 W (max.)
Overload current protection	yes
Reverse polarity protection	yes

Physical characteristics

Housing main material	Metal
Protection degree	IP30
Type of mounting	DIN rail
Dimensions (W x H x D)	115 x 154 x 159 mm (4.5 x 6.06 x 6.26 in)
Weight	IE-SW-SL20M-8GT-12GESFP-HV: 1870 g IE-SW-SL20M-8GT-12GESFP-LV: 1520 g

Environmental conditions

Operating temperature	-40 to 85 °C (-40 to 185 °F)
Storage temperature	-40 to 85 °C (-40 to 185 °F)
Humidity	5 to 95 % (non-condensing)
Operating altitude	≤ 2000 m

EMC conformity and approvals

EMC	EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 Ghz: 10 V/m IEC 61000-4-4 EFT: Power: 4 kV; Signal: 4 kV IEC 61000-4-6 CS: 10 Vrms EN 62368-1
Substation compliance	IEC 61850-3, IEC 1613
Shock	IEC 60870-2-2 class Cm
Vibration	IEC 60870-2-2 class Cm and Class Bm
Free fall	IEC 60870-2-2 class Cm

MTBF

Time	IE-SW-SL20M-8GT-12GESFP-HV: 421,961 hrs IE-SW-SL20M-8GT-12GESFP-LV: 273,551 hrs
Database	Telcordia SR322
Guarantee	
Time interval	5 years

Ordering Information

Version	Model Type	Order No.
8x RJ45 10/100/1000 Mbit/s, 12x SFP 100/1000 Mbit/s, High Voltage	IE-SW-SL20M-8GT-12GESFP-HV	2778970000
8x RJ45 10/100/1000 Mbit/s, 12x SFP 100/1000 Mbit/s, Low Voltage	IE-SW-SL20M-8GT-12GESFP-LV	2778980000

Accessories	Model Type	Order No.
19" Rack Mounting Kit	RM-KIT	1241440000
Configuration backup and restore module	IE-EBR-MODULE-RS232-ALM	2682610000

Note

Corresponding SFP modules for SubstationLine switches, see page I.4 - I.5.

26-Port 19" managed Fast/Gigabit Ethernet Switches

- Meets IEC 61850-3 / IEEE 1613 standards
- Redundant power supply modules
- Extensive set of management features enable the set-up of various redundancy, monitoring, traffic filter and security functions
- Suitable for use in harsh industrial environment thanks to rugged design and wide operating temperature range of -40°C up to 85°C
- SFP-ports for fiber optic transmission over long distances



available
Q3 2021

**Technical data**

Technology		
Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX and 100BASE-FX IEEE 802.3ab for 1000BASE-T IEEE 802.3z for 1000BASE-X IEEE 802.3x for flow control IEEE 802.3ad for port trunk with LACP IEEE 802.1D for the Spanning Tree protocol (STP) IEEE 802.1w for Rapid Spanning Tree protocol (RSTP) IEEE 802.1s for Multiple Spanning Tree Protocol (MSTP) IEEE 802.1p for Class of Service IEEE 802.1Q for VLAN Tagging IEEE 802.1X for Authentication IEEE 802.1AB for LLDP (Link Layer Discovery Protocol) IEEE 1588 PTPv2 for time synchronization	
Processing type	Store and Forward	
Flow control	IEEE 802.3x flow control	
Switch characteristics		
MAC table size	8K	
Packet buffer Size	4 Mbit	
Priority queues	8	
Number of available VLANs	4095 (1 to 4094)	
IGMP groups	256 per VLAN	
Management features		
Device configuration	Webbrowser (HTTP/HTTPS), SNMP v1/v2c/v3, Telnet console, CLI, Local serial console port, Upload of a configuration file via web-interface, TFTP-Server or external backup module	
Monitoring function	SNMP v1/v2c/v3, LLDP, Port mirroring, Port statistics, Port monitoring, Syslog, RMON, Event based warning via E-Mail, relay, SNMP trap, Ethernet cable diagnostics on RJ45 ports	
Network redundancy	STP, RSTP, MSTP, LACP, O-Ring, O-Chain, Fast recovery	
Network traffic filter	Quality of Service (QoS), Tag based VLAN, IGMP v2/v3, Traffic Rate Limiting	
IP-address management	Static, DHCP-Client, DHCP-Server (port based, pool-based), DHCP Option 82, DHCP-Relay	
Security functions	VLAN segmentation, Enable/disable ports, TACACS+ and IEEE 802.1X User Authentication, DoS/DDoS auto prevention, Access Control List (IP-based, MAC-based), Loop protection, Management access security via privilege level configuration for different user roles	
Time synchronization management	SNTP server, SNTP client, PTPv2	
Industrial protocol support	PROFINET device acc. to conformance class A, Modbus/TCP slave, EtherNet/IP	
Interfaces		
RJ45 ports	10/100BASE-T(X) or 10/100/1000BASE-T(X), auto negotiation, Full/half-duplex mode, Auto MDI/MDI-X port	
Fibre optic ports	100/1000BaseSFP-slot	
Serial console port	RS-232 (RJ45 connector)	
Relay Contact	1 relay output with a current capacity of 1 A at 24 V DC	
Reset button	< 5 sec: System reboot ; > 5 sec: Factory default	
Power supply		
Connection type	1x 10-pin fork/ring lug connection	
Power supply		
Input voltage	IEC 61850-3, IEEE 1613	
	IEC 61850-3: 110/220 V DC (100 - 370 V), 110/220 V AC (100 - 240 V), 2 redundant isolated inputs	
	IEC 61850-3: 48 V DC (24 - 72 V), 2 redundant isolated inputs	
Power consumption	23 W (max.)	
Overload current protection	yes	
Reverse polarity protection	yes	
Physical characteristics		
Housing main material	Metal	
Protection degree	IP30	
Type of mounting	19" rack mounting	
Dimensions (W x H x D)	443.7 x 44 x 262.5 mm (17.46 x 1.73 x 10.33 in)	
Weight	IE-SW-SL26M-24TX-2GC-HV: 4050 g IE-SW-SL26M-24TX-2GC-LV: 3535 g	
Environmental conditions		
Operating temperature	-40 to 85 °C (-40 to 185 °F)	
Storage temperature	-40 to 85 °C (-40 to 185 °F)	
Humidity	5 to 95 % (non-condensing)	
Operating altitude	≤ 2000 m	
EMC conformity and approvals		
EMC	EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 Ghz: 10 V/m IEC 61000-4-4 EFT: Power: 4 kV; Signal: 4 kV IEC 61000-4-5 Surge: Power: 4 kV; Signal: 4 kV IEC 61000-4-6 CS: 10 Vrms	
Safety	EN 62368-1	
Substation compliance	IEC 61850-3, IEEE 1613	
Shock	IEC 60870-2-2 class Cm	
Vibration	IEC 60870-2-2 class Cm and Class Bm	
Free fall	IEC 60870-2-2 class Cm	
MTBF		
Time	IE-SW-SL26M-24TX-2GC-HV: 262,968 hrs IE-SW-SL26M-24TX-2GC-LV: 297,924 hrs	
Database	Telcordia SR332	
Guarantee		
Time interval	5 years	
Ordering Information		
Version	Model Type	Order No.
24x RJ45 10/100 Mbit/s, 2x combo-ports usable as RJ45 10/100/1000 Mbit/s or SFP 100/1000 Mbit/s), High Voltage	IE-SW-SL26M-24TX-2GC-HV	2778990000
24x RJ45 10/100 Mbit/s, 2x combo-ports usable as RJ45 10/100/1000 Mbit/s or SFP 100/1000 Mbit/s), Low Voltage	IE-SW-SL26M-24TX-2GC-LV	2779000000
Note		
Corresponding SFP modules for SubstationLine switches, see page I.4 - I.5.		

28-Port 19" modular managed Fast/Gigabit/10-Gigabit Ethernet Switches

- Meets IEC 61850-3 / IEEE 1613 standards
- Modular design to allocate up to 28 ports with up to 10-GbE speed
- Extensive set of management features enable the set-up of various redundancy, monitoring, traffic filter and security functions
- Suitable for use in harsh industrial environment thanks to rugged design and wide operating temperature range of -40°C up to 85°C
- SFP-ports for fiber optic transmission over long distances



available
Q3 2021

**Technical data****Technology**

Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX and 100BASE-FX IEEE 802.3ab for 1000BASE-T IEEE 802.3z for 1000BASE-X IEEE 802.3ae for 10-Gigabit Ethernet IEEE 802.3x for flow control IEEE 802.3ad for port trunk with LACP IEEE 802.1D for the Spanning Tree protocol (STP) IEEE 802.1w for Rapid Spanning Tree protocol (RSTP) IEEE 802.1s for Multiple Spanning Tree Protocol (MSTP) IEEE 802.1p for Class of Service IEEE 802.1Q for VLAN Tagging IEEE 802.1X for Authentication IEEE 802.1AB for LLDP (Link Layer Discovery Protocol) IEEE 1588 PTPv2 for time synchronization
-----------	--

Processing type

Flow control	IEEE 802.3x flow control
--------------	--------------------------

Switch characteristics

MAC table size	8K
Packet buffer Size	32 Mbit
Memory (Flash)	16 MB
Memory (RAM)	128 MB
Jumbo frame support	up to 10 KB
Priority queues	8
Number of available VLANs	4095 (1 to 4094)
IGMP groups	128 per VLAN

Management features

Device configuration	Webbrowser (HTTP/HTTPS) SNMP v1/v2c/v3 Telnet console, CLI Local serial console port Upload of a configuration file via web-interface TFTP-Server or external backup module
----------------------	--

Monitoring function

SNMP v1/v2c/v3
LLDP
Port mirroring
Port statistics
Port monitoring
Syslog
RMON
Event based warning via E-Mail
relay
SNMP trap
Ethernet cable diagnostics on RJ-45 ports

Management features

Network redundancy	STP RSTP MSTP LACP O-Ring O-Chain, Fast recovery
Network traffic filter	Quality of Service (QoS) Tag based VLAN IGMP v2/v3 Traffic Rate Limiting
IP-address management	Static DHCP-Client DHCP-Server (port based, pool-based) DHCP Option 82 DHCP-Relay
Security functions	VLAN segmentation Enable/disable ports TACACS+ and IEEE 802.1X User Authentication DoS/DDoS auto prevention Access Control List (IP-based, MAC-based) Loop protection Management access security via privilege level configuration for different user roles
Time synchronization management	SNTP server SNTP client PTPv2
Industrial protocol support	PROFINET device acc. to conformance class A, Modbus/TCP slave, EtherNet/IP

Interfaces

Supported media interface modules at slots 1 - 3	IE-SWM-SL08-8GT: 8 x 10/100/1000BASE-T(X) ports IE-SWM-SL08-8GESFP: 8 x 100/1000BaseSFP ports IE-SWM-SL04-4SC: 4 x 100Base-FX ports (SC-duplex, multimode) IE-SWM-SL04-4SCS: 4 x 100Base-FX ports (SC-duplex, singlemode) IE-SWM-SL04-4ST: 4 x 100Base-FX ports (ST-duplex, multimode) IE-SWM-SL04-4STS: 4 x 100Base-FX ports (ST-duplex, singlemode)
--	--

Note: Supported media interface modules for module slots 1-3, see page C.20

Supported media interface modules at slot 4	IE-SWM-SL04-4GESFP: 4 x 1000BaseSFP slots IE-SWM-SL02-2GESFP+: 2 x 10GBaseSFP+ slots IE-SWM-SL04-4GESFP+: 4 x 10GBaseSFP+ slots
---	---

Note: Supported media interface modules for module slot 4, see page C.21

Serial console port	RS-232 (RJ45 connector)
Relay Contact	1 relay output with a current capacity of 1 A at 24 V DC
Reset button	< 5 sec: System reboot ; > 5 sec: Factory default

Power supply	
Connection type	1x 10-pin fork/ring lug connection
Input voltage	IE-SW-SL28M-HV: 110/220 V DC (100 - 370 V), 110/220 V AC (100 - 240 V), 2 redundant isolated inputs IE-SW-SL28M-LV: 48 V DC (24 - 72 V), 2 redundant isolated inputs
Power consumption	41 W (max.)
Overload current protection	yes
Reverse polarity protection	yes
Physical characteristics	
Housing main material	Metal
Protection degree	IP30
Type of mounting	19" rack mounting
Dimensions (W x H x D)	440 x 44 x 325 mm (17.32 x 1.73 x 12.80 in)
Weight	IE-SW-SL28M-HV: 6600 g IE-SW-SL28M-LV: 6450 g
Environmental conditions	
Operating temperature	-40 to 85 °C (-40 to 185 °F) -20 to 60 °C (-4 to 140 °F) if 10G SFP+ module is used
Storage temperature	-40 to 85 °C (-40 to 185 °F)
Humidity	5 to 95 % (non-condensing)
Operating altitude	≤ 2000 m
EMC conformity and approvals	
EMC	EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 Ghz: 10 V/m IEC 61000-4-4 EFT: Power: 4 kV; Signal: 4 kV IEC 61000-4-5 Surge: Power: 4 kV; Signal: 4 kV IEC 61000-4-6 CS: 10 Vrms
Safety	EN 62368-1, UL 61010-1, UL 61010-2-201 (IE-SW-SL28M-HV only)
Substation compliance	IEC 61850-3, IEEE 1613
Shock	IEC 60870-2-2 class Cm
Vibration	IEC 60870-2-2 class Cm and Class Bm
Free fall	IEC 60870-2-2 class Cm
MTBF	
Time	IE-SW-SL28M-HV: 647,420 hrs IE-SW-SL28M-LV: 608,907 hrs
Database	Telcordia SR332
Guarantee	
Time interval	5 years

Ordering Information		
Version	Model Type	Order No.
Modular 19" rack mounting switch with 4 media interface slots for up to 28 ports, High voltage	IE-SW-SL28M-HV	2779010000
Modular 19" rack mounting switch with 4 media interface slots for up to 28 ports, Low Voltage	IE-SW-SL28M-LV	2779020000
Accessories	Model Type	Order No.
Configuration backup and restore module	IE-EBR-MODULE-RS232-ALM	2682610000

Media interface modules for modular switch - Fast/Gigabit Ethernet

- Modular design provides wide variety of media interface types (RJ-45, SFP, SC/ST-Duplex)



available
Q3 2021



Technical data

Interfaces		
RJ45 ports	10/100/1000BASE-T(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port	
Fibre optic ports	100BASE-FX (SC/ST-Duplex connector) or 100/1000BaseSFP-slot	
Fibre optic transceiver characteristics		
Transmission rate	100 Mbps	
Connector type	SC-Duplex or ST-Duplex	
Transceiver type	Multimode	Singlemode
Fiber cable type	50/125 µm 62.5/125 µm	9/125 µm
Transmission distance, typical	2 km	30 km
Wavelength, typical	1310 nm	
Optical power RX range	-32 to -8 dBm	-34 to 0 dBm
Optical power TX range	-23.5 to -14 dBm	-15 to -8 dBm
Link-budget	8.5 dB	19 dB
Power supply		
Voltage supply	via Ethernet switch	
Power consumption	IE-SWM-SL04-4SC/4SCS/4ST/4STS: 5.5 W IE-SWM-SL08-8GT: 8 W IE-SWM-SL08-8GESFP: 0.5 W (w/o SFP-transceiver)	
Physical characteristics		
Housing main material	Metal	
Type of mounting	Insert in module slot 1, 2 or 3 of IE-SW-SL28M series	
Dimensions (W x H x D)	99 x 40.7 x 107 mm (3.9 x 1.6 x 4.2 in)	
Weight	326 g	
Environmental conditions		
Operating temperature	-40 to 85 °C (-40 to 185 °F)	
Storage temperature	-40 to 85 °C (-40 to 185 °F)	
Humidity	5 to 95 % (non-condensing)	
Operating altitude	≤ 2000 m	
MTBF		
Time	IE-SWM-SL04-4SC: 315,658 hrs IE-SWM-SL04-4SCS: 401,287 hrs IE-SWM-SL04-4ST: 314,863 hrs IE-SWM-SL04-4STS: 401,287 hrs IE-SWM-SL08-8GT: 1,303,990 hrs IE-SWM-SL08-8GESFP: 3,712,062 hrs	
Database	Telcordia SR332	
Guarantee		
Time interval	5 years	

Ordering Information

Version	Model Type	Order No.
Media interface module, 4x SC Multimode 100Mbit/s	IE-SWM-SL04-4SC	2779170000
Media interface module, 4x SC Singlemode 100Mbit/s	IE-SWM-SL04-4SCS	2779160000
Media interface module, 4x ST Multimode 100Mbit/s	IE-SWM-SL04-4ST	2779190000
Media interface module, 4x ST Singlemode 100Mbit/s	IE-SWM-SL04-4STS	2779180000
Media interface module, 8x RJ45 10/100/1000 Mbit/s	IE-SWM-SL08-8GT	2779140000
Media interface module, 8x SFP 100/1000 Mbit/s	IE-SWM-SL08-8GESFP	2779150000

Note

Corresponding SFP modules for SubstationLine switches, see page I.4 - I.5.

Media interface modules for modular switch - Gigabit/10-Gigabit Ethernet



available
Q3 2021



Technical data

Interfaces

Fibre optic ports 1000BaseSFP-Slot or 10GBaseSFP+ slot

Power supply

Voltage supply via Ethernet switch

Power consumption
IE-SWM-SL04-4GESFP: 0.5 W (w/o SFP-transceiver)
IE-SWM-SL02-2GESFP+: 7 W (w/o SFP-transceiver)
IE-SWM-SL04-4GESFP+: 14 W (w/o SFP-transceiver)

Physical characteristics

Housing main material Metal

Type of mounting Insert in module slot 4 of IE-SW-SL28M series

Dimensions (W x H x D) 99 x 40.7 x 136 mm (3.9 x 1.6 x 5.35 in)

Weight 314 g

Environmental conditions

Operating temperature
IE-SWM-SL04-4GESFP: -40 to 85 °C (-40 to 185 °F)
IE-SWM-SL02-2GESFP+: -40 to 60 °C (-40 to 140 °F)
IE-SWM-SL04-4GESFP+: -40 to 60 °C (-40 to 140 °F)

Storage temperature -40 to 85 °C (-40 to 185 °F)

Humidity 5 to 95 % (non-condensing)

Operating altitude ≤ 2000 m

MTBF

Time
IE-SWM-SL04-4GESFP: 4,419,625 hrs
IE-SWM-SL02-2GESFP+: 3,814,097 hrs
IE-SWM-SL04-4GESFP+: 1,871,812 hrs

Database Telcordia SR332

Guarantee

Time interval 5 years

Ordering Information

Version	Model Type	Order No.
Media interface module, 4x SFP 1000 Mbit/s	IE-SWM-SL04-4GESFP	2779200000
Media interface module, 2x SFP+ 10 Gbit/s	IE-SWM-SL02-2GESFP+	2779210000
Media interface module, 4x SFP+ 10 Gbit/s	IE-SWM-SL04-4GESFP+	2779220000

Note

Corresponding SFP modules for SubstationLine switches, see page I.5 - I.6.

Industrial Security Router

Overview

Industrial Security Router	Introduction – Industrial Security Router	D.2
	Industrial Security Router	D.4

D

Secure data communication with integrated VPN technology

Industrial security routers – versatile, reliable and flexible

As data and information networking continues to increase, Ethernet communication seeing more and more use in industrial automation technology. This is a trend that has not only changed the individual requirements of many customers, but has also had an impact on the devices used. These must now support a flexible system structure, allow networking with each other and, in addition to the targeted integration of all relevant network participants, also guarantee maximum data security.

In order to provide optimal support for meeting the many different requirements, we offer different versions of industrial security routers. These routers enable secure, reliable and location-independent communication between machines and systems, as well as reliable user authentication to protect the network.

Our routers with integrated VPN technology are ideally suited for secure remote access to components and systems in remote networks. They are available with either wired or mobile Internet connectivity and support the u-link Remote Access Service. This allows remote access systems to be set up quickly and easily, with no special IT knowledge required.

Your special advantage:

- Easy integration of subnets with identical IP address ranges through 1:1 NAT
- Secure and easy remote maintenance via Weidmüller u-link Remote Access Service
- Future-proof network connection with static and dynamic routing
- Increased network security thanks to stateful inspection firewall, IP/port forwarding and network segmentation
- Full flexibility thanks to Fast Ethernet and Gigabit Ethernet interfaces with 2 to a maximum of 6 ports



Reliable Internet connection

Reliable Internet connection thanks to integrated 4G/LTE mobile modem



Industrial Security Router

Gigabit Industrial Security Router

- 2 or 6 Gigabit ports (LAN/WAN)
- NAT masquerading, 1:1 network mapping and port forwarding
- VPN function via u-link Remote Access Service, OpenVPN and IPsec
- Key switch function for disabling/enabling of a WAN/VPN connection
- Variations with 6 routed Ethernet sub networks and individual firewall rules
- Variations with integrated 4G/LTE modem for fast, Internet-based radio communication access
- Variation without VPN functionality for NAT and security applications
(1489940000, IE-SR-2GT-LAN-FN)



Technical data

Operation modes	
Extended IP router	Each interface (LAN, WAN, optional mobile radio) can be configured as a separate IP network
IP router	IP routing (IPv4, Layer 3) with SPI firewall (Stateful Packet Inspection)
Transparent bridge	2/6-port switch with additional Layer 2 filter
Network Services	
	<ul style="list-style-type: none"> • DHCP server / DHCP relay • DNS relay • NTP-Client/Relay • DynDNS (DHCP client by RFC 2136)
Firewall	
	<ul style="list-style-type: none"> • IPv4 Stateful inspection Firewall (incoming/outgoing) • NAT-Masquerading, 1:1 NAT, Portforwarding • Layer-2/3-Filter (VLAN ID, VLAN, QoS tag, MAC address, Ethertype frame) • "Auto learning" feature to create packet filter rules (analysis of network traffic) • Layer 2/3-based packet prioritization (Ethernet frame, IP header, VLAN tag)
VPN functionality*	
u-link	OpenVPN-based remote access via Weidmüller u-link cloud
OpenVPN	<ul style="list-style-type: none"> • Configurable as OpenVPN server or client (Layer 2 and Layer 3) • Authentication with X.509 Certificates • Tunnel support via HTTP proxy • Maximum of 10 different client or server configurations • Unlimited number of client connections in server mode
IPsec	<ul style="list-style-type: none"> • Can be configured as an IPsec server or client • PSK authentication (user ID, password) or X.509 certificates • Hardware-based encryption for faster data throughput • A maximum of 64 simultaneous connections (subnet to subnet or as an IPsec server) • Encryption algorithms DES-56, 3DES-168, AES 128, AES 192, AES-256
Management	
	<ul style="list-style-type: none"> • Configuration via WEB interface (HTTP / HTTPS) • Configuration support through detailed help information (tooltip) • Configurable multi-user access with definable rights mask • Support of SNMP v1/v2/v3, event log / syslog
Miscellaneous	
Modbus/TCP	Integrated Modbus TCP Server for status queries, and software-based activation / de-activation of VPN connections
Diagnosis	Remote Capture™ feature for network diagnostics via a connected PC (Wireshark)
Monitoring	Client Monitoring (via ICMP) with alarm function in case of error
Mobile radio interface (mobile radio variants only)	
Mode of operation	Permanent connection, Manual connection control via web interface, Fallback connection with active ICMP monitoring
Wireless module	multi-band modem (4G/3G)
Transmission rate mobile radio	LTE Category: CAT 6; download rate, max. 300 Mbps; upload rate, max. 50 Mbps
Frequency band	Region: EMEA + Americas 4G / LTE: B1, B2, B3, B4, B5, B7, B12, B13, B20, B25, B26, B29, B30, B41 3G: B1, B2, B3, B4, B5, B8

* is not supported by the model IE-SR-2GT-LAN-FN

Interfaces	
RJ45 ports	10/100/1000BaseT (X), auto negotiation, full/half duplex mode
USB port	USB 2.0 interface for firmware update or restoration of the device configuration via USB flash drive
Digital outputs	<ul style="list-style-type: none"> “Alarm” → Indicates a configurable network status or error (24 V out) “VPN-active” → Indicates an active VPN connection (24 V out)*
Digital inputs	<ul style="list-style-type: none"> “Cut” → Disconnects physically (link down) the WAN port (24 V) “VPN-initiate” → Enables a pre-configured VPN connection (24 V)*
Reset button	Restoring the factory default
Connection for external antennas	SMA (socket)
Power Requirements	
Input Voltage	1x 24 V DC (7 to 36 V DC), NEC class 2, (for use in compliance with UL specifications: 7 - 30 V DC)
Current consumption	max. 0.8 A at 24 V
Technical data (housing)	
Housing	Diecast aluminium, IP20 protection
Dimensions (W x H x D)	2-Port Router: 35 x 163 x 140 mm 6-Port Router: 57 x 163 x 140 mm 2-Port DNV-GL Router: 57 x 163 x 140 mm
Installation	DIN-Rail, VESA 75
Environmental Limits	
Operating temperature	-20 °C to +70 °C
Storage Temperature	-20 °C to +85 °C
Relative ambient air humidity	5 to 95% (non-condensing)
Approvals	
Security	EN60950-1
Radio	EN 301 489-1/17, EN 301 893, EN 302 291-2
EMC	EN 61000-6-2/6-4 FCC Part 15B Class A
Ship use	DNV-GL (only for 2535980000, 2535970000)
Shock	DIN EN 60068-2-27
Vibration	DIN EN 60068-2-6
Warranty	
Warranty Period	3 years

Ordering data

Version	Type	Order No.
Security/NAT/VPN/u-link Router, 2 * RJ45 10/100/1000BaseT(X)	IE-SR-2GT-LAN	1345270000
Security/NAT Router, 2 * RJ45 10/100/1000BaseT(X)	IE-SR-2GT-LAN-FN	1489940000
Security/NAT/VPN/u-link Router, with integrated multi-band modem (4G/3G), 2 * RJ45 10/100/1000BaseT(X)	IE-SR-2GT-LTE/4G-US	2535780000
Security/NAT/VPN/u-link Router, with integrated multi-band modem (4G/3G), 2 * RJ45 10/100/1000BaseT(X)	IE-SR-2GT-LTE/4G-EU	2535930000
Security/NAT/VPN/u-link Router, 6 * RJ45 10/100/1000BaseT(X)	IE-SR-6GT-LAN	2535940000
Security/NAT/VPN/u-link Router, with integrated multi-band modem (4G/3G), 6 * RJ45 10/100/1000BaseT(X)	IE-SR-6GT-LTE/4G-US	2535950000
Security/NAT/VPN/u-link Router, with integrated multi-band modem (4G/3G), 6 * RJ45 10/100/1000BaseT(X)	IE-SR-6GT-LTE/4G-EU	2535960000
Security/NAT/VPN/u-link Router, 2 * RJ45 10/100/1000BaseT(X), DNV-GL approval	IE-SR-2GT-LAN-M	2535980000
Security/NAT/VPN/u-link Router, with integrated multi-band modem (4G/3G), 2 * RJ45 10/100/1000BaseT(X), DNV-GL approval	IE-SR-2GT-LTE/4G-EU-M	2535970000

Accessories

Model Type	Order No.
19" Rack Mounting Kit	RM-KIT

Industrial Security Router – Fast Ethernet

4-Port Fast Ethernet Industrial Security Routers

- Easy integration of subnets with identical IP address ranges through 1: 1 NAT
- Secure and easy remote maintenance with Weidmüller u-link remote access service
- Future-proof network connection with static and dynamic routing
- Increased network security through stateful inspection firewall, IP/Port-forwarding and network segmentation
- Reliable internet connection, even without on-site internet access, thanks to integrated 4G/LTE cellular modem



Technical data

Management features

Operating modes	IP router: IP routing (IPv4, Layer-3) with SPI firewall (Stateful Packet Inspection), Static or dynamic routing, Supports RIPv2 / OSPF
Device configuration	Webbrowser (HTTP/HTTPS), SNMP v1/v2c/v3, Windows tool
Monitoring function	SNMP v1/v2c/v3, Syslog
IP-address management	Static, DHCP-Client, DHCP-Server (pool-based), DHCP-Relay
Security functions	IPv4 Stateful Packet Inspection Firewall (incoming/outgoing), NAT masquerading, 1:1 NAT, IP forwarding, Port forwarding
Time synchronization management	NTP client
Industrial protocol support	Modbus/TCP slave

VPN functionality

u-link	OpenVPN-based remote access service via the Weidmüller u-link cloud
OpenVPN	Configurable as OpenVPN server or client (Layer 2 and Layer 3), Authentication via X.509 certificate, Tunnel support via HTTP proxy, Maximum 10 different client or server configurations

Ipsec

RJ45 ports	Configurable as IPsec server or client
------------	--

Interfaces

RJ45 ports	10/100BASE-T(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port
Digital inputs	1x galvanically isolated VPN-initiate: establishes a pre-configured VPN connection (24 V in) Cut: physically disconnects (Link Down) the WAN port (24 V in) Trigger pre-configured packet filter rules (24 V in)

Serial port	1x RS-485, 2-wire, galvanically isolated, 1 removable 3-pole terminal block
-------------	---

Reset button	Reset to factory default settings
--------------	-----------------------------------

SCM-card slot	1x Smart Card (ID-000 format), save and restore the configuration using smart card (memory chip)
---------------	--

SIM-card slot (mobile radio variants only)	1x Mini-SIM (ID-000 format)
--	-----------------------------

Connector for external antennas (mobile radio variants only)	1x SMA female
--	---------------

Mobile radio interface (mobile radio variants only)

Mode of operation	Permanent connection, Manual connection control via web interface
Wireless module	IE-SR-4TX-LTE/4G-EU: multi-band modem (4G/3G/2G) IE-SR-4TX-LTE/4G-USEMEA: multi-band modem (4G/3G)

Transmission rate mobile radio	IE-SR-4TX-LTE/4G-EU: LTE Category: CAT 4 download rate, max. 150 Mbps; upload rate, max. 50 Mbps IE-SR-4TX-LTE/4G-USEMEA: LTE Category: CAT 6; download rate, max. 300 Mbps; upload rate, max. 50 Mbps
--------------------------------	---

Frequency band	IE-SR-4TX-LTE/4G-EU: LTE: B1 (2100), B2 (1900), B3 (1800), B4 (AWS), B5 (850), B7 (2600), B12 (700ac), B13 (700c), B20 (800DD), B25 (1900), B26 (US 850 Ext), B29 (US 700de Lower), B30 (2300 WCS), B41 (TDD 2500) UMTS: B1 (2100), B2 (1900), B3 (1800), B4 (AWS), B5 (850), B8 (900)
----------------	--

IE-SR-4TX-LTE/4G-USEMEA:	
LTE: B1 (2100), B2 (1900), B3 (1800), B4 (AWS), B5 (850), B7 (2600), B12 (700ac), B13 (700c), B20 (800DD), B25 (1900), B26 (US 850 Ext), B29 (US 700de Lower), B30 (2300 WCS), B41 (TDD 2500) UMTS: B1 (2100), B2 (1900), B3 (1800), B4 (AWS), B5 (850), B8 (900)	

Mobile radio interface (mobile radio variants only)

Transmit power	IE-SR-4TX-LTE/4G-EU: LTE: +23 dBm +2.7/-2.7 dB (Power Class 3) WCDMA : 24 +/-3 dBm (Power Class 3) GSM900: 33 ± 2 dBm (Power Class 4) GSM1800: 30 ± 2 dBm (Power Class 1)
----------------	---

IE-SR-4TX-LTE/4G-USEMEA:	LTE Band 1, 2, 3, 4, 5, 8, 12, 13, 20, 25, 26: +23 dBm +/- 1 dB LTE Band 7, 30, 41: +22 dBm +/- 1 dB UMTS: +23 dBm +/- 1 dB
--------------------------	---

Power supply

Connection type	1 removable 4-pin terminal block
Input voltage	24 V DC (19.2 - 28.8 V), 1 single input
Current consumption at 24 V	0.8 A

Physical characteristics

Housing main material	Plastic
Protection degree	IP30
Type of mounting	DIN rail
Dimensions (W x H x D)	29.9 x 134.5 x 94.8 mm (1.17 x 5.29 x 3.73 in)
Weight	IE-SR-4TX: 175 g IE-SR-4TX-LTE/4G-EU: 213 g IE-SR-4TX-LTE/4G-USEMEA: 213 g

Environmental conditions

Operating temperature	-30 to 75 °C (-22 to 167 °F)
Storage temperature	-40 to 85 °C (-40 to 185 °F)
Humidity	5 to 90 % (non-condensing)
Operating altitude	≤ 2000 m

EMC conformity and approvals

EMC	EN 55032, EN 55024, EN 61000-6-2, EN 61000-6-4
Safety	SELV according to EN 62368-1, EN 62311

Shock	IEC 60068-2-27
Vibration	IEC 60068-2-6

Wireless	EN 301 489-1, EN 301 489-52, EN 301 511, EN 301 908-1, EN 301 908-2
----------	---

Guarantee

Time interval	3 years
---------------	---------

Ordering Information

Version	Model Type	Order No.
Security/NAT/VPN/U-link Router, 4x RJ45 10/100 Mbit/s	IE-SR-4TX	2751270000
Security/NAT/VPN/U-link Router with integrated multi-band modem (4G/3G/2G), EU-model, 4x RJ45 10/100 Mbit/s	IE-SR-4TX-LTE/4G-EU	2751280000
Security/NAT/VPN/U-link Router with integrated multi-band modem (4G/3G), US/EMEA-model, 4x RJ45 10/100 Mbit/s	IE-SR-4TX-LTE/4G-USEMEA	2759630000

Accessories

Model Type	Order No.
19" Rack Mounting Kit	RM-KIT

u-link Remote Access Service

Overview

u-link Remote Access Service	Introduction – u-link Remote Access Service	E.2
	u-link Remote Access Service	E.6

E

u-link Remote Access Service – A tool for all purposes

Advanced features for convenient remote access management


The remote maintenance of machines and systems is often a complex and time-consuming task. On top of that is the demand for a targeted and secure functional connection to the associated IT systems. For many users, these two challenges constitute a major obstacle to the global connection of systems.

E u-link guarantees a quick and secure access to machines and plants and, at the same time, allows the efficient management of production plants, user clients, access rights and firmware versions. The intuitive u-link web portal are quick and easy to configure without expert knowledge and can be adapted to specific processes. Secure servers in Europe provide an online platform that ensures conformity between different IT systems when carrying out remote maintenance.



Individual system management

u-link can manage users and groups as well as their access rights according to individual specifications. This includes group assignments and access rights to production systems.



Little configuration effort

Thanks to the intuitive user interface, the devices and clients can be connected easily and without detailed IT knowledge. Thus u-link allows you to quickly network multiple systems.



Secure remote access and remote diagnostics


Remote access to machines and systems takes place via a secure VPN connection – worldwide and regardless of location. You have secure access to your systems at all times via the highly available servers.



Condition monitoring and status reporting

Weidmüller Heartbeat can be used to report the availability of a router to u-link. This makes condition monitoring easier and enables status messages of the installed router.

u-link.weidmueller.com



Simple – secure – u-link

The integrated security concept for your networks

The growing number of network-capable devices together with the increasing networking of manufacturing through the Internet provides ample opportunities for cyber attacks. To protect your systems, u-link offers state-of-the-art functions without increasing complexity.

E

Your security features:



- X.509 certificates for authentication
- 2048 bit key length




- TLS/SSL encryption
- 2-factor authentication
- Custom password policy



- Outgoing connections only
- Port 443 exclusively used for remote access
- User and rights management



- Firewall integrated in u-link for remote access
- Option of enabling remote access on site
- Remote firmware update
- High-performance firewall



u-link Remote Access Service

u-link licences

Weidmüller offers the following usage variations and additional options for the u-link Remote Access Service:

Standard version 50/150/300/500

- Licence-dependent configuration from 50 up to 500 router objects (further license models on request)

Extensive functional and performance features as compared with the entry version, such as

- 3 simultaneous VPN through-connections per customer account (can be extended)
- China-VPN: reliable VPN connection to and from China
- Firmware management: Display of firmware status of all routers and the option of a time-controlled, automated firmware update
- Individual access rights: granular configuration of access rights to devices in the target network
- Extensive event log: Presentation of all activities in the u-link portal with extensive filter and export functions
- Password policy: Increased security through configurable specification of minimum requirements for password quality and validity period

Extension for additional VPN connections

- Licence code can be used for all Standard versions
- Additional data volumes with guaranteed bandwidth



Technical data

Functions and performance characteristics / Standard licence	
Number of configurable user objects (service PC)	Unrestricted
Number of configurable router objects (access points remote network)	depends on licence (50, 150, 300, 500,...)*
User organisation	Organisation of service users in groups, assignment of selective access rights to device topology, group-dependent assignment of rights re. device configuration and user administration
Device management	Illustration of the device infrastructure (remote access objects) in a clearly defined tree structure via location, group and device objects
Firmware management	Display of the firmware version of all routers and the possibility of timed, automated firmware updates
China-VPN	Reliable VPN connection to and from China
Password guideline	Increased security through configurable specification of minimum requirements for the password quality and validity period
Simultaneously usable pass-through VPN connections	3 (can be extended by adding on other pass-through VPN connections)
Period	1 year from activation of the licence key. When extending a "Standard 50/150/300/500" version, the validity period is extended by 1 year from the expiry date of the current period, but not less than 1 year Note: When the validity period has expired, automatic reduction of the bandwidth to the values of the free-of-charge entry version (<= 1 GB with max. 500 kBit/sec, > 1 GB with max. 64 kBit/sec)
Monthly data volume and bandwidth	<= 5 GB with max. 1 Mbit/s, > 5 GB with max. 500 Kbit/s. Increase by 1 GB/month with 1 Mbit/s per added-on pass-through VPN connection, for data volume > 12 GB/month max. 500 kbit/s
Usage information	Extended reporting and statistical information (itemised statement, usage duration, data volume)
System availability	≥ 99.6%
Functions and performance characteristics / VPN licence	
Number of additional VPN connections (per licence code)	1 (pass-through VPN connection for service PC <> u-link <> router/ target network)
VPN channel bandwidth	1 Mbit/s
Extension of data volume	Data volume of the u-link client account increased by 1 GB/month with a bandwidth of 1 Mbit/s
Period	1 year from activation of the licence key. When extending a VPN licence that has already been activated, the validity period is extended by 1 year from the expiry date of the current period, but not less than 1 year.
Usage	Use as additional VPN channel or to extend the period of a VPN channel. Can be used within the scope of all standard versions (not for entry version).

System requirements

Hardware (service PC)	PC with Windows 7, 8 or 10 operating system
Hardware, remote target network	Weidmüller router (except IE-SR-2GT-LAN-FN; 1489940000)
Portal administration (user/device configuration)	Standard browser (IE, Edge, Chrome, Firefox) via an HTTPS connection (SSL), login via username and password
VPN software (service PC)	u-link VPN Client (installation on PC)
Miscellaneous	
Activation	Account administrator enters the licence key in the u-link portal (functions immediately available)
Included in delivery	Letter with licence key

Ordering data

Version	Type	Order No.
"Standard 50" version software licence for u-link Remote Access Service. Can be used to upgrade an entry version or to extend period of a "Standard 50" version"	U-LINK-LIC-STD-50-1Y	2665050000
"Standard 150" version software licence for u-link Remote Access Service. Can be used to upgrade an entry version or „Standard 50“ version or to extend the period of a "Standard 150" version	U-LINK-LIC-STD-150-1Y	2447050000
"Standard 300" version software licence for u-link Remote Access Service. Can be used to upgrade an entry version or „Standard 50/150“ version or to extend the period of a "Standard 300" version	U-LINK-LIC-STD-300-1Y	2457840000
"Standard 500" version software licence for u-link Remote Access Service. Can be used to upgrade an entry version or „Standard 50/150/300“ versions or to extend the period of a "Standard 500" version	U-LINK-LIC-STD-500-1Y	2457850000
"VPN connection" licence code for u-link Remote Access Service. Can be used as an additional VPN connection or to extend the period of a VPN connection that has already been activated	U-LINK-LIC-VPN-1Y	2447060000

Note: * Licence models with more than 500 configurable router objects are available upon request.

Media converter and protocol gateways

Overview

Media converter and protocol gateways	Introduction – Media converter and protocol gateways	F.2
	Ethernet media converter (copper/fiber optic)	F.4
	Serial/Ethernet converter	F.5
	Serial/Ethernet converter and Modbus TCP/RTU gateway	F.6

Transmit data without interference

Media converters and protocol gateways – convenient and economical

A goal of industrial automation is to achieve the continuous networking of all system components. This also requires the interconnection of devices and network segments that use different transmission technologies or are very far away from each other. Our media converters and protocol gateways ensure smooth communication between all network participants and are also especially convenient and economical.

Serial/Ethernet converters for integrating existing devices

In many systems, serial devices with RS232, RS422 or RS485 interfaces are still widely used. These may include control systems, sensors, measuring instruments, motors, drives, barcode readers and operating displays. Our serial/Ethernet converters allow you to integrate such serial components quickly and easily into your existing Ethernet network structure. For this purpose, the converters support a variety of operating modes, such as TCP server, TCP client, UDP, Real COM, RFC2217, reverse Telnet, pair connection and Ethernet modem.

F

Media converters for easy and economical glass fibre utilisation

In case of high requirements on interference immunity or long transmission distances, optical fibres are an expedient solution – in the process industry, for example. With fibre optics, transmission distances ranging between 5 km (multi-mode fibres) and 40 km (single-mode fibres) can be achieved without the use of intermediate generators. Our media converters convert Ethernet signals on an RJ45 port to fibre optic signals for SC or ST cables. In the process, the collision domain of both participants is retained so as to ensure the greatest possible port transparency.

Seamless integration of Ethernet and serial Modbus devices


Modbus is one of the most popular automation protocols in the world and supports traditional RS-232/422/485 devices and Ethernet devices. However, the Ethernet-based Modbus protocol is different from the original serial-based protocols. In order to integrate Modbus networks, the Modbus TCP/RTU Gateway includes two Ethernet interfaces and one serial interface that supports RS-232, RS-422 and RS-485 communication. It automatically and intelligently translates between Modbus TCP (Ethernet) and Modbus ASCII/RTU (serial) protocols.



Simple warning system
Warning in case of power failure and port errors



Surge protection
Improved surge protection for serial ports, LAN and power supply connections



Power supply
Redundant power supply inputs



Extensive approvals
Developed and approved for EX areas (Class 1 Div. 2/ Atex Zone 2)

Ethernet media converter (copper/fiber optic)

Industrial Media Converter (10/100BaseT (X) to 100BaseFX)

- 10/100BaseT(X) auto-negotiation and auto-MDI/MDI-X
- Link Fault Pass-Through (LFP)
- Power failure, port break alarm by relay output
- Redundant power inputs
- Designed for hazardous locations (Zone 2)



Technical data

Technology			
Standards	IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT (X) and 100BaseFX		
Interfaces			
Fibre Ports	100BaseFX (SC/ST-duplex connection)		
RJ45 ports	10/100BaseT(X)		
DIP Switches	100BaseFX Full/Half duplex selection, Port fault alarm		
Alarm Contact	One relay output with current carrying capacity of 1 A at 24 V DC		
Specification optical fiber			
Transceiver Type	100Base FX		
	Multi-Mode		Single-Mode
Fiber Cable Type	OM1	50/125 µm 800 MHz·km	G.652
Typical Distance	4 km	5 km	40 km
Wavelength	Typical (nm)	1300	1310
	TX Range (nm)	1280 to 1360	1280 to 1340
	RX Range (nm)	1100 to 1600	1100 to 1600
Optical Power	TX Range (dBm)	-10 to -20	0 to -5
	RX Range (dBm)	-3 to -32	-3 to -34
	Link-Budget (dB)	12	29
	Dispersion Penalty (dB)	3	1

Note: When connecting a single-mode fiber transceiver over a short distance, we recommend using an attenuator to prevent the transceiver from being damaged by excessive optical power.

Power Requirements	
Input Voltage	24 V DC (12 to 48 V DC), two redundant inputs
Current consumption	0.16 A at 24 V
Connection	1 removable 6-pole terminal block
Overload Current Protection	1.1 A
Reverse Polarity Protection	Present
Technical data	
Housing	Metal, IP30 protection
Dimensions (W x H x D)	53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in)
Weight	630 g
Installation	DIN-Rail
Environmental Limits	
Operating temperature	Standard Models: 0 to 60 °C (32 to 140 °F) Wide Temp. Models: -40 to 75 °C (-40 to 167 °F)
Operating Humidity	5 to 95 % (non-condensing)
Storage Temperature	-40 to 85 °C (-40 to 185 °F)

Approvals			
Security	UL 508		
EMC	EN 55032/24		
CISPR 32, FCC Part 15B Class A			
	IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV		
	IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m		
	IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV		
	IEC 61000-4-5 Surge: Power: 1 kV; Signal: 1 kV		
	IEC 61000-4-6 CS: 3 V		
	IEC 61000-4-8		
Hazardous Location	UL/cUL Class1, Division 2, Groups A, B, C, and D, ATEX Zone 2 Ex nA nC IIC T4 Gc		
Maritime	DNV-GL		
Freefall	IEC60068-2-32		
Shock	IEC60068-2-27		
Vibration	IEC60068-2-6		
MTBF (mean time between failures)			
Time	401,000 hrs		
Database	MIL-HDBK-217F: GB 25 °C		
Warranty			
Warranty Period	5 years		

Ordering data			
Version	Type	Operating Temperature	Order No.
1 * RJ45, 1 * SC-Multimode	IE-MC-VL-1TX-1SC IE-MC-VLT-1TX-1SC	0 to +60 °C -40 to +75 °C	124140000 1286880000
1 * RJ45, 1 * ST-Multimode	IE-MC-VL-1TX-1ST IE-MC-VLT-1TX-1ST	0 to +60 °C -40 to +75 °C	1241410000 1286890000
1 * RJ45, 1 * SC-Singlemode	IE-MC-VL-1TX-1SCS IE-MC-VLT-1TX-1SCS	0 to +60 °C -40 to +75 °C	1241420000 1286900000

Accessories		
	Type	Order No.
19" Rack Mounting Kit	RM-KIT	1241440000

1 and 2-port Serial/Ethernet Converter for industrial automation

- High surge protection for the serial ports, LAN ports and power supply connection
- Rugged screw-type terminal blocks for power and serial connectors
- Cascading Ethernet ports for easy wiring
- Redundant DC power inputs
- Warning by relay output and email
- Low power consumption

**Technical data****Ethernet Interface**

Number of Ports	2
Speed	10/100 MBit/s, auto MDI/MDIX
Connection	8-pin RJ45
Magnetic Isolation Protection	1.5 KV built-in
Ethernet Line Protection	1 KV (level 2) surge protection

Serial Interface

Number of ports that can be used simultaneously	IE-CS-2TX-1RS232/485: 1 IE-CS-2TX-2RS232/485: 2
Serial Standards	RS 232/422/485
Connection	IE-CS-2TX-1RS232/485: DB9 for RS 232, terminal block for RS 422/485 IE-CS-2TX-2RS232/485: DB9 for RS 232/422/485
Serial Line Protection	• 15 KV ESD protection for all signals • 1 KV (level 2) surge protection

RS 485 Data Direction Control	ADDC® (automatic data direction control)
-------------------------------	--

Serial Communication Parameters

Data Bits	5, 6, 7, 8
Stop Bits	1, 1.5, 2
Parity	None, Even, Odd, Space, Mark
Flow Control	RTS/CTS and DTR/DSR (RS 232 only), XON/XOFF
Baud rate	50 bit/s to 921.6 kbit/s

Serial Signals

RS 232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
RS 422	Tx+, Tx-, Rx+, Rx-, GND
RS 485 4w	Tx+, Tx-, Rx+, Rx-, GND
RS 485 2w	Data+, Data-, GND

Software

Network Protocols	ICMP, IP, TCP, UDP, DHCP, BOOTP, Telnet, Rtelnet, DNS, SNMP, HTTP, SMTP, SNTP, IGMP
Configuration Options	Web Console, Serial Console, Telnet Console, Windows Utility
Windows Real COM Drivers	Windows 95/98/ME/NT/2000, Windows XP/2003/Vista/2008/7/8 x86/x64, 2012 x64

Technical data

Housing	Metal, IP30 protection
Weight	IE-CS-2TX-1RS232/485: 475 g IE-CS-2TX-2RS232/485: 485 g
Dimensions (W x H x D)	36 x 105 x 140 mm (1.42 x 4.13 x 5.51 in)

Environmental Limits

Operating temperature	Standard Models: 0 to 60 °C (32 to 140 °F) Wide Temp. Models: 40 to 75 °C (40 to 167 °F)
Ambient Relative Humidity	5 to 95 % RH
Storage Temperature	-40 to 85 °C (-40 to 185 °F)
Power Requirements	
Input Voltage	12 to 48 V DC
Current consumption	IE-CS(T)-2TX-1RS232/485: 0.22 A at 12 V IE-CS(T)-2TX-2RS232/485: 0.25 A at 12 V

Approvals

EMC	EN 55032/24 CISPR 32, FCC Part 15B Class A IEC 61000-4-2 ESD: Contact: 6 KV; Air: 8 KV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 4 KV; Signal: 2 KV IEC 61000-4-5 Surge: Power: 2 KV; Signal: 1 KV IEC 61000-4-6 CS: 10 V IEC 61000-4-8
Security	UL 508
Hazardous Location	UL/cUL Class 1 Division 2 Groups A, B, C and D ATEX Zone 2 Ex nA nC IIC T3 Gc
Shock	IEC60068-2-27
Freefall	IEC60068-2-32
Vibration	IEC60068-2-6

Reliability

Alert Tools	Built-in buzzer and RTC (real-time clock)
Automatic Reboot Trigger	Built-in WDT (watchdog timer)
MTBF (mean time between failures)	262,805 hrs
Time	Database

Time	262,805 hrs
Database	Telcordia (Bellcore), GB

Warranty	5 years
-----------------	---------

Pin assignment

RS 232/422/485 (Male DB9)	PIN	RS 232	RS 422/RS 485-4w	RS 485-2w
1	DCD	TxD(A)	-	-
2	RXD	TxD+(B)	-	-
3	TXD	RxD+(B)	Data+(B)	Data-(A)
4	DTR	RxD(A)	Data-(A)	GND
5	GND	GND	GND	-
6	DSR	-	-	-
7	RTS	-	-	-
8	CTS	-	-	-

Pin Assignment

RS 422/485 Terminal block	PIN	RS 422/RS 485-4w	RS 485-2w
1	TxD+(B)	-	-
2	TxD(A)	-	-
3	RxD+(B)	Data+(B)	Data-(A)
4	RxD(A)	Data-(A)	GND
5	GND	GND	-

Ordering data

Version	Type	Operating Temperature	Order No.
2 * RJ45; 1 * serial (RS232: Sub-DB9, RS422/485: terminal block)	IE-CS-2TX-1RS232/485 IE-CST-2TX-1RS232/485	0 to +60 °C -40 to +75 °C	1242080000 1285830000
2 * RJ45; 2 * serial (RS232/422/485: 2 * SubDB9)	IE-CS-2TX-2RS232/485 IE-CST-2TX-2RS232/485	0 to +60 °C -40 to +75 °C	1242090000 1285840000

Accessories

Type	Order No.
19" Rack Mounting Kit	RM-KIT 1241440000

Serial/Ethernet converter and Modbus TCP/RTU gateway

Serial/Ethernet converter and Modbus TCP/RTU protocol gateway

- Integrated 2-port switch for line topology without need for additional switch
- Device server and modbus protocol gateway in one device
- Suitable for use in harsh industrial environment thanks to rugged design and wide operating temperature range of -40°C up to 70°C



Technical data

Technology

Standards	IEEE 802.3 for 10BASE-T IEEE 802.3u for 100BASE-TX
-----------	---

Processing type Store and Forward

Management features

Device configuration	Webbrowser (HTTP/HTTPS) SSH Upload of a configuration file via web-interface
----------------------	--

Monitoring function Modbus traffic monitor

Syslog

Event based warning via E-Mail

Event based warning via SNMP trap

IP-address management Static

DHCP-Client

BootP

Security functions Enable/disable ports

Management access security via secure IP-list and configuration of allowed access methods (web-interface, SSH)

Time synchronization management SNTP client

Operating modes Virtual COM mode

TCP Server mode

TCP Client mode

UDP Server/Client mode

Modbus RTU/ASCII Master to Modbus TCP Slave Gateway

Modbus TCP Master to Modbus RTU/ASCII Slave Gateway

Interfaces

RJ45 ports	2x 10/100BASE-T(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDIX port
------------	--

DB9	1x DB9 male for RS-232/422/485
-----	--------------------------------

DIP switches	1x for pull low resistor setting (1 kΩ, 150 kΩ)
--------------	---

	1x for pull high resistor setting (1 kΩ, 150 kΩ)
	1x for termination resistor setting (120 Ω)

Reset button < 5 sec: System reboot ; > 5 sec: Factory default

Serial interface characteristics

Standard	RS-232/422/485
----------	----------------

Baud rate	50 bit/s to 460.8 kbit/s
-----------	--------------------------

Data Bits	7, 8
-----------	------


Stop Bits	1, 2
-----------	------

Parity	odd, even, none, mark, space
--------	------------------------------

Flow Control	XON/XOFF, RTS/CTS, DTR/DSR
--------------	----------------------------

Pin assignment

RS 232/422/485
(Male DB9)



Pin #	RS-232 (DTE Device)	RS-422	RS-485 (4-wire)	RS-485 (2-wire)
1	DCD	TX-	TX-	DATA-
2	RXD	TX+	TX+	DATA+
3	TXD	RX+	RX+	-
4	DTR	RX-	RX-	-
5	GND	GND	GND	GND
6	DSR	-	-	-
7	RTS	-	-	-
8	CTS	-	-	-
9	RI	-	-	-

Power supply

Connection type 1 removable 4-pin terminal block

Input voltage 24 V DC (12 - 48 V), 2 redundant inputs

Current consumption at 24 V 0.20 A

Overload current protection yes

Reverse polarity protection yes

Physical characteristics

Housing main material Metal

Protection degree IP30

Type of mounting DIN rail

Dimensions (W x H x D) 26.1 x 110 x 75.2 mm (1.02 x 4.33 x 2.95 in)

Weight 200 g

Environmental conditions

Operating temperature -40 to 70°C (-40 to 158°F)

Storage temperature -40 to 85 °C (-40 to 185 °F)

Humidity 5 to 95 % (non-condensing)

Operating altitude ≤ 2000 m

EMC conformity and approvals

EMC EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A

IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV

IEC 61000-4-3 RS: 80 MHz bis 1 Ghz: 3 V/m

IEC 61000-4-4 EFT: Power: 0.5 kV; Signal: 0.5 kV

IEC 61000-4-5 Surge: Power: 0.5 kV; Signal: 1 kV

IEC 61000-4-6 CS: 3 Vrms

Safety UL 61010-1, UL 61010-2-201

Shock IEC 60068-2-27

Vibration IEC 60068-2-6

Free fall IEC 60068-2-31

MTBF

Time 1,479,078 hrs

Database Telcordia SR332

Guarantee

Time interval 5 years

Ordering Information

Version	Model Type	Order No.
---------	------------	-----------

2x RJ45 10/100 Mbit/s, 1x DB9 for RS-232/422/485 IE-CS-MBGW-2TX-1COM **2682600000**

Accessories

	Model Type	Order No.
--	------------	-----------

19" Rack Mounting Kit RM-KIT **1241440000**

IoT-Gateways

Overview

IoT-Gateways	Introduction – IoT-Gateways	G.2
	IoT-Gateways	G.4

G

Integration of existing components into IoT networks

Complete application representation for the IoT gateway

The intelligent networking of machines and devices in the IoT opens up many possibilities and offers opportunities for new business models. IoT gateways enable the exchange of data between field devices and servers or cloud applications. The transmitted data can be used to deepen process knowledge, carry out optimisations or offer new services.

With the help of our IoT gateway, you can collect machine data and gain access to your field devices and controls. Various protocols and interfaces are available for this purpose. Data pre-processing is carried out using the open IoT standard Node-RED, whose large community has a wide range of solutions in store. You can set up interfaces to your own IT systems as well as to cloud solutions like Azure, AWS or IBM. For location-independent remote system maintenance, you can also integrate the gateway into the u-link Remote Access Service.

Your special advantage:

- Full flexibility for your application thanks to various interfaces and protocols as well as the open application tool Node-RED
- Easy handling thanks to pre-defined nodes and open programming using your own nodes
- Secure and cost-optimised use of cloud systems through pre-processing and storage

Also
available in
IP54

G



Flexible IoT integration

Process data can be collected via various interfaces, such as Ethernet, CAN, RS485 or RS232. In addition, many protocols for coupling with PLC systems are supported – e.g. Siemens, Rockwell, Schneider or the industry standard OPC-UA.



Integrated remote access

The simple and secure remote access solution u-link Remote Access Service enables a quick response to changes in situations on site – and that worldwide.

Versatile IT integration

Whether via company network or mobile radio: The open IoT standard Node-RED allows data to be pre-processed and transmitted to other systems, such as servers, SCADA systems or cloud platforms, via various transmission media and protocols.

Industrial IoT-Gateways

- Enables machine data acquisition and provides access to field devices and PLC's via various protocols and interfaces
- Interfaces to your own IT systems as well as to common cloud systems
- Data traffic reduction through preprocessing on edge via the open IoT standard Node-RED
- Secure and easy remote maintenance with Weidmüller u-link Remote Access Service
- Integration of most common communication interfaces in small design
- Open programming platform Node-RED with strong community support

**Technical data****System data**

Memory (Flash)	4 GB
Memory (RAM)	1 GB (DDR3)

Processor	Dual Core ARM Cortex A9, 600 MHz
-----------	----------------------------------

Real-time clock	Capacity buffered (max. 5 days)
-----------------	---------------------------------

VPN functionality

u-link	OpenVPN-based remote access service via the Weidmüller u-link cloud
--------	---

Interfaces

RJ45 ports	2x 10/100BASE-T(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDIX port
------------	---

Digital inputs	2x (>10 V high, <3.6 V low; max. 30 V DC)
----------------	---

Digital outputs	1x (19.2 - 28 V high; max. 1 A)
-----------------	---------------------------------

Serial port	1x RS-232/485
-------------	---------------

USB port	1x USB 2.0 (Type A; max. 500 mA)
----------	----------------------------------

Power supply

Connection type	1 removable 6-pin terminal block
-----------------	----------------------------------

Input voltage	24 V DC (19.2 - 28.8 V), 1 single input
---------------	---

Current consumption at 24 V	0.24 A
-----------------------------	--------

Reverse polarity protection	yes
-----------------------------	-----

Physical characteristics

Housing main material	Metal
-----------------------	-------

Protection degree	IP30
-------------------	------

Type of mounting	DIN rail
------------------	----------

Dimensions (W x H x D)	35 x 125 x 105 mm (1.37 x 4.92 x 4.13 in)
------------------------	---

Weight	412 g
--------	-------

Environmental conditions

Operating temperature	-20 to 60 °C (-4 to 140 °F)
-----------------------	-----------------------------

Storage temperature	-40 to 85 °C (-40 to 185 °F)
---------------------	------------------------------

Humidity	5 to 95 % (non-condensing)
----------	----------------------------

EMC conformity and approvals

EMC	EN 61000-6-3, EN 61000-6-2
-----	----------------------------

Shock	IEC 60068-2-27
-------	----------------

Vibration	IEC 60068-2-6
-----------	---------------

Guarantee

Time interval	2 years
---------------	---------

Ordering Information

Version	Model Type	Order No.
IoT Gateway, 2x RJ45 10/100 Mbit/s, 1x RS232/485, 2x DI, 1x DO	IOT-GW30	2682620000

Accessories

Model Type	Order No.
19" Rack Mounting Kit	1241440000

Industrial WLAN

Overview

Industrial WLAN	Introduction – Industrial WLAN	H.2
	Industrial WLAN	H.4

H

Industrial WLAN

Wireless communication solutions

In many mobile applications and industrial environments that are difficult to access, cabling does not usually make sense. Instead, WLAN-based wireless communication solutions are employed. In logistics, for example, WLAN is used to connect AGVs (Automatic Guided Vehicles). Roaming between several radio cells is important in this case in order to enable individually configurable radio coverage.

Our WLAN module can be used flexibly as an access point (AP), bridge or client. The alternative Power over Ethernet supply makes integration into an existing infrastructure especially easy. Maximum data integrity is guaranteed through integration into a RADIUS service and secure encryption with WPA2 in the radio field. Several radio fields can be flexibly spread out. Within these fields, the clients can move between the radio cells thanks to fast roaming. Several areas can be assigned for each radio cell (Multi-SSID) and allocated to different VLANs. This way, the wired infrastructure is continued 1:1 in the radio range.

Your special advantage:

- Compliant access point / client according to IEEE 802.11a/b/g/n
- MIMO technology for data rates up to 300 Mbit/s
- Fast roaming for interruption-free connection changes between access points
- DFS support in 5 Ghz band
- Power supply with PoE according to IEEE 802.3af possible
- Integrated DI/DOs for monitoring and alarms

H



Turbo roaming for interruption-free connections

Roaming technology ensures a seamless wireless connection and allows you to switch quickly between different wireless access points without the risk of discontinued data communication.



Various wireless modes of operation

The most important modes of operation for wireless networks are AP Client mode and Bridge mode. AP mode can be used to create a new WLAN or to connect an existing WLAN to a wired network. Bridge mode allows two Ethernet devices to be connected wirelessly using a point-to-point connection.



Integrated digital inputs/outputs

Weidmüller WLAN access points have integrated digital inputs/outputs that can be used to send alarm notifications in real time via the network to the responsible maintenance personnel.

BasicLine WLAN Access Point/Client

- IEEE 802.11a/b/g/n conform access point/client
- MIMO technology for data rates up to 300Mbit/s
- Fast roaming for interruption-free connection change between access points
- DFS support in 5GHz bandwidth

**Technical data****WLAN Interface**

Standards	IEEE 802.11a/b/g/n for Wireless LAN IEEE 802.11i for Wireless Security IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT(X) IEEE 802.3ab for 1000BaseT
Spread Spectrum and Modulation (typically)	<ul style="list-style-type: none"> • DSSS with DBPSK, DQPSK, CCK • OFDM with BPSK, QPSK, 16QAM, 64QAM • 802.11b: CCK at 11/5.5 Mbps, DQPSK at 2 Mbps, DBPSK at 1 Mbps • 802.11a/g: 64QAM at 54/48 Mbps, 16QAM at 36/24 Mbps, QPSK at 18/12 Mbps, BPSK at 9/6 Mbps • 802.11n: 64QAM at 300 Mbps to BPSK at 6.5 Mbps
Operating Channels (central frequency)	US model: 2.412 to 2.462 GHz (11 channels) / 5.180 to 5.240 GHz (4 channels) 5.260 to 5.320 GHz (4 channels)* / 5.500 to 5.700 GHz (8 channels, excluding 5.600 to 5.640 GHz)* / 5.745 to 5.825 GHz (5 channels) EU model: 2.412 to 2.472 GHz (13 channels) / 5.180 to 5.240 GHz (4 channels) 5.260 to 5.320 GHz (4 channels)* / 5.500 to 5.700 GHz (11 channels)*
*DFS (Dynamic Frequency Selection): If the device is operated in access point mode on these channels, the device automatically switches to another channel once a radar signal is detected. After switching to another channel, a 60-second availability check is carried out in accordance with the specification, before communication can take place on the channel.	
Security	<ul style="list-style-type: none"> • SSID Broadcast enable/disable • Firewall for MAC/IP/protocol/port-based filtering • 64-bit and 128-bit WEP encryption, WPA/WPA2 personnel and enterprise (IEEE 802.1X/RADIUS, TKIP and AES)
Transmission Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: 6.5 to 300 Mbps
Transmit Power	802.11b: Type 26±1.5 dBm at 1 Mbps, Type 26±1.5 dBm at 2 Mbps Type 26±1.5 dBm at 5.5 Mbps, Type 25±1.5 dBm at 11 Mbps 802.11g: Type 23±1.5 dBm at 6 to 24 Mbps, Type 21±1.5 dBm at 36 Mbps Type 19±1.5 dBm at 48 Mbps, Type 18±1.5 dBm at 54 Mbps 802.11n: Type 23±1.5 dBm at MCS0/8 20 MHz (2.4 GHz) Type 18±1.5 dBm at MCS7/15 20 MHz Type 23±1.5 dBm at MCS0/8 40 MHz Type 17±1.5 dBm at MCS7/15 40 MHz 802.11a: Type 23±1.5 dBm at 6 to 24 Mbps, Type 21±1.5 dBm at 36 Mbps Type 20±1.5 dBm at 48 Mbps, Type 18±1.5 dBm at 54 Mbps 802.11n: Type 23±1.5 dBm at MCS0/8 20 MHz (5 GHz) Type 18±1.5 dBm at MCS7/15 20 MHz Type 23±1.5 dBm at MCS0/8 40 MHz Type 17±1.5 dBm at MCS7/15 40 MHz

Note: In accordance with regional regulations, the maximum permissible transmit power is limited on the UNII bandwidths via the device firmware. The corresponding values are contained in the following tables:

	US model	EU model
2.4 GHz	26 dBm	18 dBm
5 GHz (UNII-1)	23 dBm	21 dBm
5 GHz (UNII-2)	23 dBm	21 dBm
5 GHz (UNII-2e)	23 dBm	23 dBm
5 GHz (UNII-3)	23 dBm	-

Receive Sensitivity	802.11b: • 93 dBm at 1 Mbps, -93 dBm at 2 Mbps • 93 dBm at 5.5 Mbps, -88 dBm at 11 Mbps 802.11g: • 88 dBm at 6 Mbps, -86 dBm at 9 Mbps • 85 dBm at 12 Mbps, -85 dBm at 18 Mbps • 85 dBm at 24 Mbps, -82 dBm at 36 Mbps • 78 dBm at 48 Mbps, -74 dBm at 54 Mbps 802.11n: • 70 dBm at MCS7 20 MHz, -69 dBm at MCS15 20 MHz (2.4 GHz) • 67 dBm at MCS7 40 MHz, -67 dBm at MCS15 40 MHz 802.11a: • 90 dBm at 6 Mbps, -88 dBm at 9 Mbps • 88 dBm at 12 Mbps, -85 dBm at 18 Mbps • 81 dBm at 24 Mbps, -78 dBm at 36 Mbps • 74 dBm at 48 Mbps, -72 dBm at 54 Mbps 802.11n: • 69 dBm at MCS7 20 MHz, -71 dBm at MCS15 20 MHz (5 GHz) • 63 dBm at MCS7 40 MHz, -68 dBm at MCS15 40 MHz
---------------------	--

Protocol Support
General Protocols
SNMP, DHCP, LLDP
Interfaces
Supplied antenna
Connector for External Antennas
RJ45 port
Console Port

Technical data

Technical data	
Housing	Metal, IP30 protection
Weight	307 g
Dimensions (W x H x D)	58 x 115 x 70 mm (2.29 x 4.53 x 2.76 in)
Installation	DIN-Rail
Environmental Limits	
Operating temperature	Standard Models: 0 to 60 °C (32 to 140 °F) Wide Temp. Models: -40 to 75 °C (-40 to 167 °F)
Storage Temperature	-40 to 85 °C (-40 to 185 °F)
Ambient Relative Humidity	5 % to 95 % (non-condensing)
Power Requirements	
Input Voltage	24 V DC (12 to 48 V DC), two redundant inputs
Connection	1 removable 4-pin terminal block, 500 V insulation
Power Consumption	0.56 A at 12 VDC 0.14 A at 48 VDC
Power consumption	6.96 W
Reverse Polarity Protection	Present
Approvals	
Safety	EN62368-1, UL 60950-1
Radio	EN 301 489-1/17, EN 300 328, EN 301 893, TELEC, FCC ID: SLE-WAPN008, KC
EMC	EN 55032/24 CISPR 32, FCC Part 15B Class B IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 3 V IEC 61000-4-8
MTBF (mean time between failures)	
Time	749,476 hrs
Database	Telcordia (Bellcore), GB
Warranty	
Warranty Period	5 years

Ordering data

Version	Type	Operating Temperature	Order No.
WLAN Access Point/Client, IEEE 802.11 a/b/g/n, EU-Modell	IE-WL-BL-AP-CL-EU	0 to +60 °C -40 to +75 °C	2536600000 2536650000
WLAN Access Point/Client, IEEE 802.11 a/b/g/n, US-Modell	IE-WL-BL-AP-CL-US	0 to +60 °C -40 to +75 °C	2536660000 2536670000
Accessories		Type	Order No.
		External Backup and Restore Module	1241430000
		19" Rack Mounting Kit	1241440000

ValueLine WLAN Access Point/Bridge/Client

- IEEE 802.11a/b/g/n conform Access Point/Client/Bridge
- MIMO technology for data rates up to 300Mbit/s
- Fast roaming for interruption-free connection change between access points
- DFS support in 5GHz bandwidth
- Power can be supplied via PoE in accordance with IEEE 802.3af
- Integrated DI/DOs for monitoring and alarms

**Technical data****WLAN-Interface**

Standards	IEEE 802.11a/b/g/n for wireless LAN IEEE 802.11i for wireless security IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT(X) IEEE 802.3ab for 1000BaseT IEEE 802.3af for Power-over-Ethernet IEEE 802.1D for Spanning Tree Protocol IEEE 802.1w for Rapid STP IEEE 802.1Q for VLAN
Spreading code process and modulation (typical)	• DSSS with DBPSK, DQPSK, CCK • OFDM with BPSK, QPSK, 16QAM, 64QAM • 802.11b: CCK at 11/5.5 Mbps, DQPSK at 2 Mbps, DBPSK at 1 Mbps • 802.11a/g: 64QAM at 54/48 Mbps, 16QAM at 36/24 Mbps, QPSK at 18/12 Mbps, BPSK at 9/6 Mbps • 802.11n: 64QAM at 300 Mbps to BPSK at 6.5 Mbps
Operating Channels (central frequency)	US model: 2.412 to 2.462 GHz (11 channels) / 5.180 to 5.240 GHz (4 channels) 5.260 to 5.320 GHz (4 channels)* / 5.500 to 5.700 GHz (8 channels, excluding 5.600 to 5.640 GHz)* / 5.745 to 5.825 GHz (5 channels) EU model: 2.412 to 2.472 GHz (13 channels) / 5.180 to 5.240 GHz (4 channels) 5.260 to 5.320 GHz (4 channels)* / 5.500 to 5.700 GHz (11 channels)*
*DFS (Dynamic Frequency Selection): If the device is operated in access point mode on these channels, the device automatically switches to another channel once a radar signal is detected. After switching to another channel, a 60-second availability check is first carried out in accordance with the specification, before communication can take place on the channel.	
Security	• SSID Broadcast enable/disable • Firewall for MAC/IP/protocol/port-based filtering • 64-bit and 128-bit WEP encryption, WPA/WPA2 personnel and enterprise (IEEE 802.1X/RADIUS, TKIP and AES)
Transmission Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: 6.5 to 300 Mbps
Transmit power	802.11b: Type 26±1.5 dBm at 1 Mbps, Type 26±1.5 dBm at 2 Mbps Type 26±1.5 dBm at 5.5 Mbps, Type 25±1.5 dBm at 11 Mbps 802.11g: Type 23±1.5 dBm at 6 to 24 Mbps, Type 21±1.5 dBm at 36 Mbps Type 19±1.5 dBm at 48 Mbps, Type 18±1.5 dBm at 54 Mbps 802.11n: Type 23±1.5 dBm at MCS0/8 20 MHz, (2.4 GHz) Type 18±1.5 dBm at MCS7/15 20 MHz Type 23±1.5 dBm at MCS0/8 40 MHz Type 17±1.5 dBm at MCS7/15 40 MHz 802.11a: Type 23±1.5 dBm at 6 to 24 Mbps, Type 21±1.5 dBm at 36 Mbps Type 20±1.5 dBm at 48 Mbps, Type 18±1.5 dBm at 54 Mbps 802.11n: Type 23±1.5 dBm at MCS0/8 20 MHz (5 GHz) Type 18±1.5 dBm at MCS7/15 20 MHz Type 23±1.5 dBm at MCS0/8 40 MHz Type 17±1.5 dBm at MCS7/15 40 MHz

Note: In accordance with regional regulations, the maximum permissible transmit power is limited on the UNII bandwidths via the device firmware. The corresponding values are contained in the following tables:

	US model	EU model
2.4 GHz	26 dBm	18 dBm
5 GHz (UNII-1)	23 dBm	21 dBm
5 GHz (UNII-2)	23 dBm	21 dBm
5 GHz (UNII-2e)	23 dBm	23 dBm
5 GHz (UNII-3)	23 dBm	-

Receive sensitivity	802.11b: • 93 dBm at 1 Mbps, -93 dBm at 2 Mbps • 93 dBm at 5.5 Mbps, -88 dBm at 11 Mbps 802.11g: • 88 dBm at 6 Mbps, -86 dBm at 9 Mbps • 85 dBm at 12 Mbps, -85 dBm at 18 Mbps • 85 dBm at 24 Mbps, -82 dBm at 36 Mbps • 78 dBm at 48 Mbps, -74 dBm at 54 Mbps 802.11n: • 70 dBm at MCS7 20 MHz, -69 dBm at MCS15 20 MHz (2.4 GHz) • 67 dBm at MCS7 40 MHz, -67 dBm at MCS15 40 MHz 802.11a: • 90 dBm at 6 Mbps, -88 dBm at 9 Mbps • 88 dBm at 12 Mbps, -85 dBm at 18 Mbps • 81 dBm at 24 Mbps, -78 dBm at 36 Mbps • 74 dBm at 48 Mbps, -72 dBm at 54 Mbps 802.11n: • 69 dBm at MCS7 20 MHz, -71 dBm at MCS15 20 MHz (5 GHz) • 63 dBm at MCS7 40 MHz, -68 dBm at MCS15 40 MHz
---------------------	--

Supported protocols	General protocols	
	Proxy ARP, DNS, HTTP, HTTPS, IP, ICMP, SNTP, TCP, UDP, RADIUS, SNMP, DHCP, LLDP, VLAN, STP/RSTP	
Interfaces	Supported protocols	
Supplied antenna	2x omni-directional dual-band antenna, 2 dBi, RP-SMA (male)	
Connection for external antennas	RP-SMA (female), 500 V insulation	
RJ45 port	1x 10/100/1000BaseT (X) auto negotiation, full/half duplex mode and auto MDI/MDI-X connection	
Console port	RS 232 (RJ45 connection)	
Alarm contact	1 relay output with a current capacity of 1 A at 24 V DC	
Digital inputs	2 galvanically separated inputs • +13 to +30 V for the state "1" • +3 to -30 V for the state "0" • max. Current consumption: 8 mA	

Technical data

Technical data	
Housing	Metal, IP30 protection class
Weight	860 g
Dimensions (W x H x D)	52.7 x 135 x 105 mm (2.08 x 5.32 x 4.13 in)
Installation	DIN-Rail
Environmental conditions	
Operating temperature	Standard models: -25 to 60°C (-13 to 140°F) Models with extended temperature range: -40 to 75 °C (-40 to 167 °F)
Storage temperature	-40 to 85 °C (-40 to 185 °F)
Relative ambient air humidity	5% to 95% (non-condensing)
Power supply	
Input voltage	24 V DC (12 to 48 V DC), two redundant inputs or 48 V DC PoE (IEEE802.3af)
Connection	1 removable 10-pin terminal block, 500 V insulation
Current consumption	0.6 A at 12 VDC 0.15 A at 48 VDC
Power consumption	7.2 W
Reverse polarity protection	Present
Approvals	
Safety	EN62368-1, UL 60950-1
Wireless	EN 301 489-1/17, EN 300 328, EN 301 893, TELEC, FCC ID: SLE-WAPN008, KC
EMC	EN 61000-6-2/6-4 CISPR 32, FCC Part 15B Class B IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 3 V/m IEC 61000-4-8 PFMF: 1 A/m
Explosive risk zones	UL / cUL Class I, Division 2; ATEX Zone 2 Ex nA IIC T4 Gc
MTBF (mean time between failures)	
Time	570,854 hrs
Database	Telcordia (Bellcore), GB
Warranty	
Period	5 Years

Ordering data

Version	Type	Operating Temperature	Order No.
WLAN Access Point/Bridge/Client, IEEE 802.11 a/b/g/n, EU-Modell	IE-WL-VL-AP-BR-CL-EU	-25 to +60 °C	2536680000
WLAN Access Point/Bridge/Client, IEEE 802.11 a/b/g/n, US-Modell	IE-WL-VL-AP-BR-CL-US	-40 to +75 °C	2536690000
WLAN Access Point/Bridge/Client, IEEE 802.11 a/b/g/n, EU-Modell	IE-WL-VL-AP-BR-CL-EU	-25 to +60 °C	2536700000
WLAN Access Point/Bridge/Client, IEEE 802.11 a/b/g/n, US-Modell	IE-WL-VL-AP-BR-CL-US	-40 to +75 °C	2536710000

Accessories	Type	Order No.
External backup and restore module	EBR-Modul RS232	1241430000
19" Rack Mounting Kit	RM-KIT	1241440000

Active components

Overview of accessories

Accessories – Active components		
Introduction – Accessories – Active components		I.2
SFP transceiver (for use with switches of Eco- Advanced- and SubstationLine)		I.4
SFP transceiver (for use with switches of Basic- Value- and PremiumLine)		I.7
Configuration backup and restore module (for use with switches of Value- and PremiumLine such as Basic- and ValueLine WLAN devices)		I.8
Configuration backup and restore module (for use with switches of Advanced- and SubstationLine)		I.9
Mounting kits for 19" rack and wall		I.10

Easy assembly, configuration and operation

Our accessories for active Industrial Ethernet solutions

Industrial Ethernet connection solutions from Weidmüller are versatile and can be precisely matched to the infrastructure of your machine, system or factory. In order to guarantee optimum functionality, we provide you with all the connection technology from a single source. We also offer a wide range of accessories for your active Industrial Ethernet components.

Configuration module

To quickly back up, restore and load configurations, we recommend our configuration module. It supports you in performing reconfigurations for replacement devices, thereby minimising your downtimes.

SFP transceivers

Our SFP transceivers give you more flexibility in your choice of transmission media. We offer you a broad selection – for transmission speeds up to 10 Gbit/s and distances up to 60 km. The modules support digital diagnostic monitoring (DDM) for the easy monitoring of the transceiver status.

19" mounting kit

For our Industrial Ethernet components, we also offer a mounting kit as an alternative for the installation of DIN rail-based components in 19" racks.

Individual solutions

In addition to our line of accessories, we provide you with a wide range of products and services for custom connection solutions. This also includes our assembly service, which supports you in mastering even the most complex cabling tasks.

Customer-specific cable configuration



Fast Ethernet SFP transceiver (for use with switches of Eco- Advanced- and SubstationLine)**Fast Ethernet SFP transceiver**

- IEEE 802.3u compliant
- Class 1 laser product; EN 60825-1 compliant
- Pluggable during operation (hot pluggable)
- Supports DDM (Digital Diagnostic Monitoring)

**Technical data****Fibre optic transceiver characteristics**

	IE-SFP-1FE-MM-2	IE-SFP-1FE-SM-30	IE-SFP-1FE-SM-60
	2682450000	2682460000	2682470000
Transmission speed	100 Mbit/s	100 Mbit/s	100 Mbit/s
Digital Diagnostic Monitor function (DDM)	Supported	Supported	Supported
Transceiver Type	Multimode	Singlemode	Singlemode
Connector type	LC-Duplex	LC-Duplex	LC-Duplex
Fiber Cable Type	OM1, OM2	G.652	G.652
Typical Distance	2 km, 4 km	30 km	60 km
Wavelength typ (nm)	1310	1310	1310
Wavelength (TX) range (nm)	1270 to 1380	1280 to 1340	1280 to 1340
Wavelength (RX) range (nm)	1260 to 1620	1260 to 1620	1260 to 1620
Optical Power (TX) range (dBm)	-14 to -20	-8 to -15	0 to -5
Optical Power (RX) range (dBm)	-3 to -32	-3 to -34	-3 to -34
Link-Budget (dB)	12	19	29

Note: When connecting a single-mode fiber transceiver over a short distance, we recommend using an attenuator to prevent the transceiver from being damaged by excessive optical power.

Power supply

Voltage supply 3.3 V (via Ethernet switch)

Physical characteristics

Type of mounting Insert in SFP slot

Weight 46 g

Environmental conditions

Operating temperature -40 to 85 °C (-40 to 185 °F)

Storage temperature -40 to 85 °C (-40 to 185 °F)

Humidity 5 to 95 % (non-condensing)

EMC conformity and approvals

EMC EN 55032, EN 55024

Guarantee

Time interval 3 years

Ordering Information

Version	Model Type	Order No.
SFP Transceiver, 100 Mbit/s, Multimode, LC-Duplex, 2 km, -40 °C...85 °C	IE-SFP-1FE-MM-2	2682450000
SFP Transceiver, 100 Mbit/s, Singlemode, LC-Duplex, 30 km, -40 °C...85 °C	IE-SFP-1FE-SM-30	2682450000
SFP Transceiver, 100 Mbit/s, Singlemode, LC-Duplex, 60 km, -40 °C...85 °C	IE-SFP-1FE-SM-60	2682470000

Gigabit Ethernet SFP transceiver

- IEEE 802.3z compliant
- Class 1 laser product; EN 60825-1 compliant
- Pluggable during operation (hot pluggable)
- Supports DDM (Digital Diagnostic Monitoring)

**Technical data****Fibre optic transceiver characteristics**

	IE-SFP-1GE-MM-05	IE-SFP-1GE-MM-2	IE-SFP-1GE-SM-10	IE-SFP-1GE-SM-40	IE-SFP-1GE-SM-10-BiDi-TX1310	IE-SFP-1GE-SM-10-BiDi-TX1550	IE-SFP-1GE-SM-20-BiDi-TX1310	IE-SFP-1GE-SM-20-BiDi-TX1550
	2682480000	2682490000	2682500000	2682510000	2682520000	2682530000	2682540000	2682550000
Transmission speed	1000 Mbit/s	1000 Mbit/s	1000 Mbit/s	1000 Mbit/s	1000 Mbit/s	1000 Mbit/s	1000 Mbit/s	1000 Mbit/s
Digital Diagnostic Monitor function (DDM)	Supported	Supported	Supported	Supported	Supported	Supported	Supported	Supported
Transceiver Type	Multimode	Multimode	Singlemode	Singlemode	Singlemode BiDi	Singlemode BiDi	Singlemode BiDi	Singlemode BiDi
Connector type	LC-Duplex	LC-Duplex	LC-Duplex	LC-Duplex	LC-Simplex	LC-Simplex	LC-Simplex	LC-Simplex
Fiber Cable Type	OM1, OM2	OM1, OM2	G.652	G.652	G.652	G.652	G.652	G.652
Typical Distance	275 m, 550 m	2 km	10 km	40 km	10 km	10 km	20 km	20 km
Wavelength typ (nm)	850	1310	1310	1310	RX 1550 / TX 1310	RX 1310 / TX 1550	RX 1550 / TX 1310	RX 1310 / TX 1550
Wavelength (TX) range (nm)	830 to 870	1270 to 1355	1280 to 1365	1280 to 1350	1270 to 1355	1510 to 1570	1270 to 1355	1510 to 1570
Wavelength (RX) range (nm)	770 to 870	1260 to 1620	1260 to 1620	1260 to 1610	1470 to 1600	1250 to 1380	1470 to 1600	1250 to 1380
Optical Power (TX) range (dBm)	-3 to -9	-1 to -9	-3 to -9	+3 to -3	-3 to -9	-3 to -9	-2 to -8	-2 to -8
Optical Power (RX) range (dBm)	-3 to -18	-1 to -19	-3 to -20	-3 to -24	-3 to -20	-3 to -20	-3 to -23	-3 to -23
Link-Budget (dB)	9	10	11	21	11	11	15	15

Note: When connecting a single-mode fiber transceiver over a short distance, we recommend using an attenuator to prevent the transceiver from being damaged by excessive optical power.

Power supply

Voltage supply 3.3 V (via Ethernet switch)

Physical characteristics

Type of mounting Insert in SFP slot

Weight 46 g

Environmental condition

Operating temperature -40 to 85 °C (-40 to 185 °F)

Storage temperature -40 to 85 °C (-40 to 185 °F)

Humidity 5 to 95 % (non-condensing)

EMC conformity and approvals

EMC EN 55032, EN 55024

Guarantee

Time interval 3 years

Ordering Information

Version	Model Type	Order No.
SFP Transceiver, 1000 Mbit/s, Multimode, LC-Duplex, 0.5 km, -40 °C...85 °C	IE-SFP-1GE-MM-05	2682480000
SFP Transceiver, 1000 MBit/s, Multimode, LC-Duplex, 2 km, -40 °C...85 °C	IE-SFP-1GE-MM-2	2682490000
SFP Transceiver, 1000 Mbit/s, Singlemode, LC-Duplex, 10 km, -40 °C...85 °C	IE-SFP-1GE-SM-10	2682500000
SFP Transceiver, 1000 MBit/s, Singlemode, LC-Duplex, 40 km, -40 °C...85 °C	IE-SFP-1GE-SM-40	2682510000
SFP Transceiver, 1000 MBit/s, Singlemode, BiDi, LC-Simplex, 10 km, -40 °C...85 °C	IE-SFP-1GE-SM-10-BiDi-TX1310	2682520000
SFP Transceiver, 1000 MBit/s, Singlemode, BiDi, LC-Simplex, 10 km, -40 °C...85 °C	IE-SFP-1GE-SM-10-BiDi-TX1550	2682530000
SFP Transceiver, 1000 Mbit/s, Singlemode, BiDi, LC-Simplex, 20 km, -40 °C...85 °C	IE-SFP-1GE-SM-20-BiDi-TX1310	2682540000
SFP Transceiver, 1000 Mbit/s, Singlemode, BiDi, LC-Simplex, 20 km, -40 °C...85 °C	IE-SFP-1GE-SM-20-BiDi-TX1550	2682550000

10 Gigabit Ethernet SFP+ transceiver (for use with switches of SubstationLine)**10 Gigabit Ethernet SFP+ transceiver**

- IEEE 802.3ae compliant
- Class 1 laser product; EN 60825-1 compliant
- Pluggable during operation (hot pluggable)
- Supports DDM (Digital Diagnostic Monitoring)

**Technical data****Fibre optic transceiver characteristics**

	IE-SFP-10GE-MM-03	IE-SFP-10GE-SM-20	IE-SFP-10GE-SM-40
	2779110000	2779120000	2779130000
Transmission speed	10 Gbit/s	10 Gbit/s	10 Gbit/s
Digital Diagnostic Monitor function (DDM)	Supported	Supported	Supported
Transceiver Type	Multimode	Singlemode	Singlemode
Connector type	LC-Duplex	LC-Duplex	LC-Duplex
Fiber Cable Type	OM1, OM2, OM3	G.652	G.652
Typical Distance	33 m, 82 m, 300 m	20 km	40 km
Wavelength typ (nm)	850	1310	1550
Wavelength (TX) range (nm)	840 to 860	1260 to 1355	1530 to 1565
Wavelength (RX) range (nm)	840 to 860	1260 to 1600	1250 to 1600
Optical Power (TX) range (dBm)	-1 to -6.5	0.5 to -4	4 to -4.7
Optical Power (RX) range (dBm)	-1 to -9.9	0.5 to -15	-1 to -15.8
Link-Budget (dB)	3.4	11	11.1

Note: When connecting a single-mode fiber transceiver over a short distance, we recommend using an attenuator to prevent the transceiver from being damaged by excessive optical power.

Power supply

Voltage supply 3.3 V (via Ethernet switch)

Physical characteristics

Type of mounting Insert in SFP slot

Weight 46 g

Environmental conditions

Operating temperature -40 to 85 °C (-40 to 185 °F)

Storage temperature -40 to 85 °C (-40 to 185 °F)

Humidity 5 to 95 % (non-condensing)

EMC conformity and approvals

EMC EN 55032, EN 55024

Guarantee

Time interval 3 years

Ordering Information

Version	Model Type	Order No.
SFP+ Transceiver, 10 Gbit/s, Multimode, LC-Duplex, 0.3 km, -40 °C...85 °C	IE-SFP-10GE-MM-03	2779110000
SFP+ Transceiver, 10 Gbit/s, Singlemode, LC-Duplex, 20 km, -40 °C...85 °C	IE-SFP-10GE-SM-20	2779120000
SFP+ Transceiver, 10 Gbit/s, Singlemode, LC-Duplex, 40 km, -40 °C...85 °C	IE-SFP-10GE-SM-40	2779130000

Gigabit Ethernet SFP-Transceiver

- Supports DDM (Digital Diagnostic Monitoring)
- IEEE 802.3z-conform
- Symmetric LVPECL inputs and outputs
- TTL signal detection indicator
- Pluggable during operation (hot pluggable)
- Class 1 laser product; EN 60825-1-conform

**Technical data****Interfaces**

Fibre-optic ports 100BaseSFP (LC-duplex connection)

Specification optical fiber

	1000BaseSFP			
	SFP-SX	SFP-LSX	SFP-LX	SFP-LHX
Transceiver Type	Multi-Mode	Multi-Mode	Single-Mode	Single-Mode
Fiber Cable Type	OM1	OM2	OM1	OM2
Typical Distance	300 m	550 m	1 km	2 km
Wave-length	Typical (nm)	850	1310	1310
	TX Range (nm)	830 to 860	1270 to 1355	1280 to 1355
	RX Range (nm)	770 to 860	1260 to 1610	1260 to 1610
	TX Range (dBm)	-4 to -9.6	-1 to -9	-3 to -9
Optical Power	RX Range (dBm)	0 to -18	-1 to -19	-3 to -21
	Link-Budget (dB)	8.5	10	12
	Dispersion Penalty (dB)	4.3	3.6	5

Note: When connecting a single-mode fiber transceiver over a short distance, we recommend using an attenuator to prevent the transceiver from being damaged by excessive optical power.

Power consumption max. 1 Watt

Environmental LimitsOperating temperature Standard Models: 0 to 60 °C (32 to 140 °F)
Wide Temp. Models: -40 to 75 °C (-40 to 167 °F)

Storage Temperature -40 to 85 °C (-40 to 185 °F)

Ambient Relative Humidity 5 to 95 % (non-condensing)

Approvals

Security CE, FCC, TÜV (EN 60825), UL 60950-1

Maritime DNV-GL

Warranty

Warranty Period 5 years

Ordering data

SFP Variants	Type	Operating Temperature	Order No.
Gigabit-Ethernet, Multimode, LC-duplex connection, 500 m	IE-SFP-1GSXL	0 to +60 °C	1241490000
	IE-SFP-1GSXL-T	-40 to 85 °C	1286700000
Gigabit-Ethernet, Multimode, LC-duplex connection, 2 km	IE-SFP-1GLSXL	0 to +60 °C	1241500000
	IE-SFP-1GLSXL-T	-40 to 85 °C	1286710000
Gigabit-Ethernet, Singlemode, LC-duplex connection, 10 km	IE-SFP-1GLXL	0 to +60 °C	1241510000
	IE-SFP-1GLXL-T	-40 to 85 °C	1286720000
Gigabit-Ethernet, Singlemode, LC-duplex connection, 40 km	IE-SFP-1GLHXL	0 to +60 °C	1241520000
	IE-SFP-1GLHXL-T	-40 to 85 °C	1286730000

Fast Ethernet SFP-Transceiver

- Supports DDM (Digital Diagnostic Monitoring)
- IEEE 802.3u-conform
- Symmetric PECL inputs and outputs
- TTL signal detection indicator
- Pluggable during operation (hot pluggable)
- Class 1 laser product; EN 60825-1-conform

**Technical data****Interfaces**

Fibre-optic ports 100BaseSFP (LC-duplex connection)

Specification optical fiber

	100BaseSFP	
	SFP-M	SFP-S
Transceiver Type	Multi-Mode	Single-Mode
Fiber Cable Type	OM1/OM2	50/125 µm 62/125 µm 800 MHz*km
Typical Distance	2 km	4 km
Wave-length	Typical (nm)	1300 1310
	TX Range (nm)	1280 to 1340
	RX Range (nm)	1100 to 1600
	TX Range (dBm)	-8 to -18
Optical Power	RX Range (dBm)	0 to -5
	Link-Budget (dB)	-3 to -32
	Dispersion Penalty (dB)	14 29

Note: When connecting a single-mode fiber transceiver over a short distance, we recommend using an attenuator to prevent the transceiver from being damaged by excessive optical power.

Power consumption max. 1 Watt

Environmental Limits

Operating temperature -40 to 85 °C (-40 to 185 °F)

Storage Temperature -40 to 85 °C (-40 to 185 °F)

Ambient Relative Humidity 5 to 95 % (non-condensing)

Approvals

Security CE, FCC, TÜV (EN 60825), UL 60950-1

Maritime DNV-GL

Warranty

Warranty Period 5 years

Ordering data

Port Variants	Type	Operating Temperature	Order No.
Fast Ethernet, Multimode, LC-duplex connection, 4 km	IE-SFP-1FEMLC-T	-40 to +85 °C	1241450000
Fast Ethernet, Singlemode, LC-duplex connection, 40 km	IE-SFP-1FESLC-T	-40 to +85 °C	1241470000

Configuration backup and restore module (for use with switches of Value- and PremiumLine such as Basic- and ValueLine WLAN devices)**Module for saving and loading a device configuration**

- Reduce system downtime by simple reconfiguration in case of replacing devices
- Automatic loading of the saved configuration possible after device restart
- Compact, rugged, reliable design
- For use with switches of Value- and PremiumLine such as Basic- and ValueLine WLAN devices

**Technical data****Basic Operation**

Connection	RS 232 (RJ45 connection), is plugged into the corresponding console port on the managed switch or WLAN Access Point.
------------	--

Configuration	Saving and loading of the corresponding device configuration via web interface of the managed switch or the WLAN Access Point
---------------	---

Power Requirements

Input Voltage	3 to 5 V DC (through the RS 232 port's RTS signal)
---------------	--

Technical data

Housing	PVC molding, IP40 protection
Dimensions (W x H x D)	32.5 x 97 x 12 mm (8.07 x 3.82 x 0.47 in)
Weight	50 g
Mounting possibility	M4 screw (< 4 mm)
Cable Length	35 cm (including connector)

Environmental Limits

Operating temperature	0 to 60 °C (32 to 140 °F)
Storage Temperature	-20 to 70 °C (-4 to 158 °F)
Ambient Relative Humidity	5 to 95 % (non-condensing)

Approvals

EMC	EN 55032 Class A CISPR 32, FCC Part 15B Class A IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8
-----	---

Warranty

Warranty Period	5 years
-----------------	---------

Ordering data

Version	Type	Order No.
External Backup and Restore Module	EBR-MODULE RS232	1241430000

Module for saving and loading a device configuration

- Reduce system downtime by simple reconfiguration in case of replacing devices
- 2 storage spaces selectable via DIP switch
- Compact, rugged, reliable design
- For use with switches of Advanced- and SubstationLine

**Technical data****Interfaces**

Connector	RJ45 connector (plugged into device's console port)
DIP switches	1x for selection of the configuration storage space (A or B) 1x for selection between upload or download of a configuration
Start button	Starts the upload or download of a configuration
LED indicators	Power, data transmitting, transmission status
Power supply	
Connection type	RJ45 connector
Input voltage	5 V DC (via RS-232 RTS signal of serial console port)
Current consumption at 5 V	0.14 A
Physical characteristics	
Housing main material	PC molding
Protection degree	IP40
Dimensions (W x H x D)	Module: 32 x 14.5 x 90.25 mm (1.25 x 0.57 x 3.5 in) Cable length: 210 mm (8.27 in) including RJ45 connector
Weight	33 g

Environmental conditions

Operating temperature	-10 to 60°C (14 to 140°F)
Storage temperature	-40 to 85 °C (-40 to 185 °F)
Humidity	5 to 95 % (non-condensing)
Operating altitude	≤ 2000 m

EMC conformity and approvals

EMC	EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz bis 1 Ghz: 3 V/m
-----	---

Safety

Safety	UL 61010-1, UL 61010-2-201
Shock	IEC 60068-2-27
Vibration	IEC 60068-2-6
Free fall	IEC 60068-2-31

MTBF

Time	6.645.051 hrs
Database	Telcordia SR332

Supported switch models

The EBR-Module can be used with the listed switches of Advanced- and SubstationLine only.	IE-SW-AL06M-4GTPoE-2GESFP IE-SW-AL08M-8GTPoE IE-SW-AL08M-8GT IE-SW-AL12M-8GT-4GESFP IE-SW-AL14M-12GT-2GESFP IE-SW-AL24M-16GT-8GESFP IE-SW-SL20M-8GT-12GESFP-HV IE-SW-SL20M-8GT-12GESFP-LV IE-SW-SL28M-HV IE-SW-SL28M-LV
---	--

Guarantee

Time interval	3 years
---------------	---------

Ordering Information

Version	Model Type	Order No.
External Backup and Restore Module	IE-EBR-MODULE-RS232-ALM	2682610000

Mounting kits for 19" rack and wall

Kit for 19" rack-mounting

- For mounting DIN-rail based devices in 19" racks



Technical data

Technical data

Dimensions (W x H x D) 481 x 177.8 x 202.4 mm

Ordering data

Version	Type	Order No.
19" Rack Mounting Kit	RM-KIT	1241440000

Wall mounting kit

- Mounting kit for alternative wall-mounting of DIN rail-based Industrial Ethernet components.



Technical data

Usage

Industrial Ethernet Switches

Product lines:
IE-SW-BL05

Ordering data

Version	Type	Order No.
Wall mounting kit	IE-WALLMOUNT-KIT-30MM	1504450000

Passive components

Introduction

Introduction – Passive components	
IE-line connectors	J.2
Cable configurator	J.4
Differences between industrial and office Ethernet	J.6
PROFINET and SERCOS III cabling solutions	J.8
EtherNet/IP cabling solutions	J.12

IE-LINE plug-in connectors

Clever and flexible with **STEADYTEC®** technology



STEADYTEC® – this name stands for the future of connection technology in the field of data and signal transmissions. Established market leaders in the industry, **STEADYTEC®** forms the foundation for reliable, application-orientated, standards-compliant solutions - for offices through to areas with harsh industrial conditions.

The objective: The development of reliable plug-in connector technologies for industrial applications. Technologies that satisfy the highest customer demands and hence enable new, specialised and dependable solutions.

The result: An extremely reliable, extraordinarily practical, flexible and especially efficient plug-in connector system for office and industrial applications. And using products whose characteristics accurately reflect the values originally laid out:

- fast
- reliable
- solution-based
- simple

The Ethernet connector system: clever – flexible

Connectors for modern industrial applications need to be designed in such a way that they simplify processes and cope with faster data transmission. Weidmüller's Ethernet connectors keep you a step ahead. These products are not only ready for 10 gigabit, they are also standardised for IEC 61076-3-106 and IEC 61076-3-117. In addition, the connector variants 4 (Ethernet TCP/IP), variants 5 and 1 (Ethernet IP) and variant 14 (PROFINET/AIDA) which are named in these standards are all specified as mandatory in the standards covering generic cabling systems for industrial premises: ISO/IEC 24702, IEC 61918 (Automation Island), as well as for Fieldbus installations IEC 61784-5. What's more, you have a unique choice of versions made of plastic or metal as well as inserts for copper and fibre-optic cabling. All of the connectors are designed for ease of use and for quick on-site assembly. They are also modular and can be tailored to suit your application.





Tool-free assembly and powerful connections: the RJ45 gigabit connector!

You can now securely plug the connector you need directly into your machinery with very little effort – and without a single tool! The 10-gigabit connector, with IDC-connection, was developed to provide quick, simple, secure and, most importantly, tool-free wiring.

In addition, zinc die-casting makes the connector more robust and therefore suitable for industrial applications and as it is fitted with a protected locking clip means it is suitable for meeting the requirements of harsh industrial environments. Weidmüllers IE product line fulfills the requirements for 10 GBit Ethernet, according to IEEE 802.3an, up to 500 MHz.

STEADYTEC®: Systematic benefits

- **Cat. 6A 10 GBit System Class E_A**
- **Assembly without tools in the field**
- **Countless variations thanks to highly diverse combinations of inserts**
- **Unrestricted compatibility because standardised to IEC 61076-3-106**
- **Reliable and long-lasting thanks to use of diecast zinc**
- **Suitable for industry thanks to IP67 class of protection**
- **Simple ordering procedure and low storage costs thanks to Weidmüller's modular system**



1. Strip sheath cladding and shorten shield to 5 mm



2. Prepare wires and shorten



3. Snap together the two pluggable elements



4. Finished

Cable configurator

Tailor-made connections

The cable configurator allows you to configure your specific cable with comfort, speed and simplicity. Just select, request order – and you are finished!

Make your selection from the list of available cables (material for cable sheathing, category, colour, ...). Next, choose the connector for both the right and left cable ends and then choose the cable length. Configurations which are not possible are marked in red, so that it is not possible to create an unsupported or wrong configuration.



The Industrial Ethernet Configurator can be found in our online catalogue.

Our configurator creates connections tailor-made.

You will be forwarded directly and will be able to configure a fibre-optic or copper cable.

Weidmüller

Industrial Ethernet product configurator

The industrial ethernet cable configurator allows you to conveniently assemble IP cables (copper and fibre-optic) according to your requirements and specifications. You have the choice of configuring a cable which is identical on both ends, or with two different mating profiles, or with one end off open. The cable configurator can also automatically create technical data sheets for all of your customised cable variants.

Connection type

- > Copper cable
- > Fiber optic cables

After you have made your selection, there are several available options:

- Locate and display the data sheet for the assembled cable
- Export the information in Excel or CSV format
- Save the configuration
- Create additional cables or load previous cables
- Place the assembled cable in the shopping cart to obtain a quote or to order



Practically all types of connectors and cables can be combined to your requirements!

Weidmüller

www.weidmueller.com

Project Management | Configuration | Parts list | Help

Product Catalog > Product variants > Industrial Ethernet

Industrial Ethernet product configurator

The Industrial Ethernet cable configurator allows you to quickly make assembled Ethernet cables, up to 1000 m long, according to your requirements, and save them in your own library. You can also combine them with other which is possible at both ends, or with two different mating profiles, or with one end left open. The cable configurator can also automatically create technical data sheets for all of your customized cable variants.

Configuration - Copper cable

Designation: IE-C6E58UQ0550B41AZS-X
Order no.:

6 m

Plug 1: Multiport Ethernet IEC metal
Termination: Female
Cable type: Screened
Cable color: Green

Plug 2: M12 IP67 PushPull V10 metal
Cable: Cat.7 PU/R
Length [m]: Individual lengths

Next > Back to choose for connection type

From office communication to Industrial Ethernet

An overview of the differences

Office Ethernet



Industrial Ethernet



Cabling

- Fixed building installation
- Variable connection options
- Pre-assembled connection cables
- Star topology most widely in use

- Individual plant-influenced networks
- Robust component characteristics
- On-site, user assembly connections
- Redundant network topologies (ring)

Transmission

- Large volume of data
- Mid-level network availability
- Mostly only acyclical transmission
- No real-time characteristics required for standard applications

- Small data packets (measurement values)
- Very high network availability
- Extremely high real-time requirement
- Mostly cyclical transmission

Surroundings

- No extreme conditions

- Extreme temperatures
- Dust, dirt, splashing water, oils gases,
- Vibration, electromagnetic fields
- Risks of danger and damage from mechanical or chemical influences

Customised cabling solutions for PROFINET and SERCOS III

Weidmüller's cabling products enable you to create a specific infrastructure that meets all the requirements of PROFINET and SERCOS III.

The cabling components for copper and fibre-optic cables are designed and tested for use in harsh industrial conditions. Interoperability in the system is assured by the PROFINET and SERCOS cabling guidelines that specifically prescribe the interfaces to be used. For PROFINET this is guaranteed through the manufacturer's declaration.

Comprehensive protection against disturbance by electromagnetic fields is achieved through the use of high quality shielding of the cables and the related connection components. Significant system reserves are offered through the star quad design of the cables and their wire cross-section of AWG 22. Stable real-time transmission is guaranteed, for applications such as PROFINET IRT or SERCOS III typical hardware synchronisation, by the low signal transmission time differences resulting from the cable construction. At the same time the cables offer high crush resistance for reliable installation in industrial applications.

The cabling components are also remarkably easy to handle when out in the field. The plug-in connectors for copper and fibre-optic can all be assembled on-site. This reduces installation time, reduces errors and simplifies maintenance.



Sercos
the automation bus

Profile specific guidelines for the connection components

Cable:

- Quad-star design of AWG 22

Connector:

- IP20 RJ45
- IP20 SC-RJ
- IP67 PushPull RJ45
- IP67 PushPull Power
- IP67 PushPull SC-RJ
- IP67 M12 D-coding



Weidmüller offers you a wide range of cabling solutions for PROFINET and SERCOS III applications. IP20 plug-in connectors for copper and fibre-optic cables are also included as well as IP67 plug-in connectors and junction

boxes for the toughest requirements. The components are designed to be used together from the floor distributors down to the machines.

IP67
assembled RJ45 cables



IP67
assembled M12 cables




IP67
plug-in M12 connectors



IP67
connection components



Raw cable
copper and fibre-optic



IP67
plug-in connectors data / power



IP67
flanges data / power



IP20
plug-in connector



IP20
assembled cables



IP20
mounting rail outlets



IP65
service interfaces



Selection table

Ideal combinations



Sercos
the automation bus

IP20 plug-in connector



Description	Type	Order No.
RJ45 tool-free PROFINET printing	IE-PS-RJ45-FH-BK-P	1132060000
RJ45 tool-free angled Profinet printing	IE-PS-RJ45-FH-90-P-1.6	1518100000
SC-RJ for POF fibres 1 mm	IE-PS-SCRJ1-POF	1206720000

IP20 assembled data cables



Description	Type	Order No.
RJ45 patch cable PVC type B - 1 m	IE-C5DS4VG0010A60A60-E	1522100010
RJ45 patch cable PVC type B - 3 m	IE-C5DS4VG0030A60A60-E	1522100030
RJ45 patch cable PVC type B - 5 m	IE-C5DS4VG0050A60A60-E	1522100050
RJ45 patch cable PVC type B - 10 m	IE-C5DS4VG0100A60A60-E	1522100100
SC-RJ zipcord patch cable - POF - 1 m	IE-FP02ZEE0001MSJ0SJ0-X	1273430010
SC-RJ zipcord patch cable - POF - 3 m	IE-FP02ZEE0003MSJ0SJ0-X	1273430030
SC-RJ zipcord patch cable - POF - 5 m	IE-FP02ZEE0005MSJ0SJ0-X	1273430050
SC-RJ zipcord patch cable - POF - 10 m	IE-FP02ZEE0010MSJ0SJ0-X	1273430100

Further PROFINET cables - SERCOS III cables can be found in Chapter L

IP20 mounting rail outlets



Description	Type	Order No.
RJ45 coupling	IE-T0-RJ45-C	8946920000
RJ45 module PROFINET printing	IE-T0-RJ45-FJ-P	8946950000
SC-RJ POF coupling / multimode	IE-T0-SCRJ-MM	8946990000
SC-RJ singlemode coupling	IE-T0-SCRJ-SM	8947000000

IP65 service interface



Beschreibung	Type	Order No.
FrontCom® Micro RJ45 coupling	IE-FCM-RJ45-C	1018790000
FrontCom® Micro RJ45 module PROFINET printing	IE-FCM-RJ45-FJ-P	1018830000

IP67 flange data



Description	Type	Order No.
PushPull standard flange RJ45 coupling	IE-BSS-V14M-RJ45-C	1012310000
PushPull central cable gland RJ45 coupling	IE-BSC-V14M-RJ45-C	1058250000
PushPull standardised flange RJ45 module PROFINET printing	IE-BSS-V14M-RJ45-FJ-P	1085260000
PushPull standardised flange hybrid (Q10) 10-pole module without contacts	IE-BSS-V14M-HYB-10P-FJ	1072900000
Contacts for Hybrid (Q10) module 0.5 mm² - 0.75 mm² VPE 300	IE-BIC-HYB-P-0,75-300	1068970000
Contacts for Hybrid (Q10) module 0.2 mm² - 0.5 mm² VPE 300	IE-BIC-HYB-P-0,5-300	1096150000
PushPull standardised flange SC-RJ coupling POF / multimode	IE-BSS-V14M-SCRJ-MM-C	1058120000
PushPull standardised flange SC-RJ coupling singlemode	IE-BSS-V14M-SCRJ-SM-C	1058140000
PushPull central cable gland SC-RJ coupling POF / multimode	IE-BSC-V14M-SCRJ-MM-C	1062590000
PushPull central cable gland SC-RJ coupling singlemode	IE-BSC-V14M-SCRJ-SM-C	1062600000
PushPull device flange	IE-BHD-V14M	1047940000

other inserts can be found in Chapter J

IP67 Power connectors



Description	Type	Order No.
PushPull Power with 24 V / 16 A use	IE-PS-VAPM-5P-2.5	2465440000

IP67 flange power



Description	Type	Order No.
PushPull Power standardised flange with 24 V / 16 A use	IE-BSS-VAPM-24V	2493480000
PushPull Power device flange	IE-BHD-VAPM	2493490000

IP67 data connectors

Description	Type	Order No.
	IE-PS-V14M-RJ45-FH-P	1012170000
		2768740000
PushPull Hybrid (Q10) use, 10-pole module without contacts	IE-PS-V14M-HYB-10P	1072910000
PushPull SC-RJ use POF 1 mm	IE-PS-V14M-2SC-POF	1191550000

IP67 assembled data cables

Description	Type	Order No.
	IE-C5DD4UG0010A2EA2EX	1119730010
PushPull RJ45 patch cable PUR - Type C - 3 m	IE-C5DD4UG0030A2EA2EX	1119730030
PushPull RJ45 patch cable PUR - Type C - 5 m	IE-C5DD4UG0050A2EA2EX	1119730050
PushPull RJ45 patch cable PUR - Type C - 10 m	IE-C5DD4UG0100A2EA2EX	1119730100

Further PROFINET cables - SERCOS III cables can be found in Chapter L

IP67 plug connector M12 D-coded and X-Type

M 12 components can be found in Chapter J

IP65 connection components

Description	Type	Order No.
	IE-CD-V14MRJ/VAPM24V-FJ	1068830000
FreeCon passive single junction box RJ45	IE-CD-V14MRJ-FJ	1068880000
FreeCon passive single junction box Hybrid (Q10) without contacts	IE-CD-V14MHYB-10P-FJ	1068850000
FreeCon passive double coupling RJ45/Power	IE-CD-V14MRJ/VAPM24V-C-MA	1068820000
FreeCon passive single coupling RJ45	IE-CD-V14MRJ-C-MA	1068870000
FreeCon passive single coupling hybrid (Q10)	IE-CD-V14MHYB-10P-C-MA	1068840000
FreeCon PushPull Power Y-distributor	IE-CD-VAPM24V-Y-MA	1297010000
FreeCon PushPull Power single coupling	IE-CD-VAPM24V-C-MA	1397690000
FreeCon passive single coupling SCRJ	IE-CD-V14MSCRJ-MM-C-MA	1318150000
FreeCon active FO PROFINET repeater	IE-CDR-V14MSCPOF/VAPM-C	1253240000
FreeCon active PROFINET media converter	IE-CDM-V14MRJSCP/VAPM-C	1324440000
FreeCon active FO PROFINET repeater II	IE-CDR-V14MSCPOF/VAPM-C II	2455360000
FreeCon active FO PROFINET media converter II	IE-CDM-V14MRJSCP/VAPM-C II	2588270000
FreeCon active PROFINET copper repeater	IE-CDR-V14MRJ/VAPM-C	2581810000
FreeCon passive cable coupling RJ45	IE-CC-V14M-RJ45-FJ-P	1990600000
FreeCon passive cable coupling hybrid	IE-CC-V14M-HYB-10P-FJ	1990610000
FreeCon passive cable coupling power	IE-CC-VAPM-24V	1990630000

Raw cable copper cable

Description	Type	Order No.
	IE-C5AS4VG-100	8899000000
500 m ring installation cable PVC type A	IE-C5AS4VG-500	2763430000
100 m ring connection cable PVC type B	IE-C5DS4VG-100	8898900000
500 m ring connection cable PVC type B	IE-C5DS4VG-500	2763470000
100 m ring dragline cable PUR type C	IE-C5DD4UG-100	8899010000
500 m ring dragline cable PUR type C	IE-C5DD4UG-500	2763450000
500 m ring Torsion cable PUR type C	IE-C5IT4UG-500	2763520000
500 m ring hybrid cable PVC	IE-C5DHAG-500	2763460000

Raw cable fibre-optic cable

Description	Type	Order No.
	IE-FP0D2UG-500	2763640000
500 m ring POF mini breakout cable 2X980/1000 µm PE	IE-FP0B2EG-500	2781950000

Customised cabling solutions for Ethernet/IP

The wiring guidelines for EtherNet/IP clearly define the interfaces to be used to ensure interoperability in EtherNet/IP systems.

Weidmüller offers all the cabling products needed to build a requirement specific infrastructure which is tailored to the needs of EtherNet/IP.

The wiring components for copper and fibre-optic cables are designed and tested for use in harsh industrial environments. The user is provided with clear guidelines about the requirements of the components for use in industrial environments with the introduction of the MICE classification (EtherNet/IP Media Planning and Installation Manual).

The high-quality shielding of the cables and connection components offers comprehensive protection against electromagnetic interference.

The cables are 8-wire twisted-pair cables for RJ45 or star quad for use in M12.

The cabling components are also easy to handle in the field. The plug-in connectors for copper and fibre optic cables can all be assembled on-site. This reduces installation time, reduces errors and simplifies maintenance.

The connectors wire/pin assignment is either according to TIA568-A or TIA568-B as required. The connectors and modules are marked accordingly, making them easier to connect.




Profile specific guidelines for the connection components

Cable:

- 8-wire twisted-pair shielded cables

Connector:

- IP20 RJ45
- IP20 SC-RJ
- IP67 bayonet RJ45
- IP67 M12 D-coding



Weidmüller offers you a wide range of cabling solutions for EtherNet/IP applications. IP20 plug-in connectors for copper and fibre-optic cables are available, as well as IP67 connectors and junction boxes for the most exacting

requirements. The components are designed to be used together from the floor distributors down to the machines.

IP67
assembled RJ45 cables



IP67
assembled M12 cables




IP67
plug-in M12 connectors



IP67
connection components



Raw cable
copper and fibre-optic



IP67
plug-in connectors data



IP67
flanges data / power



IP20
plug-in connector



IP20
assembled cables



IP20
mounting rail outlets



IP65
service interfaces



Selection table

Ideal combinations for a perfect fit



IP20 plug-in connector

Description	Type	Order No.
RJ45 crimp	IE-PS-RJ45-TH-BK	1963590000
RJ45 tool-free TIA-A printing	IE-PS-RJ45-FH-BK-A	1132040000
RJ45 tool-free TIA-B printing	IE-PS-RJ45-FH-BK-B	1132050000
SC-RJ for 1 mm POF fibres	IE-PS-SCRJ1-POF	1206720000

IP20 assembled data cables

Description	Type	Order No.
RJ45 patch cables - see CabinetLine		
SC-RJ zipcord patch cable - POF - 1 m	IE-FP02ZEE0001MSJOSJO-X	1273430010
SC-RJ zipcord patch cable - POF - 3 m	IE-FP02ZEE0003MSJOSJO-X	1273430030
SC-RJ zipcord patch cable - POF - 5 m	IE-FP02ZEE0005MSJOSJO-X	1273430050
SC-RJ zipcord patch cable - POF - 10 m	IE-FP02ZEE0010MSJOSJO-X	1273430100
Other EtherNet/IP cables available on request		

IP20 mounting rail outlets

Description	Type	Order No.
RJ45 coupling	IE-TO-RJ45-C	8946920000
RJ45 Module TIA-A printing	IE-TO-RJ45-FJ-A	8946930000
RJ45 Module TIA-B printing	IE-TO-RJ45-FJ-B	8946940000
SC-RJ POF coupling / multimode	IE-TO-SCRJ-MM	8946990000
SC-RJ singlemode coupling	IE-TO-SCRJ-SM	8947000000

IP65 service interface

Description	Type	Order No.
FrontCom® Micro RJ45 coupling	IE-FCM-RJ45-C	1018790000
FrontCom® Micro RJ45 module TIA-A printing	IE-FCM-RJ45-FJ-A	1018810000
FrontCom® Micro RJ45 module TIA-B printing	IE-FCM-RJ45-FJ-B	1018820000

IP67 flange data

Description	Type	Order No.
Bayonet flange metal RJ45 coupling	IE-BS-V01M-RJ45-C	1963470000
Bayonet flange metal RJ45 module TIA-A printing	IE-BS-V01M-RJ45-FJ-A	1963480000
Bayonet flange plastic RJ45 coupling	IE-BS-V01P-RJ45-C	1012370000
Bayonet flange metal RJ45 module TIA-B printing	IE-BS-V01P-RJ45-FJ-A	1012380000
Bayonet flange metal SC-RJ POF / multimode	IE-BS-V01M-SCRJ-MM	1221010000
Bayonet flange metal SC-RJ singlemode	IE-BS-V01M-SCRJ-SM	1221020000
Other inserts can be found in Chapter J		

IP67 data connectors

Description	Type	Order No.
Bayonet plug metal RJ45 crimped	IE-PS-V01M-RJ45-TH	1963140000
Bayonet plug metal RJ45 tool-free	IE-PS-V01M-RJ45-FH	1963120000
Bayonet plug plastic RJ45 crimped	IE-PS-V01P-RJ45-TH	1012470000
Bayonet plug plastic RJ45 tool-free	IE-PS-V01P-RJ45-FH	1012490000
Bayonet plug metal SC-RJ use POF	IE-PS-V01M-2SC-POF	1963280000

IP67 assembled data cables

Description	Type	Order No.
Bayonet metal RJ45 patch cable PUR 1 m	IE-C5ES8UG0010B41B41-E	1066850000
Bayonet metal RJ45 patch cable PUR 2 m	IE-C5ES8UG0020B41B41-E	1066860000
Bayonet metal RJ45 patch cable PUR 5 m	IE-C5ES8UG0050B41B41-E	1066870000
Bayonet metal RJ45 patch cable PUR 10 m	IE-C5ES8UG0100B41B41-E	1066880000
Bayonet plastic RJ45 patch cable PUR 1 m	IE-C5ES8UG0010P41P41-E	1106010000
Bayonet plastic RJ45 patch cable PUR 2 m	IE-C5ES8UG0020P41P41-E	1106020000
Bayonet plastic RJ45 patch cable PUR 5 m	IE-C5ES8UG0050P41P41-E	1106030000
Bayonet plastic RJ45 patch cable PUR 10 m	IE-C5ES8UG0100P41P41-E	1106040000
Other EtherNet/IP cables available on request		

IP67 plug-in M12 connectors

M 12 components can be found in Chapter J

IP65 connection components

Description	Type	Order No.
Single junction box, plastic	IE-OP-V01P-1S	1061830000
Plastic cable coupling	IE-CC-V01P	1061820000
RJ45 module TIA-A printing	IE-BI-RJ45-FJ-A	1962850000
RJ45 module TIA-B printing	IE-BI-RJ45-FJ-B	1963840000

Raw cable copper cable

Description	Type	Order No.
100 m ring installation cable PVC Cat. 5 SF/UTP	IE-C5CS8VG-100	8813150000
500 m ring installation cable PVC Cat. 5 SF/UTP	IE-C5CS8VG-500	2763440000
100 m ring installation cable PUR Cat. 5 SF/UTP	IE-C5CS8UG-100	8813160000
500 m ring installation cable PUR Cat. 5 SF/UTP	IE-C5CS8UG-500	2762870000
100 m ring connection cable PVC Cat. 5 SF/UTP	IE-C5ES8VG-100	8813190000
500 m ring connection cable PVC Cat. 5 SF/UTP	IE-C5ES8VG-500	2763510000
100 m ring connection cable PUR Cat. 5 SF/UTP	IE-C5ES8UG-100	8813200000
500 m ring connection cable PUR Cat. 5 SF/UTP	IE-C5ES8UG-500	2763500000
Other EtherNet/IP cables available on request		

Raw cable fibre-optic cable

Description	Type	Order No.
500 m ring POF breakout cable 2X980/1000 µm TPE	IE-FPOD2UG-500	2763640000
500 m ring POF mini breakout cable 2X980/1000 µm PE	IE-FPOB2EG-500	2781950000

Single Pair Ethernet

Single Pair Ethernet	Overview	K.2
	Assembled cables IP20	K.8
	Assembled cables IP67	K.9
	PCB components & field attachable components	K.11

Single Pair Ethernet

The network infrastructure for Industrial IIoT

K

In the factory of the future, machines and systems will be connected to each other consistently via a data infrastructure. These cyber-physical systems can act independently in the Industrial Internet of Things (IIoT), communicate in real time, and control production processes. In order to enable this, a continuous network with high-performance data connections from the sensor to the cloud is required. This pushes conventional Ethernet systems to their limits.

Single Pair Ethernet (SPE) facilitates the extension of the Ethernet to the sensor. It is compact, flexible, and enables high ranges. This means that data connections are achievable in situations where conventional Ethernet systems have reached their limits. SPE provides for the extension of existing installations and supports consistent communication based on the Ethernet protocol.

Indeed, SPE is considered by Weidmuller as the missing component needed to close the current gap in the supply of standard Ethernet at field level.

SPE runs at the same transmission speeds as conventional Ethernet but with simplified 2-wire cabling technology and data lines up to 1,000 m in length. Together with other new technologies such as TSN, OPC-UA, or 5G, SPE enables both continuous IP communication between the server and the cloud, as well as supplying up to 60 Watts of power in complex IIoT solutions through PoDL (Power over Data Line).



The new standard for high demands

SPE connectors for the industry

SPE connections can transfer data and power using only one twin wire. This enables both end-to-end IP communication between server and cloud, as well as power supply in complex IIoT solutions. SPE connectors therefore are particularly efficient and future-oriented.

The market requirements for data connectors in the field level are:

- Smallest, most compact design possible for implementing IIoT devices
- High robustness for use in industrial environments
- Easy to connect for safe, fast installation
- Future-proof design through international standards

Advantages of SPE connectors at a glance:

Miniaturisation



Industrial suitability



Simplicity

Future-proof

Particularly compact

Miniaturisation of SPE connectors according to IEC 63171-2



K

Weidmuller has been developing user-friendly connectors for industrial use, according to IEC63171-2. With a pitch of 7.62mm the compact connector system saves up to 50% space in comparison to RJ45 interfaces. The vertical arrangement of the two contacts allows a very high packing density. This enables device manufacturers to save valuable space on the PCB and to build smaller devices. This reduces port costs in device construction and effectively saves space in the control cabinet.

Small mating face

- Currently the smallest mating face according to IEC 63171 on the market

High packing density

- Double the packing density compared to RJ45 connectors
- Doubling of the interfaces with the same housing contour
- Only 20% of the volume of an RJ45 jack
- Minimum space requirement in the device


Easy IP67-integration

- Can be integrated into standard M8 housings and connectors as with I/O-Link or PROFINET
- M8 connectors with male and female contacts available
- Front and rear panel mounting with male and female contacts supported
- Simple integration in M8 sensors
- Inverse M8 system possible



Made for highest demands

The industrial suitability of SPE connectors



Originally developed for automotive applications, the aim of single pair ethernet technology was to realise the most efficient infrastructure capable of delivering high performance with as little cabling as possible. There are similar expectations within industry applications and building automation where the number of intelligent end devices in the plant is increasing but the amount of available space is not. Weidmuller SPE connector solutions deliver long cable lengths, a compact design that is simple, robust and vibration-proof, as well as being insensitive to electromagnetic influences.

Mechanical robustness

- Robust metal housing with metal snap-in hooks
- Safe industrial double contacting compared to single-sided contacting RJ45
- Shock resistant and vibration resistant according to IEC 60068
- Stable latching with lateral forces



EMC Compatibility

- Coupling attenuation at 600 MHz according to IEEE 802.3
- Additional burst test according to IEC 61000-6-2
- Optimum shield connection on the PCB due to four symmetrical legs

Industrial suitability

- PCB connectors for environments up to pollution degree 2
- Impulse voltage strength of 2.25 kV according to IEEE 802.3
- Optimum contact distance for 100 Ohm systems



Easy to use

The simplicity of SPE connectors



K

Ethernet technology is too complex for many industrial applications. SPE components are clearly superior due to their simplicity. Compared to four-pair Ethernet, installation is less difficult and allows a significant reduction in space and weight. SPE connectors also enable robust cabling in a short time. At the same time, they offer extended cable lengths in an extremely compact design.

Proven locking mechanism

- Industry standard plugs and sockets with metal Snap-in hooks locking
- Known locking and unlocking mechanism as for RJ45 connectors
- High holding force (> 50 N)

Tool-free installation

- Well proven IDC connection technology
- Simple assembly due to a two-part connector
- Clear colour coding to prevent miswiring
- Suitable for all commercially available SPE cables

Easy integration

- Trouble-free integration into M8 housings and connectors
- Compatibility of IP20 and IP67 variants
- Optional use of the IP20 connector as service connector for devices with M8IP67 interfaces



1



2



3

Ready for the challenges of tomorrow

Future-proof SPE connectors



SPE is the next milestone in network technology, as it enables continuous intelligent networking across all levels. SPE is scalable, deterministic, and fully compatible, allowing all components to communicate with each other. As a comprehensive key technology for applications in the field of Industry 4.0 and IIoT, it will form the core of a wide range of industrial applications in the future.

Extensive support


The SPE product family is already supported by several well-known connector manufacturers, which have joined together to form the Single Pair Ethernet System Alliance. This collaboration, with leading technology companies from a wide range of markets and application areas, means that the level of combined technological competence will result in unprecedented and lasting benefits for all users.

Suitable for low to high transmission rates

With SPE components, only a compact IEC standard interface is required to connect a sensor to the cloud via the data centre. The interface is suitable for various Ethernet applications with transfer rates from 10 Mbit/s to 1 Gbit/s. Simulations confirm a bandwidth of up to 2.5 GHz – this corresponds to the new Ethernet transmission standard IEEE 802.3ch, which is currently under development for up to 10 Gbit/s.

Increase of the port density

In the near future, a new and innovative four-chamber system will be available that will enable the port density for IP20 and IP67 systems to be quadrupled. This means that SPE technology can also be used in standard M12 connectors. It will also allow extremely compact IIoT devices with 32 ports to be implemented, and can be integrated into existing housing structures.




Assembled cable IP20

Assembled cable IP20

Plug - Plug

Socket contact / Socket contact



Technical data

Product type	Patch cable
Category	STP
Shielding	-40...80 °C
Ambient temperature (operational)	60 V
Rated voltage (DC)	3.5 A
Rated current	PoDL acc. to IEEE 802.3bu / cg
PoE / PoE+	10/100 Mbit/s, 1000 Mbit/s, 1000 Mbit/s
Transmission rate	1000 V DC
Dielectric strength, contact / contact	2250 V DC
Dielectric strength, contact / shield	100 ± 15 Ω at 20 MHz
Characteristic impedance	1.6 nF/km
Capacity at 800 Hz	Type I
Coupling attenuation 1 to 600 MHz	1 kV DC, 1 min
Coupling attenuation up to 1000 MHz	2 %
Test voltage: wire-wire-shield	10/100 Mbit/s, 1000 Mbit/s, 1000 Mbit/s
Resistance differential	SPE plug (IEC 63171-2) - IP20 socket contact straight
Transmission rate	SPE plug (IEC 63171-2) - IP20 socket contact straight
Version connector left	
Version connector right	
Number of wires	2
Colour coding	white / blue
Complete shielding / Overlap of shielding braid	Shielding braid made from copper wiring / 80 %
Insulation	PE
Insulation diameter	1.65 mm
Sheath diameter, min. / max.	4.9 / 5.3 mm
Cross-section / Strands	2*AWG 22 / 7
Shielding	STP
Material sheath	PVC
Colour	black
Halogen	Yes
UV-resistant	Complies with UL 1581 Sec. 1200
Connector standard	IEC 63171-2

Note

Ordering data

Type	Qty.	Order No.
IE-S1DS2VE0010T01T01-E	1	2725850010
IE-S1DS2VE0020T01T01-E	1	2725850020
IE-S1DS2VE0030T01T01-E	1	2725850030
IE-S1DS2VE0050T01T01-E	1	2725850050

Note

Accessories

Type	Qty.	Order No.

Note

Assembled cable
IP67



M8 / M8

Socket contact / Socket contact



M8 / M8

Socket contact / Pin contact



Technical data

Product type	Patch cable
Category	STP
Shielding	-40...85 °C
Ambient temperature (operational)	60 V
Rated voltage (DC)	3.5 A
Rated current	PoDL acc. to IEEE 802.3bu / cg
PoE / PoE+	10/100 MBit/s, 1000 MBit/s
Transmission rate	1000 V DC
Dielectric strength, contact / contact	2250 V DC
Dielectric strength, contact / shield	3.5A @ 0°C
Current-carrying capacity	100 ± 15 Ω at 20 MHz
Characteristic impedance	1.6 nF/km
Capacity at 800 Hz	Type I
Coupling attenuation 1 to 600 MHz	1 kV DC, 1 min
Coupling attenuation up to 1000 MHz	2 %
Test voltage: wire-wire-shield	10/100 MBit/s, 1000 MBit/s
Resistance differential	M8 SPE (IEC63171-5) - IP67 socket contact straight
Transmission rate	M8 SPE (IEC63171-5) - IP67 socket contact straight
Version connector left	2
Version connector right	white / blue
Number of wires	Shielding braid made from copper wiring / 80 %
Colour coding	PE
Complete shielding / Overlap of shielding braid	1.65 mm
Insulation	4.9 / 5.3 mm
Insulation diameter	2*AWG 22 / 7
Sheath diameter, min. / max.	STP
Cross-section / Strands	PVC
Shielding	black
Material sheath	Yes
Colour	Complies with UL 1581 Sec. 1200
Halogen	IEC 63171-5
UV-resistant	
Connector standard	

Note

Ordering data

2.0 m	
Note	

Accessories

Type	Qty.	Order No.
IE-S1DS2VE0020TM1M1-E	1	2726050020
Note		

Type	Qty.	Order No.
IE-S1DS2VE0020TM1M2-E	1	2726060020


Type	Qty.	Order No.

Assembled cable IP67

Assembled cable IP67

M8 / M8

Pin contact / Pin contact



Technical data

Product type	Patch cable
Category	STP
Shielding	-40...85 °C
Ambient temperature (operational)	60 V
Rated voltage (DC)	3.5 A
Rated current	PoDL acc. to IEEE 802.3bu / cg
PoE / PoE+	10/100 MBit/s, 1000 MBit/s
Transmission rate	1000 V DC
Dielectric strength, contact / contact	2250 V DC
Dielectric strength, contact / shield	3.5A @ 0°C
Current-carrying capacity	100 ± 15 Ω at 20 MHz
Characteristic impedance	1.6 nF/km
Capacity at 800 Hz	Type I
Coupling attenuation 1 to 600 MHz	1 kV DC, 1 min
Coupling attenuation up to 1000 MHz	2 %
Test voltage: wire-wire-shield	10/100 MBit/s, 1000 MBit/s
Resistance differential	M8 SPE (IEC63171-5) - IP67 pin contact straight
Transmission rate	M8 SPE (IEC63171-5) - IP67 pin contact straight
Version connector left	2
Version connector right	white / blue
Number of wires	Shielding braid made from copper wiring / 80 %
Colour coding	PE
Complete shielding / Overlap of shielding braid	1.65 mm
Insulation	4.9 / 5.3 mm
Insulation diameter	2 ² AWG 22 / 7
Sheath diameter, min. / max.	STP
Cross-section / Strands	PVC
Shielding	black
Material sheath	Yes
Colour	Complies with UL 1581 Sec. 1200
Halogen	IEC 63171-5
UV-resistant	
Connector standard	

Note

Ordering data

Type	Qty.	Order No.
IE-S1DS2VE0020TM2TM2-E	1	2726070020

Note

Accessories

Type	Qty.	Order No.


Note

Plug

- Only one pair of cables for data and power
- Multi-port support
- IP20

Field-terminated plug IP20

Socket contact

**Technical data**

Category
Protection degree
Ambient temperature (operational)
Plugging cycles
Housing main material
Contact material
Contact surface
Rated voltage
Insulation cross-section, min.
Insulation cross-section, max.
Insulation strength
PoE / PoE+
Dielectric strength, contact / contact
Dielectric strength, contact / shield
Connector standard
UL 94 flammability rating

Note**Ordering data**

Plug	field-terminated plug
Note	

Accessories**Preliminary technical data!**

IP20
40...85 °C
750
zinc diecast nickel-plated
Bronze tin-plated
0.85 mm
1.6 mm
≥ 500 MΩ
PoDL acc. to IEEE 802.3bu / cg
≥ 1000 V DC
≥ 1500 V DC
IEC 63171-2
V-0

Type	Qty.	Order No.
IE-PS-SPO-S-FH-180	1	2726040000

Note

Plug

- Only one pair of cables for data and power
- Multi-port support
- IP20

**Technical data**



Category
Protection degree
Ambient temperature (operational)
Transmission rate
Type of connection
Outgoing elbow
Number of poles
Mounting onto the PCB
Plugging cycles
Contact material
Contact surface
Rated voltage
Insulation strength
PoE / PoE+
Dielectric strength, contact / contact
Dielectric strength, contact / shield
Connector standard
UL 94 flammability rating

Note**Ordering data**

Plug
PCB connector, IP20, pin contact
PCB connector, IP20, pin contact incl. LEDs

Note**Accessories**


Type	Qty.	Order No.
IE-PCB-SPO-P-90V-THR	100	2726010000
IE-PCB-SPO-P-90V-THR-YG/YG	100	2795120000

Note**PCB connector, 90°****Pin contact****PCB connector, 180°****Pin contact****Preliminary technical data**

IP20
-40...85 °C
10/100 MBit/s, 1000 MBit/s
Solder connection, Male contact
90°
2
THT/THR solder connection
750
Cu
Ni/Au
72 V
≥ 500 MO
PoDL acc. to IEEE 802.3bu / cg
1000 V DC
2250 V DC
IEC 63171-2, ISO/IEC 11801-1
V-0



**Preliminary technical data**

IP20
-40...85 °C
10/100 MBit/s, 1000 MBit/s
Solder connection, Male contact
180°
2
THT/THR solder connection
750
Cu
Ni/Au
72 V
≥ 500 MO
PoDL acc. to IEEE 802.3bu / cg
1000 V DC
2250 V DC
IEC 63171-2
V-0



Type	Qty.	Order No.
IE-PCB-SPO-P-180V-THR	100	2795170000

Type	Qty.	Order No.
IE-PCB-SPO-P-180V-THR	100	2795170000

Empty housing**M8 front wall mounting****M8 rear wall mounting****Technical data**

Category
Ambient temperature (operational)
Protection degree
Housing main material
Seal material
Configuration
Type of mounting
Connection thread
Connector standard
Tightening torque fixing nut

-40...85 °C
IP67
Brass, nickel-plated
FKM
Frontpanel mounting
Screw mounting
M10 x 0.75
IEC 61076-2-104
2.5 Nm

40...85 °C
IP67
Brass, nickel-plated
FKM
Backpanel mounting
Screw mounting
M10 x 0.75
IEC 61076-2-104
2.5 Nm

Ordering data**Note**

Type	Qty.	Order No.
IE-BHD-SPE-M8-OT-FP	10	2726020000

Inserts must be ordered separately.

Type	Qty.	Order No.
IE-BHD-SPE-M8-OT-BP	20	2726030000

Inserts must be ordered separately.

Accessories**Note**

Type	Qty.	Order No.
IE-BHD-SPE-FP-CN-M10X0.75	10	2739640000

Type	Qty.	Order No.
IE-BHD-SPE-FP-CN-M10X0.75	10	2739640000

Note

PCB insert

M8 insert 180° pin contacts



M8 insert 90° pin contacts



Technical data

- Category
- Ambient temperature (operational)
- Protection degree
- Pollution severity
- Connection thread
- Number of poles
- Type of connection
- Outgoing elbow
- Contact material
- Contact surface
- Contact carrier material
- Operational voltage range
- Insulation strength
- Dielectric strength, contact / connection
- Dielectric strength, contact / shielded connection
- Connector standard
- UL 94 flammability rating

Ordering data

THR
SMD

Accessories

[View Details](#) | [Edit](#) | [Delete](#)

Preliminary technical data!

T1-B
-40...85 °C

2
M8
2
Solder connection, Male contact
180°
Copper alloy
Ni/Au
LCP
≤ 50 V AC, ≤ 60 V DC
≥ 500 MΩ
1000 V DC
2250 V DC
IEC 63171-5
V-Q

IE-PCB-SPM-P-180-THR 100 2735920000

IE-PCB-SPM-P-180-SMD 100 2795110000

Preliminary technical data!

T1-B
-40...85 °C

2
M8
2
Solder connection, Male contact
90°
Copper alloy
Ni/Au
LCP
≤ 50 V AC, ≤ 60 V DC
≥ 500 MO
1000 V DC
2250 V DC
IEC 63171-5
V-Q

IE-PCB-SPM-P-90-THR 100 279510000

Page 10 of 10

Notes

IP20 plug-in connectors and mounting rail outlets


Overview

IP20 plug-in connectors and mounting rail outlets	IP20 plug-in connectors	
	Single Pair Ethernet (SPE) plug	L.2
	RJ45 plug	L.4
	FO Connector	L.10
	RJ45 keystone	L.11
	IP20 mounting rail outlets	
	RJ45	L.13
	USB	L.16
	FO	L.17
	Socket adapter	L.19

L

Single Pair Ethernet (SPE) plug

- Only one pair of cables for data and power
- Multi-port support
- IP20

**Field-terminated plug IP20****Socket contact****Technical data**

Category
Protection degree
Ambient temperature (operational)
Plugging cycles
Housing main material
Contact material
Contact surface
Rated voltage
Insulation cross-section, min.
Insulation cross-section, max.
Insulation strength
PoE / PoE+
Dielectric strength, contact / contact
Dielectric strength, contact / shield
Connector standard
UL 94 flammability rating

Note**Ordering data**

Plug	field-terminated plug
Note	

Accessories**preliminary technical data!**

IP20
40...85 °C
750
zinc diecast nickel-plated
Bronze tin-plated
0.85 mm
1.6 mm
≥ 500 MΩ
PoDL acc. to IEEE 802.3bu / cg
≥ 1000 V DC
≥ 1500 V DC
IEC 63171-2
V-0

Type	Qty.	Order No.
IE-PS-SPO-S-FH-180	1	2726040000

Type	Qty.	Order No.

Note**Note**

Single Pair Ethernet (SPE) plug

- Only one pair of cables for data and power
 - Multi-port support
 - IP20

Technical data

Category
Protection degree
Ambient temperature (operation)
Transmission rate
Type of connection
Outgoing elbow
Number of poles
Mounting onto the PCB
Plugging cycles
Contact material
Contact surface
Rated voltage
Insulation strength
PoE / PoE+
Dielectric strength, contact / core
Dielectric strength, contact / shield
Connector standard
UL 94 flammability rating

Ordering data


PCB connector, IP20, pin contact
PCB connector, IP20, pin contact incl. LEDs

Accessories

Note

PCB connector, 90°

Pin contact




preliminary technical data!

IP20
-40...85 °C
10/100 MBit/s, 1000 MBit/s
Solder connection, Male contact
90°
2
THT/THR solder connection
750
Cu
Ni/Au
72 V
≥ 500 MΩ
PoDL acc. to IEEE 802.3bu / cg
1000 V DC
2250 V DC
IEC 63171-2, ISO/IEC 11801-1
V-0

PCB connector, 180°

Pin contact






preliminary technical data!

IP20
-40...85 °C
10/100 MBit/s, 1000 MBit/s
Solder connection, Male contact
180°
2
THT/THR solder connection
750
Cu
Ni/Au
72 V
≥ 500 MΩ
PoDL acc. to IEEE 802.3bu / cg
1000 V DC
2250 V DC
IEC 63171-2
V-0

RJ45 plug, tool free

- Cat. 6A (8 wires)/cat. 5 (4 wires) for PROFINET
- Multi-port support
- IP20

**8-wire****4-wire for PROFINET****Technical data****Category**

Protection degree

Housing main material

Connection diameter, flexible, min. / max.

Connection cross-section, flexible, min. / max.

Connection diameter, solid, min. / max.

Connection cross-section, solid, min. / max.

Wire connection cross-section, finely stranded

Insulation diameter, min. / max.

Sheath diameter, min. / max.

Contact surface

Shielding

Plugging cycles

Ambient temperature (operational)

Contact resistance

Insulation strength

Dielectric strength, contact / contact

Dielectric strength, contact / shield

Connector standard

Current-carrying capacity at 50 °C

Speed

PoE / PoE+

Approvals

Note**Cat.6A / Class E_A (ISO/IEC 11801 2010)**

IP20

Zinc diecast

0.48 mm / 0.76 mm

AWG 26/7 / AWG 22/7

0.41 mm / 0.64 mm

AWG 24/1 / AWG 22/1

Approval of the cable by Weidmüller necessary

0.85 mm / 1.6 mm

5.5 mm / 8.5 mm

Gold over nickel

360° all-round enclosure

750

-40 °C...70 °C

≤ 20 mΩ

> 500 MΩ

≥ 1000 V DC

≥ 1500 V DC

IEC 60603-7-51

1 A

10 GBit/s

conforming to IEEE 802.3at

CULUS

Approvals available on request

Cat.5 (ISO/IEC 11801)

IP20

Zinc diecast

0.48 mm / 0.76 mm

AWG 26/7 / AWG 22/7

0.41 mm / 0.64 mm

AWG 26/1 / AWG 22/1

Approval of the cable by Weidmüller necessary

0.85 mm / 1.6 mm

5.5 mm / 8.5 mm

Gold over nickel

360° all-round enclosure

750

-40 °C...70 °C

≤ 20 mΩ

> 500 MΩ

≥ 1000 V DC

≥ 1500 V DC

IEC 60603-7-51

1 A

10 GBit/s

conforming to IEEE 802.3at

CULUS

Ordering data**Plug**

with tear-off flags: EIA / TIA T568-A/B / PROFINET
 with printing: PROFINET
 with printing: EIA / TIA T568-A
 with printing: EIA / TIA T568-B

Note**Accessories****Strain relief**

green
 grey
 blue
 orange
 yellow
 white

Tools

Optional pressing tool

Type**Qty.****Order No.**

IE-PS-RJ45-FH-BK

10

1963600000

IE-PS-RJ45-FH-BK-A

10

1132040000

IE-PS-RJ45-FH-BK-B

10

1132050000

Type**Qty.****Order No.**

IE-PS-RJ45-FH-BK-P

10

1132060000

Type**Qty.****Order No.**

IE-CR-IP20-RJ45-FH-GN

10

1963100000

IE-CR-IP20-RJ45-FH-GY

10

1963060000

IE-CR-IP20-RJ45-FH-BU

10

1963080000

IE-CR-IP20-RJ45-FH-OG

10

1963070000

IE-CR-IP20-RJ45-FH-YE

10

1963090000

IE-CR-IP20-RJ45-FH-WH

10

1963050000

PWZ RJ45

1

1118040000

Note

RJ45 plug, straight, tool free

- Fieldattachable
- Cat. 6A (8-wire)
- Multi-port-compatible
- IP 20

**8-wire, insulation diameter 1.1 - 1.6 mm****8-wire, insulation diameter 0.85 - 1.1 mm****Technical data**

Category
Protection degree
Housing main material
Connection diameter, flexible, min. / max.
Connection cross-section, flexible, min. / max.
Connection diameter, solid, min. / max.
Connection cross-section, solid, min. / max.
Connection diameter, very finely stranded, min./max.

Connection cross-section, very finely stranded, min./max.

Insulation diameter, min. / max.

Sheath diameter, min. / max.

Contact surface

Shielding

Plugging cycles

Ambient temperature (operational)

Contact resistance

Insulation strength

Dielectric strength, contact / contact

Dielectric strength, contact / shield

Connector standard

Current-carrying capacity at 50 °C

Speed

PoE / PoE+

Approvals

Note

Ordering data**Plug with latching strain relief**

with printing: EIA / TIA T568-A
with printing: EIA / TIA T568-B

Plug with cable gland

with printing: EIA / TIA T568-A
with printing: EIA / TIA T568-B

Note

Accessories**Substitute wire manager**

TIA-A, insulation diameter 1.1...1.6 mm
TIA-B, insulation diameter 1.1...1.6 mm
TIA-A, insulation diameter 0.85...1 mm
TIA-B, insulation diameter 0.85...1 mm

Tools

Optional pressing tool

Note

Cat.6A / Class E _A (ISO/IEC 11801 2010)
IP20
Zinc diecast, nickel-plated
0.46 mm / 0.76 mm
AWG 27 / AWG 22
0.51 mm / 0.64 mm
AWG 24 / AWG 22
0.61 mm / 0.78 mm / Approval of the cable by Weidmüller necessary

AWG 24 / AWG 22 / Approval of the cable by Weidmüller necessary
1.1 mm / 1.6 mm
5 mm / 9 mm
Gold over nickel
360° all-round enclosure
750
40 °C...85 °C
≤ 20 mΩ
> 500 MΩ
≥ 1000 V DC
≥ 1500 V DC
IEC 60603-7-51
1 A
10 GBit
conforming to IEEE 802.3at
CULUS; DNVGL

Cat.6A / Class E _A (ISO/IEC 11801 2010)
IP20
Zinc diecast, nickel-plated
0.46 mm / 0.61 mm
AWG 27 / AWG 24
0.41 mm / 0.51 mm
AWG 26 / AWG 24
0.51 mm / Approval of the cable by Weidmüller necessary



AWG 26 / Approval of the cable by Weidmüller necessary
0.85 mm / 1.1 mm
5 mm / 9 mm
Gold over nickel
360° all-round enclosure
750
-40 °C...85 °C
≤ 20 mΩ
> 500 MΩ
≥ 1000 V DC
≥ 1500 V DC
IEC 60603-7-51
1 A
10 GBit
conforming to IEEE 802.3at
CULUS; DNVGL

Type	Qty.	Order No.
IE-PS-RJ45-FH-180-A-1.1	1	1992850000
IE-PS-RJ45-FH-180-B-1.1	1	1992860000
IE-PS-RJ45-FH-180-A-1.1-CG	1	2703440000
IE-PS-RJ45-FH-180-B-1.1-CG	1	2703460000

Type	Qty.	Order No.
IE-PI-RJ45-FH-A-1.1	30	1992920000
IE-PI-RJ45-FH-B-1.1	30	1992930000
PWZ RJ45	1	1118040000

RJ45 plug, angled, tool free

- Assembled
- Cat. 6A (8-wire)
- Compatible with multiple ports
- IP20

8-wire, insulation diameter 1.1 - 1.6 mm**8-wire, insulation diameter 0.85 - 1.1 mm****Technical data**

Category
Protection degree
Housing main material
Connection diameter, flexible, min. / max.
Connection cross-section, flexible, min. / max.
Connection diameter, solid, min. / max.
Connection cross-section, solid, min. / max.
Connection diameter, very finely stranded, min./max.

Connection cross-section, very finely stranded, min./max.

Insulation diameter, min. / max.

Sheath diameter, min. / max.

Contact surface

Shielding

Plugging cycles

Ambient temperature (operational)

Contact resistance

Insulation strength

Dielectric strength, contact / contact

Dielectric strength, contact / shield

Connector standard

Current-carrying capacity at 50 °C

Speed

PoE / PoE+

Approvals

Note

Cat.6A / Class E_A (ISO/IEC 11801 2010)

IP20

Zinc diecast, nickel-plated

0.46 mm / 0.76 mm

AWG 27 / AWG 22

0.51 mm / 0.64 mm

AWG 24 / AWG 22

0.61 mm / 0.78 mm / Approval of the cable by Weidmüller necessary

AWG 24 / AWG 22 / Approval of the cable by Weidmüller necessary

1.1 mm / 1.6 mm

5 mm / 9 mm

Gold over nickel

360° all-round enclosure

750

-40 °C...85 °C

≤ 20 mΩ

> 500 MΩ

≥ 1000 V DC

≥ 1500 V DC

IEC 60603-7-51

1 A

10 GBit

conforming to IEEE 802.3at

CULUS; DNVGL

Cat.6A / Class E_A (ISO/IEC 11801 2010)

IP20

Zinc diecast, nickel-plated

0.46 mm / 0.61 mm

AWG 27 / AWG 24

0.41 mm / 0.51 mm

AWG 26 / AWG 24

0.51 mm / Approval of the cable by Weidmüller necessary

AWG 26 / Approval of the cable by Weidmüller necessary

0.85 mm / 1.1 mm

5 mm / 9 mm

Gold over nickel

360° all-round enclosure

750

-40 °C...85 °C

≤ 20 mΩ

> 500 MΩ

≥ 1000 V DC

≥ 1500 V DC

IEC 60603-7-51

1 A

10 GBit

conforming to IEEE 802.3at

CULUS; DNVGL

Ordering data**Plug**

with printing: EIA / TIA T568-A
with printing: EIA / TIA T568-B

Note

Type

IE-PS-RJ45-FH-90-A-1.6

Qty. 1

Order No. 1992870000

IE-PS-RJ45-FH-90-B-1.6

Qty. 1

Order No. 1992890000

With pre-installed dust cap

Type

IE-PS-RJ45-FH-90-A-1.1

Qty. 10

Order No. 1518080000

IE-PS-RJ45-FH-90-B-1.1

Qty. 1

Order No. 1518090000

With pre-installed dust cap

Accessories**Substitute wire manager**

TIA-A, insulation diameter 1.1...1.6 mm
TIA-B, insulation diameter 1.1...1.6 mm
TIA-A, insulation diameter 0.85...1 mm
TIA-B, insulation diameter 0.85...1 mm

Tools

Optional pressing tool

Type

IE-PI-RJ45-FH-A-1.6

Qty. 30

Order No. 1992880000

IE-PI-RJ45-FH-B-1.6

Qty. 30

Order No. 1992900000

Type

IE-PI-RJ45-FH-A-1.1

Qty. 30

Order No. 1992920000

IE-PI-RJ45-FH-B-1.1

Qty. 30

Order No. 1992930000

PWZ RJ45

Qty. 1

Order No. 1118040000


Note

RJ45 plug, straight and angled, tool free


- Fieldattachable
- Cat. 5 (4-wire) for PROFINET
- Multi-port-compatible
- IP20

**4-wire for PROFINET**

straight

**4-wire for PROFINET**

angled

**Technical data**

Category
Protection degree
Housing main material
Connection diameter, flexible, min. / max.
Connection cross-section, flexible, min. / max.
Connection diameter, solid, min. / max.
Connection cross-section, solid, min. / max.
Connection diameter, very finely stranded, min./max.

Connection cross-section, very finely stranded, min./max.

Insulation diameter, min. / max.

Sheath diameter, min. / max.

Contact surface

Shielding

Plugging cycles

Ambient temperature (operational)

Contact resistance

Insulation strength

Dielectric strength, contact / contact

Dielectric strength, contact / shield

Connector standard

Current-carrying capacity at 50 °C

Speed

PoE / PoE+

Approvals

Note

Ordering data

Plug with latching strain relief
with printing: PROFINET

Plug with cable gland
with printing: PROFINET

Note

Accessories

Substitute wire manager
PROFINET, insulation diameter 1.1...1.6 mm

Tools

Optional pressing tool

Type	Qty.	Order No.
IE-PS-RJ45-FH-180-P-1.6	10	1992840000

IE-PS-RJ45-FH-180-P-1.6-CG
With pre-installed dust cap

Type	Qty.	Order No.
IE-PS-RJ45-FH-90-P-1.6	10	1518100000

With pre-installed dust cap

Type	Qty.	Order No.
IE-PI-RJ45-FH-P-1.6	30	1992910000

PWZ RJ45



Type	Qty.	Order No.
IE-PI-RJ45-FH-P-1.6	30	1992910000

PWZ RJ45

Note

RJ45 crimp plug

- Cat. 6
- With anti-folding protection
- With anti-crash lever protection

**8-wire, housing 1-part****8-wire, housing 2-part****Technical data**

Category
Protection degree
Connection diameter, flexible, min. / max.
Connection cross-section, flexible, min. / max.
Connection diameter, solid, min. / max.
Connection cross-section, solid, min. / max.
Insulation cross-section, max.
Sheath diameter, min. / max.
Shielding
Plugging cycles
Ambient temperature (operational)
Connector standard
Bending protection sleeve material
Material insulator
Contact material / Contact surface
Shielding material
Cable pull-out force, min.
Contact resistance
Insulation strength
Dielectric strength, contact / contact
Dielectric strength, contact / shield
Current-carrying capacity at 50 °C
PoE / PoE+
Approvals

Note**Ordering data**

Plug
with kink protection; 5.5 - 6.2 mm
with anti-kink protection; 6.2 - 7.1 mm
with anti-kink sleeve, black
without anti-kink sleeve

Note**Accessories**

Kink prevention sleeve
white
green
grey
yellow
orange
black
blue

Tools

Pressing tool


Type	Qty.	Order No.
IE-P63	10	8813110000
IE-P70	10	8813120000
IE-P	100	8813100000

Type	Qty.	Order No.
TT 8 RS MP 8	1	9202800000

Note

Type	Qty.	Order No.
IE-PH-RJ45-TH-WH	10	1962430000
IE-PH-RJ45-TH-GN	10	1962490000
IE-PH-RJ45-TH-GY	10	1962440000
IE-PH-RJ45-TH-YE	10	1962480000
IE-PH-RJ45-TH-OG	10	1962450000
IE-PH-RJ45-TH-BK	10	1962500000
IE-PH-RJ45-TH-BU	10	1962470000

Type	Qty.	Order No.
TT 8 RS MP 8	1	9202800000

RJ45 PROFINET crimp plug**4-wire for PROFINET, 1-part enclosure****Technical data**

Category	Cat.5 (ISO/IEC 11801)
Protection degree	IP20
Connection diameter, flexible, min. / max.	0.57 mm / 0.64 mm
Connection cross-section, flexible, min. / max.	AWG 23 / AWG 22
Connection diameter, solid, min. / max.	0.57 mm / 0.64 mm
Connection cross-section, solid, min. / max.	AWG 23 / AWG 22
Insulation cross-section, max.	1.6 mm
Sheath diameter, min. / max.	/ 7.5 mm
Shielding	360° all-round enclosure
Plugging cycles	750
Ambient temperature (operational)	-40 °C...70 °C
Connector standard	IEC 60603-7
Bending protection sleeve material	Polyamide PAG, UL 94-VO
Material insulator	
Contact material / Contact surface	Copper alloy
Shielding material	
Cable pull-out force, min.	
Contact resistance	≤ 10 mΩ
Insulation strength	500 MΩ
Dielectric strength, contact / contact	1000 V AC
Dielectric strength, contact / shield	
Current-carrying capacity at 50 °C	
PoE / PoE+	conforming to IEEE 802.3af
Approvals	

Note**Ordering data**

Plug	Type	Qty.	Order No.
	IE-PS-RJ45-TH-BK-P	10	2584980000



Note**Accessories**

Tools	Type	Qty.	Order No.
Pressing tool	IE-CWZ-RJ45-TH-P	1	2614210000

Note

F0 connector

- IP 20

**SCRJ, POF, Crimp****SCRJ, POF, reconnectable****Technical data**

Protection degree
Plugging cycles
Ambient temperature (operational)
Connector standard
Individual wire diameter, min. / max.
Crimp barrel material
Pressure spring material
Ferrule material
Dust protection cap material
Bending protection sleeve material
Cable pull-out force, min.
Housing main material
Housing material, insert
Humidity
Approvals

Note**Ordering data**

	POF
Note	

Accessories

Tools	Mounting tool, POF Replacement ferrule Contact Removal Tool
--------------	---

IP20
1000
-20 °C...80 °C
IEC 61754-24
2.1 mm...2.3 mm
Copper, nickel-plated
Stainless steel, rust-proof
Nickel silver
TPE
TPE
100 N
PC UL 94 VO
Zinc diecast, nickel-plated
0...93 % rel. humidity
UL

IP20
1000
-20 °C...80 °C
IEC 61754-24
2.1 mm...2.3 mm
Copper, nickel-plated
Stainless steel, rust-proof
Nickel silver
TPE
TPE
100 N
PC UL 94 VO
Zinc diecast, nickel-plated
0...93 % rel. humidity


Type	Qty.	Order No.
IE-PS-SCRJ1-POF	10	1206720000

Type	Qty.	Order No.
IE-PS-SCRJ1-POF-QA	10	2564950000

Type	Qty.	Order No.
HTX-IE-POF	1	1208870000
IE-SCRJ1-IP20-POF-100	100	1278420000
REMOVAL TOOL HD	1	1866730000

Type	Qty.	Order No.
HTX-IE-POF-QA	1	2602860000

Note

RJ45 keystone**RJ45 Coupling****Technical data**

Housing main material

Category

Protection degree

Plugging cycles

PoE / PoE+

Connector standard

Approvals

Note

Zinc diecast

Cat.6A / Class E_A (ISO/IEC 11801 2010)

IP20

750

conforming to IEEE 802.3at

IEC 60603-7-5

EAC

Ordering data**Note**

Type	Qty.	Order No.
IE-XR-RJ45/RJ45-2	24	8952950000


Accessories

Type	Qty.	Order No.


Note

RJ45 keystone**RJ45 module**

Mounting cut-out Rectangular

**RJ45 module**

Mounting cut-out special shape

**Technical data**

Category	Cat.6A / Class E _A (ISO/IEC 11801 2010)
Wiring	TIA-568A, TIA-568B, PROFINET
Protection degree	IP20
Housing main material	Zinc diecast
Connection diameter, flexible	0.48...0.76 mm
Conductor connection cross-section, flexible (AWG)	AWG 26...AWG 22
Connection diameter, solid	0.41...0.64 mm
Conductor connection cross-section, solid (AWG)	AWG 26...AWG 22
Insulation cross-section, max.	1.8 mm
Plugging cycles	750
Ambient temperature (operational)	-40...70 °C
Connector standard	IEC 60603-7-51
Contact surface	Gold over nickel
Contact resistance	≤ 20 mΩ
Insulation strength	500 MΩ
PoE / PoE+	conforming to IEEE 802.3at
Dielectric strength, contact / contact	≥ 1000 V DC
Dielectric strength, contact / shield	≥ 1000 V DC
Approvals	

Note**Ordering data**

Type	Qty.	Order No.
IE-KEY-RJ45/IDC-1	1	2782300000

Note	Type	Qty.	Order No.
	IE-XRJ45/IDC	1	8808330000

Accessories

Type	Qty.	Order No.

Note	Type	Qty.	Order No.

Note

Module RJ45



Outlet direction straight

- Cat. 6A
 - IP20
 - TS 35

8-wire



4-wire



Technical data

- Category
- Protection degree
- Housing main material
- Contact surface
- Colour
- Type of mounting
- Plugging cycles
- Configuration
- Ambient temperature (operational)
- Temperature range, assembly, min. / max.
- Connector standard
- Connection diameter, flexible, min. / max.
- Connection cross-section, flexible, min. / max.
- Connection diameter, solid, min. / max.
- Connection cross-section, solid, min. / max.

Electrical properties*

- PoE / PoE+
- Contact resistance
- Current-carrying capacity at 50 °C
- Dielectric strength, contact / contact
- Dielectric strength, contact / shield
- Insulation strength
- Approvals

Ordering data

A-coded
B-coded
PROFINET-coded

Accessories

Marking tags

Cat.6A / Class E_A (ISO/IEC 11801 2010)

IP20
PA UL 94 VO
Au \geq 0.8 μm
Light Grey
TS 35
750
Switchable volt. connection from module/coupling to mounting rail
40 °C...70 °C
-25 °C...70 °C
IEC 60603-7-51
0.48 mm / 0.76 mm
AWG 26 / AWG 22
0.4 mm / 0.64 mm
AWG 24 / AWG 22

conforming to IEEE 802.3af

$\leq 20 \text{ m}\Omega$
1 A
 $\geq 1000 \text{ V DC}$
 $\geq 1500 \text{ V DC}$
500 M Ω
EAC

Cat.5 (ISO/IEC 11801)

IP20
PA UL 94 VO
Au \geq 0.8 μm
Light Grey
TS 35
750
Switchable volt. connection from module/coupling to mounting rail
40 °C...70 °C
-25 °C...70 °C
IEC 60603-7-51
0.48 mm / 0.76 mm
AWG 26 / AWG 22
0.4 mm / 0.64 mm
AWG 24 / AWG 22

conforming to IEEE 802.3af

- ≤ 20 mΩ
- 1 A
- ≥ 1000 V DC
- ≥ 1500 V DC
- 500 mΩ
- FAC


Type	Qty.	Order No.
IE-TO-RJ45-FJ-A	10	8946930000
IE-TO-RJ45-FJ-B	10	8946940000

Type	Qty.	Order No.
IE-TO-RJ45-FJ-P	10	8946950000

N-1-

IP20 mounting rail outlets**Module RJ45****Outlet direction diagonal**

- Cat. 6
- IP20
- TS 35

8-wire**Technical data**

Category

Cat.6_A / Class E_A (ISO/IEC 11801 2010)

Protection degree

IP20

Housing main material

PA 66, UL 94: V-0

Contact surface

Light Grey

Colour

TS 35

Type of mounting

750

Plugging cycles

1 TE pitch dimension acc. to DIN 43880, insta-compatible

Configuration

Installation flange with mounting frame

Ambient temperature (operational)

-25 °C...70 °C

Temperature range, assembly, min. / max.

...

Connector standard

IEC 60603-7-5

Connection diameter, flexible, min. / max.

0.48 mm / 0.64 mm

Connection cross-section, flexible, min. / max.

AWG 26 / AWG 22

Connection diameter, solid, min. / max.

0.4 mm / 0.64 mm

Connection cross-section, solid, min. / max.

AWG 24 / AWG 22

Electrical properties*

PoE / PoE+

conforming to IEEE 802.3at

Contact resistance

≤ 20 mΩ

Current-carrying capacity at 50 °C

1 A

Dielectric strength, contact / contact

≥ 1000 V DC

Dielectric strength, contact / shield

≥ 1500 V DC

Insulation strength

500 MΩ

Approvals

CULUS; DNVGL

Note**Ordering data**

A/B-coded

Note

Type	Qty.	Order No.
IE-XM-RJ45/IDC	1	8808360000

Accessories**Marking tags**



Marking tag

Type	Qty.	Order No.
IE-DM	50	8813500000

Note

Coupling RJ45, 8-wire

- Cat. 6A
- IP20
- TS 35

Outlet direction straight**Outlet direction diagonal****Technical data**

Category
Protection degree
Housing main material
Contact material / Contact surface
Colour
Type of mounting
Plugging cycles
Configuration

Ambient temperature (operational)
Temperature range, assembly, min. / max.
Humidity
Shock resistance acc. to IEC 60512-4
Vibration resistance acc. to IEC 60512-4
Housing material, insert
Connector standard

Electrical properties*

PoE / PoE+
Contact resistance
Current-carrying capacity at 50 °C
Dielectric strength, contact / contact
Dielectric strength, contact / shield
Insulation strength
Approvals

Note**Ordering data****Note****Accessories****Marking tags**

MultiCard, white
Marking tag

Cat.6A / Class E_A (ISO/IEC 11801 2010)

IP20

PA UL 94 V0

Spring steel, Ni 1.2 µm / Au ≥ 0.8 µm

Light Grey

TS 35

750

Switchable volt. connection from module/coupling to mounting rail

-40 °C...70 °C

-25 °C...70 °C

0...93 % rel. humidity

250 ms²

50 ms² sinusoidal (9...500 Hz)

Zinc diecast

IEC 60603-7-51

conforming to IEEE 802.3af

≤ 20 mΩ

1 A

≥ 1000 V DC

≥ 1500 V DC

500 MΩ

EAC

Cat.6 (ISO/IEC 11801)

IP20

PA 66, UL 94: V-0

Light Grey

TS 35

750

1 TE pitch dimension acc. to DIN 43880. insta-compatible
Installation flange with mounting frame

-25 °C...70 °C

...

IEC 60603-7-5

conforming to IEEE 802.3at

≤ 20 mΩ

1 A

≥ 1000 V DC

≥ 1500 V DC

500 MΩ

CULUS; DNVGL

Type IE-T0-RJ45-C Qty. 10 Order No. 8946920000

Type IE-XM-RJ45/RJ45 Qty. 1 Order No. 8879050000



Type ESG 9/11 K MC NE WS Qty. 200 Order No. 1857440000

Type IE-DM Qty. 50 Order No. 8813500000

Note

IP20 mounting rail outlets**USB connection**

- IP20
- TS 35

USB A**USB AB****Technical data**

Protection degree

Housing main material

Colour

Type of mounting

Ambient temperature (operational)

Temperature range, assembly, min. / max.

Connector standard

Connection 1 / 2

Approvals

Note

IP20

PA UL 94 VO

Light Grey

TS 35

-40 °C...70 °C

-25 °C...70 °C

IEC 61076-3-107

USB A / USB B

EAC

IP20

PA UL 94 VO

Light Grey

TS 35

-40 °C...70 °C

-25 °C...70 °C

IEC 61076-3-107

USB A / USB B

EAC

Ordering data**USB**

Type	Qty.	Order No.
IE-TD-USB	1	8946960000

Type	Qty.	Order No.
IE-TD-USB-AB	1	1438180000

Accessories**Marking tags**

MultiCard, white

Type	Qty.	Order No.
ESG 9/11 K MC NE WS	200	1857440000

Type	Qty.	Order No.
ESG 9/11 K MC NE WS	200	1857440000



Note

Coupling fibre-optic

- IP20
- TS 35

**SC duplex****SC-RJ**

PROFI[®]
NET

**Technical data**

Protection degree

Housing main material

Colour

Type of mounting

Plugging cycles

Ambient temperature (operational)

Temperature range, assembly, min. / max.

Connector standard

Approvals

Note

IP20

PA UL 94 VO

Light Grey

TS 35

1000

-40 °C...70 °C

-25 °C...70 °C

IEC 61754-4

UL

IP20

PA UL 94 VO

Light Grey

TS 35

1000

-40 °C...70 °C

-25 °C...70 °C

IEC 61754-24

UL

Ordering data**Fibre-optic**

Singlemode
Multimode/POF

Note

Type	Qty.	Order No.
IE-T0-SCD-SM	1	8946980000
IE-T0-SCD-MM	10	8946970000

Type	Qty.	Order No.
IE-T0-SCRJ-SM	10	8947000000
IE-T0-SCRJ-MM	10	8946990000

Accessories**Marking tags**

MultiCard, white

Type	Qty.	Order No.
ESG 9/11 K MC NE WS	200	1857440000

Type	Qty.	Order No.
ESG 9/11 K MC NE WS	200	1857440000

Note

IP20 mounting rail outlets

Coupling fibre-optic



- IP20
- TS 35



LC Duplex



ST



Technical data

Protection degree

Housing main material

Colour

Type of mounting

Configuration

Plugging cycles

Ambient temperature (operational)

Temperature range, assembly, min. / max.

Connector standard

Approvals

Note

Ordering data

Singlemode
Multimode

Note

Accessories

Marking tags

MultiCard, white
Marking tag

Type	Qty.	Order No.
IE-TO-LCD-SM	10	8947020000
IE-TO-LCD-MM	10	8947010000

Type	Qty.	Order No.
IE-XM-ST/ST	1	8808340000

Type	Qty.	Order No.
ESG 9/11 K MC NE WS	200	1857440000
IE-DM	50	8813500000

Type	Qty.	Order No.
IE-DM	50	8813500000

Note

Note

Socket adapter

- IP 20
- TS 35

Socket adapter**Technical data**

Protection degree
Housing main material
Ambient temperature (operational)
Approvals

IP20
Polycarbonate PC, Acrylnitril-Butadien-Styrol (ABS)
-25 °C...70 °C

Note**Ordering data****Note****Accessories****Inserts, Power**

Socket AU 15 A
Socket AU 10 A
 Socket CH
 Socket CN
 Socket GB
 Socket DE
 Socket DE orange
 Socket FR
 Socket FR orange
 Socket IT/EU
 Socket CZ
 Socket IND
 RCBO
 ISR socket

Type	Qty.	Order No.
IE-DINRAIL-AD-PWB	1	2534680000
IE-FCI-PWB-AU	1	1450830000
IE-FCI-PWB-AU-10A	1	1546590000
IE-FCI-PWB-CH	1	1450780000
IE-FCI-PWB-CN	1	1450790000
IE-FCI-PWB-GB	1	1450770000
IE-FCI-PWB-DE	1	1450730000
IE-FCI-PWB-DE-OR	1	1554000000
IE-FCI-PWB-FR	1	1450750000
IE-FCI-PWB-FR-OR	1	2007230000
IE-FCI-PWS-IT	1	1450810000
IE-FCI-PWB-CZ	1	2426700000
IE-FCI-PWB-IND	1	2500710000
IE-FCI-PWB-RCBO	1	1534250000
IE-FCI-PWB-ISR	1	2531060000

Note

FrontCom® IP65 service interfaces


Overview

FrontCom® IP65 service interfaces	FrontCom® Vario IP65 service interface	M.2
	FrontCom® Micro IP65 service interface	
	RJ45	M.30
	USB	M.32

M

FrontCom® Vario IP65 service interface**FrontCom® Vario****Double frame**

- IP65
- Possibility of using single and double insertion plates

**Metal cover****Technical data**

Protection degree / Protection class (UL)

Material cover

Material frame

Ambient temperature (operational)

Approvals

Note

IP65, in closed state / Type 12

Zinc diecast, powder-coated

Zinc diecast

-40 °C...70 °C

CSA; CURUS

Ordering data

Rotary button operation

Lockable with key

Lockable with electrical cabinet key

Lockable with electrical cabinet key (Daimler lock)

Note

Type	Qty.	Order No.
IE-FC-DFM-KNOB	1	2003170000
IE-FC-DFM-KEY	1	2003180000
IE-FC-DFM-CAB	1	2003190000
IE-FC-DFM-CAB-DB	1	2003150000

Accessories**spare key****Marking tags**

silver

light grey

white

Type	Qty.	Order No.
IE-FC-KEY2	1	2066650000
SM 27/18 K MC NE SI	80	1713760000
SM 27/18 K MC NE GR	80	1073340000
SM 27/18 K MC NE WS	80	1707270000
ESG 7/20 SIRIUS MC NE WS	200	1736181044
IE-FC-PWPC	1	1450820000
IE-FC-DF-IPH	1	2003340000

Touch-safe protection

Touch-safe protection



Bar (for mounting single insert plates)

Partition

Note

FrontCom® Vario**Single frame**

- IP65

Metal cover**Plastic cover****Technical data**

Protection degree / Protection class (UL)

Material cover

Material frame

Ambient temperature (operational)

Approvals

Note

IP65, in closed state / Type 12

Zinc diecast, powder-coated

Zinc diecast

-40 °C...70 °C

CSA; CURUS; DNVGL

IP65, in closed state

Polycarbonate PC

Zinc diecast

-40 °C...70 °C

DNVGL

Ordering data

Rotary button operation

Lockable with key

Control cabinet key (double bit)

Control cabinet key (Daimler)

Note

Type	Qty.	Order No.
IE-FC-SFM-KNOB	1	1450530000
IE-FC-SFM-KEY2	1	1450540000
IE-FC-SFM-CAB	1	2003160000
IE-FC-SFM-CAB-DB	1	2663200000

Type	Qty.	Order No.
IE-FC-SFP-KNOB	1	1450510000
IE-FC-SFP-KEY2	1	1450520000
IE-FC-SFP-CAB	1	2003140000
IE-FC-SFP-CAB-DB	1	2663190000

Accessories**spare key**

Type	Qty.	Order No.
IE-FC-KEY2	1	2066650000
SM 27/18 K MC NE SI	80	1713760000
SM 27/18 K MC NE GR	80	1073340000
SM 27/18 K MC NE WS	80	1707270000
ESG 7/20 SIRIUS MC NE WS	200	1736181044
IE-FC-PWPC	1	1450820000

Type	Qty.	Order No.
IE-FC-KEY2	1	2066650000
SM 27/18 K MC NE SI	80	1713760000
SM 27/18 K MC NE GR	80	1073340000
SM 27/18 K MC NE WS	80	1707270000
ESG 7/20 SIRIUS MC NE WS	200	1736181044
IE-FC-PWPC	1	1450820000

Marking tags

silver

light grey

white

Touch-safe protection

Touch-safe protection

Accessories for mounting cut-out

Punch for hole punching tool

Punching tool

Note

FrontCom® Vario Frame NEMA 4X



- For particularly harsh environmental conditions (outdoor) with NEMA 4X approval



Single frame, metal lid



Double frame, metal lid



Technical data

Protection degree / Protection class (UL)

Material cover

Material frame

Ambient temperature (operational)

Approvals

Note

IP65, in closed state / NEMA 4X

Zinc diecast, powder-coated

Zinc diecast, powder-coated

-40 °C...70 °C

CSA; CURUS

IP65, in closed state / NEMA 4X

Zinc diecast, powder-coated

Zinc diecast, powder-coated

-40 °C...70 °C

CSA; CURUS

Ordering data

Rotary button operation

Note

Type	Qty.	Order No.
IE-FC-SFM-KNOB-4X	1	2669630000

Type	Qty.	Order No.
IE-FC-DFM-KNOB-4X	1	2669640000

Accessories

Marking tags

silver

light grey

white

Type	Qty.	Order No.
SM 27/18 K MC NE SI	80	1713760000
SM 27/18 K MC NE GR	80	1073340000
SM 27/18 K MC NE WS	80	1707270000
ESG 7/20 SIRIUS MC NE WS	200	1736181044
IE-FC-PWPC	1	1450820000
KOK 52 X 91	1	2008410000
IE-KO-HAT	1	1966810000
IE-FC-DF-IPH	1	2003340000

Type	Qty.	Order No.
SM 27/18 K MC NE SI	80	1713760000
SM 27/18 K MC NE GR	80	1073340000
SM 27/18 K MC NE WS	80	1707270000
ESG 7/20 SIRIUS MC NE WS	200	1736181044
IE-FC-PWPC	1	1450820000
KOK 52 X 91	1	2008410000
IE-KO-HAT	1	1966810000
IE-FC-DF-IPH	1	2003340000

Touch-safe protection

Touch-safe protection

Accessories for mounting cut-out

Punch for hole punching tool

Punching tool

Bar (for mounting single insert plates)


Partition

Note



FrontCom® Vario**Insert plates for double frames**

- IP20

1 x power, 2 x data, 1 x RCBO**Technical data**

Material
Insert, data
Insert Power large
Insert RCBO (2 modular width units)
Insert suitable for RCBO according to standard
Insert GFCI /2 x Power US pre-assembled
Ambient temperature (operational)
Approvals

Note**Ordering data**

shielded
unshielded

Note**Accessories****Inserts, Data**

RJ45 coupling
RJ45 module EIA/TIA T568 B
RJ45 module PROFINET
RJ45 module EIA/TIA T568 A
USB 2.0 A / A
USB 3.0 A / A
USB 2.0 A / B

Marking tags**Touch-safe protection**

Touch-safe protection


Type	Qty.	Order No.
IE-BI-RJ45-C	10	1962840000
IE-BI-RJ45-FJ-B	10	1963840000
IE-BI-RJ45-FJP	10	1963830000
IE-BI-RJ45-FJA	10	1962850000
IE-BI-USB-A	10	1019570000
IE-BI-USB-3.0-A	10	1487920000
IE-BI-USB-AB	10	1131380000
ESG 7/20 SIRIUS MC NE WS	200	1736181044
IE-FC-PWPC	1	1450820000

Note

An overview of the power inserts can be found in this chapter under power insert sockets.

FrontCom® Vario IP65 service interface**FrontCom® Vario****Insert plates for double frames**

- IP20

1x GFCI, 2x data, 1x signal, 1x fuse**Technical data**

Material
Insert, data
Insert Power large
Insert fuse
Signal insert D-Sub 9-pole / VGA / HDMI
Insert RCBO (2 modular width units)
Insert GFCI / 2 x Power US pre-assembled
Ambient temperature (operational)

Approvals

Technical data GFCI insert

Operating voltage / Rated current
GFCI protected US outlet
Self-test
Status indication
Type of connection
Line connection cross-section
Conductor connection cross-section, rigid

Note

Polycarbonate PC

2

1

1

1

-35 °C...66 °C

CSA; CURUS

125 V AC / 20 A

2 pieces

automatically every 3 seconds

red LED

Screw connection

1.5 ... 2.5 mm²1.5 ... 2.5 mm²1.5 ... 4 mm²**Ordering data**

shielded
unshielded

Note

Type	Qty.	Order No.
IE-FC-DSP-CI/3A/2ST/1D9	1	2004810000
IE-FC-DIP-CI/3A/2ST/1D9	1	2003370000
incl. pre-mounted GFCI		

Accessories**Inserts, Signal**

D-Sub, 9-pole, female/female
D-Sub, 9-pole, female / male
D-Sub, 9-pole, female / solder connection
VGA coupling
HDMI coupling

Fuse inserts

3 A

Inserts, Data

RJ45 coupling
RJ45 module EIA/TIA T568 A
RJ45 module EIA/TIA T568 B
RJ45 module PROFINET
USB 2.0 A / A
USB 3.0 A / A
USB 2.0 A / B



Marking tags

Type	Qty.	Order No.
IE-FCI-D9-FF	1	1450840000
IE-FCI-D9-FM	1	1450850000
IE-FCI-D9-FS	1	1450870000
IE-FCI-HD15-FF	1	1556290000
IE-FCI-HDMI-FF	1	2003390000
IE-FCI-PWCB-3A	1	1543690000
IE-BI-RJ45-C	10	1962840000
IE-BI-RJ45-FJ-A	10	1962850000
IE-BI-RJ45-FJ-B	10	1963840000
IE-BI-RJ45-FJ-P	10	1963830000
IE-BI-USB-A	10	1019570000
IE-BI-USB-3.0-A	10	1487920000
IE-BI-USB-AB	10	1131380000
ESG 7/20 SIRIUS MC NE WS	200	1736181044

Note

FrontCom® Vario**Insert plates**

- IP20

blank double plate**blank single plate****Technical data**

Material

Ambient temperature (operational)

Approvals

Note

Polycarbonate PC

-40 °C...70 °C

CSA; CURUS

Polycarbonate PC

-40 °C...70 °C

CSA; CURUS; DNVGL

Ordering data

unshielded

Note

Type	Qty.	Order No.
IE-FC-DIP-BP	1	2004890000

Type	Qty.	Order No.
IE-FC-IP-BP	1	1450710000

Accessories



Type	Qty.	Order No.

Type	Qty.	Order No.

Note

FrontCom® Vario IP65 service interface**FrontCom® Vario****Insert plates**

- IP20

1 x power, 2 x data**1x Power, 1x Signal****Technical data**

Material
Insert, data
Signal insert D-Sub 9-pole / VGA / HDMI
Insert, signal, D-Sub, 25-pole
Insert Power large
Insert Power small
Insert Power US
Ambient temperature (operational)
Approvals

Note

Polycarbonate PC

2

1

-40 °C...70 °C

CSA; CURUS; DNVGL

Polycarbonate PC

1

1

40 °C...70 °C

CSA; CURUS

Ordering data

shielded
unshielded

Note

Type	Qty.	Order No.
IE-FC-SP-PWB/2ST	1	1450550000
IE-FC-IP-PWB/2ST	1	1450630000

Type	Qty.	Order No.
IE-FC-IP-PWB/1D9	1	2003350000

Accessories**Inserts, Data**

RJ45 coupling
RJ45 module EIA/TIA T568 A
RJ45 module EIA/TIA T568 B
RJ45 module PROFINET
USB 2.0 A / A
USB 3.0 A / A
USB 2.0 A / B

Type	Qty.	Order No.
IE-BI-RJ45-C	10	1962840000
IE-BI-RJ45-FJA	10	1962850000
IE-BI-RJ45-FJB	10	1963840000
IE-BI-RJ45-FJP	10	1963830000
IE-BI-USB-A	10	1019570000
IE-BI-USB-3.0-A	10	1487920000
IE-BI-USB-AB	10	1131380000

Type	Qty.	Order No.
ESG 7/20 SIRIUS MC NE WS	200	1736181044
IE-FC-PWPC	1	1450820000

Marking tags**Touch-safe protection**

Touch-safe protection

Inserts, Signal

D-Sub, 9-pole, female/female
D-Sub, 9-pole, female / male
D-Sub, 9-pole, female / solder connection
VGA coupling
HDMI coupling

ESG 7/20 SIRIUS MC NE WS	200	1736181044
IE-FC-PWPC	1	1450820000

ESG 7/20 SIRIUS MC NE WS	200	1736181044
IE-FC-PWPC	1	1450820000
IE-FCI-D9-FF	1	1450840000
IE-FCI-D9-FM	1	1450850000
IE-FCI-D9-FS	1	1450870000
IE-FCI-HD15-FF	1	1556290000
IE-FCI-HDMI-FF	1	2003390000



Note

You will find an overview of the power inserts in this chapter under Power inserts-sockets.

You will find an overview of the power inserts in this chapter under Power inserts-sockets.

FrontCom® Vario**Insert plates**

- IP20

1x Power**1x Power, 2x Data, 1x Signal****Technical data**

Material
Insert, data
Signal insert D-Sub 9-pole / VGA / HDMI
Insert, signal, D-Sub, 25-pole
Insert Power large
Insert Power small
Insert Power US
Ambient temperature (operational)
Approvals

Note

Polycarbonate PC
1
-40 °C...70 °C
CSA; CURUS

Polycarbonate PC
2
1
-40 °C...70 °C
CSA; CURUS; DNVGL

Ordering data

shielded
unshielded

Note

Type	Qty.	Order No.
IE-FC-IP-PWB	1	2548060000

Type	Qty.	Order No.
IE-FC-SP-PWS/2ST/1D9	1	1450600000
IE-FC-IP-PWS/2ST/1D9	1	1450690000

Accessories

Inserts, Data
RJ45 coupling
RJ45 module EIA/TIA T568 A
RJ45 module EIA/TIA T568 B
RJ45 module PROFINET
USB 2.0 A / A
USB 3.0 A / A
USB 2.0 A / B

Type	Qty.	Order No.
ESG 7/20 SIRIUS MC NE WS	200	1736181044

Type	Qty.	Order No.
IE-BI-RJ45-C	10	1962840000
IE-BI-RJ45-FJ-A	10	1962850000
IE-BI-RJ45-FJ-B	10	1963840000
IE-BI-RJ45-FJ-P	10	1963830000
IE-BI-USB-A	10	1019570000
IE-BI-USB-3.0-A	10	1487920000
IE-BI-USB-AB	10	1131380000

Marking tags**Touch-safe protection**

Touch-safe protection

Inserts, Signal
D-Sub, 9-pole, female/female
D-Sub, 9-pole, female / male
D-Sub, 9-pole, female / solder connection
VGA coupling
HDMI coupling

Type	Qty.	Order No.
IE-FC-PWPC	1	1450820000

Type	Qty.	Order No.
IE-FCI-D9-FF	1	1450840000
IE-FCI-D9-FM	1	1450850000
IE-FCI-D9-FS	1	1450870000
IE-FCI-HD15-FF	1	1556290000
IE-FCI-HDMI-FF	1	2003390000

Note

You will find an overview of the power inserts in this chapter under Power inserts-sockets.

You will find an overview of the power inserts in this chapter under Power inserts-sockets.



FrontCom® Vario

- IP20

1 x power, 4 x data



1 x power, 2 x signal



Technical data

- Material
- Insert, data
- Signal insert D-Sub 9-pole / VGA / HDMI
- Insert, signal, D-Sub, 25-pole
- Insert Power large
- Insert Power small
- Insert Power US
- Ambient temperature (operational)

Polycarbonate PC
4

1

-40 °C...70 °C

Polycarbonate PC
2
1
-40 °C ... 70 °C

Ordering data

shielded
unshielded

Type	Qty.	Order No.
IE-FC-SP-PWS/4ST	1	1450570000
IE-FC-IP-PWS/4ST	1	1450640000

Type	Qty.	Order No.
IE-FC-SP-PWS/2D9	1	1450610000
IE-FC-IP-PWS/2D9	1	1450680000

Accessories

Inserts, Power	Socket IT/EU
Inserts, Data	RJ45 coupling
	RJ45 module EIA/TIA T568 A
	RJ45 module EIA/TIA T568 B
	RJ45 module PROFINET
	USB 2.0 A / A
	USB 3.0 A / A
	USB 2.0 A / B

Type	Qty.	Order No.
IE-FCI-PWS-IT	1	1450810000
IE-BI-RJ45-C	10	1962840000
IE-BI-RJ45-FJA	10	1962850000
IE-BI-RJ45-FJB	10	1963840000
IE-BI-RJ45-FJP	10	1963830000
IE-BI-USB-A	10	1019570000
IE-BI-USB-3.0-A	10	1487920000
IE-BI-USB-AB	10	1131380000

Marking tags

Touch-safe protection	Touch-safe protection
Inserts, Signal	D-Sub, 9-pole, female/female D-Sub, 9-pole, female / male D-Sub, 9-pole, female / solder connection VGA coupling HDMI coupling



ESG 7/20 SIRIUS MC NE WS	200	1736181044
IE-FC-PWPC	1	1450820000

ESG 7/20 SIRIUS MC NE WS	200	1736181044
IE-FC-PWPC	1	1450820000
IE-FCI-D9-FF	1	1450840000
IE-FCI-D9-FM	1	1450850000
IE-FCI-D9-FS	1	1450870000
IE-FCI-HD15-FF	1	1556290000
IE-FCI-HDMI-FF	1	2003390000

Note

FrontCom® Vario**Insert plates**

- IP20

1 x power, 2 x data**1 x power, 1 x 3A fuse, 1 x data****Technical data**

Material	
Insert, data	
Signal insert D-Sub 9-pole / VGA / HDMI	
Insert, signal, D-Sub, 25-pole	
Insert Power large	
Insert Power small	
Insert Power US	
Insert fuse	
Ambient temperature (operational)	-40 °C...70 °C
Approvals	CSA; CURUS; DNVGL

Note**Polycarbonate PC**

2

Polycarbonate PC

1

Ordering data

shielded	
unshielded	

Note

Type	Qty.	Order No.
IE-FC-SP-PWU/2ST	1	1450620000
IE-FC-IP-PWU/2ST	1	1450700000

For US socket the touch-safe protection is mandatory

Type	Qty.	Order No.
IE-FC-IP-PWU/1ST/CB	1	1543710000

For US socket the touch-safe protection is mandatory

Accessories

Inserts, Signal	
D-Sub, 9-pole, female/female	
D-Sub, 9-pole, female / male	
D-Sub, 9-pole, female / solder connection	
D-Sub, 25-pole, female/female	
D-Sub, 25-pole, female/male	
D-Sub, 25-pole, female / solder connection	
HDMI coupling	
VGA coupling	

Inserts, Data	
RJ45 coupling	
RJ45 module EIA/TIA T568 A	
RJ45 module EIA/TIA T568 B	
RJ45 module PROFINET	
USB 2.0 A / A	
USB 3.0 A / A	
USB 2.0 A / B	

Marking tags	
Touch-safe protection	Touch-safe protection
Inserts, Power	US socket
Fuse inserts	3 A

Type	Qty.	Order No.
IE-BI-RJ45-C	10	1962840000
IE-BI-RJ45-FJA	10	1962850000
IE-BI-RJ45-FJB	10	1963840000
IE-BI-RJ45-FJP	10	1963830000
IE-BI-USB-A	10	1019570000
IE-BI-USB-3.0-A	10	1487920000
IE-BI-USB-AB	10	1131380000

ESG 7/20 SIRIUS MC NE WS	200	1736181044
IE-FC-PWPC	1	1450820000
IE-FCI-PWS-US	1	1450800000



Type	Qty.	Order No.
IE-BI-RJ45-C	10	1962840000
IE-BI-RJ45-FJ-A	10	1962850000
IE-BI-RJ45-FJ-B	10	1963840000
IE-BI-RJ45-FJ-P	10	1963830000
IE-BI-USB-A	10	1019570000
IE-BI-USB-3.0-A	10	1487920000
IE-BI-USB-AB	10	1131380000

ESG 7/20 SIRIUS MC NE WS	200	1736181044
IE-FC-PWPC	1	1450820000
IE-FCI-PWS-US	1	1450800000

Note

FrontCom® Vario**Insert plates**

- IP20

2 x data, 2 x signal**1 x data, 2 x signal****Technical data**

Material	
Insert, data	
Signal insert D-Sub 9-pole / VGA / HDMI	
Insert, signal, D-Sub, 25-pole	
Insert Power large	
Insert Power small	
Insert Power US	
Insert fuse	
Ambient temperature (operational)	-40 °C...70 °C
Approvals	CSA; CURUS; DNVGL

Note**Polycarbonate PC**

2

2

Polycarbonate PC

1

1

1

Ordering data

shielded	
unshielded	

Note

Type	Qty.	Order No.
IE-FC-SP-2ST/2D9	1	1450590000
IE-FC-IP-2ST/2D9	1	1450670000

Type	Qty.	Order No.
IE-FC-SP-1ST/1D9/1D25	1	1450580000
IE-FC-IP-1ST/1D9/1D25	1	1450650000

Accessories

Inserts, Signal	Type	Qty.	Order No.
D-Sub, 9-pole, female/female	IE-FCI-D9-FF	1	1450840000
D-Sub, 9-pole, female / male	IE-FCI-D9-FM	1	1450850000
D-Sub, 9-pole, female / solder connection	IE-FCI-D9-FS	1	1450870000
D-Sub, 25-pole, female/female			
D-Sub, 25-pole, female/male			
D-Sub, 25-pole, female / solder connection			
HDMI coupling	IE-FCI-HDMI-FF	1	2003390000
VGA coupling	IE-FCI-HD15-FF	1	1556290000

Type	Qty.	Order No.
IE-FCI-D9-FF	1	1450840000
IE-FCI-D9-FM	1	1450850000
IE-FCI-D9-FS	1	1450870000
IE-FCI-D25-FM	1	1450890000
IE-FCI-D25-FS	1	1450900000
IE-FCI-D25-FF	1	1450880000
IE-FCI-HDMI-FF	1	2003390000
IE-FCI-HD15-FF	1	1556290000

Type	Qty.	Order No.
IE-FCI-D9-FF	1	1450840000
IE-FCI-D9-FM	1	1450850000
IE-FCI-D9-FS	1	1450870000
IE-FCI-D25-FM	1	1450890000
IE-FCI-D25-FS	1	1450900000
IE-FCI-D25-FF	1	1450880000
IE-FCI-HDMI-FF	1	2003390000
IE-FCI-HD15-FF	1	1556290000

Inserts, Data	Type	Qty.	Order No.
RJ45 coupling	IE-BI-RJ45-C	10	1962840000
RJ45 module EIA/TIA T568 A	IE-BI-RJ45-FJ-A	10	1962850000
RJ45 module EIA/TIA T568 B	IE-BI-RJ45-FJ-B	10	1963840000
RJ45 module PROFINET	IE-BI-RJ45-FJ-P	10	1963830000
USB 2.0 A / A	IE-BI-USB-A	10	1019570000
USB 3.0 A / A	IE-BI-USB-3.0-A	10	1487920000
USB 2.0 A / B	IE-BI-USB-AB	10	1131380000

Type	Qty.	Order No.
IE-BI-RJ45-C	10	1962840000
IE-BI-RJ45-FJ-A	10	1962850000
IE-BI-RJ45-FJ-B	10	1963840000
IE-BI-RJ45-FJ-P	10	1963830000
IE-BI-USB-A	10	1019570000
IE-BI-USB-3.0-A	10	1487920000
IE-BI-USB-AB	10	1131380000

Type	Qty.	Order No.
IE-BI-RJ45-C	10	1962840000
IE-BI-RJ45-FJ-A	10	1962850000
IE-BI-RJ45-FJ-B	10	1963840000
IE-BI-RJ45-FJ-P	10	1963830000
IE-BI-USB-A	10	1019570000
IE-BI-USB-3.0-A	10	1487920000
IE-BI-USB-AB	10	1131380000

Marking tags	Type	Qty.	Order No.
	ESG 7/20 SIRIUS MC NE WS	200	1736181044

Type	Qty.	Order No.
ESG 7/20 SIRIUS MC NE WS	200	1736181044

Type	Qty.	Order No.
ESG 7/20 SIRIUS MC NE WS	200	1736181044

Touch-safe protection	Type	Qty.	Order No.
	Touch-safe protection		

Type	Qty.	Order No.

Type	Qty.	Order No.

Inserts, Power	Type	Qty.	Order No.
	US socket		

Type	Qty.	Order No.

Type	Qty.	Order No.




Fuse inserts	Type	Qty.	Order No.
	3 A		

Type	Qty.	Order No.

Type	Qty.	Order No.

Data inserts**RJ45**

- Completely in Cat. 6_A
- IP20
- For housing variants 1, 4, 5, 14 and for FrontCom®

Module**Coupling****Technical data**

Protection degree

Plugging cycles

Shielding

Housing main material

Contact surface

Connection cross-section, flexible, min. / max.

Connection cross-section, solid, min. / max.

Insulation diameter, min. / max.

Connector standard

Ambient temperature (operational)

PoE / PoE+

Approvals

Note

IP67 with housing

750

360° all-round enclosure

Zinc diecast

Gold over nickel, Au ≥ 0.8 µm

AWG 26 / AWG 22

AWG 24 / AWG 22

0.85 mm...1.6 mm

IEC 60603-7-51

-40 °C...70 °C

conforming to IEEE 802.3af

CULUS

Connection of WM Cat. 7 AWG 27/7 LSZH possible

IP67 with housing

750

360° all-round enclosure

Zinc diecast

Gold over nickel, Au ≥ 0.8 µm

...

IEC 60603-7-51

-40 °C...70 °C

conforming to IEEE 802.3af

CULUS; DNVGL

Ordering data**tool-free**

TIA-A. Cat. 6_A
TIA-B. Cat. 6_A
PROFINET Cat. 5
Coupling

Note**Accessories****Tools**

Optional pressing tool

Type	Qty.	Order No.
IE-BI-RJ45-FJA	10	1962850000
IE-BI-RJ45-FJB	10	1963840000
IE-BI-RJ45-FJP	10	1963830000

Type	Qty.	Order No.
IE-BI-RJ45-C	10	1962840000



Type	Qty.	Order No.
PWZ RJ45	1	1118040000

Type	Qty.	Order No.

Note

Data inserts**USB**

- IP20
- For housing variants 1, 4, 5, 14 and for FrontCom®

Coupling USB A/A**Coupling USB A/B****Technical data**

Protection degree
Shielding
Ambient temperature (operational)
Connection 1 / 2
Connector standard
Approvals

Note**Ordering data**

USB 2.0
USB 3.0

Note**Accessories****USB cable 2.0**

0.5 m
1.0 m
1.5 m
1.8 m
3.0 m

USB cable 3.0

0.5 m
1.8 m
3.0 m
5.0 m

IP67 with housing
360° all-round enclosure
-40 °C...70 °C
USB A / USB A
IEC 61076-3-107
CULUS, DNVGL

Type	Qty.	Order No.
IE-BI-USB-A	10	1019570000
IE-BI-USB-3.0-A	10	1487920000

IP67 with housing
360° all-round enclosure
-40 °C...70 °C
USB A / USB B
IEC 61076-3-107
CULUS, DNVGL



Type	Qty.	Order No.
IE-BI-USB-AB	10	1131380000

Type	Qty.	Order No.
IE-USB-A-A-0.5M	1	1993550005
IE-USB-A-A-1.0M	1	1993550010
IE-USB-A-A-1.5M	1	1993550015
IE-USB-A-A-1.8M	1	1993550018
IE-USB-A-A-3.0M	1	1993550030
IE-USB-3.0-A-A-0.5M	1	2581730005
IE-USB-3.0-A-A-1.8M	1	2581730018
IE-USB-3.0-A-A-3M	1	2581730030
IE-USB-3.0-A-A-5M	1	2581730050

Note**Note****Note**

Signal inserts**D-sub**

- IP 20

9-pole**25-pole****Technical data**

Protection degree

IP20

Housing main material

SPCC

Number of poles

9

Housing surface

tin-plated

Material insulator

PBT glass fibre reinforced UL 94 V-0

Contact surface

Gold-plated

Contact resistance

 $\leq 20 \text{ m}\Omega$

Insulation strength

1000 MΩ at 500 V DC

Dielectric strength, contact / contact

1 kV_{eff} / 1 min.

Ambient temperature (operational)

-55 °C...105 °C

Approvals

DNVGL; UR

Note**Ordering data**

Socket / socket

Socket / plug

Socket / solder connection



Note**Accessories**

Type	Qty.	Order No.
IE-FCI-D9-FF	1	1450840000
IE-FCI-D9-FM	1	1450850000
IE-FCI-D9-FS	1	1450870000

Type	Qty.	Order No.
IE-FCI-D25-FF	1	1450880000
IE-FCI-D25-FM	1	1450890000
IE-FCI-D25-FS	1	1450900000

Signal inserts

- IP 20

HDMI**HD15 / VGA****Technical data**

Protection degree

IP20

Housing main material

PVC casting

Number of poles

9

Housing surface

Contact surface

Contact resistance

Insulation strength

Dielectric strength, contact / contact

Ambient temperature (operational)

Approvals

Note**Ordering data****Note****Accessories****Note**

Gold-plated

-15 °C...50 °C

UR

IP20

25

Gold over nickel

1000 MΩ at 500 V DC

1000 V_{eff} / 1 min

-55 °C...105 °C

DNVGL; UR












Type	Qty.	Order No.
IE-FCI-HDMI-FF	1	2003390000

Type	Qty.	Order No.
IE-FCI-HD15-FF	1	1556290000

Type	Qty.	Order No.



Type	Qty.	Order No.

Type overview: Power inserts/sockets

Type	Region	Plug-Type		Qty.	Order No.
IE-FCI-PWS-US	USA	Type B		1	1450800000
IE-FCI-PWB-IND	India, South Africa	Type D		1	2500710000
IE-FCI-PWB-CZ	Czechia	Type E		1	2426700000
IE-FCI-PWB-FR	France	Type E		1	1450750000
IE-FCI-PWB-DE	Germany	Type F		1	1450730000
IE-FCI-PWB-GB	Great Britain	Type G		1	1450770000
IE-FCI-PWS-ISR	Israel	Tpy H		1	2531060000
IE-FCI-PWB-AU-15A	Australia	Type I		1	1450830000
IE-FCI-PWB-AU-10A	Australia	Type I		1	1546590000
IE-FCI-PWB-CN	China	Type I		1	1450790000
IE-FCI-PWB-CH	Schwitzerland	Type J		1	1450780000
IE-FCI-PWB-DK	Denmark	Type K		1	2661340000
IE-FCI-PWS-IT	Italy, Europe	Type L		1	1450810000

FrontCom® Vario IP65 service interface**Power inserts****Power sockets**

- IP 20

Germany, white**Germany, orange****Technical data**

Protection degree

Housing main material

Type of connection

Connector face

Connector standard

Line connection cross-section

finely stranded with wire-end ferrule

finely stranded without wire-end ferrule

finely stranded with wire-end ferrule

finely stranded without wire-end ferrule

Conductor connection cross-section, rigid

Stripping length

Rated voltage (AC)

Rated current

Ambient temperature (operational)

Approvals

Note

IP20

Polycarbonate PC

PUSH IN

Type F

1.5 ... 1.5 mm²1.5 ... 2.5 mm²1.5 ... 1.5 mm²1.5 ... 2.5 mm²1.5 ... 2.5 mm²

10 mm

250 V

16 A

-5 °C...50 °C

DNVGL

IP20

Polycarbonate PC

PUSH IN

Type F

1.5 ... 1.5 mm²1.5 ... 2.5 mm²1.5 ... 1.5 mm²1.5 ... 2.5 mm²1.5 ... 2.5 mm²

10 mm

250 V

16 A

-5 °C...50 °C

DNVGL

Ordering data**Note**

Type	Qty.	Order No.
IE-FCI-PWB-DE	1	1450730000

Type	Qty.	Order No.
IE-FCI-PWB-DE-OR	1	1554000000

Accessories**FrontCom**

Adapter for mounting rail installation


Flat blade connector, 6.5 mm

straight, 4.8 mm, fully insulated

Type	Qty.	Order No.
IE-DINRAIL-AD-PWB	1	2534680000

Type	Qty.	Order No.
IE-DINRAIL-AD-PWB	1	2534680000


Note

Switzerland

IP20
Polycarbonate PC
PUSH IN
Type J
1.5 ... 1.5 mm ²
1.5 ... 2.5 mm ²
1.5 ... 1.5 mm ²
1.5 ... 2.5 mm ²
1.5 ... 2.5 mm ²
10 mm
250 V
10 A
-5 °C...50 °C
DNVGL

Type	Qty.	Order No.
IE-FCI-PWB-CH	1	1450780000


Type	Qty.	Order No.
IE-DINRAIL-AD-PWB	1	2534680000

France, white

IP20
Polycarbonate PC
PUSH IN
Type E
1.5 ... 1.5 mm ²
1.5 ... 2.5 mm ²
1.5 ... 1.5 mm ²
1.5 ... 2.5 mm ²
1.5 ... 2.5 mm ²
10 mm
250 V
16 A
-5 °C...50 °C
DNVGL

Type	Qty.	Order No.
IE-FCI-PWB-FR	1	1450750000

Type	Qty.	Order No.
IE-DINRAIL-AD-PWB	1	2534680000

France, orange

IP20
Polycarbonate PC
PUSH IN
Type E
1.5 ... 1.5 mm ²
1.5 ... 2.5 mm ²
1.5 ... 1.5 mm ²
1.5 ... 2.5 mm ²
1.5 ... 2.5 mm ²
10 mm
250 V
16 A
-5 °C...50 °C
DNVGL



Type	Qty.	Order No.
IE-FCI-PWB-FR-OR	1	2007230000

Type	Qty.	Order No.
IE-DINRAIL-AD-PWB	1	2534680000

FrontCom® Vario IP65 service interface

Power inserts**Power sockets**

- IP 20

UK**Italy / Europe****Technical data**

Protection degree

Housing main material

Type of connection

Connector face

Connector standard

Line connection cross-section

finely stranded with wire-end ferrule

finely stranded without wire-end ferrule

finely stranded with wire-end ferrule

finely stranded without wire-end ferrule

Conductor connection cross-section, rigid

Stripping length

Rated voltage (AC)

Rated current

Ambient temperature (operational)

Approvals

Note**Ordering data****Note****Accessories****FrontCom**

Adapter for mounting rail installation

Flat blade connector, 6.5 mm

straight, 4.8 mm, fully insulated

IP20

Polycarbonate PC

Screw connection

Type G

1.5 ... 2.5 mm²1.5 ... 4 mm²1.5 ... 2.5 mm²1.5 ... 4 mm²1.5 ... 4 mm²

9 mm

250 V

13 A

-5 °C...50 °C

DNVGL

IP20

Polycarbonate PC

Screw connection

Type L

1.5 ... 2.5 mm²1.5 ... 4 mm²1.5 ... 2.5 mm²1.5 ... 4 mm²1.5 ... 4 mm²

9 mm

250 V

16 A

-5 °C...50 °C

DNVGL

Type Qty. Order No.

IE-FCI-PWB-GB 1 1450770000

Type Qty. Order No.

IE-FCI-PWS-IT 1 1450810000

Type Qty. Order No.


IE-DINRAIL-AD-PWB 1 2534680000

Type Qty. Order No.

IE-DINRAIL-AD-PWB 1 2534680000

Note

Czech Republic




IP20
Polycarbonate PC
PUSH IN
Type E
1.5 ... 1.5 mm ²
1.5 ... 2.5 mm ²
1.5 ... 1.5 mm ²
1.5 ... 2.5 mm ²
1.5 ... 2.5 mm ²
12 mm
250 V
16 A
-5 °C...50 °C



Type	Qty.	Order No.
IE-FCI-PWB-CZ	1	2426700000

Type	Qty.	Order No.
IE-DINRAIL-AD-PWB	1	2534680000

Australia, 15 A




IP20
Polycarbonate PC
Screw connection
Type I
1.5 ... 2.5 mm ²
1.5 ... 4 mm ²
1.5 ... 2.5 mm ²
1.5 ... 4 mm ²
1.5 ... 4 mm ²
9 mm
240 V
15 A
-5 °C...50 °C
DNVGL



Type	Qty.	Order No.
IE-FCI-PWB-AU	1	1450830000

Type	Qty.	Order No.
IE-DINRAIL-AD-PWB	1	2534680000

Australia, 10 A



IP20
Polycarbonate PC
Screw connection
Type I
1.5 ... 2.5 mm ²
1.5 ... 4 mm ²
1.5 ... 2.5 mm ²
1.5 ... 4 mm ²
1.5 ... 4 mm ²
9 mm
240 V
10 A
-5 °C...50 °C
DNVGL





Type	Qty.	Order No.
IE-FCI-PWB-AU-10A	1	1546590000

Type	Qty.	Order No.
IE-DINRAIL-AD-PWB	1	2534680000

FrontCom® Vario IP65 service interface

Power inserts**Power sockets**

- IP 20

China**USA****Technical data**

Protection degree

Housing main material

Type of connection

Connector face

Connector standard

Line connection cross-section

finely stranded with wire-end ferrule

finely stranded without wire-end ferrule

finely stranded with wire-end ferrule

finely stranded without wire-end ferrule

Conductor connection cross-section, rigid

Stripping length

Rated voltage (AC)

Rated current

Ambient temperature (operational)

Approvals

Note**Ordering data****Note****Accessories****FrontCom**

Adapter for mounting rail installation

Flat blade connector, 6.5 mm

straight, 4.8 mm, fully insulated

IP20

Polycarbonate PC

Screw connection

Type I

1.5 ... 2.5 mm²1.5 ... 4 mm²1.5 ... 2.5 mm²1.5 ... 4 mm²1.5 ... 4 mm²

9 mm

250 V

10 A

-5 °C...50 °C

DNVGL

IP20

PA 66

Solder connection, FS 4.8 x 0.8

Type B

...

...

...

...

...

125 V

15 A

-20 °C...85 °C

DNVGL; UR

Type	Qty.	Order No.
IE-FCI-PWB-CN	1	1450790000

Type	Qty.	Order No.
IE-FCI-PWS-US	1	1450800000


For US socket the touch-safe protection is mandatory

Type	Qty.	Order No.
IE-DINRAIL-AD-PWB	1	2534680000

Type	Qty.	Order No.
VFSKHV/1,5-2,5/485	100	1491920000


Note**Note****Note**

India, South Africa




IP20
Polycarbonate PC
Screw connection
Type D
1.5 ... 2.5 mm ²
...
1.5 ... 2.5 mm ²
...
1.5 ... 4 mm ²
9 mm
250 V
13 A
-5 °C...50 °C

Israel



IP20
PP
Screw connection
Type H
1.5 ... 1.5 mm ²
...
1.5 ... 1.5 mm ²
...
1.5 ... 2.5 mm ²
11 mm
250 V
16 A
-5 °C...50 °C


Denmark



IP20
Polycarbonate PC
PUSH IN
Type K
1.5 ... 1.5 mm ²
1.5 ... 2.5 mm ²
1.5 ... 1.5 mm ²
1.5 ... 2.5 mm ²
1.5 ... 2.5 mm ²
13 mm
250 V
13 A
-5 °C...40 °C

Power inserts**RCBO**

- IP 20

RCBO**Technical data**

Ambient temperature (operational)

-5 °C...40 °C

Operating voltage

230 V AC

Rated current

16 A

IΔm

500 A

IΔn

30 mA

Triggering characteristic

Typ C

Type of connection

Screw connection

Line connection cross-section

1.5 ... 2.5 mm²


finely stranded with wire-end ferrule

1.5 ... 2.5 mm²

finely stranded with wire-end ferrule

1.5 ... 2.5 mm²

Conductor connection cross-section, rigid

Note**Ordering data****Note**

Type	Qty.	Order No.
IE-FCI-PWB-RCBO	1	1534250000

Accessories**FrontCom**


Adapter for mounting rail installation

Type	Qty.	Order No.
IE-DINRAIL-AD-PWB	1	2534680000

Note

Power inserts**USB charge insert**

- IP 20

USB-Charger 5 V / 2.4 A**Technical data**

Ambient temperature (operational)	0 °C...45 °C
Input voltage	220...240 V AC
Frequency range	50...60 Hz
Input current	≤ 300 mA
Output voltage	5 V DC
Output current	2.4 A
Degree of efficiency	81 %
Power consumption in standby mode	max. 0.1 W
Standards	EN 60950-1, EN 62684, EN 50558
Protection class	II
Housing main material	Polycarbonate PC
Type of connection	Screw connection
Line connection cross-section	1.5 ... 2.5 mm ²
finely stranded with wire-end ferrule	1.5 ... 2.5 mm ²
finely stranded with wire-end ferrule	1.5 ... 2.5 mm ²
Conductor connection cross-section, rigid	1.5 ... 2.5 mm ²
Stripping length	6 mm

Note**Ordering data**

Type	Qty.	Order No.
IE-FCI-PWB-2USB-A-5V	1	2505070000


Note**Accessories**

Type	Qty.	Order No.
IE-DINRAIL-AD-PWB	1	2534680000

Note

3A fuse

- IP 20

3A fuse**Technical data**

Operating voltage

32 V DC, 250 V AC

Rated current

3 A

Type of connection

Flat-blade receptacles 6.5 mm


Note**Ordering data****Note****Accessories****Flat blade connector, 6.5 mm**angled
straight**Type** **Qty.** **Order No.**

IE-FCI-PWCB-3A 1 1543690000

WFSKHV/1,5-2,5 100 1491970000

VFSKHV/1,5-2,5/638 100 1491940000

Note

Accessories**Touch-safe protection****Touch-safe protection****Technical data**

Length x width x height

47.5 / 47.5 / 45 mm

Material

PC

Note**Ordering data**

Type	Qty.	Order No.
IE-FC-PWPC	1	1450820000


Note**Accessories**

Type	Qty.	Order No.

Note

FrontCom® Vario IP65 service interface**Sets**

- shielded

2x Data 1x Power DE**Plastic cover****Technical data**

Frame
Insert plate
Data inserts
Power inserts
Rated voltage for socket
Rated current for socket
Protection degree
products included in the set

Plastic cover
2x data, 1x power, Shielded
USB 2.0 A/A, RJ45 coupling Cat.6_A
Socket DE
250 V
16 A
IP65, in closed state
1450510000;1450550000;1450730000;1019570000;196284
0000

Note**Ordering data**

shielded
unshielded

Type	Qty.	Order No.
IE-FC-SET-SPDED001-KN-P	1	1529580000

Note**Accessories**

Type	Qty.	Order No.

Note

Sets

Incl. fixed label: "Service only!", "USB", "Ethernet", "230 V AC"

2x Data, 1x Power**2x Data, 1x Power****Technical data**

Frame
Insert plate
Data inserts
Power inserts
Rated voltage for socket
Rated current for socket
Protection degree
products included in the set

Note**Ordering data**

shielded
unshielded

Note**Accessories**

Plastic cover, Lockable with key
2x data, 1x power, Shielded
USB 2.0 A/A, RJ45 coupling Cat.6_A
Socket DE
250 V
16 A
IP65, in closed state
1450520000;1450550000;1450730000;1019570000;19628400
00;1450820000

Type	Qty.	Order No.
IE-FC-SET-SPDEK001-KY-P	1	1989020000

Plastic cover, Lockable with key
2x data, 1x power, Unshielded
USB 2.0 A/A, RJ45 coupling Cat.6_A
Socket DE
250 V
16 A
IP65, in closed state
1450520000;1450630000;1450730000;1019570000;19628400
00;1450820000

Type	Qty.	Order No.
IE-FC-SET-IPDEK001-KY-P	1	1543680000



Note

FrontCom® Micro RJ45 Module

8-wire



4-wire



Technical data

Category
Protection degree
Housing main material
Contact surface
Colour
Shielding
Type of mounting
Plugging cycles
Connector standard
Connection 1 / 2
Wall thickness, min. / max.
Dust protection cap material
PoE / PoE+
Ambient temperature (operational)
Approvals

Note

Ordering data

PROFINET module
TIA-A module
TIA-B module

Note

Accessories

Fixing tool

Marking tags

SwitchMark markers white
MultiCard, white

Holder

Type	Qty.	Order No.
IE-FCM-RJ45-FJ-A	10	1018810000
IE-FCM-RJ45-FJ-B	10	1018820000

Type	Qty.	Order No.
IE-FCM-RJ45-FJ-P	10	1018830000


Type	Qty.	Order No.
IE-FISP-V4	2	9204370000
SM 27/18 MC NE WS	80	1699860000
ESG 9/11 K MC NE WS	200	1857440000

Type	Qty.	Order No.
IE-FISP-V4	2	9204370000
SM 27/18 MC NE WS	80	1699860000
ESG 9/11 K MC NE WS	200	1857440000

SM-H 27/18 SW	25	1716630000
---------------	----	------------

SM-H 27/18 SW	25	1716630000
---------------	----	------------

Note

FrontCom® Micro RJ45**Coupling****8-wire****Technical data**

Category

Cat.6A / Class E_a (ISO/IEC 11801 2010)

Protection degree

IP65, in closed state

Housing main material

PA UL 94 VO

Contact surface

Gold over nickel

Colour

black

Shielding

360° shield contact

Type of mounting

Cabinet, Distribution box

Plugging cycles

750

Connector standard

IEC 60603-7-51

Connection 1 / 2

RJ45 / RJ45

Wall thickness, min. / max.

1 mm / 3 mm

Dust protection cap material

EPDM

PoE / PoE+

conforming to IEEE 802.3af

Ambient temperature (operational)

-40 °C...70 °C

Approvals

CULUS

Note**Ordering data**

Coupling

Type	Qty.	Order No.
IE-FCM-RJ45-C	10	1018790000

Note**Accessories**

Fixing tool

Type	Qty.	Order No.
IE-FISP-V4	2	9204370000

Marking tags



SwitchMark markers white

Type	Qty.	Order No.
SM 27/18 MC NE WS	80	1699860000

Holder

Type	Qty.	Order No.
SM-H 27/18 SW	25	1716630000

Note

FrontCom® Micro USB**Coupling AA****Coupling AB****Technical data**

Ambient temperature (operational)

Protection degree

Housing main material

Colour

Shielding

Type of mounting

Connector standard

Connection 1 / 2

Dust protection cap material

Wall thickness, min. / max.

Approvals

Note

-40 °C...70 °C

IP65, in closed state

PA UL 94 VO

black

360° shield contact

Cabinet, Distribution box

IEC 61076-3-107

USB A / USB A

EPDM

1 mm / 3 mm

CULUS; EAC

Approvals available on request

-40 °C...70 °C

IP65, in closed state

PA UL 94 VO

black

360° shield contact

Cabinet, Distribution box

IEC 61076-3-107

USB A / USB B

EPDM

1 mm / 3 mm

CULUS; EAC

Ordering dataUSB 2.0
USB 3.0

Type	Qty.	Order No.
IE-FCM-USB-A	10	1018840000
IE-FCM-USB-3.0-A	10	1427960000

Type	Qty.	Order No.
IE-FCM-USB-AB	10	1222550000

Accessories**Fixing tool**

Type	Qty.	Order No.
IE-FISP-V4	2	9204370000

Type	Qty.	Order No.
IE-FISP-V4	2	9204370000

NoteSwitchMark markers white
MultiCard, white

Type	Qty.	Order No.
SM 27/18 MC NE WS	80	1699860000
ESG 9/11 K MC NE WS	200	1857440000

Type	Qty.	Order No.
SM 27/18 MC NE WS	80	1699860000
ESG 9/11 K MC NE WS	200	1857440000

Holder

Type	Qty.	Order No.
SM-H 27/18 SW	25	1716630000

Type	Qty.	Order No.
SM-H 27/18 SW	25	1716630000

USB cable 2.00.5 m
1.0 m
1.5 m
1.8 m
3.0 m

Type	Qty.	Order No.
IE-USB-A-A-0.5M	1	1993550005
IE-USB-A-A-1.0M	1	1993550010
IE-USB-A-A-1.5M	1	1993550015
IE-USB-A-A-1.8M	1	1993550018
IE-USB-A-A-3.0M	1	1993550030

Type	Qty.	Order No.
IE-USB-A-A-0.5M	1	1993550005
IE-USB-A-A-1.0M	1	1993550010
IE-USB-A-A-1.5M	1	1993550015
IE-USB-A-A-1.8M	1	1993550018
IE-USB-A-A-3.0M	1	1993550030

USB cable 3.00.5 m
1.8 m
3.0 m
5.0 m

Type	Qty.	Order No.
IE-USB-3.0-A-A-0.5M	1	2581730005
IE-USB-3.0-A-A-1.8M	1	2581730018
IE-USB-3.0-A-A-3M	1	2581730030
IE-USB-3.0-A-A-5M	1	2581730050

Type	Qty.	Order No.
IE-USB-3.0-A-A-0.5M	1	2581730005
IE-USB-3.0-A-A-1.8M	1	2581730018
IE-USB-3.0-A-A-3M	1	2581730030
IE-USB-3.0-A-A-5M	1	2581730050

Note

IP67 plug-in connectors

Overview


IP67 plug-in connectors	N.2
PushPull V14 - RJ45	
PushPull V14 - Hybrid	N.7
PushPull V14 - FO	N.10
Bayonet V1 Metal-RJ45	N.12
Bayonet V1 Metal-FO	N.14
Bayonet V1 Plastic-RJ45	N.16
PushPull V4 - RJ45	N.19
PushPull V4 - FO	N.23
RockStar® V5 - RJ45	N.25
SnapIn V6 - RJ45	N.27
M8 Single Pair Ethernet	N.30
M12 D-coded	N.32
M12 X-Type	N.41
Inserts	N.49
PushPull Power	N.60

Plug PushPull V14 - RJ45 PROFINET

- 4-wire, RJ45 plug field attachable with colour coding on the plug

**4-wire, field-attachable**

PROFINET printing

**4-wire, crimp****Technical data****Category**

Protection degree

Housing main material

Contact surface

Sheath diameter, min. / max.

Plugging cycles

Ambient temperature (operational)

Connector standard

Connection diameter, flexible, min. / max.

Connection cross-section, flexible, min. / max.

Connection diameter, solid, min. / max.

Connection cross-section, solid, min. / max.

Approvals

Note

Cat.5 (ISO/IEC 11801)

IP67

Zinc diecast

Gold over nickel

5 mm / 10 mm

750

-40 °C...70 °C

IEC 61076-3-117 Var. 14, IEC 60603-7-51

0.48 mm / 0.76 mm

AWG 26 / AWG 22

0.4 mm / 0.64 mm

AWG 24 / AWG 22

CULUS

Other approvals for individual parts of the set available

Cat.5 (ISO/IEC 11801)

IP67

Zinc diecast

Gold over nickel

5 mm / 10 mm

750

-40 °C...70 °C

IEC 60603-7, IEC 61076-3-117 Var. 14

0.57 mm / 0.64 mm

AWG 23 / AWG 22

0.57 mm / 0.64 mm

AWG 23 / AWG 22

Ordering data - Sets

RJ45 tool-free

Qty. Order No.

IE-PS-V14M-RJ45-FH-P 10 1012170000

Note

Qty. Order No.

IE-PS-V14M-RJ45-TH-P 10 2768740000

Ordering data - Empty housings**Note**

Type Qty. Order No.

IE-PH-V14M-RJ 10 1011560000

Type Qty. Order No.

IE-PH-V14M-RJ 10 1011560000

Accessories**Dust protection cap**

Protective cap

Type Qty. Order No.

IE-PP-V14P 10 1058280000

Marking tags

MultiCard, white

Type Qty. Order No.

IE-PP-V14P 10 1058280000

Plug insert for V14 PROFINET crimp

Replacement crimp inserts

Type Qty. Order No.

IE-PI-RJ45-TH-P 10 2768720000

Tools

Pressing tool

Type Qty. Order No.


IE-CWZ-RJ45-TH-P 1 2614210000

Note

Plug inserts can also be ordered separately. Refer to Inserts.

Plug PushPull V14 - RJ45

- 8-wire, RJ45 plug field attachable with colour coding on the plug

8-wire, crimp**Technical data**

Category
Protection degree
Housing main material
Contact surface
Sheath diameter, min. / max.
Plugging cycles
Ambient temperature (operational)
Connector standard
Connection diameter, flexible, min. / max.
Connection cross-section, flexible, min. / max.
Connection diameter, solid, min. / max.
Connection cross-section, solid, min. / max.
Approvals

Cat.6A / Class E_A (ISO/IEC 11801 2010)

IP67

zinc diecast

Gold over nickel

5 mm / 10 mm

750

-40 °C...70 °C

IEC 61076-3-117 Var. 14, IEC 60603-7-51

0.46 mm / 0.61 mm

AWG 27/7 / AWG 24/7

0.36 mm / 0.51 mm

AWG 26/1 / AWG 24/1

EAC

Note**Ordering data - Sets**

RJ45 tool-free

Note

Type	Qty.	Order No.
IE-PS-V14M-RJ45-TH	10	1012160000

Ordering data - Empty housings**Note**

Type	Qty.	Order No.
IE-PH-V14M-RJ	10	1011560000

Accessories

Dust protection cap	Protective cap
Marking tags	MultiCard, white
Tools	Pressing tool

Type	Qty.	Order No.
IE-PP-V14P	10	1058280000
ESG 9/11 K MC NE WS	200	1857440000
TT 8 RS MP 8	1	9202800000

Note

Plug inserts can also be ordered separately. Refer to Inserts.

PushPull V14 - RJ45 flange Module




4-wire

PROFINET printing



Standardised flange



8-wire


TIA-A



Standardised flange



Central flange



Technical data

Category

Protection degree

Housing main material

Contact surface

Sheath diameter, min. / max.

Plugging cycles

Ambient temperature (operational)

Connector standard

Connection diameter, flexible, min. / max.

Connection cross-section, flexible, min. / max.

Connection diameter, solid, min. / max.

Connection cross-section, solid, min. / max.

Approvals

Note

Ordering data - Sets

Standardised flange
Central flange

Note

Ordering data - Empty housings

Standardised flange
Central flange
Device flange

Note

Accessories

Dust protection cap

Protective cap

Note

Cat.5 (ISO/IEC 11801)

IP67

Zinc diecast

Gold over nickel

5 mm / 10 mm

750

-40 °C...70 °C

IEC 61076-3-117 Var. 14, IEC 60603-7-51

0.48 mm / 0.76 mm

AWG 26 / AWG 22

0.4 mm / 0.64 mm

AWG 24 / AWG 22

CULUS

Other approvals for individual parts of the set available

Cat.6A / Class E_A (ISO/IEC 11801 2010)

IP67

Zinc diecast

Gold over nickel

5 mm / 10 mm

750

-40 °C...70 °C

IEC 61076-3-117 Var. 14, IEC 60603-7-51

0.48 mm

AWG 26 / AWG 22

0.4 mm / 0.64 mm

AWG 24 / AWG 22

CULUS

Other approvals for individual parts of the set available

Type

Qty.

Order No.

IE-BSS-V14M-RJ45-FJ-P

10

1085260000

Type

Qty.

Order No.

IE-BSS-V14M-RJ45-FJ-A

10

1012320000

IE-BSC-V14M-RJ45-FJ-A

10

1058270000

Type

Qty.

Order No.

IE-BHS-V14M-RJA

10

1011540000

IE-BHC-V14M-RJA

10

1047950000

IE-BHD-V14M

10

1047940000

Type

Qty.

Order No.

IE-BHS-V14M-RJA

10

1011540000

IE-BHC-V14M-RJA

10

1047950000

IE-BHD-V14M

10

1047940000

Type

Qty.

Order No.

IE-BP-V14P

10

1058310000

Type

Qty.

Order No.

IE-BP-V14P

10

1058310000


Note

Plug inserts can also be ordered separately. Refer to Inserts.

Plug inserts can also be ordered separately, see Inserts

PushPull V14 - RJ45 flange Coupling

8-wire



Technical data

Category	Cat.6A / Class E _A (ISO/IEC 11801 2010)
Protection degree	IP67
Housing main material	Zinc diecast
Contact surface	Gold over nickel
Sheath diameter, min. / max.	5 mm / 10 mm
Plugging cycles	750
Ambient temperature (operational)	-40 °C...70 °C
Connector standard	IEC 61076-3-117 Var. 14, IEC 60603-7-51
Connection diameter, flexible, min. / max.	
Connection cross-section, flexible, min. / max.	
Connection diameter, solid, min. / max.	
Connection cross-section, solid, min. / max.	
Approvals	

Note

Other approvals for individual parts of the set available

Ordering data - Sets

Standardised flange	
Central flange	

Note

Type	Qty.	Order No.
IE-BSS-V14M-RJ45-C	10	1012310000
IE-BSC-V14M-RJ45-C	10	1058250000

Ordering data - Empty housings

Standardised flange	
Central flange	
Device flange	

Note

Type	Qty.	Order No.
IE-BHS-V14M-RJA	10	1011540000
IE-BHC-V14M-RJA	10	1047950000
IE-BHD-V14M	10	1047940000

Accessories

Dust protection cap

Protective cap



Type	Qty.	Order No.
IE-BP-V14P	10	1058310000

Note

Plug inserts can also be ordered separately. Refer to Inserts.

Flange-mounted empty housing /**PushPull device flange****V14**

- IP 67

Empty housing**Device flange****Technical data****Category**

Protection degree

Housing main material

Contact surface

Sheath diameter, min. / max.

Plugging cycles

Ambient temperature (operational)

Connector standard

Connection diameter, flexible, min. / max.

Connection cross-section, flexible, min. / max.

Connection diameter, solid, min. / max.

Connection cross-section, solid, min. / max.

Approvals

Note**Ordering data**

Standardised flange
Central flange
Device flange

Note**Accessories****Dust protection cap**

Protective cap

Type	Qty.	Order No.
IE-BHS-V14M-RJA	10	1011540000
IE-BHC-V14M-RJA	10	1047950000

Type	Qty.	Order No.
IE-BHD-V14M	10	1047940000


Type	Qty.	Order No.
IE-BP-V14P	10	1058310000

Type	Qty.	Order No.
IE-BP-V14P	10	1058310000

Note

Plug inserts can also be ordered separately. Refer to Inserts.

Plug inserts can also be ordered separately. Refer to Inserts.

Plug PushPull V14 - Hybrid**Hybrid**
**Technical data****Category**

Protection degree

Housing main material

Contact surface

Sheath diameter, min. / max.

Plugging cycles

Ambient temperature (operational)

Connection 1 / 2

Connector standard

Connection cross-section, flexible, min. / max.

Connection diameter, flexible, min. / max.

Rated current (hybrid connector)

Volume resistance

Approvals

Note**Cat.5 (ISO/IEC 11801)**

IP67

Zinc diecast

Gold over nickel

5 mm / 10 mm

500

-40 °C...70 °C

Hybrid (Q10) / Crimp

IEC 61076-3-119 CDV, IEC 61076-3-117 Var. 14

AWG 27 / AWG 20

0.08 mm² / 0.75 mm²

3 A per contact

<10 mΩ

CULUS

Other approvals for individual parts of the set available

Ordering data - Sets**Note**

Type	Qty.	Order No.
IE-PS-V14M-HYB-10P	10	1072910000

Order contacts separately

Ordering data - Empty housings**Note**

Type	Qty.	Order No.
IE-PH-V14M-RJ	10	1011560000

Accessories**Crimping contact**0.08...0.2 mm²0.2...0.5 mm²0.75 mm²

Type	Qty.	Order No.
IE-PIC-HYB-S-0,2-300	300	1135150000
IE-PIC-HYB-S-0,5-300	300	1096180000
IE-PIC-HYB-S-0,75-300	300	1068950000

Tools

Pressing tool

Type	Qty.	Order No.
HTF HYB	1	1119580000

Cable

Hybrid cable, 100 m

Hybrid cable, 500 m

Type	Qty.	Order No.
IE-C5DHAG-100	1	2763660000
IE-C5DHAG-500	1	2763460000

Dust protection cap

Protective cap

Type	Qty.	Order No.
IE-PP-V14P	10	1058280000

Marking tags

MultiCard, white


Type	Qty.	Order No.
ESG 9/11 K MC NE WS	200	1857440000

Note

Plug inserts can also be ordered separately. Refer to Inserts.

Flange PushPull V14 - Hybrid

Standardised flange



Technical data

Category
Protection degree
Housing main material
Seal material
Contact surface
Sheath diameter, min. / max.
Plugging cycles
Ambient temperature (operational)
Connection 1 / 2
Connector standard
Connection cross-section, flexible, min. / max.
Connection diameter, flexible, min. / max.
Rated current (hybrid connector)
Volume resistance
Approvals

Note

Cat.5 (ISO/IEC 11801)
IP67
Zinc diecast
EPDM
Gold over nickel
5 mm / 10 mm
500
-40 °C...70 °C
Hybrid (Q10) / Crimp
IEC 61076-3-119 CDV, IEC 61076-3-117 Var. 14
AWG 27 / AWG 20
0.08 mm ² / 0.75 mm ²
3 A per contact
<10 mΩ
CULUS

Other approvals for individual parts of the set available

Ordering data - Sets

Note

Type	Qty.	Order No.
IE-BSS-V14M-HYB-10P-FJ	10	1072900000
Order contacts separately		

Ordering data - Empty housings

Standardised flange

Note

Type	Qty.	Order No.
IE-BHS-V14M-RJA	10	1011540000

Accessories

Crimping contact

0.08...0.2 mm²
0.2...0.5 mm²
0.75 mm²

Tools

Pressing tool

Cable

Hybrid cable



Dust protection cap

Protective cap

Type	Qty.	Order No.
IE-BIC-HYB-P-0,2-300	300	1135160000
IE-BIC-HYB-P-0,5-300	300	1096150000
IE-BIC-HYB-P-0,75-300	300	1068970000
HTF HYB	1	1119580000
IE-C5DHAG-MW	110 M	1172250000
IE-BP-V14P	10	1058310000

Note

Plug inserts can also be ordered separately. Refer to Inserts.

V14 flange adapter**Straight****Angled****Technical data**

Protection degree
Housing main material
Seal material
Type of mounting
Ambient temperature (operational)

Note

IP67
Zinc diecast
EPDM
2 screws, M3 (not included)
-40...70 °C

IP67
Zinc diecast
EPDM
2 screws, M3 (not included)
-40...70 °C

Ordering data**Note**

Type	Qty.	Order No.
IE-AD-BHS-V14M-RJA	1	1302000000

Flange and plug inserts must be ordered separately, see Inserts/Flanges

Type	Qty.	Order No.
IE-BHS-V14M-RJA-45	10	1296710000

Flange inserts must be ordered separately, see Inserts

Accessories

Type	Qty.	Order No.



Note

PushPull V14 plug - fibre-optic

Without kink prevention, crimp



Without kink prevention, reconnectable



Technical data

Protection degree
Housing main material
Sheath diameter, min. / max.
Plugging cycles
Ambient temperature (operational)
Connector standard
Approvals

Note

IP67
Zinc diecast
5 mm / 10 mm
750
-40...70 °C
IEC 61076-3-117 Var. 14, IEC 61754-24
CULUS

IP67
Zinc diecast
5 mm / 10 mm
750
-40...70 °C
IEC 61076-3-117 Var. 14, IEC 61754-24

Ordering data - Sets

	POF
Note	

Type	Qty.	Order No.
IE-PS-V14M-2SC-POF	10	1191550000

Type	Qty.	Order No.
IE-PS-V14M-2SC-POF-QA	10	2568260000

Ordering data - Empty housings

Note	

Type	Qty.	Order No.
IE-PH-V14M-F0	10	1058100000

Type	Qty.	Order No.
IE-PH-V14M-F0	10	1058100000

Accessories

Inserts	POF
Dust protection cap	Protective cap
Tools	Tool set POF, crimp Mounting tool, POF MULTI-STRIPAX IE-POF Cevlar scissors
Replacement ferrule	
Marking tags	MultiCard, white

Type	Qty.	Order No.
IE-PI-SCRJ-POF	10	1067410000
IE-PP-V14P	10	1058280000
TOOL SET IE-POF	1	1208930000
HTX-IE-POF	1	1208870000
MULTI-STRIPAX IE-POF	1	1208880000
SCISSORS KEVLAR	1	1208910000
IE-SCRJ-IP67-POF-100	100	1278430000
ESG 9/11 K MC NE WS	200	1857440000

Type	Qty.	Order No.
IE-PI-SCRJ-POF-QA	10	2564960000
IE-PP-V14P	10	1058280000
HTX-IE-POF-QA	1	2602860000
MULTI-STRIPAX IE-POF	1	1208880000
SCISSORS KEVLAR	1	1208910000
ESG 9/11 K MC NE WS	200	1857440000

Note


Plug inserts can also be ordered separately, see Inserts

Flange PushPull V14 - fibre-optic**SC-RJ**

Standardised flange



Central flange

**Technical data**

Protection degree

Housing main material

Plugging cycles

Ambient temperature (operational)

Insertion loss

Connector standard

Approvals

Note**Ordering data - Sets**

Central flange Singlemode
Standardised flange Singlemode
Central flange Multimode/POF
Standardised flange Multimode/POF

Note**Ordering data - Empty housings**

Device flange

Note**Accessories**

Dust protection cap

Protective cap

Type	Qty.	Order No.
IE-BSC-V14M-SCRJ-SM-C	10	1062600000
IE-BSS-V14M-SCRJ-SM-C	10	1058140000
IE-BSC-V14M-SCRJ-MM-C	10	1062590000
IE-BSS-V14M-SCRJ-MM-C	10	1058120000

Type	Qty.	Order No.
IE-BSC-V14M-LCD-SM-C	10	1062620000
IE-BSS-V14M-LCD-SM-C	10	1058150000
IE-BSC-V14M-LCD-MM-C	10	1062610000
IE-BSS-V14M-LCD-MM-C	10	1058130000

Note

Plug inserts can also be ordered separately. Refer to Inserts.



Plug inserts can also be ordered separately. Refer to Inserts.

Plug bayonet V1 Metal - RJ45

Without kink prevention



With kink prevention



Technical data

Category

Protection degree

Housing main material

Contact surface

Sheath diameter, min. / max.

Plugging cycles

Ambient temperature (operational)

Connection cross-section, flexible, min. / max.

Connection diameter, flexible, min. / max.

Connection cross-section, solid, min. / max.

Connection diameter, solid, min. / max.

Connector standard

Approvals

Note

Cat.6_A / Class E_A (ISO/IEC 11801 2010)

IP67

Zinc diecast

Gold over nickel

5 mm / 10 mm

750

-40 °C...70 °C

AWG 26 / AWG 22

0.48 mm / 0.76 mm

AWG 24 / AWG 22

0.4 mm / 0.64 mm

IEC 61076-3-106 Var. 1, IEC 60603-7-51

CULUS

Cat.6_A / Class E_A (ISO/IEC 11801 2010)

IP67

Zinc diecast

Gold over nickel

5 mm / 10 mm

750

-40 °C...70 °C

AWG 26 / AWG 22

0.48 mm / 0.76 mm

AWG 24 / AWG 22

0.4 mm / 0.64 mm

IEC 61076-3-106 Var. 1, IEC 60603-7-51

CULUS

Ordering data - Sets

RJ45 without tools. AWG 26-22. TIA-A/B-/PROFINET
RJ45 Crimp. AWG 27-24

Note

Type	Qty.	Order No.
IE-PS-V01M-RJ45-FH	10	1963120000
IE-PS-V01M-RJ45-TH	10	1963140000

Type	Qty.	Order No.
IE-PS-V01M-RJ45-FH-BP	10	1963130000
IE-PS-V01M-RJ45-TH-BP	10	1963150000

Ordering data - Empty housings

Note

Type	Qty.	Order No.
IE-PH-V01M	10	1962550000

Type	Qty.	Order No.
IE-PH-V01M-BP	10	1962560000

Accessories

Dust protection cap

Plug housing protective cap

Marking tags

MultiCard, white

Type	Qty.	Order No.
IE-PP-V01P	10	1965690000
ESG 9/11 K MC NE WS	200	1857440000

Type	Qty.	Order No.
IE-PP-V01P	10	1965690000
ESG 9/11 K MC NE WS	200	1857440000

Note

Plug inserts can also be ordered separately. Refer to Inserts.

Plug inserts can also be ordered separately. Refer to Inserts.



Flange bayonet V1 Metal - RJ45

Module

TIA-A



Coupling



Technical data

Category	Cat.6A / Class E _A (ISO/IEC 11801 2010)
Protection degree	IP67
Housing main material	Zinc diecast
Contact surface	Gold over nickel
Plugging cycles	750
Ambient temperature (operational)	-40 °C...70 °C
Connector standard	IEC 61076-3-106 Var. 1, IEC 60603-7-51
Connection cross-section, flexible, min. / max.	AWG 26 / AWG 22
Connection diameter, flexible, min. / max.	0.48 mm / 0.76 mm
Connection cross-section, solid, min. / max.	AWG 24 / AWG 22
Connection diameter, solid, min. / max.	0.4 mm / 0.64 mm
Approvals	CULUS
Note	

Cat.6A / Class E_A (ISO/IEC 11801 2010)

IP67

Zinc diecast

Gold over nickel

750

-40 °C...70 °C

IEC 61076-3-106 Var. 1, IEC 60603-7-51

AWG 26 / AWG 22

0.48 mm / 0.76 mm

AWG 24 / AWG 22

0.4 mm / 0.64 mm

CULUS

Ordering data - Sets

Type	Qty.	Order No.
IE-BS-V01M-RJ45-FJ-A	10	1963480000

Type	Qty.	Order No.
IE-BS-V01M-RJ45-C	10	1963470000

Ordering data - Empty housings

Type	Qty.	Order No.
IE-BH-V01M	10	1963540000


Type	Qty.	Order No.
IE-BH-V01M	10	1963540000

Accessories

Dust protection cap	Type	Qty.	Order No.
Flange-mounted housing protective cap	IE-BP-V01P	10	1965700000

Dust protection cap	Type	Qty.	Order No.
Flange-mounted housing protective cap	IE-BP-V01P	10	1965700000

Note	Plug inserts can also be ordered separately. Refer to Inserts.	Plug inserts can also be ordered separately. Refer to Inserts.
------	--	--

Flange bayonet V1 metal - fibre-optic-SC**Standardised flange****Technical data**

Protection degree

Housing main material

Plugging cycles

Ambient temperature (operational)

Connector standard

Approvals

Note**Ordering data - Sets**Singlemode
Multimode/POF**Note**

Type	Qty.	Order No.
IE-BS-V01M-SCRJ-SM	10	1221020000
IE-BS-V01M-SCRJ-MM	10	1221010000

Ordering data - Empty housings**Note**

Type	Qty.	Order No.
IE-BHD-V01M-SCA	10	1221030000

Accessories**Dust protection cap**

Flange-mounted housing protective cap

Note


Type	Qty.	Order No.
IE-BP-V01P	10	1965700000

Note

Plug inserts can also be ordered separately. Refer to Inserts.

Flange bayonet V1 metal - fibre-optic-LC

Standardised flange



Technical data

Protection degree
Housing main material
Plugging cycles
Ambient temperature (operational)
Connector standard
Approvals

IP67
Zinc diecast
500
-40 °C...70 °C
IEC 61076-3-106 Var. 1, IEC 61754-20

Note

Ordering data - Sets

Singlemode
Multimode

Type	Qty.	Order No.
IE-BS-V01M-LCD-SM-C	10	1963430000
IE-BS-V01M-LCD-MM-C	10	1964440000

Note

Ordering data - Empty housings

Type	Qty.	Order No.
IE-BH-V01M	10	1963540000

Accessories

Dust protection cap

Flange-mounted housing protective cap

Type	Qty.	Order No.
IE-BP-V01P	10	1965700000

Note



Plug inserts can also be ordered separately. Refer to Inserts.

Plug bayonet V1 Plastic - RJ45

Without kink prevention



With kink prevention



Technical data

Category

Cat.6_A / Class E_A (ISO/IEC 11801 2010)

Protection degree

IP67

Housing main material

PA UL 94 VO

Contact surface

Gold over nickel

Sheath diameter, min. / max.

5 mm / 10 mm

Plugging cycles

750

Ambient temperature (operational)

-40 °C...70 °C

Connection cross-section, flexible, min. / max.

AWG 26 / AWG 22

Connection diameter, flexible, min. / max.

0.48 mm / 0.76 mm

Connection cross-section, solid, min. / max.

AWG 24 / AWG 22

Connection diameter, solid, min. / max.

0.4 mm / 0.64 mm

Connector standard

IEC 61076-3-106 Var. 1, IEC 60603-7-51

Approvals

CULUS

Note

Ordering data - Sets

RJ45 without tools. AWG 26-22. TIA-A/B-/PROFINET
RJ45 Crimp. AWG 27-24

Type	Qty.	Order No.
IE-PS-V01P-RJ45-FH	10	1012490000
IE-PS-V01P-RJ45-TH	10	1012470000

Type	Qty.	Order No.
IE-PS-V01P-RJ45-FH-BP	10	1012570000
IE-PS-V01P-RJ45-TH-BP	10	1012560000

Ordering data - Empty housings

Note

Type	Qty.	Order No.
IE-PH-V01P	10	1012440000

Type	Qty.	Order No.
IE-PH-V01P-BP	10	1012460000

Accessories

Dust protection cap

Plug housing protective cap

Type	Qty.	Order No.
IE-PP-V01P	10	1965690000

Type	Qty.	Order No.
IE-PP-V01P	10	1965690000

Marking tags

MultiCard, white

ESG 9/11 K MC NE WS	200	1857440000
---------------------	-----	------------

ESG 9/11 K MC NE WS	200	1857440000
---------------------	-----	------------



Note

Plug inserts can also be ordered separately. Refer to Inserts.

Plug inserts can also be ordered separately. Refer to Inserts.

Flange bayonet V1 Plastic - RJ45**Module**

TIA-A

**Coupling****Technical data**

Category	Cat.6A / Class E _A (ISO/IEC 11801 2010)
Protection degree	IP67
Housing main material	PA UL 94 VO
Contact surface	Gold over nickel
Plugging cycles	750
Ambient temperature (operational)	-40 °C...70 °C
Connector standard	IEC 61076-3-106 Var. 1, IEC 60603-7-51
Connection cross-section, flexible, min. / max.	AWG 26 / AWG 22
Connection diameter, flexible, min. / max.	0.48 mm / 0.76 mm
Connection cross-section, solid, min. / max.	AWG 24 / AWG 22
Connection diameter, solid, min. / max.	0.4 mm / 0.64 mm
Approvals	CULUS

Note**Ordering data - Sets**

Type	Qty.	Order No.
IE-BS-V01P-RJ45-FJ-A	10	1012380000

Type	Qty.	Order No.
IE-BS-V01P-RJ45-C	10	1012370000

Ordering data - Empty housings

Type	Qty.	Order No.
IE-BH-V01P	10	1016960000

Type	Qty.	Order No.
IE-BH-V01P	10	1016960000

Accessories

Dust protection cap	Type	Qty.	Order No.
Flange-mounted housing protective cap	IE-BP-V01P	10	1965700000

Type	Qty.	Order No.
IE-BP-V01P	10	1965700000


Note

Plug inserts can also be ordered separately. Refer to Inserts.

Plug inserts can also be ordered separately. Refer to Inserts.

Cable coupling bayonet V1 Plastic - RJ45

Cable coupling



Technical data

Protection degree
Housing main material
Plugging cycles
Ambient temperature (operational)
Connector standard
Sheath diameter, min. / max.
Approvals

Note

Ordering data

Variant 1

Cable coupling

Note

Type	Qty.	Order No.
IE-CC-V01P	10	1061820000

RJ45 modules can be ordered separately



Accessories

Inserts, Data

RJ45 module EIA/TIA T568 B
RJ45 module PROFINET
RJ45 module EIA/TIA T568 A

Type	Qty.	Order No.
IE-BI-RJ45-FJ-B	10	1963840000
IE-BI-RJ45-FJ-P	10	1963830000
IE-BI-RJ45-FJ-A	10	1962850000

Note

Plug PushPull V4 - RJ45**Without kink prevention****With kink prevention****Technical data**

Category
Protection degree
Housing main material
Contact surface
Sheath diameter, min. / max.
Plugging cycles
Ambient temperature (operational)
Connection cross-section, flexible, min. / max.
Connection diameter, flexible, min. / max.
Connection cross-section, solid, min. / max.
Connection diameter, solid, min. / max.
Connector standard
Approvals

Note**Ordering data - Sets**

RJ45 without tools. AWG 26-22. TIA-A/B-/PROFINET
RJ45 without tools. AWG 26-22 . TIA-B
RJ45 Crimp. AWG 27-24

Note**Ordering data - Empty housings****Note****Accessories****Dust protection cap**

Plug housing protective cap

Marking tags

MultiCard, white

Cat.6A / Class E_A (ISO/IEC 11801 2010)

IP67

PA UL 94 VO

Gold over nickel

5 mm / 10 mm

750

-40 °C...70 °C

AWG 27/7 / AWG 24/7

0.46 mm / 0.61 mm

AWG 26/1 / AWG 24/1

0.36 mm / 0.51 mm

IEC 61076-3-106 Var. 4, IEC 60603-7-51

CULUS

Cat.6A / Class E_A (ISO/IEC 11801 2010)

IP67

PA UL 94 VO

Gold over nickel

5 mm / 10 mm

750

-40 °C...70 °C

AWG 27/7 / AWG 24/7

0.46 mm / 0.61 mm

AWG 26/1 / AWG 24/1

0.36 mm / 0.51 mm

IEC 61076-3-106 Var. 4, IEC 60603-7-51

CULUS

Type	Qty.	Order No.
IE-PS-V04P-RJ45-FH	10	1963160000
IE-PS-V04P-RJ45-FH-B	10	1271240000
IE-PS-V04P-RJ45-TH	10	1963180000

Type	Qty.	Order No.
IE-PS-V04P-RJ45-FH-BP	10	1963170000
IE-PS-V04P-RJ45-TH-BP	10	1963190000

Type	Qty.	Order No.
IE-PH-V04P	10	1962520000

Type	Qty.	Order No.
IE-PH-V04P-BP	10	1962530000

Type	Qty.	Order No.
IE-PP-V04P	10	1963890000
ESG 9/11 K MC NE WS	200	1857440000

Type	Qty.	Order No.
IE-PP-V04P	10	1963890000

Note

Plug inserts can also be ordered separately. Refer to Inserts.



Plug inserts can also be ordered separately. Refer to Inserts.

Flange PushPull V4 - RJ45

Module



Coupling



Technical data

Category
Protection degree
Housing main material
Contact surface
Plugging cycles
Ambient temperature (operational)
Connector standard
Connection cross-section, flexible, min. / max.
Connection diameter, flexible, min. / max.
Connection cross-section, solid, min. / max.
Connection diameter, solid, min. / max.
Approvals

Note

Cat.6A / Class E_A (ISO/IEC 11801 2010)

IP67

PA UL 94 VO

Gold over nickel

750

-40 °C...70 °C

IEC 61076-3-106 Var. 4, IEC 60603-7-51

AWG 26 / AWG 22

0.48 mm

AWG 24 / AWG 22

0.4 mm / 0.64 mm

CULUS

Cat.6A / Class E_A (ISO/IEC 11801 2010)

IP67

PA UL 94 VO

Gold over nickel

750

-40 °C...70 °C

IEC 61076-3-106 Var. 4, IEC 60603-7-51

CULUS

Ordering data - Sets

RJ45 module TIA-A
RJ45 module TIA-B
Coupling

Type	Qty.	Order No.
IE-BS-V04P-RJ45-FJ-A	10	1963500000
IE-BS-V04P-RJ45-FJ-B	10	1963730000

Note

Other approvals for individual parts of the set available

Type	Qty.	Order No.
IE-BS-V04P-RJ45-C	10	1963490000

Ordering data - Empty housings

Empty enclosure
Device flange

Type	Qty.	Order No.
IE-BH-V04P	10	1963520000
IE-BHD-V04P	200	2027660000

Type	Qty.	Order No.
IE-BH-V04P	10	1963520000
IE-BHD-V04P	200	2027660000

Accessories

Dust protection cap	Flange-mounted housing protective cap
Marking tags	MultiCard, white
Fixing tool	


Type	Qty.	Order No.
IE-BP-V04P	10	1963900000
ESG 9/11 K MC NE WS	200	1857440000
IE-FISP-V4	2	9204370000

Type	Qty.	Order No.
IE-BP-V04P	10	1963900000
ESG 9/11 K MC NE WS	200	1857440000
IE-FISP-V4	2	9204370000

Note

Plug inserts can also be ordered separately. Refer to Inserts.

Plug inserts can also be ordered separately. Refer to Inserts.

Cable coupling PushPull V4 - RJ45**Cable coupling****Technical data**

Protection degree
Housing main material
Plugging cycles
Ambient temperature (operational)
Connector standard
Sheath diameter, min. / max.
Approvals

Note

IP67
PA UL 94 VO
750
-40 °C...70 °C
IEC 61076-3-106 Var. 4
6 mm / 9.5 mm

Ordering data

Cable coupling

Note

Type	Qty.	Order No.
IE-CC-V04P	10	1045960000

RJ45 modules can be ordered separately

Accessories**Inserts, Data**

RJ45 module EIA/TIA T568 B
RJ45 module PROFINET
RJ45 module EIA/TIA T568 A

Marking tags

MultiCard, white



Type	Qty.	Order No.
IE-BI-RJ45-FJ-B	10	1963840000
IE-BI-RJ45-FJ-P	10	1963830000
IE-BI-RJ45-FJ-A	10	1962850000
ESG 9/11 K MC NE WS	200	1857440000

Note

Plug inserts can also be ordered separately. Refer to Inserts.

**Flange-mounted empty housing /
PushPull V4 device flange**

- IP 67

**Empty housing****Device flange****Technical data**

Protection degree
Housing main material
Plugging cycles
Ambient temperature (operational)
Connector standard
Sheath diameter, min. / max.
Approvals

Note**Ordering data**

Empty enclosure
Device flange

Note**Accessories**

Dust protection cap
Flange-mounted housing protective cap
Marking tags
MultiCard, white
Fixing tool

IP67
PA UL 94 VO
750
-40 °C...70 °C
IEC 61076-3-106 Var. 4
5 mm / 10 mm
CULUS

Type	Qty.	Order No.
IE-BH-V04P	10	1963520000

IP67
PA UL 94 VO
40 °C...70 °C
IEC 61076-3-106 Var. 4


CULUS

Type	Qty.	Order No.
IE-BHD-V04P	200	2027660000

Type	Qty.	Order No.
IE-BP-V04P	10	1963900000
ESG 9/11 K MC NE WS	200	1857440000
IE-FISP-V4	2	9204370000

Note

Plug inserts can also be ordered separately. Refer to Inserts.

Flange PushPull V4 - fibre-optic-SC**Standardised flange****Technical data**

Protection degree
Housing main material
Plugging cycles
Ambient temperature (operational)
Connector standard
Approvals

IP67
PA UL 94 VO
500
-40 °C...70 °C
IEC 61076-3-106 Var. 4, IEC 61754-4, IEC 61754-24

Note**Ordering data - Sets**

Singlemode
Multimode

Type	Qty.	Order No.
IE-BS-V04P-SCRJ2SC-SM-C	10	1963420000
IE-BS-V04P-SCRJ2SC-MM-C	10	1964470000

Note**Ordering data - Empty housings**

Empty enclosure

Type	Qty.	Order No.
IE-BH-V04P	10	1963520000

Note**Accessories**

Dust protection cap
Flange-mounted housing protective cap
Marking tags
MultiCard, white
Fixing tool


Type	Qty.	Order No.
IE-BP-V04P	10	1963900000
ESG 9/11 K MC NE WS	200	1857440000
IE-FISP-V4	2	9204370000

Note

Plug inserts can also be ordered separately. Refer to Inserts.

Flange PushPull V4 - fibre-optic-LC

Standardised flange



Technical data

Protection degree

Housing main material

Plugging cycles

Ambient temperature (operational)

Connector standard

Approvals

Note

Ordering data - Sets

Singlemode
Multimode

Type	Qty.	Order No.
IE-B5-V04P-LCD-SM-C	10	1963450000
IE-B5-V04P-LCD-MM-C	10	1964460000

Note

Ordering data - Empty housings

Empty enclosure

Type	Qty.	Order No.
IE-BH-V04P	10	1963520000

Note

Accessories

Dust protection cap

Flange-mounted housing protective cap

Marking tags

MultiCard, white

Fixing tool

Type	Qty.	Order No.
IE-BP-V04P	10	1963900000
ESG 9/11 K MC NE WS	200	1857440000
IE-FISP-V4	2	9204370000

Note



Plug inserts can also be ordered separately. Refer to Inserts.

**RockStar® heavy-duty connector plug
V5 - RJ45**

Straight V5 - RJ45 plug



V5-RJ45 plug, angled



Technical data

Category

Protection degree

Housing main material

Contact surface

Sheath diameter, min. / max.

Plugging cycles

Ambient temperature (operational)

Connector standard

Approvals

Note

Cat.6A / Class E_A (ISO/IEC 11801 2010)

IP67

diecast aluminium

Gold over nickel

5 mm / 12 mm

750

-40 °C...70 °C

IEC 61076-3-106 Var. 5, IEC 60603-7-51

CULUS

Cat.6A / Class E_A (ISO/IEC 11801 2010)

IP67

diecast aluminium

Gold over nickel

5 mm / 10 mm

750

-40 °C...70 °C

IEC 61076-3-106 Var. 5, IEC 60603-7-51

EAC

Other approvals for individual parts of the set available

Ordering data - Sets

RJ45 without tools, AWG 26-22, TIA-A/B-/PROFINET
RJ45 without tools, AWG 26-22 . TIA-B
RJ45 Crimp, AWG 27-24

Note

Type	Qty.	Order No.
IE-PS-V05M-RJ45-FH	10	1963200000
IE-PS-V05M-RJ45-FH-B	10	1271250000
IE-PS-V05M-RJ45-TH	10	1963110000

Type	Qty.	Order No.
IE-PS-V05M-A-RJ45-FH	10	1077300000

Ordering data - Empty housings

Note

Type	Qty.	Order No.
IE-PH-V05M	10	1962540000

Type	Qty.	Order No.
IE-PH-V05M	10	1962540000

Accessories

Dust protection cap

Plug housing protective cap
Spare insert holder



Type	Qty.	Order No.
IE-PP-V05M	1	1968920000
IE-PP-AD-V05M-RJ45	1	1993540000

Type	Qty.	Order No.
IE-PP-V05M	1	1968920000

Note

Plug inserts can also be ordered separately. Refer to Inserts.

Plug inserts can also be ordered separately. Refer to Inserts.

**RockStar® heavy-duty connector flange
V5 - RJ45**
Module**Coupling****Technical data**

Protection degree

Housing main material

Contact surface

Plugging cycles

Ambient temperature (operational)

Connector standard

Connection cross-section, flexible, min. / max.

Connection diameter, flexible, min. / max.

Connection cross-section, solid, min. / max.

Connection diameter, solid, min. / max.

Approvals

Note**Ordering data - Sets**

TIA-A Cat. 6_A
PROFINET Cat. 5
Coupling

Note

Type	Qty.	Order No.
IE-BS-V05M-RJ45-FJ-A	10	1963460000
IE-BS-V05M-RJ45-FJ-P	10	1963700000

Type	Qty.	Order No.
IE-BS-V05M-RJ45-C	10	1963510000

Ordering data - Empty housings**Note**

Type	Qty.	Order No.
IE-BH-V05M	10	1963530000

Type	Qty.	Order No.
IE-BH-V05M	10	1963530000

Accessories

Dust protection cap

Flange-mounted housing protective cap

Type	Qty.	Order No.
IE-BP-V05M	10	1968930000

Type	Qty.	Order No.
IE-BP-V05M	10	1968930000


Note

Plug inserts can also be ordered separately. Refer to Inserts.

Plug inserts can also be ordered separately. Refer to Inserts.

Plug SnapIn V6 - RJ45

- Cat. 6
- IP 67

Without kink prevention**Technical data**

Category
Protection degree
Shielding
Housing main material
Contact surface
Colour
Plugging cycles
Wiring
Type of mounting
Ambient temperature (operational)
Connector standard
Approvals

Note

Cat.6_A / Class E_A (ISO/IEC 11801 2010)
IP67
360° shield contact
PA 66, UL 94: V-0
Gold over nickel
Light Grey
750
EIA/TIA T568 A
Floor-mounted, for exposed connections, Wall mounting
40 °C...70 °C
IEC 61076-3-106 Var. 6, IEC 60603-7-5
DNVGL

Ordering data

Note

Type	Qty.	Order No.
IE-P-IP67	1	8808380000

Accessories

Plug-in connector



Type	Qty.	Order No.
IE-PM-RJ45-TH	100	1963580000

Note

See also the "Accessories" chapter.

Flange SnapIn V6 - RJ45

- Cat. 6
- IP 67

Module**Coupling****Technical data**

N

Category
Protection degree
Shielding
Housing main material
Contact surface
Colour
Plugging cycles
Type of mounting
Wiring

Ambient temperature (operational)
Connector standard
Approvals

Note**Ordering data**

straight
angled. upwards
angled. downwards

Note**Accessories****Flange insert**

RJ45 module A, straight
RJ45 coupling, straight

Cat.6 (ISO/IEC 11801)

IP67

360° shield contact

PA 66, UL 94: V-0

Gold over nickel

Light Grey

750

Cabinet, Distribution box

Colour-coded pin assignment according to
EIA/TIA T568 A., EIA/TIA T568 B

-40 °C...70 °C

IEC 61076-3-106 Var. 6, IEC 60603-7-5

DNVGL

Cat.6 (ISO/IEC 11801)

IP67

360° shield contact

PA 66, UL 94: V-0

Gold over nickel

Light Grey

750

Cabinet, Distribution box

40 °C...70 °C

IEC 61076-3-106 Var. 6, IEC 60603-7-5

DNVGL



Type	Qty.	Order No.
IE-XM-RJ45/IDC-IP67	1	8808440000

Type	Qty.	Order No.
IE-XM-RJ45/RJ45-IP67	1	8808450000
IE-XM-6U-RJ45/RJ45-IP67	1	8829440000
IE-XM-6D-RJ45/RJ45-IP67	1	8829450000

Type	Qty.	Order No.
IE-XRJ45/IDC	1	8808330000

Type	Qty.	Order No.
IE-XR-RJ45/RJ45-2	24	8952950000

Note**Note****Note**

Single Pair Ethernet, M8 empty housing**M8 front wall mounting****M8 rear wall mounting****Technical data**

Category
Ambient temperature (operational)
Protection degree
Housing main material
Seal material
Configuration
Type of mounting
Connection thread
Connector standard
Tightening torque fixing nut

Note

-40...85 °C
IP67
Brass, nickel-plated
FKM
Frontpanel mounting
Screw mounting
M10 x 0.75
IEC 61076-2-104
2.5 Nm

40...85 °C
IP67
Brass, nickel-plated
FKM
Backpanel mounting
Screw mounting
M10 x 0.75
IEC 61076-2-104
2.5 Nm

Ordering data**Note**

Type	Qty.	Order No.
IE-BHD-SPE-M8-OT-FP	10	2726020000

Inserts must be ordered separately.

Type	Qty.	Order No.
IE-BHD-SPE-M8-OT-BP	20	2726030000



Inserts must be ordered separately.

Accessories**Fastening nut**

Type	Qty.	Order No.
IE-BHD-SPE-FP-CN-M10X0.75	10	2739640000

Type	Qty.	Order No.
IE-BHD-SPE-FP-CN-M10X0.75	10	2739640000

Note

PCB insert**M8 insert 180° pin contacts****M8 insert 90° pin contacts****Technical data**

Category	T1-B
Ambient temperature (operational)	-40...85 °C
Protection degree	IP67
Pollution severity	2
Connection thread	M8
Number of poles	2
Type of connection	Solder connection, Male contact
Outgoing elbow	180°
Contact material	Copper alloy
Contact surface	Ni/Au
Contact carrier material	LCP
Operational voltage range	≤ 50 V AC, ≤ 60 V DC
Insulation strength	≥ 500 MO
Dielectric strength, contact / contact	1000 V DC
Dielectric strength, contact / shield	2250 V DC
Connector standard	IEC 63171-5
UL 94 flammability rating	V-0

Note

Ordering data

THR	
SMD	

Note

Accessories

Type	Qty.	Order No.
IE-PCB-SPM-P-180-THR	100	2735920000
IE-PCB-SPM-P-180-SMD	100	2795110000

Type

Type	Qty.	Order No.
IE-PCB-SPM-P-90-THR	100	2795100000
IE-PCB-SPM-P-90-SMD	100	

Type

Type	Qty.	Order No.
IE-PCB-SPM-P-90-THR	100	2795100000
IE-PCB-SPM-P-90-SMD	100	

Type

Type	Qty.	Order No.
IE-PCB-SPM-P-90-THR	100	2795100000

Type

Note

**M12 plug,
Tension-clamp connection,
D-coded**

**SAISM / SAIBM**

Straight

**SAISW / SAIBW**

angled

**Ordering data**

Male	4-pole. PG 9
Female	4-pole. PG 9
Note	

Type	Qty.	Order No.
SAISM-4/8S-M12 4P D-ZF	1	1892120001
SAIBM-4/8S-M12 4P D-ZF	1	1892130001



Type	Qty.	Order No.
SAISW-4/8S-M12 4P D-ZF	1	1803930001
SAIBW-4/8S-M12 4P D-ZF	1	1139330000

Technical data


Type of connection	Tension-clamp connection
Housing main material	CuZn
Ambient temperature (operational)	-40 °C...
Connector standard	IEC 61076-2-101
Connection thread	M12
Cable diameter	6..8 mm (PG9)
Conductor cross-section min. / max.	0.25 mm ² / 0.5 mm ²
Rated current	4
Rated voltage	250
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Gold-plated
Note	

Type of connection	Tension-clamp connection
Housing main material	CuZn
Ambient temperature (operational)	-40 °C...
Connector standard	IEC 61076-2-101
Connection thread	M12
Cable diameter	6..8 mm (PG9)
Conductor cross-section min. / max.	0.25 mm ² / 0.5 mm ²
Rated current	4
Rated voltage	250
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Gold-plated
Note	

Type of connection	Tension-clamp connection
Housing main material	CuZn
Ambient temperature (operational)	-40 °C...
Connector standard	IEC 61076-2-101
Connection thread	M12
Cable diameter	6..8 mm (PG9)
Conductor cross-section min. / max.	0.25 mm ² / 0.5 mm ²
Rated current	4
Rated voltage	250
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Gold-plated
Note	

Dimensioned drawing**Dimensioned drawing**

**M12 plug,
Screw connection,
D-coded**



SAISM / SAIBM

Straight



Ordering data

Male	4-pole. PG 9
Female	4-pole. PG 9
Note	


Type	Qty.	Order No.
SAISM-4/8S-M12-4P D-COD	1	1892120000
SAIBM-4/8S-M12-4P D-COD	1	1892130000

Technical data


Type of connection	
Housing main material	
Ambient temperature (operational)	-40 °C...85 °C
Connector standard	IEC 61076-2-101
Connection thread	M12
Cable diameter	6..8 mm (PG9)
Conductor cross-section min. / max.	0.25 mm ² / 0.75 mm ²
Rated current	4
Rated voltage	250
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Gold-plated
Note	

Screw connection	
CuZn	
-40 °C...85 °C	
IEC 61076-2-101	
M12	
6..8 mm (PG9)	
0.25 mm ² / 0.75 mm ²	
4	
250	
-40 ... +85 °C	
IP67	
Gold-plated	

Dimensioned drawing



**PUSH IN M12
with shield connection
D coded**



SAISP / SAIBP

Straight



SAISWP / SAIBWP

Angled



Ordering data

Male	D-coded, 4-pole
Female	D-coded, 4-pole
Note	Other versions on request

Type	Qty.	Order No.
SAISP-M-4D-4/8-M12	1	2681680000
SAIBP-M-4D-4/8-M12	1	2681700000

Type	Qty.	Order No.
SAISWP-M-4D-4/8-M12	1	2681690000
SAIBWP-M-4D-4/8-M12	1	2681710000


Technical data

Type of connection	PUSH IN
Housing main material	PA 66
Connection thread	M12
Cable diameter	4...8 mm
Conductor cross-section min. / max.	0.14...0.75 mm ²
Rated current	4 A
Rated voltage	250 V
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Ni/Au
Note	


Type of connection	PUSH IN
Housing main material	PA 66
Connection thread	M12
Cable diameter	4...8 mm
Conductor cross-section min. / max.	0.14...0.75 mm ²
Rated current	4 A
Rated voltage	250 V
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Ni/Au
Note	

Type of connection	PUSH IN
Housing main material	PA 66
Connection thread	M12
Cable diameter	4...8 mm
Conductor cross-section min. / max.	0.14...0.75 mm ²
Rated current	4 A
Rated voltage	250 V
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Ni/Au
Note	

Dimensioned drawing



Dimensioned drawing



**Crimp connection M12
with shield connection
D-coded**



SAISC / SAIBC

straight



SAISC / SAIBC

Panel feed-through



Ordering data

Male	4-pole
Female	4-pole
Note	

Type	Qty.	Order No.
SAISC-D-18/28-4/9CG	1	2664810000
SAIBC-D-18/28-4/9CG	1	2672420000

Type	Qty.	Order No.
SAISC-WDF-D-18/28-4/9CG	1	2664790000
SAIBC-WDF-D-18/28-4/9CG	1	2664780000


Technical data

Type of connection	Crimp connection
Housing main material	CuZn
Connection thread	M12
Cable diameter	4...9 mm
Conductor cross-section min. / max.	0.08...0.75 mm ²
Rated current	4 A
Rated voltage	50 V
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Gold-plated
Note	


Type of connection	Crimp connection
Housing main material	CuZn
Connection thread	M12
Cable diameter	4...9 mm
Conductor cross-section min. / max.	0.08...0.75 mm ²
Rated current	4 A
Rated voltage	50 V
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Gold-plated
Note	

Type of connection	Crimp connection
Housing main material	CuZn
Connection thread	M12
Cable diameter	4...9 mm
Conductor cross-section min. / max.	0.08...0.75 mm ²
Rated current	4 A
Rated voltage	50 V
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Gold-plated
Note	


Dimensioned drawing



Dimensioned drawing



**Crimp connection M12
with shield connection
D-coded**



SAISC / SAIBC

angled



Ordering data

Male	4-pole
Female	4-pole
Note	


Type	Qty.	Order No.
SAISWC-D-18/28-4/9CG	1	2702690000
SAIBWC-D-18/28-4/9CG	1	2702700000

Technical data

Type of connection	Crimp connection
Housing main material	CuZn
Connection thread	M12
Cable diameter	4...9 mm
Conductor cross-section min. / max.	0.08...0.75 mm ²
Rated current	4 A
Rated voltage	50 V
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Gold-plated
Note	

Type of connection	Crimp connection
Housing main material	CuZn
Connection thread	M12
Cable diameter	4...9 mm
Conductor cross-section min. / max.	0.08...0.75 mm ²
Rated current	4 A
Rated voltage	50 V
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Gold-plated
Note	

Dimensioned drawing



Crimp contact M12



SAI - KSC / KBC

straight



Ordering data

Male	Type	Qty.	Order No.
AWG 18-20	SAI-M12-KSC-18/20	100	2664840000
AWG 20-22	SAI-M12-KSC-20/22	100	2664850000
AWG 22-24	SAI-M12-KSC-22/24	100	2673710000
AWG 26-28	SAI-M12-KSC-26/28	100	2673720000



Female	Type	Qty.	Order No.
AWG 18-20	SAI-M12-KBC-18/20	100	2664860000
AWG 20-22	SAI-M12-KBC-20/22	100	2664870000
AWG 22-24	SAI-M12-KBC-22/24	100	2673730000
AWG 26-28	SAI-M12-KBC-26/28	100	2673740000

Technical data

Type of connection	
Housing main material	
Connection thread	
Cable diameter	
Conductor cross-section min. / max.	
Rated current	7 A
Rated voltage	
Temperature range of housing	
Protection degree	
Contact surface	Gold-plated

Adapter / coupling M12

- Cat. 5
 - IP67
 - D-coding

**Adapter M12-RJ45, female****Adapter M12-RJ45, male****Technical data**

N
Category
Protection degree
Housing main material
Shielding
Ambient temperature (operational)
Connector standard
Approvals

Note**Ordering data**

Adaptor	Type	Qty.	Order No.
	IE-M12-ADAP S	1	8901620000
	IE-M12-ADAP A	1	8901630000

Coupling	Type	Qty.	Order No.

Note	Type	Qty.	Order No.

Accessories

Type	Qty.	Order No.


Category	IP67	PA 66	Yes	-25 °C...80 °C	IEC 60603-7-5, IEC 61076-2-101	CULUS

Category	IP67	PA 66	Yes	-25 °C...80 °C	IEC 60603-7-5, IEC 61076-2-101	CULUS

Note

Adapter / coupling M12

- Cat. 5
 - IP67
 - D-coding

Coupling M12-M12**Technical data**

Category
Protection degree
Housing main material
Shielding
Ambient temperature (operational)
Connector standard
Approvals

Note

Cat.5 (ISO/IEC 11801)

IP67

Polyamide, Brass, nickel-plated

360° shield contact

-5 °C...60 °C

IEC 61076-2-101

EAC

Ordering data**Adaptor**

straight
angled



Coupling**Note****Accessories**

Type	Qty.	Order No.
IE-M12-COUP	1	8901640000

Note

M12 PCB connection element

- Cat. 5
- For installation into the end device
- D-coded

Standard assembly**Additional fastening mechanism****Technical data****N**
Category

Protection degree

Configuration

Housing main material

Shielding

Ambient temperature (operational)

Connector standard

Approvals

Note**Ordering data****Connection element**straight
angled**Note****Accessories****Cat.5 (ISO/IEC 11801)**

IP65 in acc. with DIN EN 60529

Reflow compatible

CuZn, Polyamide, nickel-plated

360° shield contact

-25...85 °C

IEC 61076-2-101

EAC

Type **Qty.** **Order No.**

IE-M12-PCBCE 60 8902810000

Cat.5 (ISO/IEC 11801)

IP65 in acc. with DIN EN 60529

Reflow compatible

CuZn, Polyamide, nickel-plated

360° shield contact

-25...85 °C

IEC 61076-2-101




EAC

Type **Qty.** **Order No.**

IE-M12-PCBCE-PANEL 10 8902820000

IE-M12-PCBCE-PANEL-A 10 1393470000

Type **Qty.** **Order No.****Type** **Qty.** **Order No.****Note****Note****Note**

M12 plug**M12 X-type Cat. 6_A****Plug, AWG 26-22****Plug, AWG 27-22****Technical data**

Category	Cat.6 _A / Class E _A (ISO/IEC 11801 2010)
Protection degree	IP67
Connection 1 / 2	M12 / Insulation displacement technology
Housing main material	Zinc diecast
Connection thread	M12
Contact material / Contact surface	Brass / Gold-plated
Ambient temperature (operational)	-40 °C...85 °C
Connector standard	IEC 61076-2-109
Current-carrying capacity at 50 °C	0.5 A @ 40 °C
Rated voltage	48 V
Insulation strength	100 MΩ
Plugging cycles	≥ 100
Configuration	
Wall thickness, min. / max.	360° all-round enclosure
Shielding	0.48 mm / 0.76 mm
Connection diameter, flexible, min. / max.	AWG 26/7 / AWG 22/7
Connection cross-section, flexible, min. / max.	0.41 mm / 0.64 mm
Connection diameter, solid, min. / max.	AWG 26/1 / AWG 22/1
Connection cross-section, solid, min. / max.	1.6 mm
Insulation cross-section, max.	5 mm / 9.7 mm
Sheath diameter min. / max.	CULUS
Approvals	

Note**Ordering data**

Plugs
Note

Type	Qty.	Order No.
IE-PS-M12X-P-FH	10	1324020000

Type	Qty.	Order No.
IE-PS-M12X-P-AWG22/27FH	1	2007500000

Accessories

Note

Type	Qty.	Order No.

Type	Qty.	Order No.

Note



M12 plug / flange

M12 X-type Cat. 6A

Plug, female



Flange



Technical data

Category

Cat.6A / Class E_A (ISO/IEC 11801 2010)

Protection degree

IP67

Connection 1 / 2

M12 / Insulation displacement technology

Housing main material

Zinc diecast

Connection thread

M12

Contact material / Contact surface

Brass / Gold-plated

Ambient temperature (operational)

-40 °C...85 °C

Connector standard

IEC 61076-2-109

Current-carrying capacity at 50 °C

0.5 A @ 40 °C

Rated voltage

48 V

Insulation strength

100 MΩ

Plugging cycles

≥ 100

Configuration

360° all-round enclosure

Wall thickness, min. / max.

0.48 mm / 0.76 mm

Shielding

AWG 26 / AWG 22

Connection diameter, flexible, min. / max.

0.4 mm / 0.64 mm

Connection diameter, solid, min. / max.

AWG 24 / AWG 22

Connection cross-section, solid, min. / max.

1.6 mm

Insulation cross-section, max.

5 mm / 9.7 mm

Sheath diameter min. / max.

CULUS

Approvals

Note

Ordering data

Plugs

Note

Type	Qty.	Order No.
IE-PS-M12X-S-FH	1	1516330000

Accessories

Tools

Tool set

Tool set with torque function

Cable gland tool, M 12

Cable gland tool with torque function, M 12

Type	Qty.	Order No.
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12 F	1	1900020000
SCREWTY-M12 F-DM	1	1900021000

Type	Qty.	Order No.
IE-BS-M12X-S-FH	1	1516340000

Type	Qty.	Order No.
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12 F	1	1900020000
SCREWTY-M12 F-DM	1	1900021000

Note

**Crimp connection M12
with shield connection
X-Type**



SAISC / SAIBC

angled



SAISC / SAIBC

straight



Ordering data

Male	8-pole
Female	8-pole
Note	

Type	Qty.	Order No.
IE-PS-M12X-180-P-TH	1	2664820000
IE-PS-M12X-180-S-TH	1	2672440000

Type	Qty.	Order No.
IE-PS-M12X-90-P-TH	1	2702710000
IE-PS-M12X-90-S-TH	1	2702720000


Technical data

Type of connection	Crimp connection
Housing main material	CuZn
Connection thread	M12
Cable diameter	4...9 mm
Conductor cross-section min. / max.	0.14...0.34 mm ²
Rated current	4 A
Rated voltage	50 V
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Gold-plated
Note	


Type of connection	Crimp connection
Housing main material	CuZn
Connection thread	M12
Cable diameter	4...9 mm
Conductor cross-section min. / max.	0.14...0.34 mm ²
Rated current	4 A
Rated voltage	50 V
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Gold-plated
Note	

Type of connection	Crimp connection
Housing main material	Cu alloy Ni plated
Connection thread	M12
Cable diameter	4...9 mm
Conductor cross-section min. / max.	0.14...0.34 mm ²
Rated current	2 A
Rated voltage	30 V
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Gold-plated
Note	

Dimensioned drawing



Dimensioned drawing



**Crimp connection M12
with shield connection
X-Type**

SAISC / SAIBC

Panel feed-through, straight



SAISC / SAIBC

Panel feed-through, angled



Ordering data

Male	8-pole, Back panel mounting
Female	8-pole, Back panel mounting
Note	

Type	Qty.	Order No.
IE-BS-M12X-180-P-TH	1	2747880000
IE-BS-M12X-180-S-TH		2747900000

Type	Qty.	Order No.
IE-BS-M12X-90-P-TH	1	2747910000
IE-BS-M12X-90-S-TH		2747920000


Technical data

Type of connection	Crimp connection
Housing main material	CuZn
Connection thread	M12
Cable diameter	4...9 mm
Conductor cross-section min. / max.	0.14...0.34 mm ²
Rated current	4 A
Rated voltage	50 V
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Gold-plated
Note	


Type of connection	Crimp connection
Housing main material	CuZn
Connection thread	M12
Cable diameter	4...9 mm
Conductor cross-section min. / max.	0.14...0.34 mm ²
Rated current	4 A
Rated voltage	50 V
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Gold-plated
Note	

Type of connection	Crimp connection
Housing main material	CuZn
Connection thread	M12
Cable diameter	4...9 mm
Conductor cross-section min. / max.	0.14...0.34 mm ²
Rated current	4 A
Rated voltage	50 V
Temperature range of housing	-40 ... +85 °C
Protection degree	IP67
Contact surface	Gold-plated
Note	

Dimensioned drawing



Dimensioned drawing



**Crimp contact M12
X-Type**



SAI - KSC / KBC



Ordering data




Male	AWG 22-26
Female	AWG 22-26
Note	

Type	Qty.	Order No.
IE-PIC-M12X-P-22/26	100	2664880000
IE-PIC-M12X-S-22/26	100	2673440000

Technical data

Type of connection	
Housing main material	
Connection thread	
Cable diameter	
Conductor cross-section min. / max.	
Rated current	
Rated voltage	
Temperature range of housing	
Protection degree	
Contact material	
Note	

0.34...0.14 mm ²	
1 A	
Copper alloy, Gold-plated	

M12 X-Type**Adapter / Coupling M12
M12 X-type Cat. 6_A****Adapter M12 X-Type-RJ45****Coupling M12 X-Type****Technical data**

Category	Cat.6 _A / Class E _A (ISO/IEC 11801 2010)
Protection degree	IP67
Connection 1 / 2	RJ45 / M12
Housing main material	Zinc diecast
Connection thread	M12
Contact material / Contact surface	Copper alloy / Gold-plated
Ambient temperature (operational)	-25 °C...85 °C
Connector standard	IEC 61076-2-109, IEC 60603-7-51
Current-carrying capacity at 50 °C	50 V
Rated voltage	100 MΩ
Insulation strength	≥ 100 (M12), 750 (RJ45)
Plugging cycles	M12 socket to RJ45 socket
Configuration	0.9 mm / 3 mm
Wall thickness, min. / max.	360° shield contact
Shielding	
Connection diameter, flexible, min. / max.	
Connection cross-section, flexible, min. / max.	
Connection diameter, solid, min. / max.	
Connection cross-section, solid, min. / max.	
Insulation cross-section, max.	
Sheath diameter min. / max.	
Approvals	CULUS

Note**Ordering data**


Adapter 90°	Type	Qty.	Order No.
Adapter 180°	IE-AD-M12XRJ45-90	10	1400610000
Coupling	IE-AD-M12XRJ45-180	1	1400620000

Note**Accessories**

Type	Qty.	Order No.
IE-BS-M12X-S-C	1	2731010000

Type	Qty.	Order No.
IE-BS-M12X-S-C	1	2731010000

Note

PCB socket**M12 X-type Cat. 6_A****PCB socket****PCB socket, back panel mounting****Technical data****Category**

Protection degree

Connection 1 / 2

Housing main material

Connection thread

Contact material / Contact surface

Ambient temperature (operational)

Connector standard

Current-carrying capacity at 50 °C

Rated voltage

Insulation strength

Plugging cycles

Configuration

Wall thickness, min. / max.

Shielding

Approvals

Note**Ordering data**pre-assembled
2-part version**Note****Accessories****Cat.6_A / Class E_A (ISO/IEC 11801 2010)**

IP67, when screwed in

M12 / Solder connection

CuZn

M12

CuZn / Gold over nickel

-40 °C...85 °C

IEC 61076-2-109

0.5 A @ 40 °C

48 V

100 MΩ

≥ 100

Reflow compatible

0.9 mm / 2.5 mm

360° all-round enclosure

CULUS

Cat.6_A / Class E_A (ISO/IEC 11801 2010)

IP67, when screwed in

M12 / Solder connection

CuZn

M12

CuZn / Gold over nickel

-40 °C...85 °C

IEC 61076-2-109

0.5 A @ 40 °C

48 V

100 MΩ

≥ 100

Reflow compatible, Back panel mounting

0.9 mm / 2.5 mm

360° all-round enclosure

CULUS


Type	Qty.	Order No.
IE-PCB-M12X-S-180	10	1324010000
IE-PCB2-M12X-S-180	10	1393080000

Type	Qty.	Order No.
IE-PCBR-M12X-S-180	10	1427670000
IE-PCBR2-M12X-S-180	10	1444650000

Type	Qty.	Order No.

Type	Qty.	Order No.

Note

PCB socketM12 X-type Cat. 6_A**PCB socket, angled****Technical data****N**
CategoryCat.6_A / Class E_A (ISO/IEC 11801 2010)

Protection degree

IP67, when screwed in

Connection 1 / 2

M12 / Solder connection

Housing main material

CuZn

Connection thread

M12

Contact material / Contact surface

CuZn / Gold over nickel

Ambient temperature (operational)

-40 °C...85 °C

Connector standard

IEC 61076-2-109

Current-carrying capacity at 50 °C

0.5 A @ 40 °C

Rated voltage

48 V

Insulation strength

100 MΩ

Plugging cycles

≥ 100

Configuration

Reflow compatible

Wall thickness, min. / max.

1 mm / 2.5 mm

Shielding

360° all-round enclosure

Approvals

CULUS

Note**Ordering data**pre-assembled
2-part version

Type	Qty.	Order No.
IE-PCB-M12X-S-90	10	2168220000



Note**Accessories**

Type	Qty.	Order No.

Note

RJ45 plug inserts, tool free

- Cat. 6_A
- IP 20
- For housing variants 1, 4, 5 and 14

8-wire**4-wire****Technical data**

Category

Protection degree

Plugging cycles

Shielding

Housing main material

Contact material

Contact surface

Connection cross-section, flexible, min. / max.

Connection diameter, flexible, min. / max.

Connection cross-section, solid, min. / max.

Connection diameter, solid, min. / max.

Wire connection cross-section, finely stranded

Insulation diameter, min. / max.

Humidity

Ambient temperature (operational)

Insulation strength

Contact resistance

Dielectric strength, contact / contact

Dielectric strength, contact / shield

Current-carrying capacity at 50 °C

PoE / PoE+

Speed

Connector standard

Approvals

NoteCat.6_A / Class E_A (ISO/IEC 11801 2010)

IP67 with housing

750

360° all-round enclosure

Zinc diecast

Gold over nickel, Au ≥ 0.8 µm

AWG 26 / AWG 22

0.48 mm / 0.76 mm

AWG 24 / AWG 22

0.4 mm / 0.64 mm

Approval of the cable by Weidmüller necessary

0.85 mm...1.6 mm

-40 °C...70 °C

500 MΩ

≤ 20 mΩ

≥ 1000 V DC

≥ 1500 V DC

1 A

conforming to IEEE 802.3at

10 GBit/s

IEC 60603-7-51

CULUS; CURUS

Approvals available on request

Cat.5 (ISO/IEC 11801)

IP67 with housing

750

360° all-round enclosure

Zinc diecast

Gold over nickel, Au ≥ 0.8 µm

AWG 26 / AWG 22

0.48 mm / 0.76 mm

AWG 24 / AWG 22

0.4 mm / 0.64 mm

Approval of the cable by Weidmüller necessary

0.85 mm...1.6 mm

-40 °C...70 °C

500 MΩ

≤ 20 mΩ

≥ 1000 V DC

≥ 1500 V DC

1 A

conforming to IEEE 802.3at

100 MBit/s

IEC 60603-7-51

CULUS; CURUS

Ordering data

tool-free

TIA-A/B/PROFINET

TIA-A

TIA-B

PROFINET

Note

Type	Qty.	Order No.
IE-PI-RJ45-FH	10	1962730000
IE-PI-RJ45-FH-A	10	1132010000
IE-PI-RJ45-FH-B	10	1132020000

Type	Qty.	Order No.
IE-PI-RJ45-FH-P	10	1132030000

Accessories

Tools

Optional pressing tool


Type	Qty.	Order No.
PWZ RJ45	1	1118040000

Type	Qty.	Order No.
PWZ RJ45	1	1118040000

Note

RJ45 plug inserts, crimp

- Cat. 6_A
- IP 20
- For housing variants 1, 4, 5 and 14

8-wire**Technical data****N**
CategoryCat.6_A / Class E_A (ISO/IEC 11801 2010)

Protection degree

IP67 with housing

Plugging cycles

750

Shielding

360° all-round enclosure

Housing main material

Brass, PC UL 94 VO

Contact material

Phosphorus bronze

Contact surface

Gold over nickel, Au ≥ 0.8 µm, Ni 2.54 µm

Connection cross-section, flexible, min. / max.

AWG 27/7 / AWG 24/7

Connection diameter, flexible, min. / max.

0.46 mm / 0.61 mm

Connection cross-section, solid, min. / max.

AWG 26/1 / AWG 24/1

Connection diameter, solid, min. / max.

0.4 mm / 0.51 mm

Insulation diameter, min. / max.

0.85 mm...1.05 mm

Humidity

0...93 % rel. humidity

Ambient temperature (operational)

-40 °C...70 °C

Insulation strength

500 MΩ

Contact resistance

≤ 20 mΩ

Dielectric strength, contact / contact

≥ 1000 V DC

Dielectric strength, contact / shield

≥ 1500 V DC

Current-carrying capacity at 50 °C

1 A

PoE / PoE+

conforming to IEEE 802.3af

Speed

IEC 60603-7-51

Connector standard

CURUS

Approvals

Note**Ordering data****Crimp**

Type	Qty.	Order No.
IE-PI-RJ45-TH	10	1962720000

Note**Accessories****Tools**

Pressing tool

Type	Qty.	Order No.
TT 8 RS MP 8	1	9202800000

Note



RJ45 flange inserts, module

- Completely in Cat. 6_A
- IP20
- For housing variants 1, 4, 5, 14 and for FrontCom®

8-wire



4-wire



Technical data

Category

Protection degree

Plugging cycles

Shielding

Housing main material

Contact surface

Connection cross-section, flexible, min. / max.

Connection cross-section, solid, min. / max.

Insulation diameter, min. / max.

Connector standard

Ambient temperature (operational)

PoE / PoE+

Approvals

Note

Ordering data

tool-free

TIA-A. Cat. 6_A

TIA-B. Cat. 6_A

PROFINET Cat. 5

Note

Accessories

Tools

Optional pressing tool

Cat.6_A / Class E_A (ISO/IEC 11801 2010)

IP67 with housing

750

360° all-round enclosure

Zinc diecast

Gold over nickel, Au ≥ 0.8 µm

AWG 26 / AWG 22

AWG 24 / AWG 22

0.85 mm...1.6 mm

IEC 60603-7-51

-40 °C...70 °C

conforming to IEEE 802.3af

CULUS

Note: Connection of WM Cat. 7 AWG 27/7 LSZH possible

Cat.5 (ISO/IEC 11801)

IP67 with housing

750

360° all-round enclosure

Zinc diecast

Gold over nickel, Au ≥ 0.8 µm

AWG 26 / AWG 22

AWG 24 / AWG 22

0.85 mm...1.6 mm

IEC 60603-7-51

-40 °C...70 °C

conforming to IEEE 802.3af

CULUS; DNVGL

Type

Qty.

Order No.

IE-BI-RJ45-FJ-A 10 1962850000

IE-BI-RJ45-FJ-B 10 1963840000

Type

Qty.

Order No.

IE-BI-RJ45-FJ-P 10 1963830000

Type

Qty.

Order No.

PWZ RJ45 1 1118040000

Type

Qty.


Order No.

PWZ RJ45 1 1118040000

Note

RJ45 flange inserts, coupling

- Completely in Cat. 6_A
- IP20
- For housing variants 1, 4, 5, 14 and for FrontCom®

8-wire**Technical data**

Category

Protection degree

Plugging cycles

Shielding

Housing main material

Contact surface

Connection cross-section, flexible, min. / max.

Connection cross-section, solid, min. / max.

Insulation diameter, min. / max.

Connector standard

Ambient temperature (operational)

PoE / PoE+

Approvals

NoteCat.6_A / Class E_A (ISO/IEC 11801 2010)

IP67 with housing

750

360° all-round enclosure

Zinc diecast

Gold over nickel, Au ≥ 0.8 µm

...

IEC 60603-7-51

-40 °C...70 °C

conforming to IEEE 802.3af

CULUS; DNVGL

Ordering data

tool-free


Coupling

Note**Type** **Qty.** **Order No.**IE-BI-RJ45-C 10 **1962840000****Accessories****Type** **Qty.** **Order No.****Note**

Plug inserts Hybrid

- Cat. 5
- IP 20
- For housing variants 1 (metal) and 14

Crimp



Technical data

Category
Protection degree
Plugging cycles
Shielding
Housing main material
Contact surface
Number of poles
Connection cross-section, flexible, min. / max.
Connection diameter, flexible, min. / max.
Insulation diameter, min. / max.
Ambient temperature (operational)
Volume resistance
Rated current
Rated voltage
Contact resistance
Approvals

Cat.5 (ISO/IEC 11801)
IP67 with housing
500
360° all-round enclosure
Nickel silver, PA 66
Gold over nickel
10
AWG 27 / AWG 20
0.08 mm² / 0.75 mm²
1 mm...2.2 mm
-40 °C...70 °C
<10 mΩ
3 A per contact
24 V
≤ 5 mΩ
CULUS

Note

Ordering data

Note

Accessories

Crimping contact

0.08...0.2 mm²
0.2...0.5 mm²
0.75 mm²

Tools

Pressing tool

Type	Qty.	Order No.
IE-PI-HYB-10P	10	1068990000

Contacts should be ordered separately

Type	Qty.	Order No.
IE-PIC-HYB-S-0,2-300	300	1135150000
IE-PIC-HYB-S-0,5-300	300	1096180000
IE-PIC-HYB-S-0,75-300	300	1068950000

HTF HYB	1	1119580000
---------	---	------------

Note

Flange inserts Hybrid

- Cat. 5
- IP 20
- For housing variants 1 (metal) and 14

Module**Technical data**

N

Category
Protection degree
Plugging cycles
Shielding
Housing main material
Contact surface
Number of poles
Connection cross-section, flexible, min. / max.
Connection diameter, flexible, min. / max.
Insulation diameter, min. / max.
Rated current
Rated voltage
Contact resistance
Volume resistance
Ambient temperature (operational)
Approvals

Cat.5 (ISO/IEC 11801)
IP67 with housing
500
360° all-round enclosure
Zinc diecast, Nickel silver, PA 66
Gold over nickel
10
AWG 27 / AWG 20
0.08 mm ² / 0.75 mm ²
1 mm...2.2 mm
3 A per contact
24 V
≤ 10 mΩ
<10 mΩ
-40 °C...70 °C
CULUS

Note**Ordering data****Note**

Type	Qty.	Order No.
IE-BI-HYB-10P	10	1069010000
Contacts should be ordered separately		

Accessories**Crimping contact**

0.08...0.2 mm²
0.2...0.5 mm²
0.75 mm²

Tools



Pressing tool

Type	Qty.	Order No.
IE-BIC-HYB-P-0,2-300	300	1135160000
IE-BIC-HYB-P-0,5-300	300	1096150000
IE-BIC-HYB-P-0,75-300	300	1068970000
HTF HYB	1	1119580000

Note

Flange inserts USB

- IP20
- For housing variants 1, 4, 5, 14 and for FrontCom®

Coupling USB A/A**Coupling USB A/B****Technical data**

Protection degree
Shielding
Ambient temperature (operational)
Connection 1 / 2
Connector standard
Approvals

Note**Ordering data**

USB 2.0	
USB 3.0	

Note**Accessories****USB cable 2.0**

0.5 m
1.0 m
1.5 m
1.8 m
3.0 m

USB cable 3.0

0.5 m
1.8 m
3.0 m
5.0 m

IP67 with housing
360° all-round enclosure
-40 °C...70 °C
USB A / USB A
IEC 61076-3-107
CULUS, DNVGL

Type	Qty.	Order No.
IE-BI-USB-A	10	1019570000
IE-BI-USB-3.0-A	10	1487920000

IP67 with housing
360° all-round enclosure
-40 °C...70 °C
USB A / USB B
IEC 61076-3-107
CULUS, DNVGL

Type	Qty.	Order No.
IE-BI-USB-AB	10	1131380000

Type	Qty.	Order No.
IE-USB-A-A-0.5M	1	1993550005
IE-USB-A-A-1.0M	1	1993550010
IE-USB-A-A-1.5M	1	1993550015
IE-USB-A-A-1.8M	1	1993550018
IE-USB-A-A-3.0M	1	1993550030
IE-USB-3.0-A-A-0.5M	1	2581730005
IE-USB-3.0-A-A-1.8M	1	2581730018
IE-USB-3.0-A-A-3M	1	2581730030
IE-USB-3.0-A-A-5M	1	2581730050

Note

Plug inserts SC

- IP 20
 - For variant 1, 4 and 14 housings

Plug insert SC, POF

only for V14



Technical data

- Protection degree
- Housing main material
- Plugging cycles
- Ambient temperature (operational)
- Connector standard
- Approvals

Ordering data

POF

Accessories

Tools	Tool set POF, crimp Mounting tool, POF MULTI-STRIPAX IE-POF Cevilar scissors
-------	---

Replacement ferrule

IP67 with housing
Zinc diecast, PA
1000
-40 °C..70 °C
IEC 61754-24
UL

IP67 with housing
PA 66
≥ 500
-40 °C...70 °C
IEC 61754-24

Type	Qty.	Order No.
IE-PI-SCRJ-POF	10	1067410000
Type	Qty.	Order No.
TOOL SET IE-POF	1	1208930000
HTX-IE-POF	1	1208870000
MULTI-STRIPAX IE-POF	1	1208880000
SCISSORS KEVLAR	1	1208910000
IE-SCRJ-100-7-POF-100	100	1278420000


Type	Qty.	Order No.
IE-PI-SCRJ-POF-QA	10	2564960000
Type	Qty.	Order No.
HTX-IE-POF-QA	1	2602860000
MULTI-STRIPAX IE-POF	1	1208880000
SCISSORS KEVLAR	1	1208910000

Note

Flange inserts SC

- IP 20
- SC-RJ on 2 SC
- For variant 1, 4 and 14 housings

Flange inserts SC



Technical data

Protection degree
Housing main material
Plugging cycles
Ambient temperature (operational)
Approvals

IP67 with housing
PA
1000
-40 °C...70 °C

Note

Ordering data

Flange insert
Singlemode
Multimode/POF

Type	Qty.	Order No.
IE-BI-SCRJ2SC-SM-C	10	1962870000
IE-BI-SCRJ2SC-MM-C	1	1964430000

Note



Accessories

Type	Qty.	Order No.

Note

Flange inserts LC

- IP 20
- For variant 1, 4 and 14 housings

Flange inserts LC**Technical data**

Protection degree

Housing main material

Plugging cycles

Ambient temperature (operational)

Connector standard

Approvals

Note

IP67 with housing

PBT diecast zinc

1000

-40 °C...70 °C

IEC 61754-20

Ordering data**Flange insert**

Singlemode

Multimode

Note

Type	Qty.	Order No.
IE-BI-LCD-SM-C	10	1962880000
IE-BI-LCD-MM-C	10	1964420000

Accessories**Tools**


Crimping pliers GOF LC

Type	Qty.	Order No.
IE-CT-LC-GOF	1	9205330000

Note

Plug PushPull Power

Plug Power 24 V



Technical data

General data

Protection degree
Connector standard
Ambient temperature (operational)
Number of poles
Wire connection cross-section, flexible, min./max.
Sheath diameter, min. / max.
Connection
Approvals

Material properties

Housing base material
Sealing material
Cable sealing material
Contact material / Contact surface
UL 94 flammability rating
Pollution severity level
Plugging cycles

Electrical properties*

Current-carrying capacity at 50 °C
Rated voltage

Note

Ordering data - Sets

Type	Qty.	Order No.
IE-PS-VAPM-5P-2.5	1	2465440000
We recommend using 10-mm-long wire-end ferrules		


Ordering data - Empty housings

Type	Qty.	Order No.
IE-REDU-6-8-PS-VAPM	10	2531330000

Accessories

Sealing insert 6-8 mm

Note

Flanges PushPull Power**Flange Power 24 V****Technical data****General data**

Protection degree
Connector standard
Ambient temperature (operational)
Number of poles
Connection diameter, flexible, min. / max.
Connection 1
Approvals
Installation

Material properties

Housing base material
Sealing material
Cable sealing material
Contact carrier material
Contact material / Contact surface
UL 94 flammability rating
Pollution severity level
Plugging cycles

Electrical properties*

Current-carrying capacity at 50 °C
Rated voltage

Note**Ordering data - Sets**

Type	Qty.	Order No.
IE-BSS-VAPM-24V	1	2493480000
We recommend using 10-mm-long wire-end ferrules		

Ordering data - Empty housings

Type	Qty.	Order No.
IE-BHD-VAPM	1	2493490000

Accessories



Dust protection cap	IP54 protective cap	Dust cap	Type	Qty.	Order No.
			IE-BP-VAPP	10	1068930000
			IE-BP-VAPP-DC	10	2494060000

Note

IP65 connection components / FreeCon connecting components

Overview

IP65 connection components / FreeCon connecting components		
FreeCon Passive V14		0.2
FreeCon Active PROFINET		0.9
V1 junction boxes		0.12
V4 junction boxes		0.14
V5 junction boxes		0.16
V6 junction boxes		0.17

FreeCon V14 - junction box**Double junction box, Power / RJ45****Single junction box, RJ45****Technical data****General data**

Housing main material
Protection degree
Ambient temperature (operational)
Connector standard
Approvals

Technical specifications power connector

Housing base material
Sealing material
Contact material
Contact carrier material
Contact surface
Plugging cycles
Number of poles
Sheath diameter, min. / max.
Wire connection cross section, stranded, min. / max.
Connection

Electrical properties power connector

Current-carrying capacity at 50 °C
Rated voltage

Technical specifications for RJ45 module

Housing base material
Contact surface
Connection cross-section, flexible, min. / max.
Plugging cycles (RJ45 module)
Connection 1
Sheath diameter, min./max.

Electrical properties for RJ45 module

Category
Contact resistance
Insulation resistance
Dielectric strength, contact - contact, max.
Dielectric strength, contact - contact, min.
Current carrying capacity

Note**Ordering data****Note****Accessories****Mounting foot****Dust protection cap**

Protective cap
IP54 protective cap

Note

Aluminium profile, Cover: die-cast zinc, nickel plated

IP65

-40 °C...70 °C

IEC 61076-3-117 Var. 14, IEC 60603-7-5

CULUS

Zinc diecast, nickel-plated

NBR

Copper alloy

PA

Gold over nickel

≤ 100

5

6 mm / 12 mm

0.75 mm² / 2.5 mm²

Tension clamp

16 A

24 V

Zinc diecast, nickel-plated

Gold over nickel

AWG 26 / AWG 22

750

IDC

5 mm / 10 mm

Cat.5 (ISO/IEC 11801)

≤ 20 mΩ

> 500 MΩ

≤ 1000 V DC

≤ 1500 V DC

1 A

Aluminium profile, Cover: die-cast zinc, nickel plated

IP65

-40 °C...70 °C

IEC 61076-3-117 Var. 14, IEC 60603-7-5

CULUS

Zinc diecast, nickel-plated

Gold over nickel

AWG 26 / AWG 22

750

IDC

5 mm / 10 mm

Cat.5 (ISO/IEC 11801)

≤ 20 mΩ

> 500 MΩ

≤ 1000 V DC

≤ 1500 V DC



1 A

Type	Qty.	Order No.
IE-CD-V14MRJ/VAPM24V-FJ	1	1068830000

Type	Qty.	Order No.
IE-CD-V14MRJ-FJ	1	1068880000

Type	Qty.	Order No.
IE-CD-MA	10	1099580000
IE-BP-V14P	10	1058310000

Type	Qty.	Order No.
IE-CD-MA	10	1099580000
IE-BP-V14P	10	1058310000

FreeCon V14 - single junction box**RJ45 cable coupling****PushPull Power cable coupling****Technical data****General data**

Housing main material
Protection degree
Ambient temperature (operational)
Connector standard
Approvals

Technical specifications power connector

Housing base material
Sealing material
Contact material
Contact carrier material
Contact surface
Plugging cycles
Number of poles
Sheath diameter, min. / max.
Wire connection cross section, stranded, min. / max.
Connection

Electrical properties power connector

Current-carrying capacity at 50 °C
Rated voltage

Technical specifications for RJ45 module

Housing base material
Contact surface
Connection cross-section, flexible, min. / max.
Connection 1
Sheath diameter, min./max.

Electrical properties for RJ45 module

Category
Contact resistance
Insulation resistance
Dielectric strength, contact - contact, max.
Dielectric strength, contact - contact, min.
Current carrying capacity

Note**Ordering data - Sets**

Type	Qty.	Order No.
IE-CC-V14M-RJ45-FJ-P	1	1990600000

Type	Qty.	Order No.
IE-CC-V14M-EH	1	2583100000

Note**Note****Note****Note****diecast aluminium**

IP65
-40 °C...70 °C
in accordance with PROFINET specification
CULUS

Zinc diecast, nickel-plated



NBR
Copper alloy
PA
Gold over nickel
≤ 100
5
6 mm / 12 mm
0.75 mm² / 2.5 mm²
Tension clamp

16 A
24 V

We recommend using 10-mm-long wire-end ferrules

Type	Qty.	Order No.
IE-CC-VAPM-24V	1	1990630000

Type	Qty.	Order No.

FreeCon V14 - coupling**Double coupling, Power / RJ45****Single coupling, RJ45****Technical data****General data**

Housing main material
Protection degree
Ambient temperature (operational)
Connector standard
Approvals

Technical specifications power connector

Housing base material
Sealing material
Contact material
Contact carrier material
Contact surface
Plugging cycles
Number of poles

Electrical properties power connector

Current-carrying capacity at 50 °C
Rated voltage

Technical data for RJ45 coupling

Housing base material
Category
Contact resistance
Contact surface
Insulation resistance
Dielectric strength, contact - contact, min.
Dielectric strength, contact - shielding, max.
Current carrying capacity

Note**Ordering data****Note****Accessories****Dust protection cap**

Protective cap
IP54 protective cap


Type	Qty.	Order No.
IE-CD-V14MRJ/VAPM24V-C-MA	1	1068820000

Including mounting foot

Type	Qty.	Order No.
IE-CD-V14MRJ-C-MA	1	1068870000

Including mounting foot

Note**Note****Note**

FreeCon V14 single coupling**Single coupling, SCRJ****Technical data****General data**

Housing main material

Protection degree

Ambient temperature (operational)

Connector standard

Approvals

Technical specifications - fibre-optic coupler

Housing base material (fibre-optic coupling)

Plugging cycles (fibre-optic coupling)

Seal material (fibre-optic coupling)

Connection 1 / 2

Insertion attenuation (fibre-optic coupling)

Fibre type

Note

Aluminium profile, Cover: die-cast zinc, nickel plated

IP65

40...70 °C

IEC 61076-3-117 Var. 14, IEC 61754-24

CULUS

PA

≥ 500

NBR

SCRJ / SCRJ

< 0.2 dB

Multimode, POF

Ordering data**Note**

Type	Qty.	Order No.
IE-CD-V14MSCRJ-MM-C-MA	1	1318150000

Accessories**Dust protection cap**

Protective cap

Type	Qty.	Order No.
IE-BP-V14P	10	1058310000



Note

FreeCon V14 - Power

Y-distributor, Power



Single coupling, Power



Technical data

General data

Housing main material
Protection degree
Ambient temperature (operational)
Connector standard
Approvals

Technical specifications power connector

Housing base material
Sealing material
Cable sealing material
Contact material
Contact carrier material
Contact surface
UL 94 flammability rating
Plugging cycles
Pollution severity level

Electrical properties power connector

Current-carrying capacity at 50 °C
Rated voltage
Number of poles

Note

Ordering data

Note

Accessories

Dust protection cap

IP54 protective cap

Type	Qty.	Order No.
IE-CD-VAPM24V-Y-MA	1	1297010000

Type	Qty.	Order No.
IE-CD-VAPM24V-C-MA	1	1397690000



Type	Qty.	Order No.
IE-BP-VAPP	10	1068930000

Type	Qty.	Order No.
IE-BP-VAPP	10	1068930000

Note

Note

Note

FreeCon V14 - junction box**Single junction box, Hybrid****Hybrid cable coupling**
**Technical data****General data**

Housing main material

Protection degree

Ambient temperature (operational)

Approvals

Technical specifications hybrid connector

Housing base material

Sealing material

Contact material

Contact surface

Plugging cycles

Pole count

Connection cross-section, flexible, min. / max.

Connection cross-section, flexible, min. / max.

Electrical properties hybrid connector

Rated current (hybrid connector)

Rated voltage (DIN EN 61984)

Contact resistance

Note**Ordering data****Note****Accessories****Mounting foot****Crimping contact**0.08...0.2 mm²0.2...0.5 mm²0.75 mm²**Tools**

Pressing tool

Dust protection cap

Protective cap

Mounting frame

Aluminium profile, Cover: die-cast zinc, nickel plated

IP65

-40 °C...70 °C

CULUS

Zinc diecast (flange), PA 66

NBR

Copper alloy

Gold over nickel

500

10

AWG 27 / AWG 20

0.08 mm² / 0.75 mm²

3 A per contact

24 V

≤ 10 mΩ

Type Qty. Order No.

IE-CD-V14MHYB-10P-FJ 1 1068850000

Contacts should be ordered separately

diecast aluminium

IP65

-40 °C...70 °C

CULUS

Zinc diecast (flange), PA 66

NBR

Copper alloy

Gold over nickel

500

10

AWG 27 / AWG 20

0.08 mm² / 0.75 mm²

3 A per contact

24 V

≤ 10 mΩ

Type Qty. Order No.

IE-CC-V14M-HYB-10P-FJ 1 1990610000

Contacts should be ordered separately

Type Qty. Order No.

IE-CD-MA 10 1099580000

IE-BIC-HYB-P-0,2-300 300 1135160000

IE-BIC-HYB-P-0,5-300 300 1096150000


IE-BIC-HYB-P-0,75-300 300 1068970000

HTF HYB 1 1119580000

IE-BP-V14P 10 1058310000

IE-CC-V14M-MF 1 1990620000

Note

FreeCon V14 single coupling**Single coupling, hybrid****Technical data****General data**

Housing main material

Protection degree

Ambient temperature (operational)

Technical specifications hybrid connector

Housing base material

Sealing material

Contact material

Contact surface

Plugging cycles

Electrical properties hybrid connector

Rated current (hybrid connector)

Rated voltage (DIN EN 61984)

Contact resistance

Pole count

Approvals

Note**Ordering data****Note****Accessories****Dust protection cap**

Protective cap

Type	Qty.	Order No.
IE-CD-V14MHYB-10P-C-MA	1	1068840000

Type	Qty.	Order No.
IE-BP-V14P	10	1058310000



Note

FreeCon Active PROFINET with diagnostics functionality

POF repeater



POF repeater II



Technical data

General data

Housing main material

Weight

Data interface

Power interface

Protection degree

Ambient temperature (operational)

Network standard

Connector standard

Electrical data

Operating voltage

Operational voltage range

Current consumption

Baud rate

Protocol

LED indicator

Approvals

Note

Ordering data

Note

Accessories

Note

Aluminium profile, Cover: die-cast zinc, nickel plated

PROFINET PushPull SCRJ POF (V14)

PROFINET PushPull Power

IP65

-20 °C...55 °C

IEC 61158, IEC 61784

IEC 61076-3-117 Var. 14, IEC 61754-24

24 V DC

18...30 V DC

200 mA typical

100 MB

PROFINET IRT

F01: port active, F02: port active, SF: general error, BF: bus error, US1: voltage 1 (electronics), US2: voltage 2

CE; CULUS

Aluminium profile, Zinc die cast, electroplated lid

PROFINET PushPull SCRJ POF (V14)

PROFINET PushPull Power

IP65

-20 °C...55 °C

IEC 61158, IEC 61784

IEC 61076-3-117 Var. 14, IEC 61754-24

24 V DC

18...30 V DC

200 mA typical

100 MB

PROFINET IRT

F01: port active, F02: port active, SF: general error, BF: bus error, US1: voltage 1 (electronics), US2: voltage 2, ACT1: activity Port1, ACT2: activity Port2

CE; CULUS

Type	Qty.	Order No.
IE-CDR-V14MSCPOF/VAPM-C	1	1253240000

Delivery incl. protective caps

Type	Qty.	Order No.
IE-CDR-V14MSCPOF/VAPM-C II	1	2455360000

Further development of 1253240000, IE-CDR-V14MSCPOF/VAPM-C. For commissioning, the new GSDML file (see Downloads) must be installed.

Type	Qty.	Order No.



Type	Qty.	Order No.

FreeCon Active PROFINET with diagnostics functionality

POF media converter



POF media converter II



Technical data

General data

Housing main material

Weight

Data interface

Power interface

Protection degree

Ambient temperature (operational)

Network standard

Connector standard

Electrical data

Operating voltage

Operational voltage range

Current consumption

Baud rate

Protocol

LED indicator

Approvals

Note

Ordering data

Note

Accessories

Note

Aluminium profile, Cover: die-cast zinc, nickel plated

PROFINET PushPull SCRJ POF (V14), PROFINET PushPull RJ45 (V14)

PROFINET PushPull Power

IP65

-20 °C...55 °C

IEC 61158, IEC 61784

IEC 61076-3-117 Var. 14, IEC 61754-24, IEC 60603-7-51

24 V DC

18...30 V DC

200 mA typical

100 MB

PROFINET IRT

P1: port active, P2: port active, SF: general error, BF: bus error, US1: voltage 1 (electronics), US2: voltage 2

CE; CULUS

Aluminium profile, Zinc die cast, electroplated lid

PROFINET PushPull SCRJ POF (V14), PROFINET PushPull RJ45 (V14)

PROFINET PushPull Power

IP65

-20 °C...55 °C

IEC 61158, IEC 61784

IEC 61076-3-117 Var. 14, IEC 61754-24, IEC 60603-7-51

24 V DC

18...30 V DC

200 mA typical

100 MB

PROFINET IRT

P1: port active, P2: port active, SF: general error, BF: bus error, US1: voltage 1 (electronics), US2: voltage 2, ACT1: activity Port1, ACT2: activity Port2

CULUS

Further development of 1324440000, IE-CDM-V14MRJSCP/VAPM-C.
For commissioning, the new GSDML file (see Downloads) must be installed.

Type	Qty.	Order No.
IE-CDM-V14MRJSCP/VAPM-C	1	1324440000


Delivery incl. protective caps

Type	Qty.	Order No.
IE-CDM-V14MRJSCP/VAPM-C II	1	2588270000

Type	Qty.	Order No.

FreeCon Active PROFINET with diagnostics functionality

Copper repeater



Technical data

General data

Housing main material

Weight

Data interface

Power interface

Protection degree

Ambient temperature (operational)

Network standard

Connector standard

Electrical data

Operating voltage

Operational voltage range

Current consumption

Baud rate

Protocol

LED indicator

Approvals

Note

Ordering data

Note

Accessories

Aluminium profile, Zinc die cast, electroplated lid

PROFINET PushPull RJ45 (V14)

PROFINET PushPull Power

IP65

-20 °C...55 °C

IEC 61158, IEC 61784

IEC 61076-3-117 Var. 14

24 V DC

18...30 V DC

100 mA

100 MBit/s

PROFINET IRT

ACT1: activity Port1, ACT2: activity Port2, SF: general error, BF: bus error, US1: voltage 1 (electronics), US2: voltage 2, LNK1: port active, LNK2: port active


CULUS

Type	Qty.	Order No.
IE-CDR-V14MRJ/VAPM-C	1	2581810000

Delivery incl. protective caps

Type	Qty.	Order No.

Note

V1 junction boxes**V1 junction boxes - plastic****Single junction box****Technical data**

Protection degree
Housing main material
Plugging cycles
Ambient temperature (operational)
Connector standard
Sheath diameter min. / max.
Approvals

IP67
PA UL 94 VO
750
-40 °C...70 °C
IEC 61076-3-106 Var. 1
6 mm / 9.5 mm

Note**Ordering data**

Variant 1
Pre-assembled cable

Type	Qty.	Order No.
IE-OP-V01P-1S	10	1061830000

Order RJ45 modules separately

Accessories



Inserts, Data
RJ45 module EIA/TIA T568 B
RJ45 module PROFINET
RJ45 module EIA/TIA T568 A

Type	Qty.	Order No.
IE-BI-RJ45-FJ-B	10	1963840000
IE-BI-RJ45-FJ-P	10	1963830000
IE-BI-RJ45-FJ-A	10	1962850000

Note

V1 junction boxes - metal

- IP 67
- For wall or floor mounting

Double junction box**Single junction box****Technical data**

Protection degree

Housing main material

Colour

Type of mounting

Ambient temperature (operational)

Plugging cycles

Connector standard

Sheath diameter min. / max.

Approvals

Note

IP67

AL-Si 12

grey

Floor-mounted, Wall mounting

-40 °C...70 °C

750

IEC 61076-3-106 Var. 1

5 mm / 10 mm

GOSTME25

IP67

AL-Si 12

grey

Floor-mounted, Wall mounting

-40 °C...70 °C

750

IEC 61076-3-106 Var. 1

5 mm / 10 mm

Ordering data**Variant 1**

2 ports. straight

1 port. straight

Note

Type	Qty.	Order No.
IE-OM-V01M-K21-2S	1	1966330000

RJ45 modules can be ordered separately

Type	Qty.	Order No.
IE-OM-V01M-K11-1S	1	1966300000

RJ45 modules can be ordered separately



Accessories**Inserts, Data**

RJ45 module EIA/TIA T568 B
RJ45 module PROFINET
RJ45 module EIA/TIA T568 A

Type	Qty.	Order No.
IE-BI-RJ45-FJ-B	10	1963840000
IE-BI-RJ45-FJ-P	10	1963830000
IE-BI-RJ45-FJ-A	10	1962850000

Type	Qty.	Order No.
IE-BI-RJ45-FJ-B	10	1963840000
IE-BI-RJ45-FJ-P	10	1963830000
IE-BI-RJ45-FJ-A	10	1962850000

Note

V4 junction boxes**FreeCon V4 junction boxes****Single coupling, RJ45****Single junction box****Technical data****General data**

Plugging cycles
Housing main material
Contact surface
UL 94 flammability rating
Connector standard
Protection degree
Ambient temperature (operational)
Sheath diameter min. / max.
Approvals

Electrical properties for RJ45 module

Category
Contact resistance
Insulation resistance
Dielectric strength, contact - contact, min.
Dielectric strength, contact - shielding, max.
Current carrying capacity

Material properties RJ45 coupling

Housing base material

Note**Ordering data**

Pre-assembled cable
Coupling

Note**Accessories****Dust protection cap**

Flange-mounted housing protective cap

Inserts, Data

RJ45 module PROFINET
RJ45 module EIA/TIA T568 A
RJ45 module EIA/TIA T568 B

750

Aluminium profile, Cover: die-cast zinc, nickel plated

Gold over nickel

IEC 61076-3-106 Var. 4, IEC 60603-7-5

IP65

-40 °C...70 °C

CULUS

Cat.6A / Class E_A (ISO/IEC 11801 2010)

≤ 20 mΩ

> 500 MΩ

≥ 1000 V DC

≥ 1500 V DC

1 A

Zinc diecast, PA 66

750

PA

Gold over nickel

V-0

IEC 61076-3-106 Var. 4

IP67

-40 °C...70 °C

6 mm / 9.5 mm

Type **Qty.** **Order No.**

IE-CD-V04PRJ-C-MA 1 1122710000

Including mounting foot

Type **Qty.** **Order No.**

IE-OP-V04P-1S 10 1045780000

Order RJ45 modules separately, IP 67 protective cap included in delivery

Type **Qty.** **Order No.**

IE-BP-V04P 10 1963900000

Including mounting foot

Type **Qty.** **Order No.**

IE-BP-V04P 10 1963900000

IE-BI-RJ45-FJ-P 10 1963830000



IE-BI-RJ45-FJ-A 10 1962850000

IE-BI-RJ45-FJ-B 10 1963840000

Note**Note****Note**

V4 junction boxes

- IP 67
- For wall or floor mounting

Double junction box**Single junction box****Technical data**

Protection degree

Housing main material

Colour

Type of mounting

Ambient temperature (operational)

Plugging cycles

Connector standard

Sheath diameter min. / max.

Approvals

Note

IP67

AL-Si 12

grey

Floor-mounted, Wall mounting

-40 °C...70 °C

750

IEC 61076-3-106 Var. 4

5 mm / 10 mm

GOSTME25

IP67

AL-Si 12

grey

Floor-mounted, Wall mounting

-40 °C...70 °C

750

IEC 61076-3-106 Var. 4

5 mm / 10 mm

Ordering data**Variant 4**2 ports. straight
1 port. straight**Note****Type****Qty.****Order No.**

IE-OM-V04P-K21-2S

1

1966250000

RJ45 modules can be ordered separately

Type**Qty.****Order No.**

IE-OM-V04P-K11-1S

1

1966220000

RJ45 modules can be ordered separately

Accessories**Inserts, Data**RJ45 module EIA/TIA T568 B
RJ45 module PROFINET
RJ45 module EIA/TIA T568 A**Type****Qty.****Order No.**

IE-BI-RJ45-FJ-B

10

1963840000

IE-BI-RJ45-FJ-P

10

1963830000

IE-BI-RJ45-FJ-A

10

1962850000

Type**Qty.****Order No.**

IE-BI-RJ45-FJ-B

10

1963840000

IE-BI-RJ45-FJ-P

10

1963830000

IE-BI-RJ45-FJ-A





10

1962850000

Note

V5 junction boxes**V5 junction boxes**

- IP 67
- For wall or floor mounting

**Double junction box****Single junction box****Technical data**

Protection degree

Housing main material

Colour

Type of mounting

Ambient temperature (operational)

Plugging cycles

Connector standard

Sheath diameter min. / max.

Approvals

Note

IP67

AL-Si 12

grey

Floor-mounted, Wall mounting

-40 °C...70 °C

750

IEC 61076-3-106 Var. 5

5 mm / 10 mm

GOSTME25

IP67

AL-Si 12

grey

Floor-mounted, Wall mounting

-40 °C...70 °C

750

IEC 61076-3-106 Var. 5

5 mm / 10 mm

Ordering data**Variant 5**2 ports. straight
1 port. straight**Note****Type** **Qty.** **Order No.**

IE-OM-V05M-K21-2S 1 1966290000

RJ45 modules can be ordered separately

Type **Qty.** **Order No.**

IE-OM-V05M-K11-1S 1 1966260000

RJ45 modules can be ordered separately

Accessories**Inserts, Data**RJ45 module EIA/TIA T568 B
RJ45 module PROFINET
RJ45 module EIA/TIA T568 A**Type** **Qty.** **Order No.**

IE-BI-RJ45-FJ-B 10 1963840000

IE-BI-RJ45-FJ-P 10 1963830000

IE-BI-RJ45-FJ-A 10 1962850000

Type **Qty.** **Order No.**

IE-BI-RJ45-FJ-B 10 1963840000


IE-BI-RJ45-FJ-P 10 1963830000

IE-BI-RJ45-FJ-A 10 1962850000

Note

V6 junction boxes

- Cat. 6
- IP 67

Single junction box, RJ45**Technical data**

Protection degree
Housing main material
Colour
Type of mounting

Configuration

Wiring
Ambient temperature (operational)
Plugging cycles
Connector standard
Sheath diameter min. / max.
Approvals

Note

IP67
PA 66, UL 94: V-0
Light Grey

Floor-mounted, for exposed connections, Wall mounting

Screw-on junction box

including RJ45 module with
IDC connection

EIA/TIA T568 A, EIA/TIA T568 B

40 °C...70 °C

750

IEC 61076-3-106 Var. 6

6 mm / 9.5 mm

DNVGL

Ordering data**Note**

Type	Qty.	Order No.
IE-S-IP67	1	8808370000

Accessories**Tools**

Pressing tool

Type	Qty.	Order No.
TT 8 RS MP 8	1	9202800000

Note

Contactless Transmission

Overview

Contactless Transmission	Overview	P.2
	FreeCon Contactless Power	P.5

P

Contactless power transmission – maintenance-free and up to 240 W

High power density and maximum efficiency with small dimensions

Burnt, bent or dirty contacts are often the cause of timeconsuming and costly production failures. This is all the more true of applications requiring frequent plugging cycles. To name but one example, these include industrial robots performing frequent tool changes. Here, the level of wear is especially high. FreeCon Contactless allows power to be transmitted via an air gap by means of an inductive resonance coupling – it's a solution that's completely wear-free and especially efficient. Double the power density and a far higher degree of efficiency is achieved compared with comparable solutions that are available on the market.

Thanks to FreeCon Contactless, you can avoid contactrelated failures and cut your maintenance costs considerably. It even opens up completely new areas of application, since for the first time ever an automated process can be used to establish a connection which previously would have to be plugged manually. The process of charging driverless transport systems, for instance, can be automated. Highmaintenance slip ring transmitters can be replaced too, since FreeCon Contactless securely transmits power even in the case of rotational movements.

Wear-free electrical connection that can be switched as part of a controlled process

FreeCon Contactless enables reliable and contactless transmission of up to 240 W of power with compact dimensions and maximum efficiency. The transmission can even be controlled via PLC. It is therefore possible to switch 10 A directly via the PLC without the need for an additional contactor.

Flexible mounting options

Fastening can optionally take place on three different sides by means of direct mounting on the relevant machine component, or by using a mounting bracket or a groove profile. This allows for maximum flexibility during installation.



High flexibility thanks to unlimited approach options

The secondary side can be approached by the primary side from any direction. The connection is established as soon as both modules are positioned opposite one another. The connection remains stable even in the event of rotational movements.




Complete protection against humidity and dirt

Unlike conventional plug-in connections, which only provide IP 20 protection when unplugged and are therefore unprotected, FreeCon Contactless offers IP 65 – permanently. So, with FreeCon Contactless, contacting problems caused by dirt are a thing of the past.



High power density with maximum efficiency

For the first time ever, 240 W of power can be transmitted contactlessly via two especially small modules. Extremely low transmission losses translate into an efficiency level of up to 93 %



Fast commissioning with PROFINET PushPull Power connection

Our proven standard plug-in connector for 24 V DC applications enables fast installation and ensures that the modules are provided with a secure and reliable supply.



Drive automation forwards – the intelligent way

FreeCon Contactless makes your applications more efficient on many levels

FreeCon Contactless was developed in close collaboration with leading German car manufacturers. The system is suitable for an extremely wide range of sectors, such as machine construction, robotics, materials handling and even renewable energy. It can be retrofitted with ease and is thus an appealing solution for existing plants, too. With this multitude of advantages, it helps to increase the level of automation and optimises the production process. And best of all, FreeCon Contactless does more than simply help to avoid contact-related failures and cut maintenance costs. Completely new designs and areas of application are possible with a view to optimising production processes.

P



The automotive industry makes use of applications that require frequent plugging cycles, such as industrial robots performing tool changes. They work with a variety of tools, which they independently change for different tasks – such as gripping or welding. The high level of wear that occurs on the mechanical plug-in connections can be avoided entirely with FreeCon Contactless. This saves both time and money in terms of contact maintenance and replacement, in addition to minimising machine failures caused by maintenance work or defects.



Automatic transport systems, which are a common feature of many warehouses and production halls nowadays, complete all work without mechanical support. A member of staff only has to be present to make the plug-in connection, which is required for charging the battery. FreeCon Contactless makes even this manual work step superfluous. The driverless transport systems move to the charging station independently just before the battery goes flat, at the end of the working day, or at shutdown periods. The result is effective time and cost savings, which means your investment pays for itself in no time at all.

FreeCon Contactless

- Contactless power transmission via air gap

**Primary side (base)****Secondary side (remote)****Technical data****General data**

Housing main material	Diecast zinc, painted, Cover PBT
Technologie, version	Inductive resonance coupling
Loads	Inductive and resistive loads
Turn-on time	1 s
Coupling time	< 500 ms
Air gap	0...5 mm
Centre offset	max. 5mm
Power interface	PROFINET PushPull Power
Protection degree	IP65
Ambient temperature (operational)	-20...45 °C Consider derating
Weight	1020 g

Electrical data

Primary voltage	24 V DC (21.6...26.4 V DC)
Secondary voltage	
Secondary current max.	
Degree of efficiency	max. 91 %
LED indicator	Status indication via multi-coloured LED
Approvals	CE

Note**Ordering data**

Type	Qty.	Order No.
IE-CL240W-PP-BASE	1	1547440000

Note**Accessories**

Type	Qty.	Order No.
IE-PS-VAPM-5P-2.5	1	2465440000
ESG 6/17 K MC NE WS	200	1880120000

Note

Diecast zinc, painted, Cover PBT
Inductive resonance coupling
Inductive and resistive loads
1 s

Note

Diecast zinc, painted, Cover PBT
Inductive resonance coupling
Inductive and resistive loads

Note**Ordering data**

Type	Qty.	Order No.
IE-CL240W-PP-REMOTE	1	1547450000

Note**Accessories**

Type	Qty.	Order No.
IE-PS-VAPM-5P-2.5	1	2465440000
ESG 6/17 K MC NE WS	200	1880120000

Note**Ordering data**

Type	Qty.	Order No.
IE-PS-VAPM-5P-2.5	1	2465440000

Note**Accessories**

Type	Qty.	Order No.
ESG 6/17 K MC NE WS	200	1880120000


Note

FreeCon Contactless

- Contactless power transmission via air gap

Secondary side (remote)

27 V / 5 A

**Technical data****General data**

Housing main material	Diecast zinc, painted, Cover PBT
Technologie, version	Inductive resonance coupling
Loads	Inductive and resistive loads
Turn-on time	< 500 ms
Coupling time	0...5 mm
Air gap	max. 5mm
Centre offset	PROFINET PushPull Power
Power interface	IP65
Protection degree	-20...45 °C Consider derating
Ambient temperature (operational)	1020 g
Weight	

Electrical data

Primary voltage	26,5 V DC (+/- 5%) (necessary voltage for secondary voltage must be ensured)
Secondary voltage	27 V DC ($\pm 7\%$)
Secondary current max.	5 A
Degree of efficiency	max. 91 %
LED indicator	Status indication via multi-coloured LED
Approvals	

Note**Ordering data**

Type	Qty.	Order No.
IE-CL27V5A-PP-S	1	2623940000

Note**Accessories**

Type	Qty.	Order No.
IE-PS-VAPM-5P-2.5	1	2465440000
ESG 6/17 K MC NE WS	200	1880120000

Note

Copper cabling solutions

Overview

Copper cabling solutions	
Introduction AdvancedLine and CabinetLine	0.2
Product configurator – Copper cables	0.3
Overview – Copper cables	0.4
Raw cables – Installation cable	0.6
Raw cables – Connection cable	0.8
Raw cables – Dragline cable	0.14
Raw cables – PROFINET cable	0.15
Raw cables – Hybrid cable	0.17
Assembled cables – Patch cable	0.18
Assembled cables – PROFINET cable	0.28
Assembled cables – PROFINET cable PushPull Power	0.32
Assembled cables – PROFINET cable M12	0.34
Assembled cables – EtherNet/IP	0.42
Assembled cables – PROFINET cable M8	0.44
Assembled cables – PROFINET cable M8, D-coded	0.48
Assembled cables – Railway cable M12	0.53
Assembled cables – Railway cable RJ45	0.58
Assembled cables – USB cable	0.59
Assembled cables – Single Pair Ethernet cable	0.61

The ideal solution, whatever your needs

Our AdvancedLine and CabinetLine product ranges

AdvancedLine



Q The AdvancedLine from Weidmüller offers all combinations of cables that are possible with the extensive range of plug connections.

This means flexibility and robustness through the high quality of the used components. The range comprises standard cables and customer-specific versions. Standard cables can be found in the catalogue; customer-specific versions can be freely configured online using the "Galaxy" configuration software. All AdvancedLine cables are particularly suitable for industrial use.

- High-quality cables with very good technical characteristics
- Suitable for demanding IP20 to IP67 applications
- Suitable for temperatures from -40 to +70 °C
- High-quality shielding

CabinetLine



The new CabinetLine range of patch cables from Weidmüller is available in a variety of colours for visually differentiating between various networks.

Additional benefits:

All CabinetLine cables are fitted with Weidmüller TM marking sleeves for clearly labelling cables and ports. CabinetLine is available in many different colours in combination with LSZH sheathing material and transmission power Cat. 6A.

CabinetLine is also available in the colour green and Cat. 5 with PUR or PVC sheathing material. All variants are fitted with protected clips which facilitate, e.g., pulling through a cable duct.

- For applications in switching cabinets and simple environmental conditions
- Suitable for temperatures from -20 to +60 °C
- Simple shielding

Configurators for copper cables

Tailor-made connections

The cable configurator in Weidmüller's online catalogue makes it possible for you to create fully-assembled cables customised specifically to your requirements and specifications.

An RJ45 plug with IP20 protection is available. The following variants are also available with IP67 protection:

- Variant 1, metal and plastic
- Variant 4, plastic
- Variant 5, metal
- Variant 14, metal
- M12 connector, straight and angled

You have the choice of configuring a cable which is identical on both ends, or with two different mating profiles, or with one end left open.

The screenshot shows the Weidmüller product configurator interface. At the top, there are links for English, Project Management, Configuration, Parts list, Help, Product Catalogue, Product assistant, and Industrial Ethernet. The main title is "Industrial Ethernet product configurator". Below this, a sub-section titled "Configuration - Copper cable" shows a diagram of a green cable with two RJ45 connectors. A horizontal line indicates a length of "55 m". Below the diagram, there are dropdown menus for "Plug 1" (RJ45 IP67 Baymo V01 metal) and "Plug 2" (RJ45 IP67 PushPull V14 metal). Further down, there are dropdown menus for "Type of cable" (System cable), "Category" (Cat 7 / PUR), "Cable colour" (Green), and "Length [m]" (Individual lengths).

When selecting the cable, the following types are available:

- 8-wire system cable, AWG 26/7 in Cat. 5 or Cat. 7, with PVC or PUR sheath
- 8-wire dragline cable, AWG 26/7 in Cat. 5, PUR sheath
- 4-wire PROFINET dragline cable in Cat. 5, PUR sheath
- 4-wire PROFINET system cables in Cat. 5, PVC sheathing
- 4-wire railway cable in Cat. 5, Radox sheathing

The cable length can also be customised:

- From 0.3 m to 9.9 m, in 0.1 m steps
- From 10 m to 100 m, in 1 m steps

The cable configurator can automatically create technical data sheets for all of your customised cable variants.

All of your cable selections can be sent to Weidmüller using the "request list". You will then quickly receive a price proposal for the cables from your local Weidmüller representative.

Overview of copper cables

Solutions for every environment

Copper cables should be your first choice for applications in offices and harsh industrial environments.

Advantages:

- Available in many different variations and lengths
- Robust
- Easy to assemble
- RJ45 connections are the most popular

Raw cables

Industrial installation cables, horizontal cables



...for stationary, permanent installation in cable ducts and cable trays

- Cat. 5 or Cat. 7
- Available for PROFINET as well
- With PUR or PVC sheathing

Industrial connecting cables



...for flexible installation in machines and plants in industrial applications and difficult environments

- Cat. 5 or Cat. 7
- Available for PROFINET as well
- With PUR or PVC sheathing

Industrial trailing cables



...for applications subjected to constant movement

- Cat. 5
- Available for PROFINET as well
- With PUR sheathing

Assembled cables

Industrial patch cables / CabinetLine



...not only for office applications, but also in switching cabinets for industrial applications

- Cat. 6
- With LSZH sheathing – low smoke and zero halogens
- In straight and crossover versions

Industrial system cables



...pre-assembled cables for flexible installation in machines and plants in industrial applications and difficult environments

- Cat. 5 or Cat. 6
- With PUR sheathing

Industrial trailing cables



...pre-assembled cable for constant motion, e.g., with draglines

- Cat. 5
- Available for PROFINET as well
- With PUR sheathing

System cable for railway applications



...pre-assembled cable for flexible wiring on railway vehicles for both interior and exterior installations.

- In Cat. 5
- Also for PROFINET
- With Radox sheath

Single Pair Ethernet cables



IP20 and IP67 Patch Cables for compact Ethernet transmission with only one wire pair.

- according to IEC 63171-2 / -5
- very robust and space-saving

Ordering data for copper cables, raw cable

Type	Cat./Class	Colour	Plug-in connector left	Plug-in connector right	Length	100 m	500 m	305 m		
Industrial installation cables										
IE-C5CS8UG-xxx	Cat. 5	green	-	-	8813160000	2762870000				
IE-C5CS8VG-xxx	Cat. 5	green	-	-	8813150000	2763440000				
IE-C7BS8UG-xxx	Cat. 7	green	-	-	8813140000	2763530000				
IE-C7BS8VG-xxx	Cat. 7	green	-	-	8813130000	2763540000				
IE-C5AS4V-xxx	Cat. 5 PROFINET	green	-	-	8899000000	2763430000				
Industrial connecting cables										
IE-C5ES8UG-xxx	Cat. 5	green	-	-	8813200000	2763500000				
IE-C5ES8VG-xxx	Cat. 5	green	-	-	8813190000	2763510000				
IE-C7ES8UG-xxx	Cat. 7	green	-	-	8813180000	2763550000				
IE-C7ES8VG-xxx	Cat. 7	green	-	-	8813170000	2763490000				
IE-C5DS4V-xxx	Cat. 5 PROFINET	green	-	-	8898990000	2763470000				
IE-C5DHAG-xxx	Cat. 5 PROFINET	green	-	-	2763660000	2763460000				
IE-C7FS8LD-305M	Cat. 7	grey	-	-			1273090000			
IE-C7FS8LB-305M	Cat. 7	blue	-	-			1326540000			
IE-C7FS8LE-305M	Cat. 7	black	-	-			1344690000			
IE-C7FS8LG-305M	Cat. 7	green	-	-			1344680000			
IE-C7FS8LR-305M	Cat. 7	red	-	-			1287910000			
IE-C7FS8LV-305M	Cat. 7	violet					2779910000			
IE-C7FS8LM-305M	Cat. 7	magenta	-	-			1333160000			
IE-C7FS8LO-305M	Cat. 7	orange					2661080000			
IE-C7FS8LY-305M	Cat. 7	yellow	-	-			1344670000			
Industrial trailing cables										
IE-C5ED8UG-xxx	Cat. 5	green	-	-	8813210000	2763490000				
IE-C5ED8UB-xxx	Cat. 5	blue	-	-	8960670000	2763480000				
IE-C5DD4UG-xxx	Cat. 5 PROFINET	green	-	-	8899010000	2763450000				
IE-C5IT4UG-xxx	Cat. 5 PROFINET	green	-	-	2764770000	2763520000				

Raw cables – Installation cable

Raw cables



Installation cable Cat. 5

- In lengths from 100 or 500 metres

PUR



PVC



Technical data

Product type

Category

Shielding

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Ambient temperature (operational)

Installation temperature

Storage temperature

Abrasion resistance

Halogen

Resistance to spread of flame

Resistance to oils

Approvals

Note

Ordering data

100.0 m

500.0 m

Note

Accessories

Tools

Sheathing strippers, For UTP and STP data cables

Sheathing strippers, For coaxial and round data cables

Marking tags

Wire and cable markers. Ø 4.7 - 7.4 mm

Wire and cable markers. Ø 5.8 - 7.8 mm

Insertion label, yellow, 12 mm

Insertion label, yellow, 18 mm

Transparent sleeves, 12-mm length

Transparent sleeves, 18-mm length

Installation cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

4*2*AWG 24/1 - 4*2*0.205 mm²

6.7 mm

PUR

green (RAL 6018)

1 mm

10 x cable diameter

5 x cable diameter

-40 °C...80 °C

-15 °C...60 °C

40 °C...80 °C

very good

halogen-free, according to IEC 60754-2

in acc. with IEC 60332-1

in acc. with IEC 60811-2-1

Installation cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

4*2*AWG 24/1 - 4*2*0.205 mm²

6.3 mm

PVC

green (RAL 6018)

1 mm

10 x cable diameter

5 x cable diameter

-40 °C...80 °C

-15 °C...60 °C

40 °C...80 °C

good

in acc. with IEC 60332-1

Type	Qty.	Order No.
IE-C5CS8UG-100	1	8813160000
IE-C5CS8UG-500	1	2762870000

Type	Qty.	Order No.
IE-C5CS8VG-100	1	8813150000
IE-C5CS8VG-500	1	2763440000

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001
TMJ 12 MC NE GE	320	1718411687
TMJ 18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000



Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001
TMJ 12 MC NE GE	320	1718411687
TMJ 18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

Note

Note

Raw cables**Installation cable Cat. 7**

- In lengths from 100 or 500 metres

PUR**PVC****Technical data****Product type**

Category

Shielding

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Ambient temperature (operational)

Installation temperature

Storage temperature

Abrasion resistance

Halogen

Resistance to spread of flame

Resistance to oils

Approvals

Note**Ordering data**

	100.0 m
	500.0 m

Note**Accessories****Tools**

Sheathing strippers, For UTP and STP data cables
Sheathing strippers, For coaxial and round data cables

Marking tags

Wire and cable markers. ø 4.7 - 7.4 mm
Wire and cable markers. ø 5.8 - 7.8 mm
Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm
Transparent sleeves, 12-mm length
Transparent sleeves, 18-mm length

Installation cable

Cat.7 (ISO/IEC 11801)

S/FTP

4*2*AWG 23/1 - 4*2*0.255 mm²

8.4 mm

PUR

green (RAL 6018)

1.4 mm

10 x cable diameter

5 x cable diameter

-40 °C...80 °C

-15 °C...60 °C

-40 °C...80 °C

very good

halogen-free, according to IEC 60754-2

in acc. with IEC 60332-1

in acc. with IEC 60811-2-1

Type**Qty.****Order No.**

IE-C7BS8UG-100	1	8813140000
IE-C7BS8UG-500	1	2763530000

Installation cable

Cat.7 (ISO/IEC 11801)

S/FTP

4*2*AWG 23/1 - 4*2*0.255 mm²

8.4 mm

PVC

green (RAL 6018)

1.4 mm

10 x cable diameter

5 x cable diameter

-40 °C...80 °C

-15 °C...60 °C

-40 °C...80 °C

good

in acc. with IEC 60332-1

Type**Qty.****Order No.**

IE-C7BS8VG-100	1	8813130000
IE-C7BS8VG-500	1	2763540000

Type**Qty.****Order No.**



AM 12	1	9030060000
IE-CST	1	9204350000

VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001
TM 12 MC NE GE	320	1718411687
TM 18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

Note

Raw cables – Connection cable**Raw cables****Connecting cable Cat. 5**

- In lengths from 100 or 500 metres

PUR**PVC****Technical data**

Product type

Category

Shielding

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Ambient temperature (operational)

Installation temperature

Storage temperature

Abrasion resistance

Halogen

Resistance to spread of flame

Resistance to oils

Standard, assembly

Approvals

Note

System cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

4*2*AWG 26/7 - 4*2*0.128 mm²

6.1 mm

PUR

green (RAL 6018)

1 mm

10 x cable diameter

5 x cable diameter

-40 °C...80 °C

-10 °C...60 °C

-40 °C...80 °C

very good

halogen-free, according to IEC 60754-2

in acc. with IEC 60332-1

in acc. with IEC 60811-2-1

UL-Style 20963 (80°C/30V)

System cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

4*2*AWG 26/7 - 4*2*0.128 mm²

5.8 mm

PVC

green (RAL 6018)

1 mm

10 x cable diameter

5 x cable diameter

-40 °C...80 °C

-15 °C...60 °C

-40 °C...80 °C

good

in acc. with IEC 60332-1

Ordering data

100.0 m

500.0 m

Note

Type	Qty.	Order No.
IE-C5ES8UG-100	1	8813200000
IE-C5ES8UG-500	1	2763500000

Type	Qty.	Order No.
IE-C5ES8VG-100	1	8813190000
IE-C5ES8VG-500	1	2763510000

Accessories

Tools

Sheathing strippers, For UTP and STP data cables
Sheathing strippers, For coaxial and round data cables

Marking tags

Wire and cable markers. ø 4.7 - 7.4 mm
Wire and cable markers. ø 5.8 - 7.8 mm
Insertion label, yellow. 12 mm
Insertion label, yellow. 18 mm
Transparent sleeves. 12-mm length
Transparent sleeves. 18-mm length

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000



VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001
TMH 12 MC NE GE	320	1718411687
TMH 18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001
TMH 12 MC NE GE	320	1718411687
TMH 18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

Note

Raw cables**Connecting cable Cat. 7**

- In lengths from 100 or 500 metres

PUR**PVC****Technical data**

Product type

Category

Shielding

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Ambient temperature (operational)

Installation temperature

Storage temperature

Abrasion resistance

Halogen

Resistance to spread of flame

Resistance to oils

Standard, assembly

Approvals

Note**Ordering data**

100.0 m

500.0 m

Note**Accessories****Tools**

Sheathing strippers, For UTP and STP data cables
Sheathing strippers, For coaxial and round data cables

Marking tags

Wire and cable markers. ø 4.7 - 7.4 mm
Wire and cable markers. ø 5.8 - 7.8 mm
Insertion label, yellow. 12 mm
Insertion label, yellow. 18 mm
Transparent sleeves. 12-mm length
Transparent sleeves. 18-mm length

System cable

Cat.7 (ISO/IEC 11801)

S/FTP

4*2*AWG 26/7 - 4*2*0.128 mm²

6.6 mm

PUR

green (RAL 6018)

1.03 mm

10 x cable diameter

5 x cable diameter

-40 °C...80 °C

-15 °C...60 °C

40 °C...80 °C

very good

halogen-free, according to IEC 60754-2

in acc. with IEC 60332-1

in acc. with IEC 60811-2-1

UL-Style 20963 (80°C/30V)

System cable

Cat.7 (ISO/IEC 11801)

S/FTP

4*2*AWG 26/7 - 4*2*0.128 mm²

6.7 mm

PVC

green (RAL 6018)

0.98 mm

10 x cable diameter

5 x cable diameter

-40 °C...80 °C

-15 °C...60 °C

40 °C...80 °C

good

in acc. with IEC 60332-1

UL-Style 2879 (80°C/30V)

Type Qty. Order No.

IE-C7ES8VG-100 1 8813170000

IE-C7ES8VG-500 1 2763560000

Type Qty. Order No.

IE-C7ES8VG-100 1 9030060000

IE-C7ES8VG-500 1 9204350000

Type Qty. Order No.

VT SF 5/21 MC NE WS VO 160 1689470001

VT SF 6/21 MC NE WS VO 160 1730560001

TMH 12 MC NE GE 320 1718411687

TMH 18 MC NE GE 320 1718431687

TM 4/12 HF/HB 500 1719840000

TM 4/18 HF/HB 500 1719850000

Note

Raw cables – Connection cable

Raw cables



Connecting cable Cat. 7

- 305 m / 1,000 ft

LSZH grey



LSZH blue



Technical data

Product type

Category

Shielding

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Ambient temperature (operational)

Installation temperature

Halogen

Resistance to spread of flame

Resistance to oils

Approvals

Note

Ordering data

305 m / 1000 ft

Note

Accessories

Tools

Sheathing strippers, For UTP and STP data cables
Sheathing strippers, For coaxial and round data cables

Marking tags

Wire and cable markers. ø 4.7 - 7.4 mm
Wire and cable markers. ø 5.8 - 7.8 mm
Insertion label, yellow. 12 mm
Insertion label, yellow. 18 mm
Transparent sleeves. 12-mm length
Transparent sleeves. 18-mm length

System cable

Cat.7 (ISO/IEC 11801)

S/FTP

4*2*AWG 27/7 - 4*2*0.1 mm²

5.9 mm

LSZH

light grey (RAL 7035)

1.04 mm

50 mm

25 mm

-20 °C...60 °C

0 °C...50 °C

No

in acc. with IEC 60332-1

CULUS

System cable

Cat.7 (ISO/IEC 11801)

S/FTP

4*2*AWG 27/7 - 4*2*0.1 mm²

5.9 mm

LSZH

blue (RAL 5015)

1.04 mm

50 mm

25 mm

-20 °C...60 °C

0 °C...50 °C

No

in acc. with IEC 60332-1

CULUS

Type Qty. Order No.

IE-C7FS8LD-305M 1 1273090000

Type Qty. Order No.

IE-C7FS8LB-305M 1 1326540000

Type Qty. Order No.

AM 12 1 9030060000

Type Qty. Order No.

IE-CST 1 9204350000

VT SF 5/21 MC NE WS VO 160 1689470001

VT SF 5/21 MC NE WS VO 160 1689470001

VT SF 6/21 MC NE WS VO 160 1730560001

VT SF 6/21 MC NE WS VO 160 1730560001

TM1 12 MC NE GE 320 1718411687

TM1 12 MC NE GE 320 1718411687

TM1 18 MC NE GE 320 1718431687

TM1 18 MC NE GE 320 1718431687

TM 4/12 HF/HB 500 1719840000

TM 4/12 HF/HB 500 1719840000

TM 4/18 HF/HB 500 1719850000


TM 4/18 HF/HB 500 1719850000

Note


Note

Note


LSZH black



LSZH green



LSZH red



System cable
Cat.7 (ISO/IEC 11801)
S/FTP
4*2*AWG 27/7 - 4*2*0.1 mm ²
5.9 mm
LSZH
black
1.04 mm
50 mm
25 mm
-20 °C...60 °C
0 °C...50 °C
No
in acc. with IEC 60332-1



Type	Qty.	Order No.
IE-C7FS8LE-305M	1	1344690000

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001
TM1 12 MC NE GE	320	1718411687
TM1 18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

System cable
Cat.7 (ISO/IEC 11801)
S/FTP
4*2*AWG 27/7 - 4*2*0.1 mm ²
5.9 mm
LSZH
green
1.04 mm
50 mm
25 mm
-20 °C...60 °C
0 °C...50 °C
No
in acc. with IEC 60332-1



Type	Qty.	Order No.
IE-C7FS8LG-305M	1	1344680000

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001
TM1 12 MC NE GE	320	1718411687
TM1 18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

System cable
Cat.7 (ISO/IEC 11801)
S/FTP
4*2*AWG 27/7 - 4*2*0.1 mm ²
5.9 mm
LSZH
red
1.04 mm
50 mm
25 mm
-20 °C...60 °C
0 °C...50 °C
No
in acc. with IEC 60332-1



Type	Qty.	Order No.
IE-C7FS8LR-305M	1	1287910000

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001
TM1 12 MC NE GE	320	1718411687
TM1 18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

Raw cables – Connection cable

Raw cables



Connecting cable Cat. 7

- 305 m / 1,000 ft

LSZH magenta



LSZH violet



Technical data

Product type

Category

Shielding

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Ambient temperature (operational)

Installation temperature

Halogen

Resistance to spread of flame

Resistance to oils

Approvals

Note

Ordering data

305 m / 1000 ft

Note

Accessories

Tools

Sheathing strippers, For UTP and STP data cables
Sheathing strippers, For coaxial and round data cables

Marking tags

Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm
Transparent sleeves, 12-mm length
Transparent sleeves, 18-mm length
Wire and cable markers, ø 4.7 - 7.4 mm
Wire and cable markers, ø 5.8 - 7.8 mm

System cable

Cat.7 (ISO/IEC 11801)

S/FTP

4*2*AWG 27/7 - 4*2*0.1 mm²

5.9 mm

LSZH

Magenta

1.04 mm

50 mm

25 mm

-20 °C...60 °C

0 °C...50 °C

No

in acc. with IEC 60332-1

CULUS

System cable

Cat.7 (ISO/IEC 11801)

S/FTP

4*2*AWG 27/7 - 4*2*0.1 mm²

5.9 mm

LSZH

violet

1.04 mm

50 mm

25 mm

-20 °C...60 °C

0 °C...50 °C

No

in acc. with IEC 60332-1

CULUS

Type Qty. Order No.

IE-C7FS8LM-305M 1 1333160000

Type Qty. Order No.

IE-C7FS8LV-305M 1 2779910000

Type Qty. Order No.

AM 12 1 9030060000

Type Qty. Order No.

IE-CST 1 9204350000

TMH 12 MC NE GE 320 1718411687

TMH 12 MC NE GE 320 1718411687

TMH 18 MC NE GE 320 1718431687

TMH 18 MC NE GE 320 1718431687

TM 4/12 HF/HB 500 1719840000

TM 4/12 HF/HB 500 1719840000

TM 4/18 HF/HB 500 1719850000

TM 4/18 HF/HB 500 1719850000

VT SF 5/21 MC NE WS VO 160 1689470001

VT SF 5/21 MC NE WS VO 160 1689470001

VT SF 6/21 MC NE WS VO 160 1730560001

VT SF 6/21 MC NE WS VO 160 1730560001



Note

Note

Note

Raw cables**Connecting cable Cat. 7**

- 305 m / 1,000 ft

LSZH yellow**LZSH orange****Technical data****Product type**

Category

Shielding

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Ambient temperature (operational)

Installation temperature

Halogen

Resistance to spread of flame

Resistance to oils

Approvals

Note**Ordering data**

305 m / 1000 ft

Note**Accessories****Tools**

Sheathing strippers, For UTP and STP data cables

Sheathing strippers, For coaxial and round data cables

Marking tags

Insertion label, yellow, 12 mm

Insertion label, yellow, 18 mm

Transparent sleeves, 12-mm length

Transparent sleeves, 18-mm length

Wire and cable markers, ø 4.7 - 7.4 mm

Wire and cable markers, ø 5.8 - 7.8 mm

System cable

Cat.7 (ISO/IEC 11801)

S/FTP

4*2*AWG 27/7 - 4*2*0.1 mm²

5.9 mm

LSZH

yellow

1.04 mm

50 mm

25 mm

-20 °C...60 °C

0 °C...50 °C

No

in acc. with IEC 60332-1

CULUS**System cable**

Cat.7 (ISO/IEC 11801)

S/FTP

4*2*AWG 27/7 - 4*2*0.1 mm²

5.9 mm

LSZH

orange

1.04 mm

50 mm

25 mm

-20 °C...60 °C

0 °C...50 °C

No

in acc. with IEC 60332-1

Type **Qty.** **Order No.**

IE-C7FS8LY-305M 1 1344670000

Type **Qty.** **Order No.**

IE-C7FS8LO-305M 1 2661080000

Type **Qty.** **Order No.**

AM 12 1 9030060000

IE-CST 1 9204350000

Type **Qty.** **Order No.**

AM 12 1 9030060000

IE-CST 1 9204350000

TMH 12 MC NE GE 320 1718411687

TMH 18 MC NE GE 320 1718431687

TM 4/12 HF/HB 500 1719840000

TM 4/18 HF/HB 500 1719850000

VT SF 5/21 MC NE WS VO 160 1689470001

VT SF 6/21 MC NE WS VO 160 1730560001

TMH 12 MC NE GE 320 1718411687

TMH 18 MC NE GE 320 1718431687

TM 4/12 HF/HB 500 1719840000

TM 4/18 HF/HB 500 1719850000

VT SF 5/21 MC NE WS VO 160 1689470001

VT SF 6/21 MC NE WS VO 160 1730560001

Note

Raw cables – Dragline cable

Raw cables



Dragline cable Cat. 5

- In lengths from 100, 500 or 1000 metres

PUR green



PUR blue



Technical data

Product type

Dragline cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

4*2*AWG 26/7 - 4*2*0.128 mm²

6.8 mm

PUR

green (RAL 6018)

0.95 mm

7.5 x cable diameter

4 x cable diameter

5 Mio

-40 °C...80 °C

-20 °C...60 °C

-40 °C...80 °C

very good

halogen-free, according to IEC 60754-2

in acc. with IEC 60332-1

in acc. with IEC 60811-2-1

UL-Style 20963 (80°C/30V)

Resistance to spread of flame

Resistance to oils

Standard, assembly

Approvals

Note

Ordering data

100.0 m

500.0 m

1000.0 m

Note

Accessories

Tools

Sheathing strippers, For UTP and STP data cables

Sheathing strippers, For coaxial and round data cables

Marking tags

Wire and cable markers. ø 4.7 - 7.4 mm

Wire and cable markers. ø 5.8 - 7.8 mm

Insertion label, yellow. 12 mm

Insertion label, yellow. 18 mm

Transparent sleeves. 12-mm length

Transparent sleeves. 18-mm length

Type	Qty.	Order No.
IE-C5ED8UG-100	1	8813210000
IE-C5ED8UG-500	1	2763490000
IE-C5ED8UG-1000	1	2781890000

Type	Qty.	Order No.
IE-C5ED8UB-100	1	8960670000
IE-C5ED8UB-500	1	2763480000
IE-C5ED8UB-1000	1	2781880000

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001
TM-12 MC NE GE	320	1718411687
TM-18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000



Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001
TM-12 MC NE GE	320	1718411687
TM-18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

Note



Raw cables**PROFINET cable**

- In lengths from 100 or 500 metres

Installation cable type A, PVC**Connection cable type B, PVC****Technical data****Product type**

Category

Shielding

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Ambient temperature (operational)

Installation temperature

Storage temperature

Abrasion resistance

Resistance to spread of flame

Standard, assembly

Approvals

Note**Ordering data**

100.0 m

500.0 m

Note**Accessories****Tools**

Sheathing strippers, For UTP and STP data cables
Sheathing strippers, For coaxial and round data cables

Marking tags

Wire and cable markers. ø 4.7 - 7.4 mm
Wire and cable markers. ø 5.8 - 7.8 mm
Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm
Transparent sleeves, 12-mm length
Transparent sleeves, 18-mm length

Installation cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

4*AWG 22/1 - 0.33 mm²

6.7 mm

PVC

green (RAL 6018)

1.5 mm

7.5 x cable diameter

3.5 *diameter

-40 °C...75 °C

-20 °C...60 °C

40 °C...75 °C

good

in acc. with IEC 60332-1 / UL 1685

UL-Style 21694

System cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

4*AWG 22/7 - 0.36 mm²

6.7 mm

PVC

green (RAL 6018)

1.5 mm

7.5 x cable diameter

3.5 *diameter

-40 °C...70 °C

-20 °C...60 °C

40 °C...70 °C

good

in acc. with IEC 60332-1 / UL 1685

UL-Style 21694

Type Qty. Order No.

IE-C5AS4VG-100 1 8899000000

IE-C5AS4VG-500 1 2763430000

Type Qty. Order No.

IEC5DS4VG-100 1 8898990000

IE-C5DS4VG-500 1 2763470000

Type Qty. Order No.

AM 12 1 9030060000

IE-CST 1 9204350000

Type Qty. Order No.

AM 12 1 9030060000

IE-CST 1 9204350000

VT SF 5/21 MC NE WS VO 160 1689470001

VT SF 6/21 MC NE WS VO 160 1730560001

TMH 12 MC NE GE 320 1718411687

TMH 18 MC NE GE 320 1718431687

TM 4/12 HF/HB 500 1719840000

TM 4/18 HF/HB 500 1719850000

VT SF 5/21 MC NE WS VO 160 1689470001

VT SF 6/21 MC NE WS VO 160 1730560001

TMH 12 MC NE GE 320 1718411687

TMH 18 MC NE GE 320 1718431687

TM 4/12 HF/HB 500 1719840000

TM 4/18 HF/HB 500 1719850000

Note

Raw cables – PROFINET cable


Raw cables

PROFINET cable


- In lengths from 100 or 500 metres



Dragline cable type C, PUR



Torsion cable type C, PUR



Technical data

Product type

Category

Shielding

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Bending cycles

Torsion cycles

Torsion resistance

Ambient temperature (operational)

Installation temperature

Storage temperature

Abrasion resistance

Halogen

Resistance to spread of flame

Resistance to oils

Standard, assembly

Approvals

Note

Dragline cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

4*AWG 22/7 - 0.36 mm²

6.7 mm

PUR

green (RAL 6018)

1.5 mm

7.5 x cable diameter

5 x cable diameter

3 Mio

-40 °C...70 °C

-20 °C...60 °C

-50 °C...70 °C

very good

halogen-free, according to IEC 60754-2

in acc. with IEC 60332-1

in acc. with IEC 60811-2-1

Torsion cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

S/UTP

4*AWG 22/19 - 0.38 mm²

6.7 mm

PUR

green (RAL 6018)

1.5 mm

10 x cable diameter

5 x cable diameter

1 mill.

180 °/m

-40 °C...80 °C

-40 °C...80 °C

-40 °C...80 °C

very good

halogen-free, according to IEC 60754-2

in acc. with IEC 60332-1

in acc. with IEC 60811-2-1

UL Style 21161

Ordering data

Cat. 5 PROFINET. PUR

100.0 m

500.0 m

Note

Type

Qty.

Order No.

IE-C5DD4UG-100 1 8899010000

IE-C5DD4UG-500 1 2763450000

Type

Qty.

Order No.

IE-C5IT4UG-100 1 2764770000

IE-C5IT4UG-500 1 2763520000

Accessories

Tools

Sheathing strippers, For UTP and STP data cables
Sheathing strippers, For coaxial and round data cables

Marking tags

Wire and cable markers. ø 4.7 - 7.4 mm
Wire and cable markers. ø 5.8 - 7.8 mm
Insertion label, yellow. 12 mm
Insertion label, yellow. 18 mm
Transparent sleeves. 12-mm length
Transparent sleeves. 18-mm length

Type

Qty.

Order No.

AM 12 1 9030060000

IE-CST 1 9204350000

VT SF 5/21 MC NE WS VO 160 1689470001

VT SF 6/21 MC NE WS VO 160 1730560001

TM-I 12 MC NE GE 320 1718411687

TM-I 18 MC NE GE 320 1718431687

TM 4/12 HF/HB 500 1719840000

TM 4/18 HF/HB 500 1719850000

Type

Qty.

Order No.

AM 12 1 9030060000

IE-CST 1 9204350000

VT SF 5/21 MC NE WS VO 160 1689470001

VT SF 6/21 MC NE WS VO 160 1730560001

TM-I 12 MC NE GE 320 1718411687

TM-I 18 MC NE GE 320 1718431687

TM 4/12 HF/HB 500 1719840000

TM 4/18 HF/HB 500 1719850000


Note

Raw cables

Hybrid cable

- In lengths from 100 or 500 metres

PVC



Technical data

Product type

Category

Shielding

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Ambient temperature (operational)

Installation temperature

Storage temperature

Abrasion resistance

Halogen

Resistance to spread of flame

Resistance to oils

Standard, assembly

Approvals

Note

System cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

4*AWG 22/7 - 0.36 mm², 6*0.5 mm²

9.5 mm

PVC

green (RAL 6018)

1.5 mm / 1.75 mm

7.5 x cable diameter

3.5 *diameter

-30 °C...75 °C

0 °C...50 °C

40 °C...70 °C

good

Yes

in acc. with IEC 60332-1 / UL 1685

limited

Ordering data

100.0 m

500.0 m

Note

Type	Qty.	Order No.
IE-C5DHAG-100	1	2763660000
IE-C5DHAG-500	1	2763460000

Accessories

Tools

Sheathing strippers, For UTP and STP data cables
Sheathing strippers, For coaxial and round data cables

Marking tags

Wire and cable markers. ø 4.7 - 7.4 mm	160	1689470001
Wire and cable markers. ø 5.8 - 7.8 mm	160	1730560001
Insertion label, yellow. 12 mm	320	1718411687
Insertion label, yellow. 18 mm	320	1718431687
Transparent sleeves. 12-mm length	500	1719840000
Transparent sleeves. 18-mm length	500	1719850000

Note

Assembled cables - Patch cable**Assembled cables****Patch cable CabinetLine Cat. 6 straight****LSZH grey**

RJ45	1	white (orange)	1	RJ45
	2	orange	2	
	3	white (green)	3	
	4	blue	4	
	5	white (blue)	5	
	6	green	6	
	7	white (brown)	7	
	8	brown	8	

Technical data

Product type

Category

Shielding

Version connector left / Version connector right

Connector standard

PoE / PoE+

Cross-section

Sheath diameter, max.

Material sheath

Colour

Insulation diameter

Min. bending radius, repetitive / Min. bending radius, once only

Ambient temperature (operational)

Installation temperature

Storage temperature

Halogen

Resistance to spread of flame

Approvals

Note

Patch cable

Cat.6A / Class E_A (ISO/IEC 11801 2010)

S/FTP

RJ45 IP 20 / RJ45 IP 20

IEC 60603-7-51

conforming to IEEE 802.3at

4*2*AWG 27/7 - 4*2*0.1 mm²

5.9 mm

LSZH

grey

1.04 mm

50 mm / 25 mm

-20 °C...60 °C

0 °C...50 °C

-20 °C...60 °C

halogen-free, according to IEC 60754-2

in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)

CULUS

Ordering data

0.2 m

0.5 m

1.0 m

1.5 m

2.0 m

3.0 m

5.0 m

7.5 m

10.0 m

15.0 m

20.0 m

25.0 m

Note

Type	Qty.	Order No.
IE-C6FP8LD0002M40M40-D	1	1165940002
IE-C6FP8LD0005M40M40-D	1	1165940005
IE-C6FP8LD0010M40M40-D	1	1165940010
IE-C6FP8LD0015M40M40-D	1	1165940015
IE-C6FP8LD0020M40M40-D	1	1165940020
IE-C6FP8LD0030M40M40-D	1	1165940030
IE-C6FP8LD0050M40M40-D	1	1165940050
IE-C6FP8LD0075M40M40-D	1	1165940075
IE-C6FP8LD0100M40M40-D	1	1165940100
IE-C6FP8LD0150M40M40-D	1	1165940150
IE-C6FP8LD0200M40M40-D	1	1165940200
IE-C6FP8LD0250M40M40-D	1	1165940250

Other lengths available on request

Accessories**Tools**

Sheathing strippers, For UTP and STP data cables

Sheathing strippers, For coaxial and round data cables

Marking tags

Insertion label, yellow, 12 mm

Insertion label, yellow, 18 mm

Dust protection cap

Protective cap

Cable routing

90° outlet angle

Note

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TM-H 12 MC NE GE	320	1718411687
TM-H 18 MC NE GE	320	1718431687
IE-PP-RJ45	10	2552580000
IE-CABLE-BENDER-90	50	2704480000

Assembled cables**Patch cable CabinetLine Cat. 6 straight****LSZH blue****LSZH black**

RJ45	1	white (orange)	1	RJ45
	2	orange	2	
	3	white (green)	3	
	4	blue	4	
	5	white (blue)	5	
	6	green	6	
	7	white (brown)	7	
	8	brown	8	

RJ45	1	white (orange)	1	RJ45
	2	orange	2	
	3	white (green)	3	
	4	blue	4	
	5	white (blue)	5	
	6	green	6	
	7	white (brown)	7	
	8	brown	8	

Technical data

Product type	Patch cable
Category	Cat.6A / Class E _A (ISO/IEC 11801 2010)
Shielding	S/FTP
Version connector left / Version connector right	RJ45 IP 20 / RJ45 IP 20
Connector standard	IEC 60603-7-51
PoE / PoE+	conforming to IEEE 802.3at
Cross-section	4*2*AWG 27/7 - 4*2*0.1 mm ²
Sheath diameter, max.	5.9 mm
Material sheath	LSZH
Colour	blue
Insulation diameter	1.04 mm
Min. bending radius, repetitive	50 mm
Min. bending radius, once only	25 mm
Ambient temperature (operational)	-20 °C...60 °C
Installation temperature	0 °C...50 °C
Storage temperature	-20 °C...60 °C
Halogen	halogen-free, according to IEC 60754-2
Resistance to spread of flame	in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)
Approvals	CULUS

Note**Ordering data**

0.2 m	
0.5 m	
1.0 m	
1.5 m	
2.0 m	
3.0 m	
5.0 m	
10.0 m	
15.0 m	
20.0 m	
25.0 m	

Note**Accessories**

Tools	Type	Qty.	Order No.
Sheathing strippers, For UTP and STP data cables	AM 12	1	9030060000
Sheathing strippers, For coaxial and round data cables	IE-CST	1	9204350000
Marking tags			
	TMH 12 MC NE GE	320	1718411687
	TMH 18 MC NE GE	320	1718431687
Dust protection cap	IE-PP-RJ45	10	2552580000
Cable routing	IE-CABLE-BENDER-90	50	2704480000
Note			

Patch cable	Cat.6A / Class E _A (ISO/IEC 11801 2010)
S/FTP	
RJ45 IP 20 / RJ45 IP 20	
IEC 60603-7-51	
conforming to IEEE 802.3at	
4*2*AWG 27/7 - 4*2*0.1 mm ²	
5.9 mm	
LSZH	
blue	
1.04 mm	
50 mm	
25 mm	
-20 °C...60 °C	
0 °C...50 °C	
-20 °C...60 °C	
halogen-free, according to IEC 60754-2	
in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)	
CULUS	

Patch cable	Cat.6A / Class E _A (ISO/IEC 11801 2010)
S/FTP	
RJ45 IP 20 / RJ45 IP 20	
IEC 60603-7-51	
conforming to IEEE 802.3at	
4*2*AWG 27/7 - 4*2*0.1 mm ²	
5.9 mm	
LSZH	
black	
1.04 mm	
50 mm	
25 mm	
-20 °C...60 °C	
0 °C...50 °C	
-20 °C...60 °C	
halogen-free, according to IEC 60754-2	
in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)	
CULUS	

Type	Qty.	Order No.
IE-C6FP8LE0002M40M40-B	1	1165900002
IE-C6FP8LB0005M40M40-B	1	1165900005
IE-C6FP8LB0010M40M40-B	1	1165900010
IE-C6FP8LB0015M40M40-B	1	1165900015
IE-C6FP8LB0020M40M40-B	1	1165900020
IE-C6FP8LB0030M40M40-B	1	1165900030
IE-C6FP8LB0050M40M40-B	1	1165900050
IE-C6FP8LB0100M40M40-B	1	1165900100
IE-C6FP8LB0150M40M40-B	1	1165900150
IE-C6FP8LB0200M40M40-B	1	1165900200
IE-C6FP8LB0250M40M40-B	1	1165900250

Type	Qty.	Order No.
IE-C6FP8LE0002M40M40-E	1	1251610002
IE-C6FP8LE0005M40M40-E	1	1251610005
IE-C6FP8LE0010M40M40-E	1	1251610010
IE-C6FP8LE0015M40M40-E	1	1251610015
IE-C6FP8LE0020M40M40-E	1	1251610020
IE-C6FP8LE0030M40M40-E	1	1251610030
IE-C6FP8LE0050M40M40-E	1	1251610050
IE-C6FP8LE0100M40M40-E	1	1251610100
IE-C6FP8LE0150M40M40-E	1	1251610150
IE-C6FP8LE0200M40M40-E	1	1251610200
IE-C6FP8LE0250M40M40-E	1	1251610250

Assembled cables - Patch cable**Assembled cables****Patch cable CabinetLine Cat. 6 straight****LSZH green****LSZH red**

RJ45	1	white (orange)	1	RJ45
	2	orange	2	
	3	white (green)	3	
	4	blue	4	
	5	white (blue)	5	
	6	green	6	
	7	white (brown)	7	
	8	brown	8	

RJ45	1	white (orange)	1	RJ45
	2	orange	2	
	3	white (green)	3	
	4	blue	4	
	5	white (blue)	5	
	6	green	6	
	7	white (brown)	7	
	8	brown	8	

Technical data

Product type	Patch cable
Category	Cat.6A / Class E _A (ISO/IEC 11801 2010)
Shielding	S/FTP
Version connector left / Version connector right	RJ45 IP 20 / RJ45 IP 20
Connector standard	IEC 60603-7-51
PoE / PoE+	conforming to IEEE 802.3at
Cross-section	4*2*AWG 27/7 - 4*2*0.1 mm ²
Sheath diameter, max.	5.9 mm
Material sheath	LSZH
Colour	green
Insulation diameter	1.04 mm
Min. bending radius, repetitive	50 mm
Min. bending radius, once only	25 mm
Ambient temperature (operational)	-20 °C...60 °C
Installation temperature	0 °C...50 °C
Storage temperature	-20 °C...60 °C
Halogen	halogen-free, according to IEC 60754-2
Resistance to spread of flame	in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)
Approvals	CULUS

Note**Ordering data**

Type	Qty.	Order No.
IE-C6FP8LG0002M40M40-G	1	1251590002
IE-C6FP8LG0005M40M40-G	1	1251590005
IE-C6FP8LG0010M40M40-G	1	1251590010
IE-C6FP8LG0015M40M40-G	1	1251590015
IE-C6FP8LG0020M40M40-G	1	1251590020
IE-C6FP8LG0030M40M40-G	1	1251590030
IE-C6FP8LG0050M40M40-G	1	1251590050
IE-C6FP8LG0100M40M40-G	1	1251590100
IE-C6FP8LG0150M40M40-G	1	1251590150
IE-C6FP8LG0200M40M40-G	1	1251590200
IE-C6FP8LG0250M40M40-G	1	1251590250

Note

Patch cable	Cat.6A / Class E _A (ISO/IEC 11801 2010)
S/FTP	RJ45 IP 20 / RJ45 IP 20
IEC 60603-7-51	IEC 60603-7-51
conforming to IEEE 802.3at	conforming to IEEE 802.3at
4*2*AWG 27/7 - 4*2*0.1 mm ²	4*2*AWG 27/7 - 4*2*0.1 mm ²
5.9 mm	5.9 mm
LSZH	LSZH
green	red
1.04 mm	1.04 mm
50 mm	50 mm
25 mm	25 mm
-20 °C...60 °C	-20 °C...60 °C
0 °C...50 °C	0 °C...50 °C
-20 °C...60 °C	-20 °C...60 °C
halogen-free, according to IEC 60754-2	halogen-free, according to IEC 60754-2
in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)	in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)
CULUS	CULUS

Type	Qty.	Order No.
IE-C6FP8LR0002M40M40-R	1	1166030002
IE-C6FP8LR0005M40M40-R	1	1166030005
IE-C6FP8LR0010M40M40-R	1	1166030010
IE-C6FP8LR0015M40M40-R	1	1166030015
IE-C6FP8LR0020M40M40-R	1	1166030020
IE-C6FP8LR0030M40M40-R	1	1166030030
IE-C6FP8LR0050M40M40-R	1	1166030050
IE-C6FP8LR0100M40M40-R	1	1166030100
IE-C6FP8LR0150M40M40-R	1	1166030150
IE-C6FP8LR0200M40M40-R	1	1166030200
IE-C6FP8LR0250M40M40-R	1	1166030250

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TMH 12 MC NE GE	320	1718411687
TMH 18 MC NE GE	320	1718431687
IE-PP-RJ45	10	2552580000
IE-CABLE-BENDER-90	50	2704480000
IE-CABLE-BENDER-90	50	2704480000

Assembled cables**Patch cable CabinetLine Cat. 6 straight****LSZH magenta****LSZH violet**

RJ45	1	white (orange)	1	RJ45
	2	orange	2	
	3	white (green)	3	
	4	blue	4	
	5	white (blue)	5	
	6	green	6	
	7	white (brown)	7	
	8	brown	8	

RJ45	1	white (orange)	1	RJ45
	2	orange	2	
	3	white (green)	3	
	4	blue	4	
	5	white (blue)	5	
	6	green	6	
	7	white (brown)	7	
	8	brown	8	

Technical data

Product type	Patch cable
Category	Cat.6 _A / Class E _A (ISO/IEC 11801 2010)
Shielding	S/FTP
Version connector left / Version connector right	RJ45 IP 20 / RJ45 IP 20
Connector standard	IEC 60603-7-51
PoE / PoE+	conforming to IEEE 802.3at
Cross-section	4*2*AWG 27/7 - 4*2*0.1 mm ²
Sheath diameter, max.	5.9 mm
Material sheath	LSZH
Colour	Magenta
Insulation diameter	1.04 mm
Min. bending radius, repetitive	50 mm
Min. bending radius, once only	25 mm
Ambient temperature (operational)	-20 °C...60 °C
Installation temperature	0 °C...50 °C
Storage temperature	-20 °C...60 °C
Halogen	halogen-free, according to IEC 60754-2
Resistance to spread of flame	in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)
Approvals	CULUS

Note**Ordering data**

0.2 m	
0.5 m	
1.0 m	
1.5 m	
2.0 m	
3.0 m	
5.0 m	
10.0 m	
15.0 m	
20.0 m	
25.0 m	

Note**Accessories**

Tools	Type	Qty.	Order No.
Sheathing strippers, For UTP and STP data cables	AM 12	1	9030060000
Sheathing strippers, For coaxial and round data cables	IE-CST	1	9204350000
Marking tags			
	TMH 12 MC NE GE	320	1718411687
	Insertion label, yellow, 12 mm		
	TMH 18 MC NE GE	320	1718431687
	Insertion label, yellow, 18 mm		
Dust protection cap			
	IE-PP-RJ45	10	2552580000
Cable routing			
	IE-CABLE-BENDER-90	50	2704480000
Note			

Patch cable	Cat.6 _A / Class E _A (ISO/IEC 11801 2010)
S/FTP	
RJ45 IP 20 / RJ45 IP 20	
IEC 60603-7-51	
conforming to IEEE 802.3at	
4*2*AWG 27/7 - 4*2*0.1 mm ²	
5.9 mm	
LSZH	
Magenta	
1.04 mm	
50 mm	
25 mm	
-20 °C...60 °C	
0 °C...50 °C	
-20 °C...60 °C	
halogen-free, according to IEC 60754-2	
in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)	
CULUS	

Patch cable	Cat.6 _A / Class E _A (ISO/IEC 11801 2010)
S/FTP	
RJ45 IP 20 / RJ45 IP 20	
IEC 60603-7-51	
conforming to IEEE 802.3at	
4*2*AWG 27/7 - 4*2*0.1 mm ²	
5.9 mm	
LSZH	
violet	
1.04 mm	
50 mm	
25 mm	
-20 °C...60 °C	
0 °C...50 °C	
-20 °C...60 °C	
halogen-free, according to IEC 60754-2	
in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)	
CULUS	

Type	Qty.	Order No.
IE-C6FP8LM0002M40M40-M	1	1201270002
IE-C6FP8LM0005M40M40-M	1	1201270005
IE-C6FP8LM0010M40M40-M	1	1201270010
IE-C6FP8LM0015M40M40-M	1	1201270015
IE-C6FP8LM0020M40M40-M	1	1201270020
IE-C6FP8LM0030M40M40-M	1	1201270030
IE-C6FP8LM0050M40M40-M	1	1201270050
IE-C6FP8LM0100M40M40-M	1	1201270100
IE-C6FP8LM0150M40M40-M	1	1201270150
IE-C6FP8LM0200M40M40-M	1	1201270200

Type	Qty.	Order No.
IE-C6FP8LV0002M40M40-V	1	2701550002
IE-C6FP8LV0005M40M40-V	1	2701550005
IE-C6FP8LV0010M40M40-V	1	2701550010
IE-C6FP8LV0015M40M40-V	1	2701550015
IE-C6FP8LV0020M40M40-V	1	2701550020
IE-C6FP8LV0030M40M40-V	1	2701550030
IE-C6FP8LV0050M40M40-V	1	2701550050
IE-C6FP8LV0100M40M40-V	1	2701550100
IE-C6FP8LV0150M40M40-V	1	2701550150
IE-C6FP8LV0200M40M40-V	1	2701550200

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TMH 12 MC NE GE	320	1718411687
TMH 18 MC NE GE	320	1718431687
Insertion label, yellow, 12 mm		
IE-PP-RJ45	10	2552580000
IE-CABLE-BENDER-90	50	2704480000
Note		

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TMH 12 MC NE GE	320	1718411687
TMH 18 MC NE GE	320	1718431687
IE-PP-RJ45	10	2552580000
IE-CABLE-BENDER-90	50	2704480000
Note		

Assembled cables - Patch cable**Assembled cables****Patch cable CabinetLine Cat. 6 straight****LSZH yellow****LSZH orange**

RJ45	1	white (orange)	1	RJ45
	2	orange	2	
	3	white (green)	3	
	4	blue	4	
	5	white (blue)	5	
	6	green	6	
	7	white (brown)	7	
	8	brown	8	

RJ45	1	white (orange)	1	RJ45
	2	orange	2	
	3	white (green)	3	
	4	blue	4	
	5	white (blue)	5	
	6	green	6	
	7	white (brown)	7	
	8	brown	8	

Technical data

Product type	Patch cable
Category	Cat.6A / Class E _A (ISO/IEC 11801 2010)
Shielding	S/FTP
Version connector left / Version connector right	RJ45 IP 20 / RJ45 IP 20
Connector standard	IEC 60603-7-51
PoE / PoE+	conforming to IEEE 802.3at
Cross-section	4*2*AWG 27/7 - 4*2*0.1 mm ²
Sheath diameter, max.	5.9 mm
Material sheath	LSZH
Colour	yellow
Insulation diameter	1.04 mm
Min. bending radius, repetitive	50 mm
Min. bending radius, once only	25 mm
Ambient temperature (operational)	-20 °C...60 °C
Installation temperature	0 °C...50 °C
Storage temperature	-20 °C...60 °C
Halogen	halogen-free, according to IEC 60754-2
Resistance to spread of flame	in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)
Approvals	CULUS

Note**Ordering data**

0.2 m
0.5 m
1.0 m
1.5 m
2.0 m
3.0 m
5.0 m
10.0 m
15.0 m
20.0 m
25.0 m

Note**Accessories**

Tools	Type	Qty.	Order No.
Sheathing strippers, For UTP and STP data cables	AM 12	1	9030060000
Sheathing strippers, For coaxial and round data cables	IE-CST	1	9204350000
Marking tags			
	TMH 12 MC NE GE	320	1718411687
	TMH 18 MC NE GE	320	1718431687
Dust protection cap			
	IE-PP-RJ45	10	2552580000
Cable routing			
	IE-CABLE-BENDER-90	50	2704480000
Note			

Patch cable
Cat.6A / Class E _A (ISO/IEC 11801 2010)
S/FTP
RJ45 IP 20 / RJ45 IP 20
IEC 60603-7-51
conforming to IEEE 802.3at
4*2*AWG 27/7 - 4*2*0.1 mm ²
5.9 mm
LSZH
yellow
1.04 mm
50 mm
25 mm
-20 °C...60 °C
0 °C...50 °C
-20 °C...60 °C
halogen-free, according to IEC 60754-2
in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)

Patch cable
Cat.6A / Class E _A (ISO/IEC 11801 2010)
S/FTP
RJ45 IP 20 / RJ45 IP 20
IEC 60603-7-51
conforming to IEEE 802.3at
4*2*AWG 27/7 - 4*2*0.1 mm ²
5.9 mm
LSZH
orange
1.04 mm
50 mm
25 mm
-20 °C...60 °C
0 °C...50 °C
-20 °C...60 °C
halogen-free, according to IEC 60754-2
in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)

Type	Qty.	Order No.
IE-C6FP8LY0002M40M40-Y	1	1251580002
IE-C6FP8LY0005M40M40-Y	1	1251580005
IE-C6FP8LY0010M40M40-Y	1	1251580010
IE-C6FP8LY0015M40M40-Y	1	1251580015
IE-C6FP8LY0020M40M40-Y	1	1251580020
IE-C6FP8LY0030M40M40-Y	1	1251580030
IE-C6FP8LY0050M40M40-Y	1	1251580050
IE-C6FP8LY0100M40M40-Y	1	1251580100
IE-C6FP8LY0150M40M40-Y	1	1251580150
IE-C6FP8LY0200M40M40-Y	1	1251580200
IE-C6FP8LY0250M40M40-Y	1	1251580250

Type	Qty.	Order No.
IE-C6FP8L0002M40M40-0	1	2563810002
IE-C6FP8L0005M40M40-0	1	2563810005
IE-C6FP8L0010M40M40-0	1	2563810010
IE-C6FP8L0015M40M40-0	1	2563810015
IE-C6FP8L0020M40M40-0	1	2563810020
IE-C6FP8L0030M40M40-0	1	2563810030
IE-C6FP8L0050M40M40-0	1	2563810050
IE-C6FP8L0100M40M40-0	1	2563810100
IE-C6FP8L0150M40M40-0	1	2563810150
IE-C6FP8L0200M40M40-0	1	2563810200
IE-C6FP8L0250M40M40-0	1	2563810250

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TMH 12 MC NE GE	320	1718411687
TMH 18 MC NE GE	320	1718431687
IE-PP-RJ45	10	2552580000
IE-CABLE-BENDER-90	50	2704480000

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TMH 12 MC NE GE	320	1718411687
TMH 18 MC NE GE	320	1718431687
IE-PP-RJ45	10	2552580000
IE-CABLE-BENDER-90	50	2704480000

Assembled cables**Patch cable CabinetLine Cat. 6 angled****LSZH grey 270°****LSZH grey 90°**

RJ45	1	white (orange)	1	RJ45
	2	orange	2	
	3	white (green)	3	
	4	blue	4	
	5	white (blue)	5	
	6	green	6	
	7	white (brown)	7	
	8	brown	8	

RJ45	1	white (orange)	1	RJ45
	2	orange	2	
	3	white (green)	3	
	4	blue	4	
	5	white (blue)	5	
	6	green	6	
	7	white (brown)	7	
	8	brown	8	

Technical data

Product type	Patch cable
Category	Cat.6A / Class E _A (ISO/IEC 11801 2010)
Shielding	S/FTP
Version connector left / Version connector right	RJ45 IP 20, Angled 270° / RJ45 IP 20
Connector standard	IEC 60603-7-51
PoE / PoE+	conforming to IEEE 802.3at
Cross-section	4*2*AWG 27/7 - 4*2*0.1 mm ²
Sheath diameter, max.	5.9 mm
Material sheath	LSZH
Colour	grey
Insulation diameter	1.04 mm
Min. bending radius, repetitive	50 mm
Min. bending radius, once only	25 mm
Ambient temperature (operational)	-20 °C...60 °C
Installation temperature	0 °C...50 °C
Storage temperature	-20 °C...60 °C
Halogen	halogen-free, according to IEC 60754-2
Resistance to spread of flame	in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)
Approvals	CULUS

Note**Ordering data**

0.5 m
1.0 m
1.2 m
1.5 m
2.0 m
3.0 m
5.0 m
10.0 m

Note**Accessories**

Tools	Sheathing strippers, For UTP and STP data cables
	Sheathing strippers, For coaxial and round data cables
Marking tags	Insertion label, yellow, 12 mm
	Insertion label, yellow, 18 mm
Dust protection cap	Protective cap

Note

Type	Qty.	Order No.
IE-C6FP8LD0005M40W40-D	1	1233160005
IE-C6FP8LD0010M40W40-D	1	1233160010
IE-C6FP8LD0012M40W40-D	1	1233160012
IE-C6FP8LD0015M40W40-D	1	1233160015
IE-C6FP8LD0020M40W40-D	1	1233160020
IE-C6FP8LD0030M40W40-D	1	1233160030
IE-C6FP8LD0050M40W40-D	1	1233160050
IE-C6FP8LD0100M40W40-D	1	1233160100

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TM-1 12 MC NE GE	320	1718411687
TM-1 18 MC NE GE	320	1718431687
IE-PP-RJ45	10	2552580000

Type	Qty.	Order No.
IE-C6FP8LD0005M40V40-D	1	1248280005
IE-C6FP8LD0010M40V40-D	1	1248280010
IE-C6FP8LD0012M40V40-D	1	1248280012
IE-C6FP8LD0015M40V40-D	1	1248280015
IE-C6FP8LD0020M40V40-D	1	1248280020
IE-C6FP8LD0030M40V40-D	1	1248280030
IE-C6FP8LD0050M40V40-D	1	1248280050
IE-C6FP8LD0100M40V40-D	1	1248280100

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TM-1 12 MC NE GE	320	1718411687
TM-1 18 MC NE GE	320	1718431687
IE-PP-RJ45	10	2552580000

Assembled cables - Patch cable**Assembled cables****Patch cable CabinetLine Cat. 6 angled****LSZH 90° left****LSZH 90° right**

RJ45	1 white (orange)	2 orange	3 white (green)	4 blue	5 white (blue)	6 green	7 white (brown)	8 brown	RJ45

RJ45	1 white (orange)	2 orange	3 white (green)	4 blue	5 white (blue)	6 green	7 white (brown)	8 brown	RJ45

Technical data

Product type	Patch cable
Category	Cat.6A / Class E _A (ISO/IEC 11801 2010)
Shielding	S/FTP
Version connector left / Version connector right	RJ45 IP 20 / RJ45 IP 20, Angled 90° left
Connector standard	IEC 60603-7-51
PoE / PoE+	conforming to IEEE 802.3at
Cross-section	4*2*AWG 27/7 - 4*2*0.1 mm ²
Sheath diameter, max.	5.9 mm
Material sheath	LSZH
Colour	grey
Insulation diameter	1.04 mm
Min. bending radius, repetitive	50 mm
Min. bending radius, once only	25 mm
Ambient temperature (operational)	-20 °C...60 °C
Installation temperature	0 °C...50 °C
Storage temperature	-20 °C...60 °C
Halogen	halogen-free, according to IEC 60754-2
Resistance to spread of flame	in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)
Approvals	CULUS

Note**Ordering data**

0.5 m	
1.0 m	
1.2 m	
1.5 m	
2.0 m	
3.0 m	
5.0 m	
10.0 m	

Note**Accessories**

Tools	Sheathing strippers, For UTP and STP data cables
	Sheathing strippers, For coaxial and round data cables
Marking tags	Insertion label, yellow, 12 mm
	Insertion label, yellow, 18 mm
Dust protection cap	Protective cap

Note


Type	Qty.	Order No.
IE-C6FP8LD0005M40L40-D	1	2703320005
IE-C6FP8LD010M40L40-D	1	2703320010
IE-C6FP8LD0012M40L40-D	1	2703320012
IE-C6FP8LD0015M40L40-D	1	2703320015
IE-C6FP8LD0020M40L40-D	1	2703320020
IE-C6FP8LD0030M40L40-D	1	2703320030
IE-C6FP8LD0050M40L40-D	1	2703320050
IE-C6FP8LD0100M40L40-D	1	2703320100

Type	Qty.	Order No.
IE-C6FP8LD0005M40R40-D	1	2703330005
IE-C6FP8LD0010M40R40-D	1	2703330010
IE-C6FP8LD0012M40R40-D	1	2703330012
IE-C6FP8LD0015M40R40-D	1	2703330015
IE-C6FP8LD0020M40R40-D	1	2703330020
IE-C6FP8LD0030M40R40-D	1	2703330030
IE-C6FP8LD0050M40R40-D	1	2703330050
IE-C6FP8LD0100M40R40-D	1	2703330100

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TM-1 12 MC NE GE	320	1718411687
TM-1 18 MC NE GE	320	1718431687

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TM-1 12 MC NE GE	320	1718411687
TM-1 18 MC NE GE	320	1718431687

IE-PP-RJ45	10	2552580000
------------	----	------------

Assembled cables**Patch cable CabinetLine Cat. 6 crossover****LSZH grey****Technical data**

Product type
Category
Shielding
Version connector left / Version connector right
Connector standard
PoE / PoE+
Cross-section
Sheath diameter, max.
Material sheath
Colour
Insulation diameter
Min. bending radius, repetitive
Min. bending radius, once only
Ambient temperature (operational)
Installation temperature
Storage temperature
Halogen
Resistance to spread of flame

Approvals**Note****Ordering data**

0.3 m
0.4 m
0.5 m
1.0 m
2.0 m
3.0 m
5.0 m
10.0 m
15.0 m
20.0 m

Note**Accessories**

Tools
Sheathing strippers, For UTP and STP data cables
Sheathing strippers, For coaxial and round data cables
Marking tags
Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm
Dust protection cap
Protective cap
Cable routing
90° outlet angle

Note

Patch cable, crossover
Cat.6A / Class E _A (ISO/IEC 11801 2010)
S/FTP
RJ45 IP 20 / RJ45 IP 20
IEC 60603-7-51
conforming to IEEE 802.3at
4*2*AWG 27/7 - 4*2*0.1 mm ²
5.9 mm
LSZH
grey
1.04 mm
50 mm
25 mm
-20 °C...60 °C
0 °C...50 °C
-20 °C...60 °C
halogen-free, according to IEC 60754-2
in acc. with IEC 60332-2-2, in acc. with IEC 60332-1-2, in acc. with IEC 60332-3-24, in acc. with UL 2556 (FT1)

CULUS

Type	Qty.	Order No.
IE-C6FP8LD0003X40X40-Y	1	1312160003
IE-C6FP8LD0004X40X40-Y	1	1312160004
IE-C6FP8LD0005X40X40-Y	1	1312160005
IE-C6FP8LD0010X40X40-Y	1	1312160010
IE-C6FP8LD0020X40X40-Y	1	1312160020
IE-C6FP8LD0030X40X40-Y	1	1312160030
IE-C6FP8LD0050X40X40-Y	1	1312160050
IE-C6FP8LD0100X40X40-Y	1	1312160100
IE-C6FP8LD0150X40X40-Y	1	1312160150
IE-C6FP8LD0200X40X40-Y	1	1312160200

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000

TMH 12 MC NE GE	320	1718411687
TMH 18 MC NE GE	320	1718431687

IE-PP-RJ45	10	2552580000
IE-CABLE-BENDER-90	50	2704480000

Assembled cables - Patch cable**Assembled cables****Patch cable CabinetLine Cat. 5 straight****PVC green****PUR green**

RJ45	1 white (orange)	2 orange	3 white (green)	4 blue	5 white (blue)	6 green	7 white (brown)	8 brown	RJ45

RJ45	1 white (orange)	2 orange	3 white (green)	4 blue	5 white (blue)	6 green	7 white (brown)	8 brown	RJ45

Technical data

Product type	
Category	
Shielding	
Version connector left / Version connector right	
Connector standard	
PoE / PoE+	
Cross-section	
Sheath diameter, max.	
Material sheath	
Sheathing colour	
Insulation diameter	
Min. bending radius, repetitive	
Min. bending radius, once only	
Ambient temperature (operational)	
Abrasion resistance	
Halogen	
Resistance to spread of flame	
Resistance to oils	
Approvals	
Note	

System cable	
Cat.5 (ISO/IEC 11801)	
SF/UTP	
RJ45 IP 20 / RJ45 IP 20	
IEC 60603-7-51	
conforming to IEEE 802.3at	
4*2*AWG 26/7 - 4*2*0.128 mm ²	
5.8 mm	
PVC	
green (RAL 6018)	
0.98 mm	
10 x cable diameter	
5 x cable diameter	
-40 °C...75 °C	
good	
in acc. with IEC 60332-1	
EAC	

System cable	
Cat.5 (ISO/IEC 11801)	
SF/UTP	
RJ45 IP 20 / RJ45 IP 20	
IEC 60603-7-51	
conforming to IEEE 802.3at	
4*2*AWG 26/7 - 4*2*0.128 mm ²	
6 mm	
PUR	
green (RAL 6018)	
0.98 mm	
10 x cable diameter	
5 x cable diameter	
-40 °C...85 °C	
very good	
halogen-free, according to IEC 60754-2	
in acc. with IEC 60332-1	
EN 50305	

Ordering data

Type	Qty.	Order No.
IE-C5ES8VG0005M40M40-G	1	1166020005
IE-C5ES8VG010M40M40-G	1	1166020010
IE-C5ES8VG015M40M40-G	1	1166020015
IE-C5ES8VG020M40M40-G	1	1166020020
IE-C5ES8VG0030M40M40-G	1	1166020030
IE-C5ES8VG0050M40M40-G	1	1166020050
IE-C5ES8VG0100M40M40-G	1	1166020100
IE-C5ES8VG0150M40M40-G	1	1166020150
IE-C5ES8VG0200M40M40-G	1	1166020200

Type	Qty.	Order No.
IE-C5ES8UG005M40M40-G	1	1166000005
IE-C5ES8UG010M40M40-G	1	1166000010
IE-C5ES8UG015M40M40-G	1	1166000015
IE-C5ES8UG020M40M40-G	1	1166000020
IE-C5ES8UG0030M40M40-G	1	1166000030
IE-C5ES8UG0050M40M40-G	1	1166000050
IE-C5ES8UG0100M40M40-G	1	1166000100
IE-C5ES8UG0150M40M40-G	1	1166000150
IE-C5ES8UG0200M40M40-G	1	1166000200

Note

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TM-1 12 MC NE GE	320	1718411687
TM-1 18 MC NE GE	320	1718431687
IE-PP-RJ45	10	2552580000
IE-CABLE-BENDER-90	50	2704480000

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TM-1 12 MC NE GE	320	1718411687
TM-1 18 MC NE GE	320	1718431687
IE-PP-RJ45	10	2552580000
IE-CABLE-BENDER-90	50	2704480000

Note

Assembled cables**Patch cable CabinetLine Cat. 6 straight****PUR green**

RJ45	1 white (orange)	1	RJ45
2	orange	2	
3	white (green)	3	
4	blue	4	
5	white (blue)	5	
6	green	6	
7	white (brown)	7	
8	brown	8	

Technical data

Product type

Category

Shielding

Version connector left / Version connector right

Connector standard

PoE / PoE+

Cross-section

Sheath diameter, max.

Material sheath / Sheathing colour

Insulation diameter

Min. bending radius, repetitive / Min. bending radius, once only

Ambient temperature (operational)

Abrasion resistance

Halogen

Resistance to spread of flame

Resistance to oils

Approvals

Note

System cable

Cat.6A / Class E_A (ISO/IEC 11801 2010)

S/FTP

RJ45 IP 20 / RJ45 IP 20

IEC 60603-7-51

conforming to IEEE 802.3at

4*2*AWG 27/7 - 4*2*0.1 mm²

6.4 mm

PUR / green (RAL 6018)

1.02 mm

10 x cable diameter / 5 x cable diameter

-40 °C...85 °C

very good

halogen-free, according to IEC 60754-2

in acc. with IEC 60332-1 / UL 1581 FT2

in acc. with IEC 60811-2-1

Ordering data0.3 m
0.5 m
1.0 m
1.5 m
2.0 m
3.0 m
5.0 m
10.0 m
15.0 m
20.0 m

Type	Qty.	Order No.
IE-C6FS8UG0003A40A40-G	1	8941350003
IE-C6FS8UG0005A40A40-G	1	8941350005
IE-C6FS8UG0010A40A40-G	1	8941350010
IE-C6FS8UG0015A40A40-G	1	8941350015
IE-C6FS8UG0020A40A40-G	1	8941350020
IE-C6FS8UG0030A40A40-G	1	8941350030
IE-C6FS8UG0050A40A40-G	1	8941350050
IE-C6FS8UG0100A40A40-G	1	8941350100
IE-C6FS8UG0150A40A40-G	1	8941350150
IE-C6FS8UG0200A40A40-G	1	8941350200

Other lengths available on request

Note

Accessories

Tools

Sheathing strippers, For UTP and STP data cables
Sheathing strippers, For coaxial and round data cables

Marking tags

Wire and cable markers. ø 4.7 - 7.4 mm
Wire and cable markers. ø 5.8 - 7.8 mm
Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm
Transparent sleeves, 12-mm length
Transparent sleeves, 18-mm length

Dust protection cap

Protective cap

Cable routing

90° outlet angle

Note

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000

VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001
TM 12 MC NE GE	320	1718411687
TM 18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

IE-PP-RJ45	10	2552580000
IE-CABLE-BENDER-90	50	2704480000

Assembled cables

Patch cable PROFINET dragline cable (type C)

Cat. 5
IP 20

RJ45 IP20



EtherCAT®



RJ45 IP20 incl. protective cap



EtherCAT®



RJ45		RJ45
1	yellow	1
2	orange	2
3	white	3
6	blue	6

RJ45		RJ45
1	yellow	1
2	orange	2
3	white	3
6	blue	6

Technical data

Product type

Category

Shielding

Version connector left / Version connector right

Cross-section

Sheath diameter, max.

Material sheath

Insulation diameter

Min. bending radius, repetitive / Min. bending radius, once only

Bending cycles

Speed

Acceleration

Pulling force

Ambient temperature (operational)

Installation temperature

Storage temperature

Abrasion resistance

Halogen

Resistance to spread of flame

Resistance to oils

Approvals

Note

Dragline cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

RJ45 IP 20 / RJ45 IP 20

4*AWG 22/7 - 0.36 mm²

6.7 mm

PUR

1.5 mm

7.5 x cable diameter / 5 x cable diameter

3 Mio

180 m/min

4 m/s²

≤ 150 N

-40 °C...70 °C

-20 °C...60 °C

-50 °C...70 °C

very good

halogen-free, according to IEC 60754-2

in acc. with IEC 60332-1

in acc. with IEC 60811-2-1

CULUS

Dragline cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

RJ45 IP 20 with protective cap / RJ45 IP 20 with protective cap

4*AWG 22/7 - 0.36 mm²

6.7 mm

PUR

1.5 mm

7.5 x cable diameter / 5 x cable diameter

3 Mio

180 m/min

4 m/s²

≤ 150 N

-40 °C...70 °C

-20 °C...60 °C

-50 °C...70 °C

very good

halogen-free, according to IEC 60754-2

in acc. with IEC 60332-1

in acc. with IEC 60811-2-1

Ordering data

0.5 m

1.0 m

2.0 m

3.0 m

5.0 m

10.0 m

15.0 m

20.0 m

Note

Type	Qty.	Order No.
IE-C5DD4UG0005A20A20-E	1	1173030005
IE-C5DD4UG0010A20A20-E	1	1173030010
IE-C5DD4UG0020A20A20-E	1	1173030020
IE-C5DD4UG0030A20A20-E	1	1173030030
IE-C5DD4UG0050A20A20-E	1	1173030050
IE-C5DD4UG0100A20A20-E	1	1173030100
IE-C5DD4UG0150A20A20-E	1	1173030150
IE-C5DD4UG0200A20A20-E	1	1173030200

Type	Qty.	Order No.
IE-C5DD4UG0005A2DA2D-E	1	1376510005
IE-C5DD4UG0010A2DA2D-E	1	1376510010
IE-C5DD4UG0020A2DA2D-E	1	1376510020
IE-C5DD4UG0030A2DA2D-E	1	1376510030
IE-C5DD4UG0050A2DA2D-E	1	1376510050
IE-C5DD4UG0100A2DA2D-E	1	1376510100
IE-C5DD4UG0150A2DA2D-E	1	1376510150
IE-C5DD4UG0200A2DA2D-E	1	1376510200

Accessories

Tools

Sheathing strippers, For UTP and STP data cables

Sheathing strippers, For coaxial and round data cables

Marking tags

Insertion label, yellow, 12 mm

Insertion label, yellow, 18 mm

Dust protection cap

Protective cap

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TMH 12 MC NE GE	320	1718411687
TMH 18 MC NE GE	320	1718431687
IE-PP-RJ45	10	2552580000

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TMH 12 MC NE GE	320	1718411687
TMH 18 MC NE GE	320	1718431687

Note

Assembled cables**Patch cable PROFINET RJ45 crimp**

Cat.5

IP20

Connecting cable (Type B), PVC**Dragline cable (Type C), PUR**

RJ45		RJ45
1	yellow	1
2	orange	2
3	white	3
6	blue	6

RJ45		RJ45
1	yellow	1
2	orange	2
3	white	3
6	blue	6

Technical data

Product type

Category

Shielding

Version connector left / Version connector right

Cross-section

Sheath diameter, max.

Material sheath

Insulation diameter

Min. bending radius, repetitive / Min. bending radius, once only

Bending cycles

Speed

Acceleration

Pulling force

Ambient temperature (operational)

Installation temperature

Storage temperature

Abrasion resistance

Halogen

Resistance to spread of flame

Resistance to oils

Approvals

Note**Ordering data**

System cable		
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)		
SF/UTP		
RJ45 IP 20 / RJ45 IP 20		
4*AWG 22/7 - 0.36 mm ²		
6.7 mm		
PVC		
1.5 mm		
7.5 x cable diameter / 3.5 *diameter		
-40 °C...70 °C		
-20 °C...60 °C		
-40 °C...70 °C		
good		
in acc. with IEC 60332-1 / UL 1685		

Dragline cable		
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)		
SF/UTP		
RJ45 IP 20 / RJ45 IP 20		
4*AWG 22/7 - 0.36 mm ²		
6.7 mm		
PUR		
1.5 mm		
7.5 x cable diameter / 5 x cable diameter		
3 Mio		
180 m/min		
4 m/s ²		
≤ 150 N		
-40 °C...70 °C		
-20 °C...60 °C		
-50 °C...70 °C		
very good		
halogen-free, according to IEC 60754-2		
in acc. with IEC 60332-1		
in acc. with IEC 60811-2-1		

Note**Accessories****Dust protection cap**

Protective cap

Type	Qty.	Order No.
IE-C5DS4VG0005A60A60-E	1	1522100005
IE-C5DS4VG0010A60A60-E	1	1522100010
IE-C5DS4VG0015A60A60-E	1	1522100015
IE-C5DS4VG0020A60A60-E	1	1522100020
IE-C5DS4VG0025A60A60-E	1	1522100025
IE-C5DS4VG0030A60A60-E	1	1522100030
IE-C5DS4VG0040A60A60-E	1	1522100040
IE-C5DS4VG0050A60A60-E	1	1522100050
IE-C5DS4VG0075A60A60-E	1	1522100075
IE-C5DS4VG0100A60A60-E	1	1522100100
IE-C5DS4VG0150A60A60-E	1	1522100150
IE-C5DS4VG0200A60A60-E	1	1522100200

Other lengths available on request

Type	Qty.	Order No.
IE-C5DD4UG0005A60A60-E	1	2047310005
IE-C5DD4UG0010A60A60-E	1	2047310010
IE-C5DD4UG0015A60A60-E	1	2047310015
IE-C5DD4UG0020A60A60-E	1	2047310020
IE-C5DD4UG0025A60A60-E	1	2047310025
IE-C5DD4UG0030A60A60-E	1	2047310030
IE-C5DD4UG0040A60A60-E	1	2047310040
IE-C5DD4UG0050A60A60-E	1	2047310050
IE-C5DD4UG0075A60A60-E	1	2047310075
IE-C5DD4UG0100A60A60-E	1	2047310100
IE-C5DD4UG0150A60A60-E	1	2047310150
IE-C5DD4UG0200A60A60-E	1	2047310200

Note

Assembled cables**Patch cable PROFINET dragline cable (type C)****Cat. 5****IP 67****V14 RJ45 IP67**

RJ45		RJ45
1	yellow	1
2	orange	2
3	white	3
6	blue	6

Technical data

Product type
Category
Connector standard
Shielding
Version connector left / Version connector right
Cross-section
Sheath diameter, max.
Material sheath
Insulation diameter
Min. bending radius, repetitive / Min. bending radius, once only
Bending cycles
Speed
Acceleration
Pulling force
Ambient temperature (operational)
Installation temperature
Storage temperature
Abrasion resistance
Halogen
Resistance to spread of flame
Resistance to oils
Approvals

Note

Dragline cable
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA 568-B)
IEC 61076-3-117 Var. 14, IEC 60603-7-51
SF/UTP
RJ45 IP 67 PushPull V14 metal / RJ45 IP 67 PushPull V14 metal
4*AWG 22/7 - 0.36 mm ²
6.7 mm
PUR
1.5 mm
7.5 x cable diameter / 5 x cable diameter
3 Mio
180 m/min
4 m/s ²
≤ 150 N
-40 °C...70 °C
-20 °C...60 °C
-50 °C...70 °C
very good
halogen-free, according to IEC 60754-2
in acc. with IEC 60332-1
in acc. with IEC 60811-2-1

Ordering data

1.0 m
2.0 m
3.0 m
5.0 m
10.0 m
15.0 m
20.0 m

Note

Type	Qty.	Order No.
IE-C5DD4UG0010A2EA2E-X	1	1119730010
IE-C5DD4UG0020A2EA2E-X	1	1119730020
IE-C5DD4UG0030A2EA2E-X	1	1119730030
IE-C5DD4UG0050A2EA2E-X	1	1119730050
IE-C5DD4UG0100A2EA2E-X	1	1119730100
IE-C5DD4UG0150A2EA2E-X	1	1119730150
IE-C5DD4UG0200A2EA2E-X	1	1119730200

Accessories**Tools**

Sheathing strippers, For UTP and STP data cables

Sheathing strippers, For coaxial and round data cables

Marking tags

Insertion label, yellow, 12 mm

Insertion label, yellow, 18 mm

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TMH 12 MC NE GE	320	1718411687
TMH 18 MC NE GE	320	1718431687

Note

Assembled cables

Patch cable PROFINET (Type C) Cat. 5, over-moulded IP 67

V14 RJ45 IP67

Dragline cable

**V14 RJ45 IP67**

Torsion cable



RJ45		RJ45
1	yellow	1
2	orange	2
3	white	3
6	blue	6

RJ45		RJ45
1	yellow	1
2	orange	2
3	white	3
6	blue	6

Technical data

Product type
Category
Connector standard
Shielding
Version connector left / Version connector right

Cross-section
Sheath diameter, max.
Material sheath
Insulation diameter
Min. bending radius, repetitive / Min. bending radius, once only
Bending cycles / Pulling force
Torsion cycles / Torsion resistance
Speed / Acceleration
Ambient temperature (operational)
Installation temperature
Storage temperature
Abrasion resistance
Halogen
Resistance to spread of flame
Resistance to oils
Approvals

Note**Ordering data**

1.0 m
2.0 m
3.0 m
5.0 m
10.0 m

Note**Accessories**

Tools
Sheathing strippers, For UTP and STP data cables
Sheathing strippers, For coaxial and round data cables

Marking tags
Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm

Dragline cable
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)
IEC 61076-3-117 Var. 14

SF/UTP
RJ45 IP 67 PushPull moulded V14 metal / RJ45 IP 67 PushPull moulded V14 metal
4*AWG 22/7 - 0.36 mm²
6.7 mm
PUR
1.5 mm
7.5 x cable diameter / 5 x cable diameter
3 Mio / ≤ 150 N

180 m/min / 4 m/s²
-40 °C...70 °C
-20 °C...60 °C
-50 °C...70 °C
very good
halogen-free, according to IEC 60754-2
in acc. with IEC 60332-1
in acc. with IEC 60811-2-1

Torsion cable
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)
IEC 61076-3-117 Var. 14

S/UTP
RJ45 IP 67 PushPull moulded V14 metal / RJ45 IP 67 PushPull moulded V14 metal
4*AWG 22/19 - 0.38 mm²
6.7 mm
PUR
1.5 mm
10 x cable diameter / 5 x cable diameter
1 mill. / 180 °C/m
40 °C...80 °C
40 °C...80 °C
40 °C...80 °C
very good
halogen-free, according to IEC 60754-2
in acc. with IEC 60332-1
in acc. with IEC 60811-2-1

Type	Qty.	Order No.
IE-C5DD4UG0010B2EB2E-X	1	1307610010
IE-C5DD4UG0020B2EB2E-X	1	1307610020
IE-C5DD4UG0030B2EB2E-X	1	1307610030
IE-C5DD4UG0050B2EB2E-X	1	1307610050
IE-C5DD4UG0100B2EB2E-X	1	1307610100

Type	Qty.	Order No.
IE-C5IT4UG0010B2EB2E-X	1	1312690010
IE-C5IT4UG0020B2EB2E-X	1	1312690020
IE-C5IT4UG0030B2EB2E-X	1	1312690030
IE-C5IT4UG0050B2EB2E-X	1	1312690050
IE-C5IT4UG0100B2EB2E-X	1	1312690100

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TMH 12 MC NE GE	320	1718411687
TMH 18 MC NE GE	320	1718431687

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TMH 12 MC NE GE	320	1718411687
TMH 18 MC NE GE	320	1718431687

Note

Assembled cables**Patch cable PushPull Power****Power IP67, PVC****Power IP67, PUR****Technical data**

Connector standard
Version connector left / Version connector right
Ambient temperature (operational)
Cross-section
Wire connection cross section AWG, max.
Sheath diameter, max.
Material sheath
Sheathing colour
Insulation
Number of wires
Min. bending radius, once only
Rated voltage
Current-carrying capacity at 50 °C
Approvals

Note**Ordering data**

1.0 m
3.0 m
5.0 m
10.0 m
15.0 m
20.0 m

Note**Accessories**

Tools
Sheathing strippers, For UTP and STP data cables
Sheathing strippers, For coaxial and round data cables

Marking tags
Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm

in acc. with PROFINET specification

PushPull Power / PushPull Power

-40 °C...70 °C

5*1.5 mm²

AWG 16

8.1 mm

PVC

grey (similar to RAL 7001)

PVC

5

4 x cable diameter

24 V

16 A

EAC

in acc. with PROFINET specification

PushPull Power / PushPull Power

-40 °C...80 °C

5*1.5 mm²

AWG 16

9 mm

PUR

grey (similar to RAL 7001)

TPE

5

5 x cable diameter

24 V

16 A

EAC

Type	Qty.	Order No.
IE-CSPS5VS0010VAPVAP-X	1	1350120010
IE-CSPS5VS0030VAPVAP-X	1	1350120030
IE-CSPS5VS0050VAPVAP-X	1	1350120050
IE-CSPS5VS0100VAPVAP-X	1	1350120100
IE-CSPS5VS0150VAPVAP-X	1	1350120150
IE-CSPS5VS0200VAPVAP-X	1	1350120200

Other lengths available on request

Type	Qty.	Order No.
IE-CSPD5US0050VAPVAP-X	1	1403680050
IE-CSPD5US0100VAPVAP-X	1	1403680100
IE-CSPD5US0150VAPVAP-X	1	1403680150

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000

TM-12 MC NE GE	320	1718411687
TM-18 MC NE GE	320	1718431687

TM-12 MC NE GE	320	1718411687
TM-18 MC NE GE	320	1718431687

Note

Assembled cables

Patch cable PushPull Power
M12 L-coded

Power IP67, PUR**Technical data**

Connector standard
Version connector left / Version connector right
Ambient temperature (operational)
Cross-section
Wire connection cross section AWG, max.
Sheath diameter, max.
Material sheath
Sheathing colour
Insulation
Number of wires
Min. bending radius, once only
Min. bending radius, repetitive
Rated voltage
Rated current
Approvals

in acc. with PROFINET specification, IEC 61076-2-111
M12 L-code - IP 67 straight socket / PushPull Power
-25 °C...70 °C
5*1.5 mm²
8.2 mm
PUR
Silver grey
PP
5
4 x cable diameter
7.5 x cable diameter
24 V
16 A

Note**Ordering data**

1.5 m
3.0 m
5.0 m
10.0 m

Type	Qty.	Order No.
IE-CSPD5UD0015LSSVAP-X	1	2732640015
IE-CSPD5UD0030LSSVAP-X	1	2732640030
IE-CSPD5UD0050LSSVAP-X	1	2732640050
IE-CSPD5UD0100LSSVAP-X	1	2732640100

Note**Accessories**

Tools
Sheathing strippers, For UTP and STP data cables
Sheathing strippers, For coaxial and round data cables
Marking tags
Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687

Note

Assembled cables – PROFINET cable M12

Assembled cable

Dragline cable M12

- Cat. 5
- PUR
- D-coded
- PROFINET type C

M12 - M12

Plug / plug



M12 - M12

Plug / socket



M12		M12
1	yellow	1
2	white	2
3	orange	3
4	blue	4

M12		M12
1	yellow	1
2	white	2
3	orange	3
4	blue	4

Technical data

Product type

Category

Shielding

Version connector left / Version connector right

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Bending cycles

Speed

Acceleration

Pulling force

Ambient temperature (operational)

Installation temperature

Storage temperature

Abrasion resistance

Halogen

Resistance to spread of flame

Resistance to oils

Approvals

Note

Dragline cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

M12 D-code - IP 67 straight pin / M12 D-code - IP 67 straight pin

4*AWG 22/7 - 0.36 mm²

6.7 mm

PUR

green (RAL 6018)

1.5 mm

7.5 x cable diameter

5 x cable diameter

3 Mio

180 m/min

4 m/s²

≤ 150 N

-40 °C...70 °C

-20 °C...60 °C

-50 °C...70 °C

very good

halogen-free, according to IEC 60754-2

in acc. with IEC 60332-1

in acc. with IEC 60811-2-1

CULUS

Dragline cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

M12 D-code - IP 67 straight pin / M12 D-code - IP 67 straight socket

4*AWG 22/7 - 0.36 mm²

6.7 mm

PUR

green (RAL 6018)

1.5 mm

7.5 x cable diameter

5 x cable diameter

3 Mio

180 m/min

4 m/s²

≤ 150 N

-40 °C...70 °C

-20 °C...60 °C

-50 °C...70 °C

very good

halogen-free, according to IEC 60754-2

in acc. with IEC 60332-1

in acc. with IEC 60811-2-1

CULUS

Ordering data

0.5 m

1.5 m

3.0 m

5.0 m

10.0 m

Note

Type	Qty.	Order No.
IE-C5DD4UG0005MCSMCS-E	1	1025950005
IE-C5DD4UG0015MCSMCS-E	1	1025950015
IE-C5DD4UG0030MCSMCS-E	1	1025950030
IE-C5DD4UG0050MCSMCS-E	1	1025950050
IE-C5DD4UG0100MCSMCS-E	1	1025950100

Type	Qty.	Order No.
IE-C5DD4UG0015MSSMCS-E	1	1059330015
IE-C5DD4UG0030MSSMCS-E	1	1059330030
IE-C5DD4UG0050MSSMCS-E	1	1059330050
IE-C5DD4UG0100MSSMCS-E	1	1059330100

Accessories

Marking tags

Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm

Tools

Tool set
Tool set with torque function
Mounting tool
Screwy-M12

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

Note

Assembled cable**Dragline cable M12**

- Cat. 5
- PUR
- D-coded
- PROFINET type C

M12 - open**M12 - RJ45**

	M12
yellow	1
white	2
orange	3
blue	4

RJ45	M12
yellow	1
white	2
orange	3
blue	4

Technical data

Product type	Dragline cable
Category	Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)
Shielding	SF/UTP
Version connector left / Version connector right	M12 D-code - IP 67 straight pin / Open
Cross-section	4*AWG 22/7 - 0.36 mm ²
Sheath diameter, max.	6.7 mm
Material sheath	PUR
Sheathing colour	green (RAL 6018)
Insulation diameter	1.5 mm
Min. bending radius, repetitive	7.5 x cable diameter
Min. bending radius, once only	5 x cable diameter
Bending cycles	3 Mio
Speed	180 m/min
Acceleration	4 m/s ²
Pulling force	≤ 150 N
Ambient temperature (operational)	-40 °C...70 °C
Installation temperature	-20 °C...60 °C
Storage temperature	-50 °C...70 °C
Abrasion resistance	very good
Halogen	halogen-free, according to IEC 60754-2
Resistance to spread of flame	in acc. with IEC 60332-1
Resistance to oils	in acc. with IEC 60811-2-1
Approvals	
Note	

Dragline cable
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)
SF/UTP
M12 D-code - IP 67 straight pin / Open
4*AWG 22/7 - 0.36 mm ²
6.7 mm
PUR
green (RAL 6018)
1.5 mm
7.5 x cable diameter
5 x cable diameter
3 Mio
180 m/min
4 m/s ²
≤ 150 N
-40 °C...70 °C
-20 °C...60 °C
-50 °C...70 °C
very good
halogen-free, according to IEC 60754-2
in acc. with IEC 60332-1
in acc. with IEC 60811-2-1
Note

Dragline cable
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)
SF/UTP
M12 D-code - IP 67 straight pin / RJ45 IP 20
4*AWG 22/7 - 0.36 mm ²
6.7 mm
PUR
green (RAL 6018)
1.5 mm
7.5 x cable diameter
5 x cable diameter
3 Mio
180 m/min
4 m/s ²
≤ 150 N
-40 °C...70 °C
-20 °C...60 °C
-50 °C...70 °C
very good
halogen-free, according to IEC 60754-2
in acc. with IEC 60332-1
in acc. with IEC 60811-2-1
Note

Ordering data

1.0 m
1.5 m
3.0 m
5.0 m
10.0 m

Note

Type	Qty.	Order No.
IE-C5DD4UG0010MCSXXX-X	1	1025940010
IE-C5DD4UG0015MCSXXX-X	1	1025940015
IE-C5DD4UG0030MCSXXX-X	1	1025940030
IE-C5DD4UG0050MCSXXX-X	1	1025940050
IE-C5DD4UG0100MCSXXX-X	1	1025940100

Type	Qty.	Order No.
IE-C5DD4UG0010MCSA20-E	1	1044470010
IE-C5DD4UG0015MCSA20-E	1	1044470015
IE-C5DD4UG0030MCSA20-E	1	1044470030
IE-C5DD4UG0050MCSA20-E	1	1044470050
IE-C5DD4UG0100MCSA20-E	1	1044470100

Accessories

Tools	Sheathing strippers, For UTP and STP data cables
	Sheathing strippers, For coaxial and round data cables

Tool set
Mounting tool
Screwy-M12

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

Type	Qty.	Order No.
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

Marking tags

Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm

TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687

Dust protection cap

Protective cap

--	--	--

Note

IE-PP-RJ45	10	2552580000
------------	----	------------

Assembled cables**M12 dragline cable, angled**



- Cat. 5
- PUR
- D-coded
- PROFINET type C

M12 - M12

Plug / plug

**M12 - M12**

Plug / plug

**Technical data**

Product type

Category

Shielding

Version connector left / Version connector right

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter, min. / max.

Min. bending radius, repetitive

Ambient temperature (operational)

Installation temperature

Storage temperature

Abrasion resistance

Halogen

Resistance to oils

Fire safety for railway vehicles

Note

Dragline cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

M12 D-code - IP 67 straight pin / M12 D-code - IP 67 straight pin

4*AWG 22/7 - 0.36 mm²

6.7 mm

PUR

green (RAL 6018)

1.5 mm

7.5 x cable diameter

-40 °C...70 °C

-20 °C...60 °C

-50 °C...70 °C

very good

halogen-free, according to IEC 60754-2

in acc. with IEC 60811-2-1

Dragline cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

M12 D-code - IP 67 angled pin / M12 D-code - IP 67 angled pin

4*AWG 22/7 - 0.36 mm²

6.7 mm

PUR

green (RAL 6018)

1.5 mm

7.5 x cable diameter

-40 °C...70 °C

-20 °C...60 °C

-50 °C...70 °C

very good

halogen-free, according to IEC 60754-2

in acc. with IEC 60811-2-1

Ordering data**Cat. 5 PROFINET. PUR. M12 straight-M12 angled**

1.5 m
3.0 m
5.0 m
10.0 m

Cat. 5 PROFINET. PUR. M12 angled-M12 angled

1.5 m
3.0 m
5.0 m
10.0 m

Cat. 5. PUR. M12 angled-open

1.5 m
3.0 m
5.0 m
10.0 m

Note**Type****Qty.****Order No.**

IE-C5DD4UG0015MCSMCA-E	1	1059770015
IE-C5DD4UG0030MCSMCA-E	1	1059770030
IE-C5DD4UG0050MCSMCA-E	1	1059770050
IE-C5DD4UG0100MCSMCA-E	1	1059770100

Type**Qty.****Order No.**

IE-C5DD4UG0015MCAMCA-E	1	1059890015
IE-C5DD4UG0030MCAMCA-E	1	1059890030
IE-C5DD4UG0050MCAMCA-E	1	1059890050
IE-C5DD4UG0100MCAMCA-E	1	1059890100

Type**Qty.****Order No.**

TM1-12 MC NE GE	320	1718411687
TM1-18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

Type**Qty.****Order No.**

TM1-12 MC NE GE	320	1718411687
TM1-18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

Accessories**Marking tags**

Insertion label, yellow, 12 mm

Insertion label, yellow, 18 mm

Transparent sleeves, 12-mm length

Transparent sleeves, 18-mm length


Note

Assembled cables**M12 dragline cable, angled**

- Cat. 5
- PUR
- D-coded
- PROFINET type C

M12 - open

Plug / -

**Technical data**

Product type

Category

Shielding

Version connector left / Version connector right

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter, min. / max.

Min. bending radius, repetitive

Ambient temperature (operational)

Installation temperature

Storage temperature

Abrasion resistance

Halogen

Resistance to oils

Fire safety for railway vehicles

Note

Dragline cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

M12 D-code - IP 67 angled pin / Open

4*AWG 22/7 - 0.36 mm²

6.7 mm

PUR

green (RAL 6018)

1.5 mm

7.5 x cable diameter

-40 °C...70 °C

-20 °C...60 °C

-50 °C...70 °C

very good

halogen-free, according to IEC 60754-2

in acc. with IEC 60811-2-1

Ordering data**Cat. 5 PROFINET. PUR. M12 straight-M12 angled**

1.5 m
3.0 m
5.0 m
10.0 m

Cat. 5 PROFINET. PUR. M12 angled-M12 angled

1.5 m
3.0 m
5.0 m
10.0 m

Cat. 5. PUR. M12 angled-open

1.5 m
3.0 m
5.0 m
10.0 m

Note**Type****Qty.****Order No.**

IE-C5DD4UG0015MCAXXX-X	1	1059750015
IE-C5DD4UG0030MCAXXX-X	1	1059750030
IE-C5DD4UG0050MCAXXX-X	1	1059750050
IE-C5DD4UG0100MCAXXX-X	1	1059750100

Accessories**Marking tags**

Insertion label, yellow, 12 mm

Insertion label, yellow, 18 mm

Transparent sleeves, 12-mm length

Transparent sleeves, 18-mm length

Type**Qty.****Order No.**

TM-12 MC NE GE	320	1718411687
TM-18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

Note

Assembled cables**System cable M12 flange**

- Cat. 5
- PUR
- D-coded
- PROFINET type B

M12 flange - M12 male

Plug / socket


EtherCAT®
**M12 flange - RJ45**

Plug / socket


EtherCAT®


M12		M12
1	yellow	1
2	white	2
3	orange	3
4	blue	4

M12		M12
1	yellow	1
2	white	2
3	orange	3
4	blue	4

Technical data

Product type

Category

Shielding

Version connector left / Version connector right

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Ambient temperature (operational)

Installation temperature

Storage temperature

Approvals

Note**Ordering data**

Type	Qty.	Order No.
IE-C5DS4UG0005MBSMCS-E	1	1244130005
IE-C5DS4UG0010MBSMCS-E	1	1244130010
IE-C5DS4UG0015MBSMCS-E	1	1244130015
IE-C5DS4UG0020MBSMCS-E	1	1244130020
IE-C5DS4UG0050MBSMCS-E	1	1244130050

Type	Qty.	Order No.
IE-C5DS4UG0005MBSA20-E	1	1234750005
IE-C5DS4UG0010MBSA20-E	1	1234750010
IE-C5DS4UG0015MBSA20-E	1	1234750015
IE-C5DS4UG0020MBSA20-E	1	1234750020
IE-C5DS4UG0050MBSA20-E	1	1234750050

Accessories

Marking tags

Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm

Tools

Tool set
Tool set with torque function
Mounting tool
Screwy-M12

Dust protection cap

Protective cap

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

Type	Qty.	Order No.
TMH 12 MC NE GE	320	1718411687
TMH 18 MC NE GE	320	1718431687
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000
IE-PP-RJ45	10	2552580000

Note

Assembled cables**System cable M12 flange**

- Cat. 5
- PUR
- D-coded
- PROFINET type B

M12 flange - open

Socket / -



M12	
yellow	1
white	2
orange	3
blue	4

Technical data

Product type
Category
Shielding
Version connector left / Version connector right
Cross-section
Sheath diameter, max.
Material sheath
Sheathing colour
Insulation diameter
Min. bending radius, repetitive
Min. bending radius, once only
Ambient temperature (operational)
Installation temperature
Storage temperature
Approvals

Note**Ordering data**

0.5 m
1.0 m
1.5 m
2.0 m
5.0 m

Note**Accessories****Marking tags**

Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm

Tools

Tool set
Tool set with torque function
Mounting tool
Screwy-M12

Dust protection cap

Protective cap

System cable
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)
360° shield contact
M12 D-code - flange / Open
4*AWG 22/7 - 0.36 mm²
6.7 mm
PUR
green (RAL 6018)
1.5 mm
15 x cable diameter
5 x cable diameter
-40 °C...70 °C
-20 °C...60 °C
-50 °C...70 °C


Type	Qty.	Order No.
IE-C5DS4UG0005MBSXXX-E	1	1234770005
IE-C5DS4UG0010MBSXXX-E	1	1234770010
IE-C5DS4UG0015MBSXXX-E	1	1234770015
IE-C5DS4UG0020MBSXXX-E	1	1234770020
IE-C5DS4UG0050MBSXXX-E	1	1234770050

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
SCREWTY SET	1	1910000000
SCREWTY SET -DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

Note

Assembled cable**Connecting cable M12**

- Cat. 6
- PVC
- X-type
- PROFINET type B

**M12 - M12**

Plug / plug

**M12 - open**

Plug / -

**Technical data**

Product type

Category

Shielding

Version connector left / Version connector right

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Pulling force

Ambient temperature (operational)

Installation temperature

Storage temperature

Halogen

Resistance to spread of flame

Standard, assembly

Approvals

Note**Ordering data**

	M12		M12
1	white, orange	1	
2	orange	2	
3	white, green	3	
4	green	4	
5	white, brown	5	
6	brown	6	
7	white, blue	7	
8	blue	8	

	White, Orange	1	M12
Orange		2	
White, Green		3	
Green		4	
White, Brown		5	
Brown		6	
White, Blue		7	
Blue		8	

Accessories**Marking tags**

- Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm

Type	Qty.	Order No.
IE-C6KS8VG0005XCSXCS-E	1	1398070005
IE-C6KS8VG0015XCSXCS-E	1	1398070015
IE-C6KS8VG0030XCSXCS-E	1	1398070030
IE-C6KS8VG0050XCSXCS-E	1	1398070050
IE-C6KS8VG0100XCSXCS-E	1	1398070100

Type	Qty.	Order No.
IE-C6KS8VG0005XCSXXX-E	1	1449470005
IE-C6KS8VG0015XCSXXX-E	1	1449470015
IE-C6KS8VG0030XCSXXX-E	1	1449470030
IE-C6KS8VG0050XCSXXX-E	1	1449470050
IE-C6KS8VG0100XCSXXX-E	1	1449470100

Note

Type	Qty.	Order No.
TM-12 MC NE GE	320	1718411687
TM-18 MC NE GE	320	1718431687

Type	Qty.	Order No.
TMH 12 MC NE GE	320	1718411687
TM-18 MC NE GE	320	1718431687

Assembled cable**Dragline cable M12**

- Cat. 6
- PUR
- X-type
- PROFINET type C

M12 - M12

Plug / plug

**M12 - RJ45**

Plug / plug



M12	1	white, orange	1	M12
	2	orange	2	
	3	white, green	3	
	4	green	4	
	5	white, brown	5	
	6	brown	6	
	7	white, blue	7	
	8	blue	8	

RJ45	1	White, Orange	1	M12
	2	Orange	2	
	3	White, Green	3	
	4	Blue	8	
	5	White, Blue	7	
	6	Green	4	
	7	White, Brown	5	
	8	Brown	6	

Technical data

Product type

Category

Shielding

Version connector left / Version connector right

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Pulling force

Ambient temperature (operational)

Installation temperature

Storage temperature

Halogen

Resistance to spread of flame

Standard, assembly

Approvals

Note**Ordering data**

Dragline cable

Cat.6A / Class E_A (ISO/IEC 11801 2010)

S/FTP

M12 X-type IP 67 straight male / M12 X-type IP 67 straight male

4*2*AWG 26/19 - 4*2*0.128 mm²

7.8 mm

PUR

green (RAL 6018)

0.98 mm

7.5 x cable diameter

4 x cable diameter

≤ 100 N

-40 °C...80 °C

-30 °C...70 °C

...

halogen-free

in acc. with IEC 60332-1-2, in acc. with UL 1581 VW-1 and CSA FT1

Dragline cable

Cat.6A / Class E_A (ISO/IEC 11801 2010)

S/FTP

M12 X-type IP 67 straight male / RJ45 IP 20

4*2*AWG 26/19 - 4*2*0.128 mm²

7.8 mm

PUR

green (RAL 6018)

0.98 mm

7.5 x cable diameter

4 x cable diameter

≤ 100 N

-40 °C...80 °C

-30 °C...70 °C

...

halogen-free

in acc. with IEC 60332-1-2, in acc. with UL 1581 VW-1 and CSA FT1

Note**Accessories**

Marking tags

Insertion label, yellow, 12 mm

Insertion label, yellow, 18 mm

Type	Qty.	Order No.
IE-C6HD8UG0010E40XCS-E	1	2723040010
IE-C6HD8UG0030E40XCS-E	1	2723040030
IE-C6HD8UG0050E40XCS-E	1	2723040050
IE-C6HD8UG0075E40XCS-E	1	2723040075
IE-C6HD8UG0100E40XCS-E	1	2723040100
IE-C6HD8UG0150E40XCS-E	1	2723040150

Type	Qty.	Order No.
IE-C6HD8UG0010E40XCS-E	1	2723030010
IE-C6HD8UG0030E40XCS-E	1	2723030030
IE-C6HD8UG0050E40XCS-E	1	2723030050
IE-C6HD8UG0075E40XCS-E	1	2723030075
IE-C6HD8UG0100E40XCS-E	1	2723030100
IE-C6HD8UG0150E40XCS-E	1	2723030150

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687


Note

Assembled cables**M12 connecting cables**

- Cat. 6
- PUR
- X-type

M12 - RJ45

Plug / plug



RJ45	1	White, Orange	1	M12
	2	Orange	2	
	3	White, Green	3	
	4	Blue	8	
	5	White, Blue	7	
	6	Green	4	
	7	White, Brown	5	
	8	Brown	6	

Technical data

Product type

Category

Shielding

Version connector left / Version connector right

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Pulling force

Ambient temperature (operational)

Installation temperature

Storage temperature

Halogen

Resistance to spread of flame

Standard, assembly

Approvals

Note

System cable

Cat.6A / Class E_A (ISO/IEC 11801 2010)

S/FTP

RJ45 IP 20 / M12 X-type IP 67 straight male

4*2*AWG 26/7 - 4*2*0.128 mm²

6.7 mm

PUR

green (RAL 6018)

0.98 mm

10 x cable diameter

5 x cable diameter

-40 °C...80 °C

-20 °C...60 °C

-40 °C...80 °C

halogen-free, according to IEC 60754-1

in acc. with IEC 60332-1-2

UL Style 20963

Ordering data

1.0 m

2.0 m

3.0 m

5.0 m

10.0 m

12.0 m

Type	Qty.	Order No.
IE-C6EL8UG0010U40XCS-E	1	1457580010
IE-C6EL8UG0020U40XCS-E	1	1457580020
IE-C6EL8UG0030U40XCS-E	1	1457580030
IE-C6EL8UG0050U40XCS-E	1	1457580050
IE-C6EL8UG0100U40XCS-E	1	1457580100
IE-C6EL8UG0120U40XCS-E	1	1457580120

Note**Accessories**

Marking tags

Insertion label, yellow, 12 mm

Insertion label, yellow, 18 mm

Dust protection cap

Protective cap

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
IE-PP-RJ45	10	2552580000

Note

Assembled cables**EtherNet/IP patch cable**

- in PUR

V1 RJ45 IP 67 - metal**V1 RJ45 IP 67 - plastic**

RJ45	1	white (orange)	1	RJ45
	2	orange	2	
	3	white (green)	3	
	4	blue	4	
	5	white (blue)	5	
	6	green	6	
	7	white (brown)	7	
	8	brown	8	

RJ45	1	white (orange)	1	RJ45
	2	orange	2	
	3	white (green)	3	
	4	blue	4	
	5	white (blue)	5	
	6	green	6	
	7	white (brown)	7	
	8	brown	8	

Technical data

Product type

Category

Shielding

Version connector left / Version connector right

Cross-section

Sheath diameter, max.

Material sheath

Sheathing colour

Insulation diameter

Min. bending radius, repetitive

Min. bending radius, once only

Ambient temperature (operational)

Installation temperature

Storage temperature

Abrasion resistance

Halogen

Resistance to spread of flame

Resistance to oils

Approvals

Note**Ordering data**

1.0 m

2.0 m

5.0 m

10.0 m

Note**Accessories**

Marking tags

Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm

Type	Qty.	Order No.
IE-C5ES8UG0010B41B41-E	1	1066850000
IE-C5ES8UG0020B41B41-E	1	1066860000
IE-C5ES8UG0050B41B41-E	1	1066870000
IE-C5ES8UG0100B41B41-E	1	1066880000

Type	Qty.	Order No.
IE-C5ES8UG0010P41P41-E	1	1106010000
IE-C5ES8UG0020P41P41-E	1	1106020000
IE-C5ES8UG0050P41P41-E	1	1106030000
IE-C5ES8UG0100P41P41-E	1	1106040000

Note**Note****Note**

Assembled cables – PROFINET cable M8

Assembled cable

Dragline cable M8

- Cat. 5
- PUR
- P-coded

M8 - open

Plug / -



M8 - open

Plug / -



M8

1	yellow
2	white
3	blue
4	orange

M8

1	yellow
2	white
3	blue
4	orange

Technical data

Product type
Category
Shielding
Version connector left / Version connector right
Cross-section
Sheath diameter, max.
Material sheath
Sheathing colour
Insulation diameter
Min. bending radius, repetitive
Min. bending radius, once only
Ambient temperature (operational)
Installation temperature
Storage temperature
Approvals

Note

Dragline cable

Cat. 5e

SF/UTP

M8 P-code - IP67 straight socket / Open

2*2*AWG 22/7 - 2*2*0.36 mm²

6.7 mm

PUR

black

1.6 mm

8 x cable diameter

5 x cable diameter

-40 °C...80 °C

...

...

Dragline cable

Cat. 5e

SF/UTP

M8 D-code - IP67 straight pin / Open

2*2*AWG 22/7 - 2*2*0.36 mm²

6.7 mm

PUR

black

1.6 mm

8 x cable diameter

5 x cable diameter

-40 °C...80 °C

...

...

Ordering data

1.5 m

3.0 m

5.0 m

7.5 m

10.0 m

20.0 m

30.0 m

Type	Qty.	Order No.
IE-C5DE4UP0015PSSXXX-E	1	2717740015
IE-C5DE4UP0030PSSXXX-E	1	2717740030
IE-C5DE4UP0050PSSXXX-E	1	2717740050
IE-C5DE4UP0075PSSXXX-E	1	2717740075
IE-C5DE4UP0100PSSXXX-E	1	2717740100
IE-C5DE4UP0200PSSXXX-E	1	2717740200
IE-C5DE4UP0300PSSXXX-E	1	2717740300

Type	Qty.	Order No.
IE-C5DE4UP0015PCSXXX-E	1	2717750015
IE-C5DE4UP0030PCSXXX-E	1	2717750030
IE-C5DE4UP0050PCSXXX-E	1	2717750050
IE-C5DE4UP0075PCSXXX-E	1	2717750075
IE-C5DE4UP0100PCSXXX-E	1	2717750100
IE-C5DE4UP0200PCSXXX-E	1	2717750200
IE-C5DE4UP0300PCSXXX-E	1	2717750300

Accessories

Marking tags

Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm

Tools

Tool set
Tool set with torque function
Mounting tool
Screwty-M12

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

Note

Assembled cable**Dragline cable M8**

- Cat. 5
- PUR
- P-coded

M8 - open

Plug angled / -

**M8 - open**

Socket angled / -

**M8**

1	yellow
2	white
3	blue
4	orange

M8

1	yellow
2	white
3	blue
4	orange

Technical data

Product type	Dragline cable
Category	Cat. 5e
Shielding	SF/UTP
Version connector left / Version connector right	M8 P-code - IP67 angled socket / Open
Cross-section	2*2*AWG 22/7 - 2*2*0.36 mm ²
Sheath diameter, max.	6.7 mm
Material sheath	PUR
Sheathing colour	black
Insulation diameter	1.6 mm
Min. bending radius, repetitive	8 x cable diameter
Min. bending radius, once only	5 x cable diameter
Ambient temperature (operational)	-40 °C...80 °C
Installation temperature	...
Storage temperature	...
Approvals	...

Note**Ordering data**

1.5 m
3.0 m
5.0 m
7.5 m
10.0 m
20.0 m
30.0 m

Note**Accessories**

Marking tags	Insertion label, yellow, 12 mm
	Insertion label, yellow, 18 mm
Tools	
Tool set	Tool set
Tool set with torque function	SCREWTY SET
Mounting tool	SCREWTY-SET-DM
Screwty-M12	SCREWTY-M12-DM

Dragline cable

Cat. 5e
SF/UTP
M8 P-code - IP67 angled socket / Open
2*2*AWG 22/7 - 2*2*0.36 mm ²
6.7 mm

Dragline cable

Cat. 5e
SF/UTP
M8 P-code - IP67 angled pin / Open
2*2*AWG 22/7 - 2*2*0.36 mm ²
6.7 mm

Type

Type	Qty.	Order No.
IE-C5DE4UP0015PSAXXX-E	1	2717760015
IE-C5DE4UP0030PSAXXX-E	1	2717760030
IE-C5DE4UP0050PSAXXX-E	1	2717760050
IE-C5DE4UP0075PSAXXX-E	1	2717760075
IE-C5DE4UP0100PSAXXX-E	1	2717760100
IE-C5DE4UP0200PSAXXX-E	1	2717760200
IE-C5DE4UP0300PSAXXX-E	1	2717760300

Type

Type	Qty.	Order No.
IE-C5DE4UP0015PCAXXX-E	1	2717770015
IE-C5DE4UP0030PCAXXX-E	1	2717770030
IE-C5DE4UP0050PCAXXX-E	1	2717770050
IE-C5DE4UP0075PCAXXX-E	1	2717770075
IE-C5DE4UP0100PCAXXX-E	1	2717770100

Note

Assembled cables – PROFINET cable M8

Assembled cable

Dragline cable M8

- Cat. 5
- PUR
- P-coded

M8 - M8

Plug straight / Plug straight



M8 - M8

Plug straight / Socket straight



M8		M8
1	yellow	1
2	white	2
3	blue	3
4	orange	4

M8		M8
1	yellow	1
2	white	2
3	blue	3
4	orange	4

Technical data

Product type	Dragline cable
Category	Cat. 5e
Shielding	SF/UTP
Version connector left / Version connector right	M8 P-code - IP67 straight pin / M8 P-code - IP67 straight pin
Cross-section	2*2*AWG 22/7 - 2*2*0.36 mm ²
Sheath diameter, max.	6.7 mm
Material sheath	PUR
Sheathing colour	black
Insulation diameter	1.6 mm
Min. bending radius, repetitive	8 x cable diameter
Min. bending radius, once only	5 x cable diameter
Ambient temperature (operational)	-40 °C...80 °C
Installation temperature	...
Storage temperature	...
Approvals	...

Note

Dragline cable
Cat. 5e
SF/UTP
M8 P-code - IP67 straight pin / M8 P-code - IP67 straight pin
2*2*AWG 22/7 - 2*2*0.36 mm ²
6.7 mm
PUR
black
1.6 mm
8 x cable diameter
5 x cable diameter
-40 °C...80 °C
...
...

Dragline cable
Cat. 5e
SF/UTP
M8 P-code - IP67 straight pin / M8 P-code - IP67 straight socket
2*2*AWG 22/7 - 2*2*0.36 mm ²
6.7 mm
PUR
black
1.6 mm
8 x cable diameter
5 x cable diameter
-40 °C...80 °C
...
...

Ordering data

Type	Qty.	Order No.
IE-C5DE4UP0015PCSPCS-E	1	2717780015
IE-C5DE4UP0030PCSPCS-E	1	2717780030
IE-C5DE4UP0050PCSPCS-E	1	2717780050
IE-C5DE4UP0075PCSPCS-E	1	2717780075
IE-C5DE4UP0100PCSPCS-E	1	2717780100
IE-C5DE4UP0200PCSPCS-E	1	2717780200
IE-C5DE4UP0300PCSPCS-E	1	2717780300

Type	Qty.	Order No.
IE-C5DE4UP0015PCSPSS-E	1	2717790015
IE-C5DE4UP0030PCSPSS-E	1	2717790030
IE-C5DE4UP0050PCSPSS-E	1	2717790050
IE-C5DE4UP0075PCSPSS-E	1	2717790075
IE-C5DE4UP0100PCSPSS-E	1	2717790100
IE-C5DE4UP0200PCSPSS-E	1	2717790200
IE-C5DE4UP0300PCSPSS-E	1	2717790300

Note

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

Accessories

Marking tags	Insertion label, yellow, 12 mm
	Insertion label, yellow, 18 mm
Tools	Tool set
	Tool set with torque function
	Mounting tool
	Screwty-M12

Note



Assembled cable**Dragline cable M8**

- Cat. 5
- PUR
- P-coded

M8 - M8

Plug angled / Plug angled

**M8 - M8**

Plug angled / socket angled



M8		M8
1	yellow	1
2	white	2
3	blue	3
4	orange	4

M8		M8
1	yellow	1
2	white	2
3	blue	3
4	orange	4

Technical data

Product type
Category
Shielding
Version connector left / Version connector right

Cross-section
Sheath diameter, max.
Material sheath
Sheathing colour
Insulation diameter
Min. bending radius, repetitive
Min. bending radius, once only
Ambient temperature (operational)
Installation temperature
Storage temperature
Approvals

Note**Ordering data**

1.5 m
3.0 m
5.0 m
7.5 m
10.0 m

Note**Accessories**

Marking tags	Insertion label, yellow, 12 mm
	Insertion label, yellow, 18 mm

Tools	Tool set
	Tool set with torque function
	Mounting tool
	Screwty-M12

Dragline cable
Cat. 5e
SF/UTP
M8 P-code - IP67 angled pin / M8 P-code - IP67 angled pin

Dragline cable
Cat. 5e
SF/UTP
M8 P-code - IP67 angled pin / M8 P-code - IP67 angled socket

Type	Qty.	Order No.
IE-C5DE4UP0015PCAPCA-E	1	2717800015
IE-C5DE4UP0030PCAPCA-E	1	2717800030
IE-C5DE4UP0050PCAPCA-E	1	2717800050
IE-C5DE4UP0075PCAPCA-E	1	2717800075
IE-C5DE4UP0100PCAPCA-E	1	2717800100

Type	Qty.	Order No.
IE-C5DE4UP0015PCAPSA-E	1	2717810015
IE-C5DE4UP0030PCAPSA-E	1	2717810030
IE-C5DE4UP0050PCAPSA-E	1	2717810050
IE-C5DE4UP0075PCAPSA-E	1	2717810075
IE-C5DE4UP0100PCAPSA-E	1	2717810100

Note

Assembled cable**Dragline cable M8**

- Cat. 5
- PUR
- D-coded

M8 - open

Plug / -

**M8 - open**

Socket / -

**M8**

1	yellow
2	white
3	orange
4	blue

M8

1	yellow
2	white
3	orange
4	blue

Technical data

Product type
Category
Shielding
Version connector left / Version connector right
Cross-section
Sheath diameter, max.
Material sheath
Sheathing colour
Insulation diameter
Min. bending radius, repetitive
Min. bending radius, once only
Ambient temperature (operational)
Installation temperature
Storage temperature
Approvals

Note

Dragline cable
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)
SF/UTP
M8 D-code - IP67 straight pin / Open
4*AWG 22/7 - 0.36 mm ²
6.7 mm
PUR
green (RAL 6018)
1.5 mm
7.5 x cable diameter
5 x cable diameter
-40 °C...70 °C
-20 °C...60 °C
-50 °C...70 °C

Dragline cable
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)
SF/UTP
M8 D-code - IP67 straight socket / Open
4*AWG 22/7 - 0.36 mm ²
6.7 mm
PUR
green (RAL 6018)
1.5 mm
7.5 x cable diameter
5 x cable diameter
-40 °C...70 °C
-20 °C...60 °C
-50 °C...70 °C

Ordering data

1.5 m
3.0 m
5.0 m
7.5 m
10.0 m
20.0 m
30.0 m

1.5 m
3.0 m
5.0 m
7.5 m
10.0 m
20.0 m
30.0 m

Note**Type**

Qty.

Order No.

IE-C5DD4UG0015DCSXXX-E 1 2706150015

IE-C5DD4UG0030DCSXXX-F 1 2706150030

IE-C5DD4UG0050DCSXXX-E 1 2706150050

IE-C5DD4UG0075DCSXXX-E 1 2706150075

IE-C5DD4UG0100DCSXXX-E 1 2706150100

IE-C5DD4UG0200DCSXXX-E 1 2706150200

IE-C5DD4UG0300DCSXXX-E 1 2706150300

Type

Qty.

Order No.

IE-C5DD4UG0015DSSXXX-E 1 2706260015

IE-C5DD4UG0030DSSXXX-F 1 2706260030

IE-C5DD4UG0050DSSXXX-E 1 2706260050

IE-C5DD4UG0075DSSXXX-E 1 2706260075

IE-C5DD4UG0100DSSXXX-E 1 2706260100

IE-C5DD4UG0200DSSXXX-E 1 2706260200

IE-C5DD4UG0300DSSXXX-E 1 2706260300

Accessories**Marking tags**Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm**Type**

Qty.

Order No.

TM-I 12 MC NE GE 320 1718411687

TM-I 18 MC NE GE 320 1718431687

Type

Qty.

Order No.

TM-I 12 MC NE GE 320 1718411687

TM-I 18 MC NE GE 320 1718431687

ToolsTool set
Tool set with torque function
Mounting tool
Screwty-M12

SCREWTY SET

SCREWTY SET-DM

SCREWTY-M12-DM

SCREWTY-M12

SCREWTY SET

SCREWTY SET-DM

SCREWTY-M12-DM

SCREWTY-M12

Note**Type**

Qty.

Order No.

SCREWTY SET

SCREWTY SET-DM

SCREWTY-M12-DM

SCREWTY-M12

Assembled cable**Dragline cable M8**

- Cat. 5
- PUR
- D-coded

M8 - open

Plug angled / -

**M8 - open**

Socket angled / -

**M8**

1	yellow
2	white
3	orange
4	blue

M8

1	yellow
2	white
3	orange
4	blue

Technical data

Product type
Category
Shielding
Version connector left / Version connector right
Cross-section
Sheath diameter, max.
Material sheath
Sheathing colour
Insulation diameter
Min. bending radius, repetitive
Min. bending radius, once only
Ambient temperature (operational)
Installation temperature
Storage temperature
Approvals

Note**Ordering data**

1.5 m
3.0 m
5.0 m
7.5 m
10.0 m
20.0 m
30.0 m

Note**Accessories**

Marking tags
Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm
Tools
Tool set
Tool set with torque function
Mounting tool
Screwty-M12

Note**Dragline cable**

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

M8 D-code - IP67 angled pin / Open

4*AWG 22/7 - 0.36 mm²

6.7 mm

PUR

green (RAL 6018)

1.5 mm

7.5 x cable diameter

5 x cable diameter

-40 °C...70 °C

-20 °C...60 °C

-50 °C...70 °C

Dragline cable

Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

M8 D-code - IP67 angled socket / Open

4*AWG 22/7 - 0.36 mm²

6.7 mm

PUR

green (RAL 6018)

1.5 mm

7.5 x cable diameter

5 x cable diameter

-40 °C...70 °C

-20 °C...60 °C

-50 °C...70 °C

Type	Qty.	Order No.
IE-C5DD4UG0015DCAXXX-E	1	2706190015
IE-C5DD4UG0030DCAXXX-F	1	2706190030
IE-C5DD4UG0050DCAXXX-E	1	2706190050
IE-C5DD4UG0075DCAXXX-E	1	2706190075
IE-C5DD4UG0100DCAXXX-E	1	2706190100

Type	Qty.	Order No.
IE-C5DD4UG0015DSAXXX-E	1	2706160015
IE-C5DD4UG0030DSAXXX-F	1	2706160030
IE-C5DD4UG0050DSAXXX-E	1	2706160050
IE-C5DD4UG0075DSAXXX-E	1	2706160075
IE-C5DD4UG0100DSAXXX-E	1	2706160100
IE-C5DD4UG0200DSAXXX-E	1	2706160200
IE-C5DD4UG0300DSAXXX-E	1	2706160300

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

Assembled cable**Dragline cable M8**

- Cat. 5
- PUR
- D-coded

M8 - M8

Plug straight / Plug straight

**M8 - M8**

Plug straight / Socket straight

**M8**

1	yellow
2	white
3	orange
4	blue

M8

1	yellow
2	white
3	orange
4	blue

Technical data

Product type
Category
Shielding
Version connector left / Version connector right
Cross-section
Sheath diameter, max.
Material sheath
Sheathing colour
Insulation diameter
Min. bending radius, repetitive
Min. bending radius, once only
Ambient temperature (operational)
Installation temperature
Storage temperature
Approvals

Dragline cable
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

M8 D-code - IP67 straight pin / M8 D-code - IP67 straight pin

4*AWG 22/7 - 0.36 mm²

6.7 mm

PUR

green (RAL 6018)

1.5 mm

7.5 x cable diameter

5 x cable diameter

-40 °C...70 °C

-20 °C...60 °C

-50 °C...70 °C

Dragline cable
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)

SF/UTP

M8 D-code - IP67 straight pin / M8 D-code - IP67 straight socket

4*AWG 22/7 - 0.36 mm²

6.7 mm

PUR

green (RAL 6018)

1.5 mm

7.5 x cable diameter

5 x cable diameter

-40 °C...70 °C

-20 °C...60 °C

-50 °C...70 °C

Note**Ordering data**1.5 m
3.0 m
5.0 m
7.5 m
10.0 m
20.0 m
30.0 m

Type	Qty.	Order No.
IE-C5DD4UG0015DCSDCS-E	1	2706200015
IE-C5DD4UG0030DCSDCS-E	1	2706200030
IE-C5DD4UG0050DCSDCS-E	1	2706200050
IE-C5DD4UG0075DCSDCS-E	1	2706200075
IE-C5DD4UG0100DCSDCS-E	1	2706200100
IE-C5DD4UG0200DCSDCS-E	1	2706200200
IE-C5DD4UG0300DCSDCS-E	1	2706200300

Type	Qty.	Order No.
IE-C5DD4UG0015DCSDSS-E	1	2706210015
IE-C5DD4UG0030DCSDSS-E	1	2706210030
IE-C5DD4UG0050DCSDSS-E	1	2706210050
IE-C5DD4UG0075DCSDSS-E	1	2706210075
IE-C5DD4UG0100DCSDSS-E	1	2706210100
IE-C5DD4UG0200DCSDSS-E	1	2706210200
IE-C5DD4UG0300DCSDSS-E	1	2706210300

Note**Accessories**

Marking tags
Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687

ToolsTool set
Tool set with torque function
Mounting tool
Screwty-M12

SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

Note

Assembled cable**Dragline cable M8**

- Cat. 5
- PUR
- D-coded

M8 - M8

Plug angled / Plug angled

**M8 - M8**

Plug angled / socket angled

**M8**

1	yellow
2	white
3	orange
4	blue

M8

1	yellow
2	white
3	orange
4	blue

Technical data

Product type
Dragline cable
Category
Shielding
Version connector left / Version connector right

Cross-section
Sheath diameter, max.
Material sheath
Sheathing colour
Insulation diameter
Min. bending radius, repetitive
Min. bending radius, once only
Ambient temperature (operational)
Installation temperature
Storage temperature
Approvals

Note**Ordering data**

1.5 m
3.0 m
5.0 m
7.5 m
10.0 m

Note**Accessories**

Marking tags
Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm

Tools

Tool set
Tool set with torque function
Mounting tool
Screwty-M12

Dragline cable
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)
SF/UTP
M8 D-code - IP67 angled pin / M8 D-code - IP67 angled pin

4*AWG 22/7 - 0.36 mm²
6.7 mm
PUR
green (RAL 6018)
1.5 mm
7.5 x cable diameter
5 x cable diameter
-40 °C...70 °C
-20 °C...60 °C
-50 °C...70 °C

Dragline cable
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)
SF/UTP
M8 D-code - IP67 angled pin / M8 D-code - IP67 angled socket

4*AWG 22/7 - 0.36 mm²
6.7 mm
PUR
green (RAL 6018)
1.5 mm
7.5 x cable diameter
5 x cable diameter
-40 °C...70 °C
-20 °C...60 °C
-50 °C...70 °C

Type	Qty.	Order No.
IE-C5DD4UG0015DCADCA-F	1	2706220015
IE-C5DD4UG0030DCADCA-E	1	2706220030
IE-C5DD4UG0050DCADCA-E	1	2706220050
IE-C5DD4UG0075DCADCA-E	1	2706220075
IE-C5DD4UG0100DCADCA-E	1	2706220100

Type	Qty.	Order No.
IE-C5DD4UG0015DCADSA-F	1	2706230015
IE-C5DD4UG0030DCADSA-E	1	2706230030
IE-C5DD4UG0050DCADSA-E	1	2706230050
IE-C5DD4UG0075DCADSA-E	1	2706230075
IE-C5DD4UG0100DCADSA-E	1	2706230100

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

Note

Assembled cables – PROFINET cable M8, D-coded

Assembled cable

Dragline cable M8

- Cat. 5
- PUR
- D-coded

M8 - RJ45

Plug straight / Plug straight



RJ45		M8
1	yellow	1
3	white	2
2	orange	3
6	blue	4

Technical data

Product type	Dragline cable
Category	Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)
Shielding	SF/UTP
Version connector left / Version connector right	M8 D-code - IP67 straight pin / RJ45 IP 20
Cross-section	4*AWG 22/7 - 0.36 mm ²
Sheath diameter, max.	6.7 mm
Material sheath	PUR
Sheathing colour	green (RAL 6018)
Insulation diameter	1.5 mm
Min. bending radius, repetitive	7.5 x cable diameter
Min. bending radius, once only	5 x cable diameter
Ambient temperature (operational)	-40 °C...70 °C
Installation temperature	-20 °C...60 °C
Storage temperature	-50 °C...70 °C
Approvals	

Note

Dragline cable
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)
SF/UTP
M8 D-code - IP67 straight pin / RJ45 IP 20
4*AWG 22/7 - 0.36 mm ²
6.7 mm
PUR
green (RAL 6018)
1.5 mm
7.5 x cable diameter
5 x cable diameter
-40 °C...70 °C
-20 °C...60 °C
-50 °C...70 °C

Ordering data

Type	Qty.	Order No.
IE-C5DD4UG0015DCSE40-E	1	2706250015
IE-C5DD4UG0030DCSE40-E	1	2706250030
IE-C5DD4UG0050DCSE40-E	1	2706250050
IE-C5DD4UG0075DCSE40-E	1	2706250075
IE-C5DD4UG0100DCSE40-E	1	2706250100
IE-C5DD4UG0200DCSE40-E	1	2706250200
IE-C5DD4UG0300DCSE40-E	1	2706250300

Note

Accessories

Marking tags	Insertion label, yellow, 12 mm
	Insertion label, yellow, 18 mm

Tools	Tool set
	Tool set with torque function
	Mounting tool
	Screwty-M12

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
SCREWTY SET	1	1910000000
SCREWTY SET-DM	1	1920000000
SCREWTY-M12-DM	1	1900001000
SCREWTY-M12	1	1900000000

Note

Assembled cable**Railway cable M12**

- Cat. 5
- Radox
- D-coded

M12 - M12

Plug / plug

**M12 - M12**

Plug / socket



M12		M12
1	yellow	1
2	white	2
3	orange	3
4	blue	4

M12		M12
1	yellow	1
2	white	2
3	orange	3
4	blue	4

Technical data

Product type	System cable
Category	Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)
Shielding	SF/UTP
Version connector left / Version connector right	M12 D-code - IP 67 straight pin / M12 D-code - IP 67 straight pin
Cross-section	2*2*AWG 22/7 - 2*2*0.36 mm ²
Sheath diameter, max.	7.55 mm
Material sheath	Radox GKW S
Sheathing colour	black
Insulation diameter	1.95 mm
Min. bending radius, repetitive	6 *diameter
Ambient temperature (operational)	-40 °C...90 °C
Installation temperature	-25 °C...90 °C
Storage temperature	40 °C...90 °C
Abrasion resistance	very good
Halogen	halogen-free, according to IEC 60754-2
Resistance to oils	in acc. with EN 50306-3
Fire safety for railway vehicles	According to DIN 5510-2 fire safety levels 1,2,3,4, According to BS 6853, According to EN50288-2-2, According to EN 45545, HL1 - HL3
Approvals	CULUS

Note**Ordering data**

1.5 m
3.0 m
5.0 m
10.0 m

Note**Accessories****Marking tags**

Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm

Type	Qty.	Order No.
IE-C5DB4RE0015MCSMCS-E	1	1010850015
IE-C5DB4RE0030MCSMCS-E	1	1010850030
IE-C5DB4RE0050MCSMCS-E	1	1010850050
IE-C5DB4RE0100MCSMCS-E	1	1010850100

Type	Qty.	Order No.
IE-C5DB4RE0015MSSMCS-E	1	1059340015
IE-C5DB4RE0030MSSMCS-E	1	1059340030
IE-C5DB4RE0050MSSMCS-E	1	1059340050
IE-C5DB4RE0100MSSMCS-E	1	1059340100

Note

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687

Assembled cables - Railway cable M12

Assembled cable

Railway cable M12

- Cat. 5
- Radox
- D-coded

M12 - open

Plug / -



M12	
yellow	1
white	2
orange	3
blue	4

Technical data

Product type	System cable
Category	Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)
Shielding	SF/UTP
Version connector left / Version connector right	M12 D-code - IP 67 straight pin / Open
Cross-section	2*2*AWG 22/7 - 2*2*0.36 mm ²
Sheath diameter, max.	7.55 mm
Material sheath	Radox GKW S
Sheathing colour	black
Insulation diameter	1.95 mm
Min. bending radius, repetitive	6 *diameter
Ambient temperature (operational)	-40 °C...90 °C
Installation temperature	-25 °C...90 °C
Storage temperature	-40 °C...90 °C
Abrasion resistance	very good
Halogen	halogen-free, according to IEC 60754-2
Resistance to oils	in acc. with EN 50306-3
Fire safety for railway vehicles	According to DIN 5510-2 fire safety levels 1,2,3,4, According to BS 6853, According to EN50288-2-2, According to EN 45545, HL1 - HL3
Approvals	CULUS

Note

Ordering data

1.5 m	
3.0 m	
5.0 m	
10.0 m	

Note

Accessories

Type	Qty.	Order No.
IE-C5DB4RE0015MCSXXX-X	1	1010840015
IE-C5DB4RE0030MCSXXX-X	1	1010840030
IE-C5DB4RE0050MCSXXX-X	1	1010840050
IE-C5DB4RE0100MCSXXX-X	1	1010840100

Note

Tools

Sheathing strippers, For UTP and STP data cables
Sheathing strippers, For coaxial and round data cables

Marking tags

Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TM-12 MC NE GE	320	1718411687
TM-18 MC NE GE	320	1718431687

Note

Assembled cables**Railway cable M12**

- Cat. 5
- Radox
- D-coded

M12 - M12

Plug / plug

**M12 - M12**

Plug / plug



M12		M12
1	yellow	1
2	white	2
3	orange	3
4	blue	4

M12		M12
1	yellow	1
2	white	2
3	orange	3
4	blue	4

Technical data

Product type
Category
Shielding
Version connector left / Version connector right

Cross-section
Sheath diameter, max.
Material sheath
Sheathing colour
Insulation diameter, min. / max.
Min. bending radius, repetitive
Ambient temperature (operational)
Installation temperature
Storage temperature
Abrasion resistance
Halogen
Resistance to oils
Fire safety for railway vehicles

Note**Ordering data**

1.5 m
3.0 m
5.0 m
10.0 m

Note**Accessories****Marking tags**

Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm
Transparent sleeves, 12-mm length
Transparent sleeves, 18-mm length

Type	Qty.	Order No.
IE-C5DB4RE0015MCSMCA-E	1	1059940015
IE-C5DB4RE0030MCSMCA-E	1	1059940030
IE-C5DB4RE0050MCSMCA-E	1	1059940050
IE-C5DB4RE0100MCSMCA-E	1	1059940100

Type	Qty.	Order No.
IE-C5DB4RE0015MCAMCA-E	1	1059970015
IE-C5DB4RE0030MCAMCA-E	1	1059970030
IE-C5DB4RE0050MCAMCA-E	1	1059970050
IE-C5DB4RE0100MCAMCA-E	1	1059970100

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

Note

Assembled cables**Railway cable M12**

- Cat. 5
- Radox
- D-coded

M12 - open

Plug / -



M12	
yellow	1
white	2
orange	3
blue	4

Technical data

Product type
Category
Shielding
Version connector left / Version connector right

Cross-section
Sheath diameter, max.
Material sheath
Sheathing colour
Insulation diameter, min. / max.
Min. bending radius, repetitive
Ambient temperature (operational)
Installation temperature
Storage temperature
Abrasion resistance
Halogen
Resistance to oils
Fire safety for railway vehicles

System cable
Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)
SF/UTP
M12 D-code - IP 67 angled pin / Open

2*2*AWG 22/7 - 2*2*0.36 mm²
7.55 mm
Radox GKW S
black
1.95 mm
6 *diameter
-40 °C...90 °C
-25 °C...90 °C
-40 °C...90 °C
very good
halogen-free, according to IEC 60754-2
in acc. with EN 50306-3
According to DIN 5510-2 fire safety levels 1,2,3,4, According to BS 6853, According to EN50288-2-2, According to EN 45545, HL1 - HL3

Note**Ordering data**

1.5 m
3.0 m
5.0 m
10.0 m

Type	Qty.	Order No.
IE-C5DB4RE0015MCAXXX-X	1	1059900015
IE-C5DB4RE0030MCAXXX-X	1	1059900030
IE-C5DB4RE0050MCAXXX-X	1	1059900050
IE-C5DB4RE0100MCAXXX-X	1	1059900100

Note**Accessories****Marking tags**

Insertion label, yellow, 12 mm
Insertion label, yellow, 18 mm
Transparent sleeves, 12-mm length
Transparent sleeves, 18-mm length

Type	Qty.	Order No.
TM-I 12 MC NE GE	320	1718411687
TM-I 18 MC NE GE	320	1718431687
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

Note

Assembled cables**Railway cable RW M12**

- Cat. 5
- Radox
- D-coded
- RW (reduced wire): suitable for RJ45 connectors

M12 - open

Plug / -

**M12 - RJ45**

Plug / plug



	M12
yellow	1
white	2
orange	3
blue	4

RJ45	M12
yellow	1
white	2
orange	3
blue	4

Technical data

Product type	
Category	
Shielding	
Version connector left / Version connector right	
Cross-section	
Sheath diameter, max.	
Material sheath	
Sheathing colour	
Insulation diameter	
Min. bending radius, repetitive	
Ambient temperature (operational)	
Storage temperature	
Abrasion resistance	
Halogen	
Resistance to oils	
Fire safety for railway vehicles	

Approvals

Note**Ordering data**

4.0 m
5.0 m
10.0 m

Note**Accessories**

Tools	
Sheathing strippers, For UTP and STP data cables	
Sheathing strippers, For coaxial and round data cables	

Marking tags	
Transparent sleeves, 12-mm length	
Transparent sleeves, 18-mm length	

Dust protection cap	
Protective cap	

System cable	
Cat.5 (ISO/IEC 11801)	
SF/UTP	
M12 D-code - IP 67 straight pin / Open	
2*2*AWG 22/7 - 2*2*0.36 mm ²	
7 mm	
Radox GKW S	
black	
1.58 mm	
6 *diameter	
-40 °C...90 °C	
-40 °C...90 °C	
very good	
halogen-free, according to IEC 60754-2	
in acc. with EN 50306-3	
According to DIN 5510-2 fire safety levels 1,2,3,4, According to BS 6853, According to EN50288-2-2, According to EN 45545, HL1 - HL3	

System cable	
Cat.5 (ISO/IEC 11801)	
SF/UTP	
M12 D-code - IP 67 straight pin / RJ45 IP 20 no tools needed	
2*2*AWG 22/7 - 2*2*0.36 mm ²	
7 mm	
Radox GKW S	
black	
1.58 mm	
6 *diameter	
-40 °C...90 °C	
-40 °C...90 °C	
very good	
halogen-free, according to IEC 60754-2	
in acc. with EN 50306-3	
According to DIN 5510-2 fire safety levels 1,2,3,4, According to BS 6853, According to EN50288-2-2, According to EN 45545, HL1 - HL3	

Type	Qty.	Order No.
IE-C5DB4WE0040MCSA20-E	1	1220310040
IE-C5DB4WE100MCSXXX-E	1	1269740100

Type	Qty.	Order No.
IE-C5DB4WE0040MCSA20-E	1	1220310040

Type	Qty.	Order No.
AM 12	1	9030060000
IE-CST	1	9204350000
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000

Type	Qty.	Order No.
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000
IE-PP-RJ45	10	2552580000

Note

Assembled cables – Railway cable RJ45

Assembled cables

Railway cable RJ45 - RJ45

- Cat. 5
- Radox
- RW (reduced wire)

RJ45 - RJ45

Plug / plug



RJ45		RJ45
1	yellow	1
2	orange	2
3	white	3
6	blue	6

Technical data

Product type
Category
Shielding
Version connector left / Version connector right
Cross-section
Sheath diameter, max.
Material sheath
Sheathing colour
Insulation diameter
Min. bending radius, repetitive
Ambient temperature (operational)
Storage temperature
Abrasion resistance
Halogen
Resistance to oils
Fire safety for railway vehicles

Approvals

Note

System cable
Cat.5 (ISO/IEC 11801)
SF/UTP
RJ45 IP 20 no tools needed / RJ45 IP 20 no tools needed
2*2*AWG 22/7 - 2*2*0.36 mm ²
7 mm
Radox GKW S
black
1.58 mm
6 *diameter
-40 °C...90 °C
-40 °C...90 °C
very good
halogen-free, according to IEC 60754-2
in acc. with EN 50306-3
According to DIN 5510-2 fire safety levels 1,2,3,4, According to BS 6853, According to EN50288-2-2, According to EN 45545, HL1 - HL3

Ordering data

1.0 m
2.0 m
3.0 m
4.0 m
5.0 m
10.0 m
20.0 m

Note

Type	Qty.	Order No.
IE-C5DB4WE0010A20A20-E	1	1421710010
IE-C5DB4WE0020A20A20-E	1	1421710020
IE-C5DB4WE0030A20A20-E	1	1421710030
IE-C5DB4WE0040A20A20-E	1	1421710040
IE-C5DB4WE0050A20A20-E	1	1421710050
IE-C5DB4WE0100A20A20-E	1	1421710100
IE-C5DB4WE0200A20A20-E	1	1421710200

Accessories

Marking tags

Transparent sleeves. 12-mm length
Transparent sleeves. 18-mm length

Dust protection cap

Protective cap

Type	Qty.	Order No.
TM 4/12 HF/HB	500	1719840000
TM 4/18 HF/HB	500	1719850000
IE-PP-RJ45	10	2552580000

Note

Assembled cables
USB cable
USB A - USB A**USB A - USB Micro****Technical data**

Sheathing colour
Material sheath
Version connector left
Version connector right
Ambient temperature (operational)

Note

black
PVC
USB A
USB A
-15 °C...80 °C

black
PVC
USB A
USB Micro
-15 °C...80 °C

Ordering data

0.3 m
0.5 m
1.0 m
1.5 m
1.8 m
3.0 m

Note

Type	Qty.	Order No.
IE-USB-A-A-0.3M	1	1993550003
IE-USB-A-A-0.5M	1	1993550005
IE-USB-A-A-1.0M	1	1993550010
IE-USB-A-A-1.5M	1	1993550015
IE-USB-A-A-1.8M	1	1993550018
IE-USB-A-A-3.0M	1	1993550030

Type	Qty.	Order No.
IE-USB-A-MICRO-1.8M	1	1487980000

Accessories

Type	Qty.	Order No.

Type	Qty.	Order No.

Note

Assembled cables
USB cable
USB A 3.0 - USB A 3.0**Technical data**

Sheathing colour
Material sheath
Version connector left
Version connector right
Ambient temperature (operational)

blue
PVC
USB A 3.0
USB A 3.0
-15 °C...80 °C

Note**Ordering data**

0.5 m
1.8 m
3.0 m
5.0 m

Type	Qty.	Order No.
IE-USB-3.0-A-A-0.5M	1	2581730005
IE-USB-3.0-A-A-1.8M	1	2581730018
IE-USB-3.0-A-A-3M	1	2581730030
IE-USB-3.0-A-A-5M	1	2581730050


Note**Accessories**

Type	Qty.	Order No.

Note

Assembled cable**Single Pair Ethernet IP20****Plug - Plug**

Socket contact / Socket contact

**Technical data**

Product type

Category

Shielding

Ambient temperature (operational)

Rated voltage (DC)

Rated current

PoE / PoE+

Transmission rate

Dielectric strength, contact / contact

Dielectric strength, contact / shield

Characteristic impedance

Capacity at 800 Hz

Coupling attenuation 1 to 600 MHz

Coupling attenuation up to 1000 MHz

Test voltage: wire-wire-shield

Resistance differential

Transmission rate

Version connector left

Version connector right

Number of wires

Colour coding

Complete shielding / Overlap of shielding braid

Insulation

Insulation diameter

Sheath diameter, min. / max.

Cross-section / Strands

Shielding

Material sheath

Colour

Halogen

UV-resistant

Connector standard

Note**Ordering data**

1.0 m

2.0 m

3.0 m

5.0 m

Type	Qty.	Order No.
IE-S1DS2VE0010T01T01-E	1	2725850010
IE-S1DS2VE0020T01T01-E	1	2725850020
IE-S1DS2VE0030T01T01-E	1	2725850030
IE-S1DS2VE0050T01T01-E	1	2725850050

Note**Accessories**

Type	Qty.	Order No.

Note

Assembled cables – Single Pair Ethernet cable

Assembled cable

Single Pair Ethernet IP67



M8 / M8

Socket contact / Socket contact



M8 / M8

Socket contact / Pin contact



Technical data

Product type	Patch cable
Category	STP
Shielding	-40...85 °C
Ambient temperature (operational)	60 V
Rated voltage (DC)	3.5 A
Rated current	PoDL acc. to IEEE 802.3bu / cg
PoE / PoE+	10/100 MBit/s, 1000 MBit/s
Transmission rate	1000 V DC
Dielectric strength, contact / contact	2250 V DC
Dielectric strength, contact / shield	3.5A @ 0°C
Current-carrying capacity	100 ± 15 Ω at 20 MHz
Characteristic impedance	1.6 nF/km
Capacity at 800 Hz	Type I
Coupling attenuation 1 to 600 MHz	1 kV DC, 1 min
Coupling attenuation up to 1000 MHz	2 %
Test voltage: wire-wire-shield	10/100 MBit/s, 1000 MBit/s
Resistance differential	M8 SPE (IEC63171-5) - IP67 socket contact straight
Transmission rate	M8 SPE (IEC63171-5) - IP67 socket contact straight
Version connector left	2
Version connector right	white / blue
Number of wires	Shielding braid made from copper wiring / 80 %
Colour coding	PE
Complete shielding / Overlap of shielding braid	1.65 mm
Insulation	4.9 / 5.3 mm
Insulation diameter	2*AWG 22 / 7
Sheath diameter, min. / max.	STP
Cross-section / Strands	PVC
Shielding	black
Material sheath	Yes
Colour	Complies with UL 1581 Sec. 1200
Halogen	IEC 63171-5
UV-resistant	
Connector standard	

Note

Ordering data

2.0 m

Note

Accessories

Type	Qty.	Order No.
IE-S1DS2VE0020TM1TM1-E	1	2726050020

Note


Type	Qty.	Order No.
IE-S1DS2VE0020TM1TM2-E	1	2726060020

Type	Qty.	Order No.
IE-S1DS2VE0020TM1TM2-E	1	2726060020

Type	Qty.	Order No.

Assembled cable**Single Pair Ethernet IP67****M8 / M8**

Pin contact / Pin contact

**Technical data**

Product type
Category
Shielding
Ambient temperature (operational)
Rated voltage (DC)
Rated current
PoE / PoE+
Transmission rate
Dielectric strength, contact / contact
Dielectric strength, contact / shield
Current-carrying capacity
Characteristic impedance
Capacity at 800 Hz
Coupling attenuation 1 to 600 MHz
Coupling attenuation up to 1000 MHz
Test voltage: wire-wire-shield
Resistance differential
Transmission rate
Version connector left
Version connector right
Number of wires
Colour coding
Complete shielding / Overlap of shielding braid
Insulation
Insulation diameter
Sheath diameter, min. / max.
Cross-section / Strands
Shielding
Material sheath
Colour
Halogen
UV-resistant
Connector standard

Note**Ordering data**

2.0 m
Note

Accessories

Type	Qty.	Order No.
IE-S1DS2VE0020TM2M2-E	1	2726070020

Note

Fibre-optic cabling solutions

Overview

Fibre-optic cabling solutions	Overview – Fibre-optic cables	R.2
	Product configurator – Fibre-optic cables	R.3
	Raw cable – FO connection cable / dragline cable	R.4
	Assembled cables – FO patch cable	R.5
	Assembled cables – FO PROFINET cable	R.10
	Assembled cables – FO dragline cable	R.11

Overview – Fibre-optic cables

First choice for industry

Fibre-optic cables are the best option for working in harsh industrial environments, especially if you:

- Need long transmission paths (up to 120 km!)
- Need to take account of EMC issues
- Must ensure electrical isolation in the case of potential differences

Raw cables

Industrial fibre-optic dragline cable



For flexible installations in and around machinery and plants – for harsh, industrial surroundings, dragline cable compatible

- Polymer optic fibre (POF)
- Breakout cable
- Raw cable for assembling your own connecting cables

Assembled cables

Industrial FO patch cables



...for use in industrial switching cabinets or junction boxes

- Multimode glass fibre
- Zipcord cable

Industrial FO adapter cables



...for linking ST and SC connections

- Multimode glass fibre
- Zipcord cable

R

Industrial fibre-optic dragline cable



...for flexible installations in and around machinery and plants – for harsh, industrial surroundings, dragline cable compatible

- Multimode fibre-optic
- Breakout cable
- Pre-assembled cable

Configurators for fibre-optic cables

Tailor-made connections

The cable configurator in Weidmüller's online catalogue makes it possible for you to create a fully-assembled cable adapted to your requirements and specifications.

A variety of plug types in the following protective classes are available:

IP20

- SCRJ
- ST
- LC Duplex
- SC duplex

IP67

- Variant 1, metal with SC- or LC-Duplex plugs
- Variant 4, plastic with SC- or LC-Duplex plugs
- Additional housing variants to follow shortly.
- Variant 14, metal with SC or LC Duplex plugs

You then have the choice of configuring a cable which is identical on both ends, or with two different mating profiles, or with one end left open.

The screenshot shows the Weidmüller Industrial Ethernet product configurator. At the top, there are links for 'www.weidmueller.com', 'Project Management', 'Configuration', 'Parts list', and 'Help'. Below that, the 'Product Catalogue' and 'Industrial Ethernet' sections are visible. The main area is titled 'Industrial Ethernet product configurator' and describes the cable configurator's ability to create custom cables according to requirements. It shows a diagram of a cable with two SC IP67 bayonet V01 metal plugs, a length of 55 m, and a breakdown of the cable structure. Configuration options include 'Plug 1: ST IP20' and 'Plug 2: SC IP67 bayonet V01 metal'. The 'Type of cable' dropdown is set to 'BREAKOUT dragline cable G50/125'. A 'Length [m]' dropdown is set to 'Individual lengths' with a value of '55'.

When selecting the cable, the following types are available:

- Zipcord, inner conductor G50 µm/125 µm and G62.5 µm/125 µm with PVC sheath
- Breakout, interior wire G50 µm/125 µm and G62.5 µm/125 µm with PVC sheath
- Breakout dragline cable, inner conductor G50 µm/125 µm and G62.5 µm/125 µm with PUR sheath.
- Zipcord inner conductor POF 980/1000 µm with PE sheathing

The cable length can also be customised:

- From 0.3 m to 9.9 m, in 0.1 m steps
- From 10 m to 9999 m, in 1 m steps

The cable configurator can also automatically create technical data sheets for all of your customised cable variants.

All of your customised cable selections can be sent to Weidmüller using the "request list". You will then quickly receive a price proposal for the cables from your local Weidmüller representative.

Raw cables – FO connection cable / dragline cable



Raw cables

- Polymer optical fibre
- Customisable

Mini-Breakout (Typ B)



Breakout (Typ C)



Technical data

Product type
Cable layout
Sheath diameter
Material sheath
Sheathing colour
Insulation
Min. bending radius, repetitive
Min. bending radius, once only
Bending cycles
Ambient temperature (operational)
Fibre type
Bandwidth
Attenuation
Core diameter
Installation temperature
Storage temperature
Halogen
Approvals

Note

Ordering data

POF 980/1000 µm

500.0 m

Note

Accessories

Marking tags

- Insertion label, yellow, 12 mm
- Insertion label, yellow, 18 mm
- Transparent sleeves, 12-mm length
- Transparent sleeves, 18-mm length
- Wire and cable markers, ø 4.7 - 7.4 mm
- Wire and cable markers, ø 5.8 - 7.8 mm

Tools

- Crimping tool POF
- POF tool set

System cable

Mini-Breakout

7,5 mm

Polyethylene

green

10.000

-30 °C...70 °C

POF

> 35 MHz*100 m at 650 nm

≤ 160 dB/km at 650 nm

980 µm

...

-30 °C...70 °C

No

Dragline cable

Break-out dragline

7,5 mm

PUR

green

60 mm

25 mm

6 Mio

-40 °C...85 °C

POF

> 35 MHz*100 m at 650 nm

≤ 160 dB/km at 650 nm

980 µm

...

-40 °C...85 °C

No

Type Qty. Order No.

IE-FPOB2EG-500 1 2781950000

Type Qty. Order No.

IE-FPOD2UG-500 1 2763640000

Type Qty. Order No.

TM-I 12 MC NE GE 320 1718411687

TM-I 18 MC NE GE 320 1718431687

TM 4/12 HF/HB 500 1719840000

TM 4/18 HF/HB 500 1719850000

VT SF 5/21 MC NE WS VO 160 1689470001

VT SF 6/21 MC NE WS VO 160 1730560001

Type Qty. Order No.

TM-I 12 MC NE GE 320 1718411687

TMH 18 MC NE GE 320 1718431687

TM 4/12 HF/HB 500 1719840000

TM 4/18 HF/HB 500 1719850000

VT SF 5/21 MC NE WS VO 160 1689470001

VT SF 6/21 MC NE WS VO 160 1730560001

Type Qty. Order No.

HTX-IE-POF 1 1208870000

TOOL SET IE-POF 1 1208930000



Note

Note

Note

Assembled cables**CabinetLine FO patch cable**

- Multi-mode glass fibre optics
- LSZH Casing

SC-Duplex / SC-Duplex**ST / ST****Technical data**

Product type

Cable layout

Sheath diameter

Material sheath

Sheathing colour

Ambient temperature (operational)

Installation temperature

Storage temperature

Approvals

Note**Ordering data****Core 62.5 µm, OM1**

0.5 m
1.0 m
2.0 m
3.0 m
5.0 m
10.0 m

Type Qty. Order No.

IE-FM6Z2L00005DSD0SD0-X	1	1433960005
IE-FM6Z2L00001MSD0SD0-X	1	1433960010
IE-FM6Z2L00002MSD0SD0-X	1	1433960020
IE-FM6Z2L00003MSD0SD0-X	1	1433960030
IE-FM6Z2L00005MSD0SD0-X	1	1433960050
IE-FM6Z2L00010MSD0SD0-X	1	1433960100

Core 50 µm, OM2

0.5 m
1.0 m
2.0 m
3.0 m
5.0 m
10.0 m

IE-FM5Z2L00005DSD0SD0-X	1	1433970005
IE-FM5Z2L00001MSD0SD0-X	1	1433970010
IE-FM5Z2L00002MSD0SD0-X	1	1433970020
IE-FM5Z2L00003MSD0SD0-X	1	1433970030
IE-FM5Z2L00005MSD0SD0-X	1	1433970050
IE-FM5Z2L00010MSD0SD0-X	1	1433970100

Note**Accessories****Marking tags**

Wire and cable markers. ø 4.7 - 7.4 mm
Wire and cable markers. ø 5.8 - 7.8 mm


Type	Qty.	Order No.
VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001

Type	Qty.	Order No.
VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001

Note

Assembled cables**CabinetLine FO patch cable**

- Multi-mode glass fibre optics
- LSZH Casing

LC-Duplex / LC-Duplex**Technical data**

Product type

Cable layout

Sheath diameter

Material sheath

Sheathing colour

Ambient temperature (operational)

Installation temperature

Storage temperature

Approvals

Note

Patch cable, duplex clip included

ZIPCORD

2.0 * 4.1 mm

LSZH

orange

-20 °C...70 °C

...

...

Ordering data**Core 62.5 µm, OM1**

Type	Qty.	Order No.
IE-FM6Z2L00005MLD0LDO-X	1	1433930005
IE-FM6Z2L00001MLD0LDO-X	1	1433930010
IE-FM6Z2L00002MLD0LDO-X	1	1433930020
IE-FM6Z2L00003MLD0LDO-X	1	1433930030
IE-FM6Z2L00005MLD0LDO-X	1	1433930050
IE-FM6Z2L00010MLD0LDO-X	1	1433930100

Core 50 µm, OM2

Type	Qty.	Order No.
IE-FM5Z2L00005MLD0LDO-X	1	1433940005
IE-FM5Z2L00001MLD0LDO-X	1	1433940010
IE-FM5Z2L00002MLD0LDO-X	1	1433940020
IE-FM5Z2L00003MLD0LDO-X	1	1433940030
IE-FM5Z2L00005MLD0LDO-X	1	1433940050
IE-FM5Z2L00010MLD0LDO-X	1	1433940100

Note**Accessories****Marking tags**


Wire and cable markers. ø 4.7 - 7.4 mm
Wire and cable markers. ø 5.8 - 7.8 mm

Type	Qty.	Order No.
VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001

Note

Assembled cables**CabinetLine FO patch cable**

- Single-mode glass fibre optics
- LSZH Casing

LC-Duplex / LC-Duplex**Technical data**

Product type

Cable layout

Sheath diameter

Material sheath

Sheathing colour

Ambient temperature (operational)

Installation temperature

Storage temperature

Approvals

Note

Patch cable, duplex clip included

ZIPCORD

2.0 * 4.1 mm

LSZH

yellow

-20 °C...70 °C

...

...

Ordering data**Core 9 µm. OS2**

0.5 m
1.0 m
2.0 m
3.0 m
5.0 m
10.0 m

Type	Qty.	Order No.
IE-FSMZ2LY0005MLD0LD0-X	1	1433950005
IE-FSMZ2LY0001MLD0LD0-X	1	1433950010
IE-FSMZ2LY0002MLD0LD0-X	1	1433950020
IE-FSMZ2LY0003MLD0LD0-X	1	1433950030
IE-FSMZ2LY0005MLD0LD0-X	1	1433950050
IE-FSMZ2LY0010MLD0LD0-X	1	1433950100

Note**Accessories****Marking tags**



Wire and cable markers. ø 4.7 - 7.4 mm
Wire and cable markers. ø 5.8 - 7.8 mm

Type	Qty.	Order No.
VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001

Note

Assembled cable**FO patch cable**

- Multimode glass optical fibre
- PVC outer cladding

SC-Duplex / SC-Duplex**ST / ST****Technical data**

Product type

Cable layout

Sheath diameter

Material sheath

Sheathing colour

Ambient temperature (operational)

Installation temperature

Storage temperature

Approvals

Note

Pre-assembled patch cable, crossover

ZIPCORD

3*6 mm

PVC

orange

-5 °C...75 °C

-5 °C...50 °C

-25 °C...75 °C

Patch cable

ZIPCORD

3*6 mm

PVC

orange

-5 °C...75 °C

-5 °C...50 °C

-25 °C...75 °C

Ordering data**Core 50 µm, OM2**

1.0 m

2.0 m

3.0 m

5.0 m

10.0 m

Core 62.5 µm, OM1

1.0 m

2.0 m

3.0 m

5.0 m

10.0 m

Note**Accessories****Marking tags**Wire and cable markers. ø 4.7 - 7.4 mm
Wire and cable markers. ø 5.8 - 7.8 mm



Type	Qty.	Order No.
IE-FM5Z2V00001MSD0SDOX	1	8813300000
IE-FM5Z2V00002MSD0SDOX	1	8813310000
IE-FM5Z2V00003MSD0SDOX	1	8813320000
IE-FM5Z2V00005MSD0SDOX	1	8876350050
IE-FM5Z2V00010MSD0SDOX	1	8876350100

Type	Qty.	Order No.
IE-FM5Z2V00001MST0STOX	1	8876370010
IE-FM5Z2V00002MST0STOX	1	8876370020
IE-FM5Z2V00003MST0STOX	1	8876370030
IE-FM5Z2V00005MST0STOX	1	8876370050
IE-FM5Z2V00010MST0STOX	1	8876370100

Note

Assembled cable**FO patch cable**

- Multimode glass optical fibre
- PVC outer cladding

ST / SC-Duplex**LC-Duplex / LC-Duplex****Technical data**

Product type

Cable layout

Sheath diameter

Material sheath

Sheathing colour

Ambient temperature (operational)

Installation temperature

Storage temperature

Approvals

Note

Pre-assembled patch cable, crossover

ZIPCORD

3*6 mm

PVC

orange

-5 °C...75 °C

-5 °C...50 °C

-25 °C...75 °C

Pre-assembled patch cable, crossover

ZIPCORD

3*6 mm

PVC

orange

-5 °C...75 °C

-5 °C...50 °C

-25 °C...75 °C

Ordering data**Core 62.5 µm, OM1**

1.0 m

2.0 m

Core 50 µm, OM2

1.0 m

2.0 m

5.0 m

10.0 m

Note**Type** **Qty.** **Order No.**

IE-FM6Z2V00002MST0SDOX 1 8813400000

IE-FM5Z2V00002MST0SDOX 1 8813390000

Type **Qty.** **Order No.**

IE-FM6Z2V00001MLD0LDOX 1 1296450000

IE-FM5Z2V00001MLD0LDOX 1 1276880000

IE-FM5Z2V00002MLD0LDOX 1 1062570000

IE-FM5Z2V00005MLD0LDOX 1 1062550000

IE-FM5Z2V00010MLD0LDOX 1 1062580000

Accessories**Marking tags**

Wire and cable markers. ø 4.7 - 7.4 mm

Wire and cable markers. ø 5.8 - 7.8 mm

Type **Qty.** **Order No.**

VT SF 5/21 MC NE WS V0 160 1689470001

VT SF 6/21 MC NE WS V0 160 1730560001

Type **Qty.** **Order No.**


VT SF 5/21 MC NE WS V0 160 1689470001

VT SF 6/21 MC NE WS V0 160 1730560001

Note

Assembled cable**FO patch cable PROFINET**

- Polymer optical fibre

SC-RJ / SC-RJ**Technical data**

Product type
Version connector left / Version connector right
Cable layout
Sheath diameter
Insulation
Sheathing colour
Fibre type
Core diameter
Ambient temperature (operational)
Attenuation
Insertion loss
Bandwidth
Halogen
Approvals

Connecting line
SCRJ IP 20 / SCRJ IP 20
ZIPCORD
2.2*4.5 mm
PE
black
POF
980 µm
-20 °C...80 °C
≤ 160 dB/km at 650 nm
≤ 1.0 dB
≥ 100 MHz*km at 650 nm
No

Note**Ordering data****POF 980/1000 µm**

1.0 m
3.0 m
5.0 m
10.0 m
20.0 m

Type	Qty.	Order No.
IE-FPOZ2EE0001MSJ0SJ0-X	1	1273430010
IE-FPOZ2EE0003MSJ0SJ0-X	1	1273430030
IE-FPOZ2EE0005MSJ0SJ0-X	1	1273430050
IE-FPOZ2EE0010MSJ0SJ0-X	1	1273430100
IE-FPOZ2EE0020MSJ0SJ0-X	1	1273430200

Note**Accessories****Marking tags**


Wire and cable markers. ø 4.7 - 7.4 mm
Wire and cable markers. ø 5.8 - 7.8 mm

Type	Qty.	Order No.
VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001

Note

Assembled cables**FO dragline cable**

- Multimode glass optical fibre

LC-Duplex / LC-Duplex**Technical data**

Product type
Version connector left / Version connector right
Cable layout
Sheath diameter
Material sheath
Sheathing colour
Ambient temperature (operational)
Installation temperature
Storage temperature
Approvals

Dragline cable
LC-Duplex IP 20 / LC-Duplex IP 20
Break-out dragline
6 mm
PUR
black
-40 °C...80 °C
-20 °C...60 °C
-40 °C...80 °C

Note**Ordering data****Core 62.5 µm, OM1**

5.0 m
20.0 m
50.0 m

Core 50 µm, OM2

10.0 m
50.0 m
100.0 m

Note

Type	Qty.	Order No.
IE-FM6D2UE0005MLD0LDOX	1	1220930000
IE-FM6D2UE0020MLD0LDOX	1	1174830000
IE-FM6D2UE0050MLD0LDOX	1	8993220000
IE-FM5D2UE0010MLD0LDOX	1	8979020000
IE-FM5D2UE0050MLD0LDOX	1	8979040000
IE-FM5D2UE0100MLD0LDOX	1	8979030000

Accessories**Marking tags**

Wire and cable markers. ø 4.7 - 7.4 mm
Wire and cable markers. ø 5.8 - 7.8 mm

Type	Qty.	Order No.
VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001

Note

Assembled cables - FO dragline cable

Assembled cable



FO dragline cable

- Multimode glass optical fibre

SC-Duplex / SC-Duplex



ST / ST



Technical data

Product type

Dragline cable

Sheath diameter

Material sheath

Sheathing colour

Ambient temperature (operational)

Installation temperature

Storage temperature

Approvals

Note

Dragline cable

Break-out dragline

6 mm

PUR

black

-40 °C...80 °C

-20 °C...60 °C

-40 °C...80 °C

Dragline cable

Break-out dragline

6 mm

PUR

black

-40 °C...80 °C

-20 °C...60 °C

-40 °C...80 °C

Ordering data

Core 62.5 µm, OM1

1.0 m

3.0 m

5.0 m

10.0 m

50.0 m

100.0 m

Core 50 µm, OM2

1.0 m

3.0 m

5.0 m

10.0 m

50.0 m

100.0 m

Note

Type Qty. Order No.

IE-FM6D2UE0001MSD0SDOX 1 8876440010

IE-FM6D2UE0003MSD0SDOX 1 8876440030

IE-FM6D2UE0005MSD0SDOX 1 8876440050

IE-FM6D2UE0010MSD0SDOX 1 8876440100

IE-FM6D2UE0050MSD0SDOX 1 8876440500

IE-FM6D2UE0100MSD0SDOX 1 8876441000

IE-FM5D2UE0001MSD0SDOX 1 8876430010

IE-FM5D2UE0003MSD0SDOX 1 8876430030

IE-FM5D2UE0005MSD0SDOX 1 8876430050

IE-FM5D2UE0010MSD0SDOX 1 8876430100

IE-FM5D2UE0050MSD0SDOX 1 8876430500

IE-FM5D2UE0100MSD0SDOX 1 8876431000

Type Qty. Order No.

IE-FM6D2UE0001MST0STOX 1 8876460010

IE-FM6D2UE0003MST0STOX 1 8876460030

IE-FM6D2UE0005MST0STOX 1 8876460050

IE-FM6D2UE0010MST0STOX 1 8876460100

IE-FM6D2UE0100MST0STOX 1 8876461000

IE-FM5D2UE0001MST0STOX 1 8876450010

IE-FM5D2UE0003MST0STOX 1 8876450030

IE-FM5D2UE0005MST0STOX 1 8876450050

IE-FM5D2UE0010MST0STOX 1 8876450100

IE-FM5D2UE0050MST0STOX 1 8876450500

IE-FM5D2UE0100MST0STOX 1 8876451000

Accessories

Marking tags

Wire and cable markers. ø 4.7 - 7.4 mm

Wire and cable markers. ø 5.8 - 7.8 mm

Type Qty. Order No.

VT SF 5/21 MC NE WS VO 160 1689470001

VT SF 6/21 MC NE WS VO 160 1730560001

Type Qty. Order No.

VT SF 5/21 MC NE WS VO 160 1689470001

VT SF 6/21 MC NE WS VO 160 1730560001


Note

Note

Note

Assembled cables**FO dragline cable with extended temperature range**

- Multimode glass optical fibre

SC-Duplex IP67**Technical data**

Product type
Cable layout
Version connector left / Version connector right
Sheath diameter
Material sheath
Sheathing colour
Fibre type
Bandwidth
Attenuation
Ambient temperature (operational)
Installation temperature
Storage temperature
Approvals

Dragline cable
Break-out dragline
SC IP 67 bayonet VO1 metal / SC IP 67 bayonet VO1 metal
7.5-8 mm
PUR
black
GOF, Multimode, OM1
200 MHz*km at 850 nm, 500 MHz*km at 1300 nm
2.7 dB/km at 850 nm, ≤ 0.5 dB/km at 1300 nm
40 °C...85 °C
-55 °C...60 °C
-55 °C...85 °C

Note**Ordering data****Core 62.5 µm. OM1**

100.0 m
180.0 m
200.0 m
250.0 m
300.0 m
350.0 m
500.0 m

Type	Qty.	Order No.
IE-FM6C2UE0100MSD1SD1X	1	1318011000
IE-FM6C2UE0180MSD1SD1X	1	1318011800
IE-FM6C2UE0200MSD1SD1X	1	1318012000
IE-FM6C2UE0250MSD1SD1X	1	1318012500
IE-FM6C2UE0300MSD1SD1X	1	1318013000
IE-FM6C2UE0350MSD1SD1X	1	1318013500
IE-FM6C2UE0500MSD1SD1X	1	1318015000

Note**Accessories****Marking tags**


Wire and cable markers. ø 4.7 - 7.4 mm
Wire and cable markers. ø 5.8 - 7.8 mm

Type	Qty.	Order No.
VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001

Note

Assembled cables - FO dragline cable**Assembled cables****FO dragline cable**

- Singlemode glass optical fibre

SC-Duplex IP67**Technical data**

Product type
Cable layout
Version connector left / Version connector right
Sheath diameter
Material sheath
Sheathing colour
Fibre type
Bandwidth
Insertion loss
Attenuation
Ambient temperature (operational)
Installation temperature
Storage temperature
Approvals

Dragline cable
Break-out dragline
SC IP 67 PushPull V14 metal / SC IP 67 PushPull V14 metal
6 mm
PUR
black
Singlemode, OS 2
≤ 0.5 dB
≤ 0.4 dB/km at 1310 nm
-40 °C...80 °C
-20 °C...60 °C
-40 °C...80 °C

Note**Ordering data****Core 9 µm. OS2**

5.0 m
20.0 m
25.0 m
40.0 m

Type	Qty.	Order No.
IE-FSMD2UE0005MSDESDEX	1	1449420050
IE-FSMD2UE0020MSDESDEX	1	1449420200
IE-FSMD2UE0025MSDESDEX	1	1449420250
IE-FSMD2UE0040MSDESDEX	1	1449420400

Note**Accessories****Marking tags**

Wire and cable markers. ø 4.7 - 7.4 mm
Wire and cable markers. ø 5.8 - 7.8 mm

Type	Qty.	Order No.
VT SF 5/21 MC NE WS VO	160	1689470001
VT SF 6/21 MC NE WS VO	160	1730560001

Note

Passive components

Overview of accessories

Accessories – Passive components	
Introduction	S.2
Connection system	S.3
Copper cabling tools	S.4
Fibre-optic cabling tools	S.10
General tools	S.15
Cabtite cable entry system	S.18
Cable guiding	S.23
Protective caps	S.24
Inkjet printer	S.25
Markers for cables and STEADYTEC®	S.27
Surge protection for data interfaces	S.28

Overview of accessories

Everything from a single source

Cable connector



Connection, repair or extension of Industrial Ethernet cables to Cat. 7_A

- fieldattachable with IDC connection technology
- Specified for class F_A
- IP67

Copper cabling tools



For assembling

- RJ45 crimp
- Hybrid insert

for stripping
to test the wiring

Cable guiding



Cable bender to guide patch cables safely and without cable breakage or data loss by 90° angles

Cabtite



System-based cable entry

- Cable entry strips
- Cable grommets

Fibre-optic cabling tools



For assembling

- SCRJ-POF
- SC-GOF
- ST-GOF

General tools



For pressing conductors into IDC terminals and pressing RJ45 contacts

- Indentation tool
- Pressing tool

Protective caps



to protect all IE-LINE connectors with **STEADYTEC®** technology

Marker




For identifying conductors, plugs and devices

- Line markers
- Housing and plug marker

Surge protection for data interfaces



For the protection of Cat. 5 and Cat. 6 data lines - also in PoE and PoE + applications

Cable connector class 7**Cable connector****Technical data**

Category	Class F _A (ISO/IEC11801 2011) with cat. 7 _A Cable
Protection degree	IP67
Connection 1 / 2	Insulation displacement technology / Insulation displacement technology
Housing main material	Zinc diecast
Ambient temperature (operational)	-40 °C...85 °C
Current-carrying capacity at 50 °C	0.5 A @ 40 °C
Rated voltage	63 V
Insulation strength	100 MO
Shielding	360° all-round enclosure
Connection diameter, flexible, min. / max.	0.48 mm / 0.76 mm
Connection cross-section, flexible, min. / max.	AWG 26 / AWG 22
Connection diameter, solid, min. / max.	0.4 mm / 0.64 mm
Connection cross-section, solid, min. / max.	AWG 24 / AWG 22
Insulation cross-section, max.	1.6 mm
Sheath diameter min. / max.	5 mm / 9.7 mm
Approvals	EAC

Note**Ordering data**

Type	Qty.	Order No.
IE-CC-8W-FA-IP67	1	1499940000

Note**Accessories**

Type	Qty.	Order No.

Note

Copper cabling tools

Stripping tools

IE-CST

1- and 2-step stripping in one operation



AM 12

For UTP and STP data cables



Stripping tool for round (shielded) data cables of Ø 2.5...8 mm

- Specially designed for Ethernet cables
- Strips sheathing and cuts shield in one operation
- Blue blade cartridge included in delivery

- Cutting of UTP and STP data cables and other flexible copper cables with a diameter of up to 4 mm² (~AWG11)
- Stripping of the outer insulations of UTP and STP data cables and other round cables with Ø 0.5 ... 12.5 mm
- No damage to the shielding or conductor due to adjustable stripping blade
- Length gauge for repeated stripping lengths

S

Technical data

Max. cutting performance copper cable

Cable model	
Conductor cross-section	AWG
Conductor diameter	mm
Adjustable depth of cut	mm
Cutting performance	
Non-shielded & shielded data cables	mm
Flexible copper cable	mm ²
Tool data	
Length	mm
Weight	g

IE-CST

coaxial & round data cables

2.5 ... 8

AM 12

UTP and STP data cables

0.5...12.5

adjustable

8

4

97

36

Note

Ordering data

Type Qty. Order No.

IE-CST 1 9204350000

Type Qty. Order No.

AM 12 1 9030060000

Note

Accessories

Type Qty. Order No.

Spare cutter cassette 1 9032020000

Type Qty. Order No.

Note

Pressing tools

- Press (punch-down) tool for Ethernet connectors
- Ratchet for precise crimping
- Release option in the event of incorrect operation

TT 8 RS MP 8

For 8-pole shielded RJ45 plug

- AWG 27...24

**Technical data****Description of contact**

No. of poles

Tool data

Length

mm

Weight

g

Note**Ordering data****Version****TT 8 RS MP 8**

8

255

1251

Note

Type	Qty.	Order No.
TT 8 RS MP 8	1	9202800000

Copper cabling tools**Pressing tools**

- Press (punch-down) tool for Ethernet connectors
- Ratchet for precise crimping
- Release option in the event of incorrect operation

IE-CWZ-RJ45-TH-P

For 4-pole shielded RJ45 plug

- AWG 23..22

**S****Technical data**

Description of contact		
No. of poles		
Tool data		
Length	mm	
Weight	g	
Note		

IE-CWZ-RJ45-TH-P		
4		
250		
570		

Ordering data

Version	Type	Qty.	Order No.
	IE-CWZ-RJ45-TH-P	1	2614210000
Note			

Type	Qty.	Order No.
IE-CWZ-RJ45-TH-P	1	2614210000

Cable Tester

Test devices for testing Ethernet cables, including remote box

LAN USB TESTER

- Indication of connection errors:
Connection error
Interrupt
Short-circuit
Permutation
- Network cable tester for LAN and USB connections

**IE-CT**

- Indication of connection errors:
Connection error
Interrupt
Short-circuit
Permutation
Wire mix-up (split pair)
External voltage
- External voltage resistance: 80 V AC / DC

Technical data

Display	
Supply	
Type of connection	
Remote box dimensions	
Remote box weight	
Length / Width / Height	mm
Weight	
Note	

LED	
9 V battery	
RJ45, USB A, USB B	
65 x 28 x 27 mm	
30 g	
135 / 65 / 27	
174 g	

Ordering data

Version	Type	Qty.	Order No.
	LAN USB TESTER	1	9205400000

Note

Type	Qty.	Order No.
IE-CT	1	8808420000

Battery, accessories and bag included in delivery.
--

7-segment display	
9 V battery	
RJ45	
30 x 68 x 23 mm	
31 g	
140 / 70 / 36	
185 g	

Battery, accessories and bag included in delivery.	
Spare IE-CT: 1506880000	

Copper cabling tools

Cutting tools

- The cutting blade design for different cable sizes increases the quality of the cuts for smaller cross-sections
- Not suitable for steel wires, steel-armoured cables, aluminium alloys and hard-drawn copper conductors!
- Cutting without deformation of the conductor
- Do not cut live conductors
- Individually tested protective insulation, 1000V, VDE and GS tested in accordance with EN/IEC 60900
- Optimised handle ergonomics
- Minimal hand force required



KT 8



KT 12



max. 8 mm

max. 16 mm²

max. 16 mm²

max. 16 mm²

max. 12 mm

max. 16 mm²

max. 25 mm²

max. 35 mm²



Technical data

Max. cutting performance, copper cable

Copper cable - solid, max.
Copper cable - stranded, max.
Copper cable - flexible, max.
Copper cable, max. diameter

Max. cutting performance, aluminium cable

Stranded aluminium cable, max (mm²)
Stranded aluminium cable, max. diameter
Single-core aluminium cable, max.(mm²)

Data / telephone / control cable

Data / telephone / control cable, max. Ø

Tool data

Depth / Width / Height

Weight

Note

Ordering data

Version

KT8

16 mm² / 6 AWG

16 mm² / 6 AWG

16 mm² / 6 AWG

8 mm

16 mm² / 6 AWG

8 mm

16 mm²

8 mm

30 / 185 / 65.5 mm

180 g

Tool closed

KT12

16 mm² / 6 AWG

25 mm² / 3 AWG

35 mm² / 2 AWG

12 mm

25 mm² / 6 AWG

8 mm

25 mm²

12 mm

30 / 225 / 63.5 mm

300 g

Tool closed

Note

Type Qty. Order No.

KT 8	1	9002650000
------	---	------------

Type Qty. Order No.

KT 12	1	9002660000
-------	---	------------

SEE ESD 120**Electronic ESD diagonal-cutting pliers with pointed head**

- Hard wire (spring wire or steel nails):
0.2 mm/AWG 32
- Semi-hard wire (iron or nails):
1.0 mm/AWG 18
- Soft wire (copper or aluminium):
1.5 mm/AWG 15

Ordering data

Type	Qty.	Order No.
SEE ESD 120	1	9205130000

**SEE ESD 125****Electronic ESD diagonal-cutting pliers with oval head**

- Semi-hard wire (iron or nails):
0.3 mm/AWG 29
- Soft wire (copper or aluminium):
1.5 mm/AWG 15

Ordering data

Type	Qty.	Order No.
SEE ESD 125	1	9204750000

**FZE ESD 130****Electronic ESD flat-nosed pliers****Ordering data**

Type	Qty.	Order No.
FZE ESD 130	1	9204760000

**SZE ESD 130****Electronic ESD Snipe-nosed pliers****Ordering data**

Type	Qty.	Order No.
SZE ESD 130	1	9204770000

**SVSE ESD 130****Electronic ESD angle-cutting pliers**

- Hard wire (spring wire or steel nails):
0.6 mm/AWG 22
- Semi-hard wire (iron or nails):
1.0 mm/AWG 18
- Soft wire (copper or aluminium):
1.2 mm/AWG 16

Ordering data

Type	Qty.	Order No.
SVSE ESD 130	1	9205140000

**SUPER CUT****Electronic diagonal-cutting pliers**

- Soft wire (copper or aluminium):
1.2 mm/AWG 16

Ordering data

Type	Qty.	Order No.
SUPER CUT	1	9205150000

**KOF SET ESD****Electronic ESD case set**

Contents:

- Diagonal-cutting pliers
- Snipe-nosed pliers
- Flat-nose pliers
- Angle-cutting pliers

Ordering data

Type	Qty.	Order No.
KOF SET ESD	1	9205210000



Fibre-optic cabling tools

Crimping tools

Cutting, stripping and crimping tools for processing POF fibres in compliance with IEC 60793-2 A4A fibres (1000 µm/980 µm POF)

- Multifunction tool for POF fibres
- Processing the duplex POF fibres
- Stripping tool for processing POF fibres and cables
- The new set of blades for POF cables makes stripping the outer covering and the POF fibres simple
- Cable shears specially designed for aramid fibres
- Only for cutting aramid fibres
(strain relief in fibre-optic cables)

Tool-Set IE-POF



Contents:

- Assortment case PSC 80
- Kevlar scissors for aramid fibres
- Multifunction tool HTX-IE-POF
- Stripping tool multi-stripax® IE-POF

multi-stripax® POF



- Excellent stripping quality for industrial applications
- Specially shaped blades enable stripping of special types of insulation and conductor configurations
- Stripping length with end stop, adjustable from 2.3...30 mm
- Very versatile thanks to interchangeable stripping units
- Stripping results reproduced accurately over and over again
- No damage to the conductor
- A long-lasting, reliable tool thanks to its sturdy design
- Integrated cutting function up to 6 mm²

S

Technical data

Length / Width / Height	mm	241 / 338 / 79
Weight	g	1,800
Note		

250 / 85 / 40	250

Ordering data

Version	Type	Qty.	Order No.
	TOOL SET IE-POF	1	1208930000

Type	Qty.	Order No.
MULTI-STRIPAX IE-POF	1	1208880000

Accessories

Type	Qty.	Order No.
HTX-IE-POF	1	1208870000
MULTI-STRIPAX IE-POF	1	1208880000
KEVLAR SCISSORS	1	1208910000

Type	Qty.	Order No.
Replacement cutting blade	1	9203100000
Replacement stop set	1	9203070000
AIE MULTI-STRIPAX POF	1	1212770000

Mounting tools

- Release option in the event of incorrect operation
- With end stop for exact positioning of the contacts

HTX-IE-POF**HTX-HTX-IE-POF-QA**

- Only one tool needed for all SC-RJ plug processing steps
- For processing 1 mm thick polymer optical fibres, especially for the PROFINET and EtherNet/IP-SC-RJ connectors
- For stripping Duplex polymer optical fibres
- The plug is crimped and the polymer optical fibres are separated, all in a single step
- Cut surfaces do not need to be polished after cutting
- Locator for precise positioning of the SC-RJ plugs
- Ergonomic handles
- High repeat accuracy
- Ratchet for precise crimping

Three steps to produce IP67 connectors:

- 1) Strip the Duplex polymer optical fibres
- 2) Crimp and separate
- 3) Crimp the strain relief

- Only one tool needed for all SC-RJ QA (reconnectable) plug processing steps
- For processing 1 mm thick polymer optical fibres, especially for the PROFINET and EtherNet/IP-SC-RJ connectors
- For stripping Duplex polymer optical fibres
- Cut surfaces do not need to be polished after cutting
- Locator for precise positioning of the SC-RJ plugs
- Ergonomic handles
- High repeat accuracy

Three steps to produce IP67 connectors:

- 1) Strip the Duplex polymer optical fibres
- 2) Tighten strain relief
- 3) Insert and Cutting

Technical data**Material data**

Length
Weight

Note**Ordering data****Version****Note****HTX-IE-POF**

220
450

HTX-HTX-IE-POF-QA

220
450

Type

HTX-IE-POF

Qty.

1

Order No.

1208870000

Type

HTX-HTX-IE-POF-QA

Qty.

1

Order No.

2602860000

Kevlar Scissor

- Cable shears specially designed for aramid fibres

SCISSOR Kevlar

- Only for cutting aramid fibres (strain relief in fibre-optic cables)
- Do not use for other materials
- Special blade geometry
- Blades ground
- With teeth on the cutting edge
- Riveted joint
- Hand-friendly, impact-resistant plastic handles

S**Technical data****Material data**

Length
Weight

Note**SCISSORS KEVLAR**

147
100

Ordering data**Version**

Type	Qty.	Order No.
SCISSORS KEVLAR	1	1208910000

Note

Crimping tool for other contacts

- Ratchet for precise crimping
- Release option in the event of incorrect operation
- With end stop for exact positioning of the contacts
- Contact and insulation are crimped in one step

HTF HYB

0.08...1.0 mm²



For Weidmüller hybrid sockets and pins

- ~AWG 28...AWG 17



Technical data

Description of contact

Type of contact	
Crimping range	mm ²
Crimping range 1 (with multiple crimping positions)	mm ²
Crimping range 2 (with multiple crimping positions)	mm ²
Crimping range 3 (with multiple crimping positions)	mm ²

Tool data

Length	mm
Weight	g

Note

Ordering data

Version

HTF HYB

Hybrid sockets / plugs

0.08...1
0.08...0.2
0.2...0.5
0.75...1

200
438

Note

Type	Qty.	Order No.
HTF HYB	1	1119580000

Special stripping tools

- Quick and accurate stripping
- No need to adjust cutting depth
- No damage to inner conductors

LWL-stripax®

Stripping and cutting tool for plastic fibre-optic cables with 1-mm diameter inner conductor

- Stripping length adjustable via end stop
- Automatic opening of the clamping jaws after stripping

S**Technical data****Max. stripping performance**

Cable type	
Conductor diameter, min. / max.	-
Stripping length, max.	-

Tool data

Width	mm
Height	mm
Weight	g

Note**M-D-STRIPAX LWL**

POF conductor with an inner conductor of 1 mm Ø

7.5

82

135

110

POF: polymer optical fibre

Ordering data**Version**

Type	Qty.	Order No.
M-D-STRIPAX LWL	1	9003750000

Note**Accessories****Note**

Type	Qty.	Order No.
Spare stripping blades	1	9003760000

Incision tool for twisted-pair cable

For connecting twisted-pair cable to terminal rails with IDC contacts e.g. in main and floor distributors, and in modular wall junction boxes for structured building cabling.

PDT



IE-FISP-V4



The punch-down tool has the following features:

- Mechanics made from metal components
- Adjustable pressing force for conductor sizes AWG 20 to AWG 28
- Different blades for connector blocks of type 110 from AT&T, type 66, type LSA Plus from Krone (Standard and scissors cutting function) as well as for telephone outlets 630A6
- Incision blades with 2 functions: incision or incision with cutting off of remaining conductor
- Storage compartment for one blade

Fastening tool for the hexagon cap nut from **STEADYTEC®** V4 flange and FrontCom® Micro.



A = PD blade 110

B = PD blade 66

C = PD blade 630

D = PD blade Krone LSA (standard)

E = PD blade Krone LSA (scissor)

Technical data

Length / Width / Height	mm
Weight	g
Note	

Ordering data

Version

Type	Qty.	Order No.
PUNCH DOWN TOOL PDT	1	9013970000
(without blade)		

Type	Qty.	Order No.
IE-FISP-V4	2	9204370000

Accessories

Note

Type	Qty.	Order No.
PD blade Krone LSA Plus (scissor)	1	9014050000
PD blade 110	1	9013960000
PD blade 630	1	9013990000
PD blade 66	1	9013980000
PD blade Krone LSA Plus (standard)	1	9014000000

Type	Qty.	Order No.

Note

General tools

Hydraulic sheet holes

Incl. accessories:

- 1 HSS pre-drill Ø 10 mm
- 1 tension bolt Ø 19 mm
- 1 tension bolt Ø 19 x 9.5 mm
- 1 spacer nut set (3-part)
- 1 bridge

IE-KO-HAT



- Pressure relief valve protects against overloading
- Cylinder head angled at 90°
- Angled head can be rotated through 360°
- Ergonomic handle springs back automatically
- The waste piece no longer becomes jammed thanks to 3-fold splitter
- Hydraulic punch made of high-strength aluminium (approx. 40% weight saving)
- Service life greatly reduced when stainless steel sheets are used

Technical data

Maximum steel-sheet punching performance

Round holes from 1 to Ø 85 mm

Round holes from 2 to Ø 64 mm

Square holes up to

Rectangular holes up to

Maximum stainless steel sheet punching performance

Round holes from 3 to Ø 64 mm

Tool data

Depth / Width / Height

Weight

Punching force

Max. operating pressure

Note

Ordering data

Version

IE-KO-HAT

2,0 mm F = 370 N/mm²

3,0 mm F = 370 N/mm²

68 x 68 mm; 2,0 mm F = 370 N/mm²

36 x 112 mm; 2,0 mm F = 370 N/mm²

2,5 mm F = 600 N/mm²

70 / 290 / 120 mm

1.9 kg

75 kN

650 bar

Tension bolt KOHS 19



Tension bolts KOHS 9.5+19



Accessories

Tension bolt

Tension bolts

Pre-drill

Note

Type Qty. Order No.

IE-KO-HAT 1 1966810000



Pre-drill KOPD 10.0

Custom stamp for Industrial Ethernet connections



Type	Description	Dimensions	Qty.	Order No.
IE-KOK-V1	Custom shape for Bajonet O1 metal	Diameter 27 mm x 1 side 25.9 mm	1	1966780000
IE-KOK-V4	Custom shape for Push Pull V04 plastic	Diameter 23.2 mm x 2 sides 20.2 mm	1	1966790000
IE-KOK-V5	Custom shape for RockStar® V05 metal	22.0 x 22.0 mm	1	9204790000

Cabtite cable entry system**Cabtite SE - Sealing element small**Cable grommets
for ASI cables

The Cabtite SE sealing elements are used in the Cabtite FR frame or in the separable cable gland Cabtite CGS. The conical design allows easy installation, reliably seals gaps and provides strain relief in accordance with DIN EN 62444. For installation, the sealing elements are pressed from the inside to the outside into the snap-in inlays previously fitted in the frame or, in the case of the Cabtite CGS divisible cable gland, are placed between the cable gland half-shells. Various sealing elements with different cable diameters and geometries are available.

Technical data

Material	TPE
Halogen / Silicone	No / No
Operating temperature, min.	Light Grey: -40 °C; Deep black: -40 °C
Operating temperature, max.	Light Grey: 90 °C; Deep black: 120 °C
UL 94 flammability rating	Light Grey: V-0; Deep black: HB
Note	

Ordering data

Type	Clamping range	Qty.	Deep black	Light Grey
			Order No.	Order No.
Individual sealing elements				
CABTITE SE 1.5-2 SML	1.5...2 mm	10	2584780000	2583360000
CABTITE SE 2-3 SML	2...3 mm	10	2584760000	2583380000
CABTITE SE 3-4 SML	3...4 mm	10	2584730000	2583400000
CABTITE SE 4-5 SML	4...5 mm	10	2584680000	2583440000
CABTITE SE 5-6 SML	5...6 mm	10	2584710000	2583450000
CABTITE SE 6-7 SML	6...7 mm	10	2584690000	2583460000
CABTITE SE 7-8 SML	7...8 mm	10	2584670000	2584660000
CABTITE SE 8-9 SML	8...9 mm	10	2584330000	2584650000
CABTITE SE 9-10 SML	9...10 mm	10	2584080000	2584630000
CABTITE SE 10-11 SML	10...11 mm	10	2584060000	2584610000
CABTITE SE 11-12 SML	11...12 mm	10	2584040000	2584600000
CABTITE SE 12-13 SML	12...13 mm	10	2584020000	2584590000
CABTITE SE 13-14 SML	13...14 mm	10	2584000000	2584570000
CABTITE SE 14-15 SML	14...15 mm	10	2583980000	2584560000
CABTITE SE 15-16 SML	15...16 mm	10	2583960000	2584550000
Special geometry ASI				
CABTITE SE 1/ASI SML		10	2583530000	2584810000
CABTITE SE 2/ASI SML		10	2583520000	2584800000
Multiple sealing element				
CABTITE SE 2/4-5 SML	4...5 mm	10	2583620000	2584900000
CABTITE SE 2/5-6 SML	5...6 mm	10	2583610000	2584890000
CABTITE SE 2/7 SML	7...8 mm	10	2583550000	2584830000
CABTITE SE 2/8 SML	8...9 mm	10	2583540000	2584820000
CABTITE SE 3/5-6 SML	5...6 mm	10	2652280000	2652290000
CABTITE SE 4/2-3 SML	2...3 mm	10	2583590000	2584870000
CABTITE SE 4/3-4 SML	3...4 mm	10	2583580000	2584860000
CABTITE SE 4/4-5 SML	4...5 mm	10	2583560000	2584840000
Cone sealing element				
CABTITE CSE 2-11 SML	2...11 mm	10	2583510000	
Blind plugs				
CABTITE BSE SML		10	2584790000	2583350000
Note				

Cabtite SE - sealing elements large

Blanking plugs

Cone sealing element



The Cabtite SE sealing elements in large design are identical in construction to those in small design. However, they can accommodate cables with a larger outer diameter.

Technical data

Material	TPE
Halogen / Silicone	No / No
Operating temperature, min.	Deep black: -40 °C; Light Grey: -40 °C
Operating temperature, max.	Deep black: 120 °C; Light Grey: 90 °C
UL 94 flammability rating	Deep black: HB; Light Grey: V-0
Note	

Ordering data

Type	Clamping range	Qty.	Deep black	Light Grey
			Order No.	Order No.
Individual sealing elements				
CABTITE SE 14-15 LRG	14...15 mm	10	2583880000	2584510000
CABTITE SE 15-16 LRG	15...16 mm	10	2583860000	2584500000
CABTITE SE 16-17 LRG	16...17 mm	10	2583850000	2584490000
CABTITE SE 17-18 LRG	17...18 mm	10	2583840000	2584480000
CABTITE SE 18-19 LRG	18...19 mm	10	2583830000	2584470000
CABTITE SE 19-20 LRG	19...20 mm	10	2583810000	2584460000
CABTITE SE 20-21 LRG	20...21 mm	10	2583790000	2584450000
CABTITE SE 21-22 LRG	21...22 mm	10	2583770000	2584440000
CABTITE SE 22-23 LRG	22...23 mm	10	2583750000	2584430000
CABTITE SE 23-24 LRG	23...24 mm	10	2583730000	2584420000
CABTITE SE 24-25 LRG	24...25 mm	10	2583710000	2584410000
CABTITE SE 25-26 LRG	25...26 mm	10	2583700000	2584400000
CABTITE SE 26-27 LRG	26...27 mm	10	2583690000	2584390000
CABTITE SE 27-28 LRG	27...28 mm	10	2583680000	2584370000
CABTITE SE 28-29 LRG	28...29 mm	10	2583670000	2584350000
CABTITE SE 29-30 LRG	29...30 mm	10	2583660000	2584380000
CABTITE SE 30-31 LRG	30...31 mm	10	2583650000	2584360000
CABTITE SE 31-32 LRG	31...32 mm	10	2583640000	2584340000
CABTITE SE 32-33 LRG	32...33 mm	10	2583630000	2584920000
CABTITE SE 33-34 LRG	33...34 mm	10	2595510000	2584910000
CABTITE SE 34-35 LRG	34...35 mm	10	2595520000	2595530000
Cone sealing element				
CABTITE CSE 7-24 LRG	7...24 mm	10	2583500000	
Blind plugs				
CABTITE BSE LRG		10	2583900000	2584520000
Note				

Cabtite FR - CABTITE FR 4-1 BK SET

The one-piece frame, consisting of a dimensionally stable, fibreglass-reinforced plastic, is quick and easy to assemble and available in four different sizes. The foamed, captive seal guarantees a high degree of impermeability to IP66, even with painted or rough surfaces. The frame sets contain the appropriate Rastinlays to realize the individual configuration (see above a or b) of small and large sealing elements. The sealing elements are not included in the frame set and must be selected to match the cable diameter.

Technical data

Material	Polyamide, glass fibre-reinforced	
Colour	Deep black	
Operating temperature	-40...120 °C	
Protection class / Protection class (UL)	IP54, IP65, IP66 / Type 12, Type 4x	
UL 94 flammability rating	V-0	



Note**Ordering data**

Type	Qty.	Order No.
Set		
CABTITE FR 4-1 BK SET	1	2583780000
Single frame (without snap-in inlay)		
CABTITE FR 4-1 BK	1	2583490000

Note The individual frames do not contain any Rastinlays or sealing elements.

Accessories

Product type	Type	Qty.	Order No.
Locking frame (inside)	CABTITE FRL 4-1 BK	10	2584260000
Operating tool	CABTITE TOOL ATSE PA	1	2637360000
Mounting screw set	CABTITE SC M5X25 SET	1	2635120000

Note**Dimensioned drawing****Cabtite FR - CABTITE FR 10/6 BK SET**

The one-piece frame, consisting of a dimensionally stable, fibreglass-reinforced plastic, is quick and easy to assemble and available in four different sizes. The foamed, captive seal guarantees a high degree of impermeability to IP66, even with painted or rough surfaces. The frame sets contain the appropriate Rastinlays to realize the individual configuration (see above a or b) of small and large sealing elements. The sealing elements are not included in the frame set and must be selected to match the cable diameter.

Technical data

Material	Polyamide, glass fibre-reinforced	
Colour	Deep black	
Operating temperature	-40...120 °C	
Protection class / Protection class (UL)	IP54, IP65, IP66 / Type 12, Type 4x	
UL 94 flammability rating	V-0	


Note**Ordering data**


Type	Qty.	Order No.
Set		
CABTITE FR 10/6 BK SET	1	2583760000
Single frame (without snap-in inlay)		
CABTITE FR 10/6 BK	1	2583480000

Note The individual frames do not contain any Rastinlays or sealing elements.

Accessories

Product type	Type	Qty.	Order No.
Locking frame (inside)	CABTITE FRL 10/6 BK	10	2584240000
Operating tool	CABTITE TOOL ATSE PA	1	2637360000
Mounting screw set	CABTITE SC M5X25 SET	1	2635120000

Note**Dimensioned drawing**

Cabtite cable entry system**Cabtite FR - CABTITE FR 16/8 BK SET**

The one-piece frame, consisting of a dimensionally stable, fibreglass-reinforced plastic, is quick and easy to assemble and available in four different sizes. The foamed, captive seal guarantees a high degree of impermeability to IP66, even with painted or rough surfaces. The frame sets contain the appropriate Rastinlays to realize the individual configuration (see above a, b or c) of small and large sealing elements. The sealing elements are not included in the frame set and must be selected to match the cable diameters.

Technical data

Material	Polyamide, glass fibre-reinforced	
Colour	Deep black	
Operating temperature	-40...120 °C	
Protection class / Protection class (UL)	IP54, IP65, IP66 / Type 12, Type 4x	
UL 94 flammability rating	V-0	



Note**Ordering data**

Type	Qty.	Order No.
Set		
CABTITE FR 16/8 BK SET	1	2583740000
Single frame (without snap-in inlay)		
CABTITE FR 16/8 BK	1	2583470000

Note The individual frames do not contain any Rastinlays or sealing elements.

Accessories

Product type	Type	Qty.	Order No.
Locking frame (inside)	CABTITE FRL 16/8 BK	10	2584220000
Operating tool	CABTITE TOOL ATSE PA	1	2637360000
Mounting screw set	CABTITE SC M5X25 SET	1	2635120000

Note**Dimensioned drawing****Cabtite FR - CABTITE FR 24/10 BK SET**

The one-piece frame, consisting of a dimensionally stable, fibreglass-reinforced plastic, is quick and easy to assemble and available in four different sizes. The foamed, captive seal guarantees a high degree of impermeability to IP66, even with painted or rough surfaces. The frame sets contain the appropriate Rastinlays to realize the individual configuration (see above a, b or c) of small and large sealing elements. The sealing elements are not included in the frame set and must be selected to match the cable diameters.

Technical data

Material	Polyamide, glass fibre-reinforced	
Colour	Deep black	
Operating temperature	-40...120 °C	
Protection class / Protection class (UL)	IP54, IP65, IP66 / Type 12, Type 4x	
UL 94 flammability rating	V-0	


Note**Ordering data**

Type	Qty.	Order No.
Set		
CABTITE FR 24/10 BK SET	1	2583720000
Single frame (without snap-in inlay)		
CABTITE FR 24/10 BK	1	2583800000

Note The individual frames do not contain any Rastinlays or sealing elements.

Accessories

Product type	Type	Qty.	Order No.
Locking frame (inside)	CABTITE FRL 24/10 BK	10	2584210000
Operating tool	CABTITE TOOL ATSE PA	1	2637360000
Mounting screw set	CABTITE SC M5X25 SET	1	2635120000

Note**Dimensioned drawing**

Cabtite CGD - separable cable gland

Spare counter nut

For metric through holes from M20 to M63, the Cabtite cable entry system offers separable cable glands for cables with and without plugs. In case of maintenance or changes in the system, pre-assembled cables with diameters from 2 to 35 mm can be quickly and safely inserted into switch cabinets or housings. After inserting the sealing elements (Cabtite SE), the two halves of the cable gland are simply snapped together. A likewise separable lock nut on the inside of the cabinet ensures a secure and firm hold.

Technical data

Material	Polyamide, glass fibre-reinforced
Colour	Deep black
Operating temperature	-40...120 °C
Protection class / Protection class (UL)	IP54, IP65, IP66 /
UL 94 flammability rating	V-0


Note

Ordering data

Type	Qty.	Order No.
Divisible cable gland*		
CABTITE CGS M20 BK	10	2584200000
CABTITE CGS M25 BK	10	2584180000
CABTITE CGS M32 BK	10	2584160000
CABTITE CGS M40 BK	5	2584150000
CABTITE CGS M50 BK	5	2584130000
CABTITE CGS M63 BK	5	2584120000
Articulated locknut		
CABTITE LNS M20 BK	10	2584110000
CABTITE LNS M25 BK	10	2584090000
CABTITE LNS M32 BK	10	2584070000
CABTITE LNS M40 BK	5	2584050000
CABTITE LNS M50 BK	5	2584030000
CABTITE LNS M63 BK	5	2584010000
Rastinly for M40-M63**		
CABTITE GI X BK	5	2584290000

Note

*The cable glands are supplied with a locknut. **The snap-in insert is required to install 4 small sealing elements in the cable gland.

Dimensioned drawing**Cabtite GI - Rastinlay**

The insertable snap-in inlay allows the frame openings/cable glands to be configured as required for the small or large sealing elements used. Thus the Cabtite cable entry system can be variably configured for different requirements (cables, lines, hoses, pneumatic and hydraulic lines).

Technical data


Material	Polyamide, glass fibre-reinforced
Colour	Deep black
Operating temperature	-40...120 °C
Protection class / Protection class (UL)	IP54, IP65, IP66 /
UL 94 flammability rating	V-0

Note

Ordering data

Type	Qty.	Order No.
CABTITE GI I BK	5	2584320000
CABTITE GI T BK	5	2584300000
CABTITE GI H BK	5	2584270000
Rastinly for M40-M63**		
CABTITE GI X BK	5	2584290000

Note **The locking inlay is required to install 4 small sealing elements in the cable gland.

Dimensioned drawing

Cabtite cable entry system**Cabtite CR - Cable support strips (EMC)**


In combination with a large number of different shield connection clamps (KL Bü), the shield connection rails enable practical, uncomplicated and fast shielding of cables.

Technical data

Material	Steel, galvanized
Colour	silver

Note**Ordering data**

Type	Qty.	Order No.
CABTITE CR 4-1 EMV	10	2583950000
CABTITE CR 10/6 EMV	10	2583930000
CABTITE CR 16/8 EMV	10	2583910000
CABTITE CR 24/10 EMV	10	2583890000

Note**Dimensioned drawing****Cabtite BP - Blanking plug**

The blind plugs are used for the safe closing of unneeded cable passages in the sealing elements.

Technical data

Material	Polyamide
Colour	red
Operating temperature	-60...100 °C

Note**Ordering data**

Type	Qty.	Order No.
CABTITE BP 2MM PA	50	2652300000
CABTITE BP 3MM PA	50	2652310000
CABTITE BP 4MM PA	50	2652320000
CABTITE BP 5MM PA	50	2652330000
CABTITE BP 6MM PA	50	2652340000
CABTITE BP 7MM PA	50	2652350000
CABTITE BP 8MM PA	50	2652360000
CABTITE BP 9MM PA	50	2652370000
CABTITE BP 10MM PA	50	2652380000
CABTITE BP 12MM PA	50	2652400000
CABTITE BP 13MM PA	50	2652410000
CABTITE BP 14MM PA	50	2652420000
CABTITE BP 17MM PA	50	2652430000
CABTITE BP 20MM PA	50	2652440000
CABTITE BP 21MM PA	50	2652450000
CABTITE BP 25MM PA	50	2652460000
CABTITE BP 28MM PA	50	2652470000
CABTITE BP 35MM PA	50	2652480000

Note

Cable Bender

Cable bender to guide patch cables safely and without cable breakage or data loss by 90° angles

Cable bender**Technical data**

Cable bending radius

90 °

Colour

black

Temperature range

-25 °C...85 °C

Sheath diameter, min.


5.5 mm

Sheath diameter, max.

6.5 mm

Hinweis**Ordering data****Note**

Type	Qty.	Order No.
IE-CABLE-BENDER-90	50	2704480000

Dimensioned drawings

Protective caps

Dust-protection plugs for protecting empty ports

- RJ45
- **STEADYTEC®** variants
- M12

Dust Cap RJ45



Protective caps IP67



- Dust Cap RJ45 with finger grip

- Protective caps for all **STEADYTEC®** variants and for M12 plug-in connectors

Ordering data

Type	Qty.	Order No.
IE-DPC	100	8813490000

Type	Qty.	Order No.
V1 Bayonet plug	10	1965690000
V1 Bayonet flange	10	1965700000
V4 PushPull plug	10	1963890000
V4 PushPull flange	10	1963900000
V5 HDC plug	10	1968920000
V5 HDC flange	10	1968930000
V14 PushPull plug	10	1058280000
V14 PushPull flange	10	1058310000
PushPull Power flange	10	1068930000
M12 plug	1	2330260000
M12 flange	1	8425960000

Note

S

PrintJet CONNECT

The networked high-performance printer for efficient and high-quality markings

Your direct connection to the optimal marking process

The PrintJet CONNECT is the consistent further development of our tried-and-tested PrintJet series. Focusing on the modern needs of industry and panel building, it combines maximum process and cost efficiency with intelligent networking and complete data consistency. For example, you can use existing data directly in the marking process – for working more efficiently and with a minimal error rate. The PrintJet CONNECT is part of the Weidmüller marking system consisting of software, markers and printers. It has an extremely durable industrial print head and has been specially optimised for fast working speed and high throughput.

Your advantages at a glance:

- Perfect printing results every time
- Fast handling of large volumes
- High level of automation thanks to magazine capacity of 50 MultiCards
- Durable and robust markers thanks to thermal fixing
- User-friendly operation thanks to intuitive touch display
- Flexible connection possibilities
- Simple function monitoring on the device

Technical data

	Description	
Intended use	Printing Weidmüller MultiCards and MetalliCards	
Technology	Inkjet procedure with integrated thermal fixing unit	
Feed	Automatic magazine for max. 30 MultiCards Individual feed for MetalliCards and MultiCards	
Removal	Automatic dispenser magazine for up to 50 MultiCards	
Fuses	10 ATH 240/120 V	
Application site	Office conditions	
Ambient temperature	10 °C - 35 °C 0 °F - 95 °F	
Dimensions	Length including output rail: Length not including output rail: Width: Height:	approx. 1.133 mm (44,60") approx. 930 mm (36,60") 590 mm (23,20") 454 mm (17,90")
Weight	63 kg with packaging 38 kg without packaging	
Ink system	Colour system - black, cyan, magenta, yellow	
Included in delivery	<ul style="list-style-type: none"> • PrintJet CONNECT • Mains cable • LAN cable • USB cable • WIFI stick • one MultiCard DEK 5/5 • DVD with M-Print® PRO software • Quick start guide • Operating manual • Ink set PJ CON INK SET • 2 PrintJet cleaner cloths 	
The ink cartridges are not installed in the printer.		




The new 7" touch colour display with a multitude of new functions ensures optimal operation.



Whether LAN, WLAN or USB: the PrintJet CONNECT offers a wide connectivity spectrum.



High magazine capacity for loading and dispensing of up to 50 MultiCards.

Inkjet printer**Ink-jet printer****PrintJet CONNECT****Technical data**

EAN	4064675016922
Depth	930 mm
Width	590 mm
Height	454 mm
Net weight	38 kg
Printing method	Ink jet technology
Printer driver / Operating system	Windows 7, Windows 8, Windows 8.1, Windows 10
Printing speed	Depends on printing quality
Print quality	300 dpi, 600 dpi, 1200 dpi
Marker type	MultiCard, MetallCard
Interface	USB, LAN, WiFi
Fueling system	Ink cartridge, CMYK
Voltage supply	230 V AC / 16 A, 115 V AC / 20 A
Software	M-Print® PRO

Note**Ordering data**

Type	Qty.	Order No.
PRINTJET CONNECT	1	2715590000

Accessories**PrintJet CONNECT**

Type	Qty.	Order No.
M-PRINT PRO	1	1905490000
PJ CON INK SET	1	2715600000
PJ CON INK C	1	2715610000
PJ CON INK M	1	2715620000
PJ CON INK Y	1	2715630000
PJ CON INK K	1	2715640000
PJ CON FLUID SET	1	2715650000
PJ CON WASTE PAD	1	2715660000
PJ CON TEXTILE COVER	1	2715670000
PJ CON WIFI STICK	1	2715680000

PrintJet ADVANCED

Type	Qty.	Order No.
PJ ADV TNW	1	1338710000
PJ ADV TNTK INK C	1	1338680000
PJ ADV TNTK INK M	1	1338670000
PJ ADV TNTK INK Y	1	1338650000
PJ ADV TNTK INK K	1	1338690000
PJ ADV TNTK INK SET	1	1338720000

Note

Markers for cables and wires**SlimFix VO for cables and wires**

- Ø 4.7 to 6.8 mm SF5/21
- Ø 5.8 to 8.5 mm SF6/21

Markers for IE-Line **STEADYTEC®****MultiCard ESG 9/11 K for IE-Line **STEADYTEC®****

- 9 x 11 mm
- White

TM-I for pre-assembled M12 cables**MultiCard markers for labelling transparent M12 TM-I sleeves**

- Tag length: 18 mm
- Tag width: 4 mm

Ordering data

Type	Qty.	Order No.
VT SF 5/21 NE WS VO	160	1689470001
VT SF 6/21 NE WS VO	160	1730560001

Note: Can be printed with PrintJet PRO.

Accessories

Type	Qty.	Order No.

Ordering data

Type	Qty.	Order No.
ESG 9/11 K MC NE WS	200	1857440000

Note: Can be printed with PrintJet PRO.

Accessories

Type	Qty.	Order No.

Ordering data

Type	Qty.	Order No.
TM-I 18 MC NE WS	320	1718431044
TM-I 18 MC NE GE	320	1718431687


Note: Can be printed with PrintJet PRO.

Surge protection for data interfaces

V DATA Cat. 6 - surge protection for 8 wires with RJ45 socket

- RJ45 connection
- All 4 lines are protected
- Robust and compact metal housing
- Suitable for Cat. 5 (to 100 MHz) and Cat. 6 to 250 MHz (class E)
- Suitable for PoE (IEEE 802.3af) and PoE + (IEEE 802.3at)

V DATA CAT6



S

Technical data

Requirements category acc. to IEC 61643-21

Surge current-carrying capacity C2

Surge current-carrying capacity D1

Discharge current I_{d} (8/20 μs) wire-wire/wire-PE/GND-PE

Discharge I_{max} (8/20 μs) wire-wire/wire-PE/GND-PE

Lightning test I_{imp} (10/350 μs) wire-wire/wire-PE/GND-PE

Type of connection

Storage temperature

Ambient temperature (operational)

Protection degree

Rated voltage (AC)

Rated current

Insertion loss at 250 MHz

Protection level U_p typical

Approvals

Standards

Dimensions of complete module (arrester + base element)

Height x width x depth

Note

C2, D1

10 kA

1 kA 10/350 μs

150 A / 1,25 kA

10 kA / 5 kA

1 kA / 1 kA

RJ45-Port

-40 ... +85 °C

-40 ... +80 °C

IP20

48 V

1 A

≤ 1 dB at 250 MHz

≤ 550 V

According to IEC61643-21

75 / 19 / 46 mm

Can also be used for Cat.5 applications

Ordering data

Note

Type	Qty.	Order No.
VDATA CAT6	1 ST	1348590000

Service and support

Service and support	Our expertise for your requirements	V.2
	Engineering support and customised assembly	V.3
	Personal support	V.4

Our expertise for your requirements

Service connects – worldwide



Automation technology functions are becoming more complex in a globally-oriented world facing ambitious targets in terms of energy efficiency and smart production. We are your equal partners for the best connections in Industrial Connectivity.

Our personal support can answer any questions reliably and expertly. Our online services are available 365 day a year around the clock to provide answers to your questions on our products – from user documentation through software to planning tools.

In short: Weidmüller's global service combines our expertise with your requirements.

V



Your way to our service

www.weidmueller.com/service

Engineering support and customised assembly

Automation engineering and connectivity consulting belongs to our services as well as assembly of engineered products. We also support the process from the idea to the product with our Weidmüller Configurator and the Configure-to-Order process.



Consulting and engineering

The challenge for you is reducing costs and increasing efficiency. This requires intelligent, individual solutions. Whether it is modified products, pre-fitted mounting rails or complete small cabinets – our application centres provide a highly qualified custom-made engineering and production service.



Connectivity Consulting

Alongside our product offering, we support you with our range of services through all the phases of machine construction. The result of this collaboration is a reduction of up to 30% in cycle times, up to 20% more space in the control cabinet and significant fault reduction. Our experienced Connectivity Consulting team delivers a practical impetus rather than just abstract theories.



Fitted mounting rails

Your processes in panel building have to be fast, flexible and productive. This is the only way you can cut your costs and increase efficiency. Depending on the application in question, you will have different requirements with respect to the engineering service, delivery speed and flexibility to be provided.



Processed and assembled enclosures

To compete internationally, your plants need to satisfy high standards of safety, quality and performance. The smart combination of consultation, application expertise and industry know-how is our key to finding a custom-fit solution for your application. Reduce costs and increase efficiency.

Personal support

Exactly the right help and information on our solutions and products



If our products are used in your automation technology applications, you need the best possible individual support, from planning through installation to operation. For every stage of your application, we can offer the right tools and information for our products and solutions. Up-to-date, uncomplicated, comprehensive and around the clock via our service portal at www.weidmueller.com/support.

V



Your way to your local personal support


www.weidmueller.com/support





Technical downloads

All information, such as technical data, manuals, certificates and much more for the appropriate use of our products and solutions in your application.



Engineering data

For the quick integration of our products into your design, there are a lot of digital product data for engineering systems like EPLAN, Zuken E3.series, WSCAD and many others available for download.



Product software

Our software makes using and configuration of our products easier for you when it comes to operation, configuration and monitoring.



Approvals, certificates & declaration of conformity

We supply product- or company-related approvals and certificates for your documentation.



Security advisory board

Our Product Security Incident Response Team (PSIRT) continuously informs you about possible security-related vulnerabilities of our products.

Index

Index

Index Type	X.2
Index Order No.	X.8
Addresses worldwide	X.16

Type	Order No.	Page	Type	Order No.	Page	Type	Order No.	Page	Type	Order No.	Page
A			CABITTE SE 10-11 SML BK	2584060000	S.18	ERAN MULTI-STRIPAX	9203100000	S.10	IE-BHS-V14M-RJA	1011540000	N.6
AIE MULTI-STRIPAX POF	1212770000	S.10	CABITTE SE 10-11 SML GY	2584610000	S.18	ERME 110 PDT	9013960000	S.15	IE-BHS-V14M-RJA	1011540000	N.8
AM 12	9030060000	0.6	CABITTE SE 11-12 SML BK	2584040000	S.18	ERME 630 PDT	9013990000	S.15	IE-BHS-V14M-RJA-45	1296710000	N.9
AM 12	9030060000	0.7	CABITTE SE 11-12 SML GY	2584600000	S.18	ERME 66 PDT	9013980000	S.15	IE-BI-HYB-10P	1069010000	N.54
AM 12	9030060000	0.8	CABITTE SE 12-13 SML BK	2584020000	S.18	ERME LSA PLUS SCHERE	9014050000	S.15	IE-BI-LCD-MM-C	1964420000	N.58
AM 12	9030060000	0.9	CABITTE SE 12-13 SML GY	2584590000	S.18	ERME LSA PLUS STANDARD	9014000000	S.15	IE-BI-LCD-SM-C	1962800000	N.58
AM 12	9030060000	0.10	CABITTE SE 13-14 SML BK	2584000000	S.18	ERME MULTI-STRIPAX	9203070000	S.10	IE-BI-RJ45-C	1962840000	M.5
AM 12	9030060000	0.11	CABITTE SE 13-14 SML GY	2584570000	S.18	ESG 6/17 K MC NE WS	1880120000	P.5	IE-BI-RJ45-C	1962840000	M.6
AM 12	9030060000	0.12	CABITTE SE 14-15 LRG BK	2583880000	S.18	ESG 6/17 K MC NE WS	1880120000	P.6	IE-BI-RJ45-C	1962840000	M.8
AM 12	9030060000	0.13	CABITTE SE 14-15 LRG GY	2584510000	S.18	ESG 7/20 SIRIUS MC NE WS	1736181044	M.2	IE-BI-RJ45-C	1962840000	M.9
AM 12	9030060000	0.14	CABITTE SE 14-15 SML BK	2583980000	S.18	ESG 7/20 SIRIUS MC NE WS	1736181044	M.3	IE-BI-RJ45-C	1962840000	M.10
AM 12	9030060000	0.15	CABITTE SE 14-15 SML GY	2584560000	S.18	ESG 7/20 SIRIUS MC NE WS	1736181044	M.4	IE-BI-RJ45-C	1962840000	M.11
AM 12	9030060000	0.16	CABITTE SE 15-16 LRG BK	2583860000	S.18	ESG 7/20 SIRIUS MC NE WS	1736181044	M.5	IE-BI-RJ45-C	1962840000	M.12
AM 12	9030060000	0.17	CABITTE SE 15-16 LRG GY	2584550000	S.18	ESG 7/20 SIRIUS MC NE WS	1736181044	M.6	IE-BI-RJ45-C	1962840000	M.13
AM 12	9030060000	0.18	CABITTE SE 15-16 SML BK	2584550000	S.18	ESG 7/20 SIRIUS MC NE WS	1736181044	M.8	IE-BI-RJ45-C	1962840000	N.52
AM 12	9030060000	0.19	CABITTE SE 16-17 LRG BK	2583850000	S.18	ESG 7/20 SIRIUS MC NE WS	1736181044	M.9	IE-BI-RJ45-FJA	1962850000	J.15
AM 12	9030060000	0.20	CABITTE SE 16-17 LRG GY	2584490000	S.18	ESG 7/20 SIRIUS MC NE WS	1736181044	M.10	IE-BI-RJ45-FJA	1962850000	M.5
AM 12	9030060000	0.21	CABITTE SE 17-18 LRG BK	2583840000	S.18	ESG 7/20 SIRIUS MC NE WS	1736181044	M.11	IE-BI-RJ45-FJA	1962850000	M.6
AM 12	9030060000	0.22	CABITTE SE 17-18 LRG GY	2584480000	S.18	ESG 9/11 K MC NE WS	1857440000	L.13	IE-BI-RJ45-FJA	1962850000	M.7
AM 12	9030060000	0.23	CABITTE SE 18-19 LRG BK	2583830000	S.18	ESG 9/11 K MC NE WS	1857440000	L.14	IE-BI-RJ45-FJA	1962850000	M.10
AM 12	9030060000	0.24	CABITTE SE 18-19 LRG GY	2584470000	S.18	ESG 9/11 K MC NE WS	1857440000	L.15	IE-BI-RJ45-FJA	1962850000	M.11
AM 12	9030060000	0.25	CABITTE SE 19-20 LRG BK	2583810000	S.18	ESG 9/11 K MC NE WS	1857440000	L.17	IE-BI-RJ45-FJA	1962850000	M.12
AM 12	9030060000	0.26	CABITTE SE 19-20 LRG GY	2584460000	S.18	ESG 9/11 K MC NE WS	1857440000	L.18	IE-BI-RJ45-FJA	1962850000	M.13
AM 12	9030060000	0.27	CABITTE SE 2-3 SML BK	2584760000	S.18	ESG 9/11 K MC NE WS	1857440000	M.12	IE-BI-RJ45-FJA	1962850000	M.8
AM 12	9030060000	0.28	CABITTE SE 2-3 SML GY	2583380000	S.18	ESG 9/11 K MC NE WS	1857440000	M.32	IE-BI-RJ45-FJA	1962850000	M.9
AM 12	9030060000	0.30	CABITTE SE 2/4-5 SML BK	2583620000	S.18	ESG 9/11 K MC NE WS	1857440000	M.2	IE-BI-RJ45-FJA	1962850000	N.51
AM 12	9030060000	0.31	CABITTE SE 2/4-5 SML GY	2584900000	S.18	ESG 9/11 K MC NE WS	1857440000	N.3	IE-BI-RJ45-FJA	1962850000	0.12
AM 12	9030060000	0.32	CABITTE SE 2/5-6 SML BK	2583610000	S.18	ESG 9/11 K MC NE WS	1857440000	N.7	IE-BI-RJ45-FJA	1962850000	0.13
AM 12	9030060000	0.33	CABITTE SE 2/5-6 SML GY	2584890000	S.18	ESG 9/11 K MC NE WS	1857440000	N.10	IE-BI-RJ45-FJA	1962850000	0.14
AM 12	9030060000	0.35	CABITTE SE 2/7 SML BK	2583550000	S.18	ESG 9/11 K MC NE WS	1857440000	N.12	IE-BI-RJ45-FJA	1962850000	0.15
AM 12	9030060000	0.54	CABITTE SE 2/7 SML GY	2584830000	S.18	ESG 9/11 K MC NE WS	1857440000	N.16	IE-BI-RJ45-FJA	1962850000	0.16
AM 12	9030060000	0.57	CABITTE SE 2/8 SML BK	2583540000	S.18	ESG 9/11 K MC NE WS	1857440000	N.19	IE-BI-RJ45-FJB	1963840000	J.15
AM 12	9030060000	S.4	CABITTE SE 2/8 SML GY	2584820000	S.18	ESG 9/11 K MC NE WS	1857440000	N.20	IE-BI-RJ45-FJB	1963840000	M.5
C			CABITTE SE 2/AS1 SML BK	2583520000	S.18	ESG 9/11 K MC NE WS	1857440000	N.21	IE-BI-RJ45-FJB	1963840000	M.6
CABITTE BP 10MM PA	2652380000	S.22	CABITTE SE 20-21 LRG BK	2584450000	S.18	ESG 9/11 K MC NE WS	1857440000	N.22	IE-BI-RJ45-FJB	1963840000	M.9
CABITTE BP 12MM PA	2652400000	S.22	CABITTE SE 21-22 LRG BK	2583770000	S.18	ESG 9/11 K MC NE WS	1857440000	S.27	IE-BI-RJ45-FJB	1963840000	M.11
CABITTE BP 13MM PA	2652410000	S.22	CABITTE SE 21-22 LRG GY	2584440000	S.18	HTF HYB	1119580000	N.7	IE-BI-RJ45-FJB	1963840000	M.12
CABITTE BP 14MM PA	2652420000	S.22	CABITTE SE 22-23 LRG BK	2583750000	S.18	HTF HYB	1119580000	N.8	IE-BI-RJ45-FJB	1963840000	M.13
CABITTE BP 17MM PA	2652430000	S.22	CABITTE SE 22-23 LRG GY	2584430000	S.18	HTF HYB	1119580000	N.53	IE-BI-RJ45-FJB	1963840000	N.18
CABITTE BP 20MM PA	2652440000	S.22	CABITTE SE 23-24 LRG BK	2583730000	S.18	HTF HYB	1119580000	N.54	IE-BI-RJ45-FJB	1963840000	N.21
CABITTE BP 21MM PA	2652450000	S.22	CABITTE SE 23-24 LRG GY	2584420000	S.18	HTF HYB	1119580000	N.55	IE-BI-RJ45-FJB	1963840000	N.51
CABITTE BP 25MM PA	2652460000	S.22	CABITTE SE 24-25 LRG BK	2583710000	S.18	HTF HYB	1119580000	N.7	IE-BI-RJ45-FJB	1963840000	0.12
CABITTE BP 28MM PA	2652470000	S.22	CABITTE SE 24-25 LRG GY	2584410000	S.18	HTF HYB	1119580000	N.8	IE-BI-RJ45-FJB	1963840000	0.13
CABITTE BP 2MM PA	2652300000	S.22	CABITTE SE 25-26 LRG BK	2583700000	S.18	HTF HYB	1119580000	N.14	IE-BI-RJ45-FJB	1963840000	0.14
CABITTE BP 35MM PA	2652480000	S.22	CABITTE SE 25-26 LRG GY	2584400000	S.18	HTF HYB	1119580000	N.15	IE-BI-RJ45-FJB	1963840000	0.15
CABITTE BP 3MM PA	2652310000	S.22	CABITTE SE 26-27 LRG BK	2583690000	S.18	HTF HYB	1119580000	N.16	IE-BI-RJ45-FJB	1963840000	0.16
CABITTE BP 4MM PA	2652320000	S.22	CABITTE SE 26-27 LRG GY	2584390000	S.18	HTF HYB	1119580000	N.17	IE-BI-RJ45-FJB	1963840000	0.17
CABITTE BP 5MM PA	2652330000	S.22	CABITTE SE 27-28 LRG BK	2583680000	S.18	HTF HYB	1119580000	N.18	IE-BI-RJ45-FJB	1963840000	0.18
CABITTE BP 6MM PA	2652340000	S.22	CABITTE SE 27-28 LRG GY	2584370000	S.18	HTF HYB	1119580000	N.19	IE-BI-RJ45-FJB	1963840000	0.19
CABITTE BP 7MM PA	2652350000	S.22	CABITTE SE 28-29 LRG BK	2583670000	S.18	HTX-IE-POF	1208870000	L.10	IE-BI-RJ45-FJB	1963840000	M.13
CABITTE BP 8MM PA	2652360000	S.22	CABITTE SE 28-29 LRG GY	2584350000	S.18	HTX-IE-POF	1208870000	N.10	IE-BI-RJ45-FJB	1963840000	M.14
CABITTE BP 9MM PA	2652370000	S.22	CABITTE SE 29-30 LRG BK	2583660000	S.18	HTX-IE-POF	1208870000	N.11	IE-BI-RJ45-FJB	1963840000	M.15
CABITTE BSE LRG BK	2583900000	S.18	CABITTE SE 29-30 LRG GY	2584380000	S.18	HTX-IE-POF	1208870000	N.12	IE-BI-RJ45-FJB	1963840000	M.16
CABITTE BSE LRG GY	2584520000	S.18	CABITTE SE 34-34 SML BK	2584730000	S.18	HTX-IE-POF	1208870000	N.13	IE-BI-RJ45-FJB	1963840000	M.17
CABITTE BSE SML BK	2584790000	S.18	CABITTE SE 34-34 SML GY	2583400000	S.18	HTX-IE-POF	1208870000	N.14	IE-BI-RJ45-FJB	1963840000	M.18
CABITTE BSE SML GY	2583350000	S.18	CABITTE SE 3/5-6 SML BK	2652280000	S.18	HTX-IE-POF-0A	2602860000	L.10	IE-BI-RJ45-FJB	1963840000	N.21
CABITTE CGS M20 BK	2584200000	S.21	CABITTE SE 3/5-6 SML GY	2652290000	S.18	HTX-IE-POF-0A	2602860000	N.10	IE-BI-RJ45-FJB	1963840000	N.51
CABITTE CGS M25 BK	2584180000	S.21	CABITTE SE 30-31 LRG BK	2583650000	S.18	HTX-IE-POF-0A	2602860000	N.56	IE-BI-RJ45-FJB	1963840000	0.12
CABITTE CGS M32 BK	2584160000	S.21	CABITTE SE 30-31 LRG GY	2584360000	S.18	HTX-IE-POF-0A	2602860000	S.11	IE-BI-RJ45-FJB	1963840000	0.13
CABITTE CGS M40 BK	2584150000	S.21	CABITTE SE 31-32 LRG BK	2583640000	S.18	HTX-IE-POF-0A	2602860000	S.18	IE-BI-RJ45-FJB	1963840000	0.14
CABITTE CGS M50 BK	2584130000	S.21	CABITTE SE 31-32 LRG GY	2584340000	S.18	HTX-IE-POF-0A	2602860000	S.19	IE-BI-RJ45-FJB	1963840000	0.15
CABITTE CGS M63 BK	2584120000	S.21	CABITTE SE 32-33 LRG BK	2583630000	S.18	HTX-IE-POF-0A	2602860000	S.20	IE-BI-RJ45-FJB	1963840000	0.16
CABITTE CR 10/6 EMV	2583930000	S.22	CABITTE SE 32-33 LRG GY	2584920000	S.18	HTX-IE-POF-0A	2602860000	S.21	IE-BI-RJ45-FJB	1963840000	M.5
CABITTE CR 16/8 EMV	2583910000	S.22	CABITTE SE 33-34 LRG BK	2583510000	S.18	HTX-IE-POF-0A	2602860000	S.22	IE-BI-RJ45-FJB	1963840000	M.6
CABITTE CR 24/10 EMV	2583890000	S.22	CABITTE SE 33-34 LRG GY	2584910000	S.18	HTX-IE-POF-0A	2602860000	S.23	IE-BI-RJ45-FJB	1963840000	M.7
CABITTE CR 4-1 EMV	2583950000	S.22	CABITTE SE 34-35 LRG BK	2595520000	S.18	HTX-IE-POF-0A	2602860000	S.24	IE-BI-RJ45-FJB	1963840000	M.8
CABITTE CSE 2-11 SML BK	2583510000	S.18	CABITTE SE 34-35 LRG GY	2595530000	S.18	HTX-IE-POF-0A	2602860000	S.25	IE-BI-RJ45-FJB	1963840000	M.9
CABITTE CSE 7-24 LRG BK	2583500000	S.18	CABITTE SE 4-5 SML BK	2584680000	S.18	HTX-IE-POF-0A	2602860000	S.26	IE-BI-RJ45-FJB	1963840000	M.10
CABITTE FR 10/6 BK	2583480000	S.19	CABITTE SE 4-5 SML GY	2583440000	S.18	HTX-IE-POF-0A	2602860000	S.27	IE-BI-RJ45-FJB	1963840000	M.11
CABITTE FR 10/6 BK SET	2583700000	S.20	CABITTE SE 4-5 SML	2584840000	S.18	HTX-IE-POF-0A	2602860000	S.28	IE-BI-RJ45-FJB	1963840000	

Type	Order No.	Page	Type	Order No.	Page	Type	Order No.	Page	Type	Order No.	Page
IE-BIC-HYB-P-0,5-300	1096150000	N.54	IE-C5CS8UG-100	8813160000	0.6	IE-C5DD4U0030DSSXXX-E	2706260030	0.48	IE-C5DE4UP0050PCAPCA-E	2717800050	0.47
IE-BIC-HYB-P-0,5-300	1096150000	0.7	IE-C5CS8UG-500	2762870000	J.15	IE-C5D04U0030MCAMCA-E	1059890030	0.36	IE-C5DE4UP0050PCAPSA-E	2717810050	0.47
IE-BIC-HYB-P-0,75-300	1068970000	J.10	IE-C5CS8UG-500	2762870000	0.5	IE-C5D04U0030MCAXXX-E	1059750030	0.37	IE-C5DE4UP0050PCAXXX-E	2717770075	0.45
IE-BIC-HYB-P-0,75-300	1068970000	N.8	IE-C5CS8UG-500	2762870000	0.6	IE-C5D04U0030MCMSA20-E	1044470030	0.35	IE-C5DE4UP0050PCPS-E	2717780050	0.46
IE-BIC-HYB-P-0,75-300	1068970000	N.54	IE-C5CS8VG-100	8813150000	J.15	IE-C5D04U0030MCMSCA-E	1059770030	0.36	IE-C5DE4UP0050PCSSXX-E	2717750050	0.44
IE-BIC-HYB-P-0,75-300	1068970000	0.7	IE-C5CS8VG-100	8813150000	0.5	IE-C5D04U0030MCMSCS-E	1025950030	0.34	IE-C5DE4UP0050PAXXX-E	2717760050	0.45
IE-BP-V01P	1965700000	N.13	IE-C5CS8VG-100	8813150000	0.6	IE-C5D04U0030MCSSXXX	1025940030	0.35	IE-C5DE4UP0050PSXXX-E	2717740050	0.44
IE-BP-V01P	1965700000	N.14	IE-C5CS8VG-500	2763440000	J.15	IE-C5D04U0030MSSMCS-E	1059330030	0.34	IE-C5D04U0040A60A60-E	2047310040	0.29
IE-BP-V01P	1965700000	N.15	IE-C5CS8VG-500	2763440000	0.5	IE-C5D04U0040A60A60-E	2047310040	0.29	IE-C5DE4UP0075PCAPCA-E	2717800075	0.47
IE-BP-V01P	1965700000	N.17	IE-C5CS8VG-500	2763440000	0.6	IE-C5D04U0050A20A20-E	1173903005	0.28	IE-C5DE4UP0075PCAPSA-E	2717810075	0.47
IE-BP-V01P	1965700000	S.24	IE-C5DB4RE0015MCAMCA-E	1059970015	0.55	IE-C5D04U0050A20A2D-E	1376610050	0.28	IE-C5DE4UP0075PCAXXX-E	2717770075	0.45
IE-BP-V04P	1963900000	N.20	IE-C5DB4RE0015MCAXXX-E	1059900015	0.56	IE-C5D04U0050A2E2-E	1197300050	J.11	IE-C5DE4UP0075PCPS-E	2717780075	0.46
IE-BP-V04P	1963900000	N.22	IE-C5DB4RE0015MCMSCA-E	1059940015	0.55	IE-C5D04U0050A2E2-E	1197300050	0.30	IE-C5DE4UP0075PCSS-E	2717790075	0.46
IE-BP-V04P	1963900000	N.23	IE-C5DB4RE0015MCMSCS-E	1010850015	0.53	IE-C5D04U0050A60A60-E	2047310050	0.29	IE-C5DE4UP0075PCSSXX-E	2717750075	0.44
IE-BP-V04P	1963900000	N.24	IE-C5DB4RE0015MCSSXXX	1010840015	0.54	IE-C5D04U0050B2E2B-E	1307610050	0.31	IE-C5DE4UP0075PSAXXX-E	2717760075	0.45
IE-BP-V04P	1963900000	0.14	IE-C5DB4RE0015MSMCS-E	1059340015	0.53	IE-C5D04U0050CADC-E	2706220050	0.51	IE-C5DE4UP0075SSXXX-E	2717740075	0.44
IE-BP-V04P	1963900000	S.24	IE-C5DB4RE0030MCAMCA-E	1059970030	0.55	IE-C5D04U0050CADSA-E	2706230050	0.51	IE-C5DE4UP0100PCAPCA-E	271780100	0.47
IE-BP-V05M	1968930000	N.26	IE-C5DB4RE0030MCAXXX-E	1059900030	0.56	IE-C5D04U0050CADCXX-E	206190050	0.49	IE-C5DE4UP0100PCAPSA-E	271781100	0.47
IE-BP-V05M	1968930000	S.24	IE-C5DB4RE0030MCMSCA-E	1059940030	0.55	IE-C5D04U0050CSDS-E	2706200050	0.50	IE-C5DE4UP0100PCAXXX-E	2717770100	0.45
IE-BP-V14P	1058310000	N.4	IE-C5DB4RE0030MCMSCS-E	1010850030	0.53	IE-C5D04U0050CSDSS-E	2706210050	0.50	IE-C5DE4UP0100PCSPCS-E	2717780100	0.46
IE-BP-V14P	1058310000	N.5	IE-C5DB4RE0030MCSSXXX	1010840030	0.54	IE-C5D04U0050CSE4-E	2706250050	0.50	IE-C5DE4UP0200PCSPSS-E	2717790200	0.46
IE-BP-V14P	1058310000	N.6	IE-C5DB4RE0030SMSMCS-E	1059340030	0.53	IE-C5D04U0050CSCS-E	2706150050	0.48	IE-C5DE4UP0200PSXXX-E	2717750200	0.44
IE-BP-V14P	1058310000	N.8	IE-C5DB4RE0050MCAMCA-E	1059970050	0.55	IE-C5D04U0050DSSXXX	2706160050	0.49	IE-C5DE4UP0100PSXXX-E	2717760100	0.45
IE-BP-V14P	1058310000	N.11	IE-C5DB4RE0050MCAXXX-E	1059900050	0.56	IE-C5D04U0060DSSXXX	2706260050	0.50	IE-C5DE4UP0300PCPS-E	2717780300	0.46
IE-BP-V14P	1058310000	0.2	IE-C5DB4RE0050MCMSCA-E	1059940050	0.55	IE-C5D04U0050MCAMCA-E	1059890050	0.36	IE-C5DE4UP0100PCSPSS-E	2717790200	0.46
IE-BP-V14P	1058310000	0.4	IE-C5DB4RE0050MCMSCS-E	1010850050	0.53	IE-C5D04U0050MCAXXX-E	1099750050	0.37	IE-C5DE4UP0200PCSPSS-E	2717790200	0.46
IE-BP-V14P	1058310000	0.5	IE-C5DB4RE0050MCSSXXX	1010840050	0.54	IE-C5D04U0060MCMSA20-E	1044470050	0.50	IE-C5DE4UP0300PSAXXX-E	2717760300	0.45
IE-BP-V14P	1058310000	0.7	IE-C5DB4RE0050SMSMCS-E	1059340050	0.53	IE-C5D04U0060MCMSCA-E	1059770050	0.36	IE-C5DE4UP0100PSXXX-E	2717750100	0.44
IE-BP-V14P	1058310000	0.8	IE-C5DB4RE0100MCAMCA-E	1059970100	0.55	IE-C5D04U0060MCMSCS-E	1025950050	0.34	IE-C5DE4UP0200PSXXX-E	2717740200	0.44
IE-BP-V14P	1058310000	S.24	IE-C5DB4RE0100MCAXXX-E	1059900100	0.56	IE-C5D04U0060MCSSXXX	2706150050	0.49	IE-C5DE4UP0300PCPS-E	2717780300	0.46
IE-BP-VAPP	1068930000	N.61	IE-C5DB4RE0100MCMSCA-E	1059940100	0.55	IE-C5D04U0060MSSMCS-E	1059330050	0.34	IE-C5DE4UP0100PSXXX-E	2717790300	0.46
IE-BP-VAPP	1068930000	0.2	IE-C5DB4RE0100MCMSCS-E	1010850100	0.53	IE-C5D04U0075A60A60-E	2047310075	0.29	IE-C5DE4UP0300PCXXX-E	2717750300	0.44
IE-BP-VAPP	1068930000	0.4	IE-C5DB4RE0100MCSSXXX	1010840100	0.54	IE-C5D04U0075PCADC-E	2706220075	0.48	IE-C5DE4UP0300PSAXXX-E	2717760300	0.45
IE-BP-VAPP	1068930000	0.6	IE-C5DB4RE0100SMSMCS-E	1059340100	0.53	IE-C5D04U0075PCADS-E	2706230075	0.51	IE-C5DE4UP0100PSXXX-E	2717740300	0.44
IE-BP-VAPP	1068930000	S.24	IE-C5DB4WE0010A20A20-E	1421710010	0.58	IE-C5D04U0075DCAXXX-E	2706190075	0.49	IE-C5D0HAG-100	2763660000	N.7
IE-BP-VAPP-DC	2494060000	N.61	IE-C5DB4WE0020A20A20-E	1421710020	0.58	IE-C5D04U0075DCSDS-E	2706200075	0.50	IE-C5D0HAG-100	2763660000	0.5
IE-BS-M12X-180-P-T	2747880000	N.44	IE-C5DB4WE0030A20A20-E	1421710030	0.58	IE-C5D04U0075DCSDSS-E	2706210075	0.50	IE-C5D0HAG-100	2763660000	0.17
IE-BS-M12X-180-S-T	2747900000	N.44	IE-C5DB4WE0040A20A20-E	1421710040	0.58	IE-C5D04U0075DCSE40-E	2706250075	0.52	IE-C5D0HAG-500	2763460000	J.11
IE-BS-M12X-90-P-T	2747910000	N.44	IE-C5DB4WE0040MCMSA20-E	1220310040	0.57	IE-C5D04U0075DCSXXX-E	2706150075	0.48	IE-C5D0HAG-500	2763460000	N.7
IE-BS-M12X-90-S-T	2747920000	N.44	IE-C5DB4WE0050A20A20-E	1421710050	0.58	IE-C5D04U0075DCAXXX-E	2706160075	0.49	IE-C5D0HAG-500	2763460000	0.5
IE-BS-M12X-S-C	2731010000	N.46	IE-C5DB4WE0050MCSSXXX	1269740050	0.57	IE-C5D04U0075DSSXXX-E	2706260075	0.48	IE-C5D0HAG-500	2763460000	0.17
IE-BS-M12X-S-FH	1516340000	N.42	IE-C5DB4WE0100A20A20-E	1421710100	0.58	IE-C5D04U0075MBA20-E	1173903100	0.28	IE-C5D0HAG-MW	1122500000	N.8
IE-BS-V01M-LCD-MM-C	1964440000	N.15	IE-C5DB4WE0100MCMSXXX	1269740100	0.57	IE-C5D04U0075MBSA20-E	1234750010	0.28	IE-C5D0HAG-500	1234750005	0.38
IE-BS-V01M-LCD-SM-C	1964340000	N.15	IE-C5DB4WE0200A20A20-E	1421710200	0.58	IE-C5D04U0100A2E2-E	1119730100	J.11	IE-C5D0HAG-500	1234750005	0.38
IE-BS-V01M-RJ45-C	1963470000	J.14	IE-C5D04U0050A20A20-E	1889901000	0.58	IE-C5D04U0100A2E2-E	1119730100	J.11	IE-C5D0HAG-500	1234770005	0.39
IE-BS-V01M-RJ45-C	1963470000	N.13	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0100A60A60-E	2047310100	0.29	IE-C5D0HAG-500	1234750010	0.38
IE-BS-V01M-RJ45-FJA	1963480000	J.14	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0100A60A60-E	2047310100	0.29	IE-C5D0HAG-500	1234750010	0.38
IE-BS-V01M-RJ45-FJA	1963480000	N.13	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0100A60A60-E	2047310100	0.29	IE-C5D0HAG-500	1234770010	0.39
IE-BS-V01M-RJ45-FJA	1963480000	J.14	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0100A60A60-E	2047310100	0.29	IE-C5D0HAG-500	1234770010	0.39
IE-BS-V01M-SCR-JMM	1221010000	N.14	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0100A60A60-E	2047310100	0.29	IE-C5D0HAG-500	1234750010	0.38
IE-BS-V01M-SCR-JMM	1221010000	N.14	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0100A60A60-E	2047310100	0.29	IE-C5D0HAG-500	1234750010	0.38
IE-BS-V01M-SCR-JMM	1221010000	N.14	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0100A60A60-E	2047310100	0.29	IE-C5D0HAG-500	1234750010	0.38
IE-BS-V01P-RJ45-C	1012370000	J.14	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0050A20A2D-E	1234750010	0.28	IE-C5D0HAG-500	1234750010	0.38
IE-BS-V01P-RJ45-C	1012370000	N.17	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0050A20A2D-E	1234750010	0.28	IE-C5D0HAG-500	1234750010	0.38
IE-BS-V01P-RJ45-FJA	1012370000	N.17	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0050A20A2D-E	1234750010	0.28	IE-C5D0HAG-500	1234750010	0.38
IE-BS-V01P-RJ45-FJA	1012370000	N.17	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0050A20A2D-E	1234750010	0.28	IE-C5D0HAG-500	1234750010	0.38
IE-BS-V01P-RJ45-FJA	1012370000	N.17	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0050A20A2D-E	1234750010	0.28	IE-C5D0HAG-500	1234750010	0.38
IE-BS-V01P-RJ45-FJA	1012370000	N.17	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0050A20A2D-E	1234750010	0.28	IE-C5D0HAG-500	1234750010	0.38
IE-BS-V14M-HYB-10P-FJ	1058270000	N.4	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0050A20A2D-E	1234750010	0.28	IE-C5D0HAG-500	1234750010	0.38
IE-BS-V14M-HYB-10P-FJ	1058270000	N.8	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0050A20A2D-E	1234750010	0.28	IE-C5D0HAG-500	1234750010	0.38
IE-BS-V14M-HYB-10P-FJ	1058270000	N.8	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0050A20A2D-E	1234750010	0.28	IE-C5D0HAG-500	1234750010	0.38
IE-BS-V14M-HYB-10P-FJ	1058270000	N.8	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0050A20A2D-E	1234750010	0.28	IE-C5D0HAG-500	1234750010	0.38
IE-BS-V14M-HYB-10P-FJ	1058270000	N.8	IE-C5D04U0050A20A2D-E	1889901000	0.58	IE-C5D04U0050A20A					

Type	Order No.	Page	Type	Order No.	Page	Type	Order No.	Page	Type	Order No.	Page
IE-C5ES8UG0010P41P41-E	1106010000	J.15	IE-C6FP8LD0050M40L40-D	2703320050	0.24	IE-C6FS8UG0050A40A40-G	8941350050	0.27	IE-CD-VAPM24V-Y-MA	1297010000	J.11
IE-C5ES8UG0010P41P41-E	1106010000	0.43	IE-C6FP8LD0050M40M40-D	1165940050	0.18	IE-C6FS8UG0100A40A40-G	8941350100	0.27	IE-CD-VAPM24V-Y-MA	1297010000	0.6
IE-C5ES8UG0015M40M40-G	1166000015	0.26	IE-C6FP8LD0050M40R40-D	2703330050	0.24	IE-C6FS8UG0150A40A40-G	8941350150	0.27	IE-CDM-V14MRJSCP/VAPM-C	1324440000	J.11
IE-C5ES8UG0020B41B41-E	1066860000	J.15	IE-C6FP8LD0050M40A40-D	1248280050	0.23	IE-C6FS8UG0200A40A40-G	8941350200	0.27	IE-CDM-V14MRJSCP/VAPM-C	1324440000	0.10
IE-C5ES8UG0020B41B41-E	1066860000	0.43	IE-C6FP8LD0050M40W40-D	1233160050	0.23	IE-C6HD8UG00100XCSXCS-E	2723030010	0.41	IE-CDM-V14MRJSCP/VAPM-C II	2588270000	J.11
IE-C5ES8UG0020M40M40-G	1166000020	0.26	IE-C6FP8LD0050X40X40-Y	1312160050	0.25	IE-C6HD8UG00100XCSXCS-E	2723040010	0.41	IE-CDM-V14MRJSCP/VAPM-C II	2588270000	0.10
IE-C5ES8UG0020P41P41-E	1106020000	J.15	IE-C6FP8LD0075M40M40-D	1165940075	0.18	IE-C6HD8UG0030E40XCS-E	2723030030	0.41	IE-CDR-V14MRJ/VAPM-C	2581810000	J.11
IE-C5ES8UG0020P41P41-E	1106020000	0.43	IE-C6FP8LD0100M40L40-D	2703320100	0.24	IE-C6HD8UG0030X40XCS-E	2723040030	0.41	IE-CDR-V14MRJ/VAPM-C	2581810000	0.11
IE-C5ES8UG0020M40M40-G	1166000030	0.26	IE-C6FP8LD0100M40R40-D	1165940100	0.18	IE-C6HD8UG0050E40XCS-E	2723050050	0.41	IE-CDR-V14MSCP0/VAPM-C	1253240000	J.11
IE-C5ES8UG0050B41B41-E	1066870000	J.15	IE-C6FP8LD0100M40V40-D	2703330100	0.24	IE-C6HD8UG0050X40XCS-E	2723040050	0.41	IE-CDR-V14MSCP0/VAPM-C	1253240000	0.9
IE-C5ES8UG0050B41B41-E	1066870000	0.43	IE-C6FP8LD0100M40V40-D	1248280100	0.23	IE-C6HD8UG0075E40XCS-E	2723030075	0.41	IE-CDR-V14MSCP0/VAPM-C II	2455360000	J.11
IE-C5ES8UG0050M40M40-G	1166000050	0.26	IE-C6FP8LD0100M40W40-D	1233160100	0.23	IE-C6HD8UG0075X40XCS-E	2723040075	0.41	IE-CDR-V14MSCP0/VAPM-C II	2455360000	0.9
IE-C5ES8UG0050P41P41-E	1106030000	J.15	IE-C6FP8LD0100X40X40-Y	1312160100	0.25	IE-C6HD8UG0100E40XCS-E	2723030100	0.41	IE-CL240W-PP-BASE	1547440000	P.5
IE-C5ES8UG0050P41P41-E	1106030000	0.43	IE-C6FP8LD0150M40M40-D	1165940150	0.18	IE-C6HD8UG0100XCSXCS-E	2723040100	0.41	IE-CL240W-PP-REMOTE	1547450000	P.5
IE-C5ES8UG0100B41B41-E	1066880000	J.15	IE-C6FP8LD0150X40X40-Y	1312160150	0.25	IE-C6HD8UG0150E40XCS-E	2723030150	0.41	IE-CL27V5A-PP-S	2623940000	P.6
IE-C5ES8UG0100B41B41-E	1066880000	0.43	IE-C6FP8LD0200M40M40-D	1165940200	0.18	IE-C6HD8UG0150XCSXCS-E	2723040150	0.41	IE-CP20-RJ45-FH-BU	1963080000	L.4
IE-C5ES8UG0100M40M40-G	1166000100	0.26	IE-C6FP8LD0200X40X40-Y	1312160200	0.25	IE-C6KS8VG0005XCSXCS-E	1398070005	0.40	IE-CP20-RJ45-FH-GN	1963100000	L.4
IE-C5ES8UG0100P41P41-E	1106040000	J.15	IE-C6FP8LD0250M40M40-D	1165940250	0.18	IE-C6KS8VG0005XCSXCS-E	1449470005	0.40	IE-CP20-RJ45-FH-GY	1963060000	L.4
IE-C5ES8UG0100P41P41-E	1106040000	0.43	IE-C6FP8LE0020M40M40-E	1251610002	0.19	IE-C6KS8VG0010XCSXCS-E	1398070015	0.40	IE-CP20-RJ45-FH-HG	1963070000	L.4
IE-C5ES8UG0150M40M40-G	1166000150	0.26	IE-C6FP8LE005M40M40-E	1251610005	0.19	IE-C6KS8VG0015XCSXCS-E	1449470015	0.40	IE-CP20-RJ45-FH-WH	1963050000	L.4
IE-C5ES8UG0200M40M40-G	1166000200	0.26	IE-C6FP8LE0100M40M40-E	1251610100	0.19	IE-C6KS8VG0030XCSXCS-E	139807030	0.40	IE-CP20-RJ45-FH-YE	1963090000	L.4
IE-C5ES8VG-100	8813190000	J.15	IE-C6FP8LE0100M40M40-E	1251610105	0.19	IE-C6KS8VG0030XCSXXX-E	1449470030	0.40	IE-CS-2TX-1RS232/485	1242080000	F.5
IE-C5ES8VG-100	8813190000	0.5	IE-C6FP8LE0020M40M40-E	1251610200	0.19	IE-C6KS8VG0050XCSXCS-E	1398070050	0.40	IE-CS-2TX-2RS232/485	1242090000	F.5
IE-C5ES8VG-100	8813190000	0.8	IE-C6FP8LE0030M40M40-E	1251610300	0.19	IE-C6KS8VG0050XCSXCS-E	1449470050	0.40	IE-CS-MBWG-2T1-1COM	2682600000	F.6
IE-C5ES8VG-500	2763510000	J.15	IE-C6FP8LE005M40M40-E	1251610500	0.19	IE-C6KS8VG0010XCSXCS-E	1398070100	0.40	IE-CSP05D00105LSSVAP-X	2732640015	0.33
IE-C5ES8VG-500	2763510000	0.5	IE-C6FP8LE0100M40M40-E	1251610500	0.19	IE-C6KS8VG0010XCSXCS-E	1449470100	0.40	IE-CSP05D0030LSSVAP-X	2732640030	0.33
IE-C5ES8VG-500	2763510000	0.8	IE-C6FP8LE0150M40M40-E	1251610510	0.19	IE-C7BS8VG-100	8813140000	0.5	IE-CSP05D0050LSSVAP-X	2732640050	0.33
IE-C5ES8VG0005M40M40-G	1166000205	0.26	IE-C6FP8LE0200M40M40-E	1251610600	0.19	IE-C7BS8VG-100	8813140000	0.7	IE-CSP05D0100LSSVAP-X	2732640100	0.33
IE-C5ES8VG0010M40M40-G	1166020010	0.26	IE-C6FP8LE0250M40M40-E	1251610250	0.19	IE-C7BS8VG-500	2763530000	0.5	IE-CSP05D0500V50VAPVAP-X	1403680050	0.32
IE-C5ES8VG0015M40M40-G	1166020015	0.26	IE-C6FP8LG0020M40M40-G	1251590002	0.20	IE-C7BS8VG-500	2763530000	0.7	IE-CSP05D050100VAPVAP-X	1403680100	0.32
IE-C5ES8VG0020M40M40-G	1166020020	0.26	IE-C6FP8LG005M40M40-G	1251590005	0.20	IE-C7BS8VG-100	8813130000	0.5	IE-CSP05D050150VAPVAP-X	1403680150	0.32
IE-C5ES8VG0030M40M40-G	1166020030	0.26	IE-C6FP8LG0010M40M40-G	1251590010	0.20	IE-C7BS8VG-100	8813130000	0.7	IE-CSP5SVS0010VAPVAP-X	1350120010	0.32
IE-C5ES8VG0050M40M40-G	1166020050	0.26	IE-C6FP8LG015M40M40-G	1251590015	0.20	IE-C7BS8VG-500	2763540000	0.5	IE-CSP5SVS0030VAPVAP-X	1350120030	0.32
IE-C5ES8VG0100M40M40-G	1166020100	0.26	IE-C6FP8LG0200M40M40-G	1251590020	0.20	IE-C7BS8VG-500	2763540000	0.7	IE-CSP5SVS0050VAPVAP-X	1350120050	0.32
IE-C5ES8VG0150M40M40-G	1166020150	0.26	IE-C6FP8LG030M40M40-G	1251590030	0.20	IE-C7ES8VG-100	8813180000	0.5	IE-CSP5SVS0100VAPVAP-X	1350120100	0.32
IE-C5ES8VG0200M40M40-G	1166020200	0.26	IE-C6FP8LG050M40M40-G	1251590050	0.20	IE-C7ES8VG-100	8813180000	0.9	IE-CSP5SVS0150VAPVAP-X	1350120150	0.32
IE-C5T4I4UG-100	2764770000	0.5	IE-C6FP8LG0100M40M40-G	1251590100	0.20	IE-C7ES8VG-500	2763550000	0.5	IE-CSP5SVS0200VAPVAP-X	1350120200	0.32
IE-C5T4I4UG-100	2764770000	0.16	IE-C6FP8LG0150M40M40-G	1251590150	0.20	IE-C7ES8VG-500	2763550000	0.9	IE-CST	9204350000	0.6
IE-C5T4I4UG-500	2763520000	J.11	IE-C6FP8LG0200M40M40-G	1251590200	0.20	IE-C7ES8VG-100	8813170000	0.5	IE-CST	9204350000	0.7
IE-C5T4I4UG-500	2763520000	0.5	IE-C6FP8LG0250M40M40-G	1251590250	0.20	IE-C7ES8VG-100	8813170000	0.9	IE-CST	9204350000	0.8
IE-C5T4I4UG-500	2763520000	0.16	IE-C6FP8LM0002M40M40-M	1201270002	0.21	IE-C7ES8VG-500	2763560000	0.9	IE-CST	9204350000	0.9
IE-C5T4I4UG0010B2E2-X	1312690010	0.31	IE-C6FP8LM0010M40M40-M	1201270005	0.21	IE-C7ES8LV-305M	1326540000	0.5	IE-CST	9204350000	0.10
IE-C5T4I4UG0020B2E2-X	1312690020	0.31	IE-C6FP8LM0010M40M40-M	1201270100	0.21	IE-C7FS8LV-305M	1326540000	0.5	IE-CST	9204350000	0.11
IE-C5T4I4UG0030B2E2-X	1312690030	0.31	IE-C6FP8LM0015M40M40-M	1201270105	0.21	IE-C7FS8LV-305M	1273090000	0.5	IE-CST	9204350000	0.12
IE-C5T4I4UG0050B2E2-X	1312690050	0.31	IE-C6FP8LM0020M40M40-M	1201270200	0.21	IE-C7FS8LV-305M	1273090000	0.12	IE-CST	9204350000	0.13
IE-C5T4I4UG00104DXCS-E	1457580100	0.42	IE-C6FP8LM0030M40M40-M	1201270300	0.21	IE-C7FS8LV-305M	1344690000	0.5	IE-CST	9204350000	0.14
IE-C5T4I4UG00104DXCS-E	1457580120	0.42	IE-C6FP8LM0050M40M40-M	1201270500	0.21	IE-C7FS8LV-305M	1344690000	0.11	IE-CST	9204350000	0.15
IE-C6EL8UG0010U40XCS-E	1457580010	0.42	IE-C6FP8LM0010M40M40-M	1201270500	0.21	IE-C7FS8LV-305M	1344680000	0.5	IE-CST	9204350000	0.16
IE-C6EL8UG0020U40XCS-E	1457580020	0.42	IE-C6FP8LM0010U40M40-M	1201271000	0.21	IE-C7FS8LV-305M	1344680000	0.11	IE-CST	9204350000	0.17
IE-C6EL8UG0030U40XCS-E	1457580030	0.42	IE-C6FP8LM0100M40M40-M	1201271050	0.21	IE-C7FS8LV-305M	1333160000	0.5	IE-CST	9204350000	0.18
IE-C6EL8UG0050U40XCS-E	1457580050	0.42	IE-C6FP8LM0200M40M40-M	1201272000	0.21	IE-C7FS8LV-305M	1333160000	0.12	IE-CST	9204350000	0.19
IE-C6EL8UG0070U40XCS-E	1457580070	0.42	IE-C6FP8LM0300M40M40-M	1201273000	0.21	IE-C7FS8LV-305M	1344670000	0.5	IE-CST	9204350000	0.20
IE-C6EL8UG0090U40XCS-E	1457580090	0.19	IE-C6FP8LM0500M40M40-M	1201275000	0.21	IE-C7FS8LV-305M	1344670000	0.13	IE-CST	9204350000	0.21
IE-C6EL8UG0100M40M40-G	1165900010	0.19	IE-C6FP8LM080020M40M40-M	1201280000	0.21	IE-CABLE-BENDER-90	2704480000	0.18	IE-CST	9204350000	0.22
IE-C6EL8UG0100M40M40-G	1165900010	0.19	IE-C6FP8LM080015M40M40-M	1201280100	0.21	IE-CABLE-BENDER-90	2704480000	0.19	IE-CST	9204350000	0.23
IE-C6EL8UG0100M40M40-G	1165900010	0.19	IE-C6FP8LM080020M40M40-M	1201280200	0.21	IE-CABLE-BENDER-90	2704480000	0.26	IE-CST	9204350000	0.24
IE-C6EL8UG0100M40M40-G	1165900010	0.19	IE-C6FP8LM080030M40M40-M	1201280300	0.21	IE-CABLE-BENDER-90	2704480000	0.27	IE-CST	9204350000	0.25
IE-C6EL8UG0100M40M40-G	1165900010	0.19	IE-C6FP8LM080050M40M40-M	1201280500	0.21	IE-CABLE-BENDER-90	2704480000	0.21	IE-CST	9204350000	0.26
IE-C6EL8UG0100M40M40-G	1165900010	0.19	IE-C6FP8LG0020M40M40-Y	1251580020	0.22	IE-CABLE-BENDER-90	2704480000	0.22	IE-CST	9204350000	0.27
IE-C6EL8UG0100M40M40-G	1165900010	0.23	IE-C6FP8LG0030M40M40-Y	1251580030	0.22	IE-CABLE-BENDER-90	2704480000	0.22	IE-CST	9204350000	0.28
IE-C6EL8UG0100M40M40-G	1165900010	0.23	IE-C6FP8LG0050M40M40-Y	1251580050	0.22	IE-CABLE-BENDER-90	2704480000	0.23	IE-CST	9204350000	0.29
IE-C6EL8UG0100M40M40-G	1165900010	0.23	IE-C6FP8LG0070M40M40-Y	1251580070	0.22	IE-CABLE-BENDER-90	2704480000	0.24	IE-CST	9204350000	0.30
IE-C6EL8UG0100M40M40											

Type	Order No.	Page	Type	Order No.	Page	Type	Order No.	Page	Type	Order No.	Page
IE-FC-DFM-KNOB-4X	2669640000	M.4	IE-FC1-PWB-CZ	2426700000	M.21	IE-FM52ZV00010MLD0D0X	1062580000	R.9	IE-MC-VL1-TX-1ST	1241410000	F.4
IE-FC-DIP-BP	2004890000	M.7	IE-FC1-PWB-DE	1450730000	L.19	IE-FM52ZV00010MSD0D0X	8876350100	R.8	IE-MC-VL1-TX-1SC	1266880000	F.4
IE-FC-DIP-CU/3A/2ST/1D9	2003370000	M.6	IE-FC1-PWB-DE	1450730000	M.17	IE-FM6C2UE0100MSD0D1X	8876370100	R.8	IE-MC-VL1-TX-1SCS	1266900000	F.4
IE-FC-DIP-PWB/2/ST/FILS	2067070000	M.5	IE-FC1-PWB-DE	1450730000	M.18	IE-FM6C2UE0180MSD0D1X	1318011000	R.13	IE-MC-VL1-TX-1ST	1266890000	F.4
IE-FC-DSP-CI/3A/2ST/1D9	2004810000	M.6	IE-FC1-PWB-DE-OR	1554000000	L.19	IE-FM6C2UE0200MSD0D1X	1318011800	R.13	IE-OM-V01M-K11-1S	1966300000	0.13
IE-FC-DSP-PWB/2/ST/FILS	2067080000	M.5	IE-FC1-PWB-DE-OR	1554000000	M.18	IE-FM6C2UE0250MSD0D1X	1318012000	R.13	IE-OM-V01M-K21-2S	1966330000	0.13
IE-FC1-IP-1ST/109/ID25	1450850000	M.12	IE-FC1-PWB-DK	2661340000	M.17	IE-FM6C2UE0300MSD0D1X	1318012500	R.13	IE-OM-V04P-K11-1S	1966200000	0.15
IE-FC1-IP-2ST/2D9	1450670000	M.12	IE-FC1-PWB-DK	2661340000	M.23	IE-FM6C2UE0350MSD0D1X	1318013000	R.13	IE-OM-V04P-K21-2S	1966250000	0.15
IE-FC1-IP-BP	1450710000	M.7	IE-FC1-PWB-FR	1450750000	L.19	IE-FM6C2UE0400MSD0D1X	1318013500	R.13	IE-OM-V05M-K11-1S	1966260000	0.16
IE-FC1-IP-PWB	2548060000	M.9	IE-FC1-PWB-FR	1450750000	M.17	IE-FM6D2UE0050MSD0D1X	1318015000	R.13	IE-OM-V05M-K21-2S	1966290000	0.16
IE-FC1-IP-PWB/1D9	2003350000	M.8	IE-FC1-PWB-FR	1450750000	M.19	IE-FM6D2UE0001MSD0D0X	8876440010	R.12	IE-OP-V01P-1S	1061830000	J.15
IE-FC1-IP-PWB/2/ST	1450630000	M.8	IE-FC1-PWB-FR-OR	2007230000	L.19	IE-FM6D2UE0001MST0D0X	8876460010	R.12	IE-OP-V01P-1S	1061830000	J.12
IE-FC1-IP-PWS/2D9	1450680000	M.10	IE-FC1-PWB-FR-OR	2007230000	M.19	IE-FM6D2UE0003MSD0D0X	8876440030	R.12	IE-OP-V04P-1S	1045780000	0.14
IE-FC1-IP-PWS/2ST/1D9	1450690000	M.9	IE-FC1-PWB-G8	1450770000	L.19	IE-FM6D2UE0030MSD0T0X	8876460030	R.12	IE-P	881310000	L.8
IE-FC1-IP-PWS/4ST	1450640000	M.10	IE-FC1-PWB-G8	1450770000	M.17	IE-FM6D2UE0050MLD0D0X	1220930000	R.11	IE-PJ67	880838000	N.27
IE-FC1-IP-PWI/1ST/CB	1543710000	M.11	IE-FC1-PWB-IND	2500710000	L.19	IE-FM6D2UE0050MSD0D0X	8876440050	R.12	IE-P63	881311000	L.8
IE-FC1-IP-PWI/2ST	1450700000	M.11	IE-FC1-PWB-IND	2500710000	M.17	IE-FM6D2UE0050MSD0T0X	8876460050	R.12	IE-P70	881312000	L.8
IE-FC2KEY	2066650000	M.2	IE-FC1-PWB-IND	2500710000	M.23	IE-FM6D2UE0100MSD0T0X	8876440100	R.12	IE-PCB-M12X-S-180	1324010000	N.47
IE-FC2KEY	2066650000	M.3	IE-FC1-PWB-IND	2500710000	M.23	IE-FM6D2UE0100MSD0T0X	8876460100	R.12	IE-PCB-M12X-S-90	2168220000	N.48
IE-FC-PWPC	1450820000	M.2	IE-FC1-PWB-ISR	2531060000	L.19	IE-FM6D2UE0200MLD0D0X	1174830000	R.11	IE-PCB-SPD-P-180V-THR	2795170000	K.12
IE-FC-PWPC	1450820000	M.3	IE-FC1-PWB-ISR	2531060000	M.17	IE-FM6D2UE0350MLD0D0X	899322000	R.11	IE-PCB-SPD-P-180V-SMD	2795170000	L.3
IE-FC-PWPC	1450820000	M.4	IE-FC1-PWB-ISR	2531060000	M.23	IE-FM6D2UE0400MSD0D0X	8876440050	R.12	IE-PCB-SPD-P-180-THR	2735920000	K.14
IE-FC-PWPC	1450820000	M.5	IE-FC1-PWB-RCB0	1534250000	L.19	IE-FM6D2UE0400MSD0D0X	8876441000	R.12	IE-PCB-SPD-P-180-THR	2726010000	L.3
IE-FC-PWPC	1450820000	M.8	IE-FC1-PWB-RCB0	1534250000	M.24	IE-FM6D2UE0100MSD0T0X	8876461000	R.12	IE-PCB-SPD-P-180V-YG/YG	2795120000	K.12
IE-FC-PWPC	1450820000	M.9	IE-FC1-PWB-C8-3A	1543690000	M.6	IE-FM6ZL200001MLD0D0X	1433930010	R.6	IE-PCB-SPD-P-180V-YG/YG	2795120000	L.3
IE-FC-PWPC	1450820000	M.10	IE-FC1-PWB-C8-3A	1543690000	M.11	IE-FM6ZL200001MSD0D0-X	1433960010	R.5	IE-PCB-SPM-P-180-SMD	2795110000	K.14
IE-FC-PWPC	1450820000	M.11	IE-FC1-PWB-C8-3A	1543690000	M.26	IE-FM6ZL200001MST0D0-X	1433980010	R.5	IE-PCB-SPM-P-180-SMD	2795110000	N.31
IE-FC-PWPC	1450820000	M.12	IE-FC1-PWS-IT	1450810000	L.19	IE-FM6ZL200002MLD0D0X	1433930020	R.6	IE-PCB-SPM-P-180-THR	2735920000	K.14
IE-FC-PWPC	1450820000	M.27	IE-FC1-PWS-IT	1450810000	M.10	IE-FM6ZL200002MSD0D0-X	1433960020	R.5	IE-PCB-SPM-P-180-THR	2735920000	N.31
IE-FC-SET-1PDE001-KY-P	1543680000	M.29	IE-FC1-PWS-IT	1450810000	M.17	IE-FM6ZL200002MSST0D0-X	1433980020	R.5	IE-PCB-SPM-90-THR	2795100000	K.14
IE-FC-SET-SPDE001-KN-P	1529580000	M.28	IE-FC1-PWS-IT	1450810000	M.20	IE-FM6ZL200003MLD0D0X	1433930030	R.6	IE-PCB-SPM-90-THR	2795100000	N.31
IE-FC-SET-SPDE001-KY-P	1989020000	M.29	IE-FC1-PWS-US	1450800000	M.11	IE-FM6ZL200003MSD0D0-X	1433960030	R.5	IE-PCB-SPM-12X-S-180	1393080000	N.47
IE-FC-SFP-CAB	2003160000	M.3	IE-FC1-PWS-US	1450800000	M.17	IE-FM6ZL200003MSST0D0-X	1433980030	R.5	IE-PCB-SPM-12X-S-180	1442760000	N.47
IE-FC-SFP-CAB-DB	2663200000	M.3	IE-FC1-PWS-US	1450800000	M.22	IE-FM6ZL200005MLD0D0X	1433930035	R.6	IE-PCB-SPR2-M12X-S-180	1444650000	N.47
IE-FC-SFM-KEY2	1450540000	M.3	IE-FCM-RJ45-C	1018790000	J.10	IE-FM6ZL200005MSD0D0-X	1433960035	R.5	IE-PHAD-V09M-RJ45	1993540000	N.25
IE-FC-SFM-KNOB	1450530000	M.3	IE-FCM-RJ45-C	1018790000	J.14	IE-FM6ZL200005MSD0T0X	1433980035	R.5	IE-PHJ45-TH-BK	1962500000	L.8
IE-FC-SFM-KNOB-4X	2669630000	M.4	IE-FCM-RJ45-C	1018790000	M.31	IE-FM6ZL200005MLD0D0X	1433930035	R.6	IE-PHJ45-TH-BU	1962470000	L.8
IE-FC-SFP-CAB	2003140000	M.3	IE-FCM-RJ45-FJ-A	1018810000	J.14	IE-FM6ZL200005MSD0D0-X	1433960035	R.5	IE-PHJ45-TH-GN	1962490000	L.8
IE-FC-SFP-CAB-DB	2663190000	M.3	IE-FCM-RJ45-FJ-A	1018810000	M.30	IE-FM6ZL200005MSST0D0-X	1433980035	R.5	IE-PHJ45-TH-GY	1962440000	L.8
IE-FC-SFP-KEY2	1450520000	M.3	IE-FCM-RJ45-FJ-B	1018820000	J.14	IE-FM6ZL200010MLD0D0X	1433930100	R.6	IE-PCB-SPR2-M12X-S-180	1444650000	N.47
IE-FC-SFP-KNOB	1450510000	M.3	IE-FCM-RJ45-FJ-B	1018820000	M.30	IE-FM6ZL200010MSD0D0-X	1433960100	R.5	IE-PHJ45-TH-06	1962450000	L.8
IE-FC-SFP-1ST/1D9/1025	1450580000	M.12	IE-FCM-RJ45-FJ-P	1018830000	J.10	IE-FM6ZL200010MSD0T0X	1433980100	R.5	IE-PHJ45-TH-WH	1962430000	L.8
IE-FC-SP-2ST/2D9	1450590000	M.12	IE-FCM-RJ45-FJ-P	1018830000	M.30	IE-FM6ZL200001MLD0D0X	1296450000	R.9	IE-PHV01M	1962550000	N.12
IE-FC-SP-PWB/2ST	1450550000	M.8	IE-FCM-USB-3.0-A	1427960000	M.32	IE-FM6ZV00001MSD0D0X	8813330000	R.8	IE-PHV01M-BP	1962560000	N.12
IE-FC-SP-PWS/2D9	1450610000	M.10	IE-FCM-USB-A	1018840000	M.32	IE-FM6ZV00001MSST0D0X	8813270000	R.8	IE-PHV01P	1012440000	N.16
IE-FC-SP-PWS/2ST/1D9	1450600000	M.9	IE-FCM-USB-AB	1222550000	M.32	IE-FM6ZV00002MSD0D0X	8813340000	R.8	IE-PHV01P-BP	1012460000	N.16
IE-FC-SP-PWS/4ST	1450570000	M.10	IE-FISP-V4	9204370000	M.30	IE-FM6ZV00002MSST0D0X	8813400000	R.9	IE-PHV04P	1962520000	N.19
IE-FC-SP-PWU/2ST	1450620000	M.11	IE-FISP-V4	9204370000	M.31	IE-FM6ZV00002MSST0D0X	8813280000	R.8	IE-PHV04P-BP	1962530000	N.19
IE-FCL025-FF	1450880000	M.12	IE-FISP-V4	9204370000	M.32	IE-FM6ZV00003MSD0D0X	8813350000	R.8	IE-PHV05M	1962540000	N.25
IE-FCL025-FF	1450880000	M.15	IE-FISP-V4	9204370000	M.20	IE-FM6ZV00003MSST0D0X	8813290000	R.8	IE-PHV14M-0	1058100000	N.10
IE-FCL025-FM	1450890000	M.12	IE-FISP-V4	9204370000	N.22	IE-FM6ZV00005MSD0D0X	8813600050	R.8	IE-PHV14M-R	1011560000	N.2
IE-FCL025-FS	1450890000	M.15	IE-FISP-V4	9204370000	N.23	IE-FM6ZV00005MSD0T0X	8876380050	R.8	IE-PHV14M-RJ	1011560000	N.3
IE-FCL025-FS	1450900000	M.12	IE-FISP-V4	9204370000	N.24	IE-FM6ZV00010MSD0D0X	8876360100	R.8	IE-PHV14M-RJ	1011560000	N.7
IE-FCL025-FS	1450900000	M.15	IE-FISP-V4	9204370000	S.19	IE-FM6ZV00010MSD0T0X	8876380100	R.8	IE-PHYB-10P	1068990000	N.53
IE-FCL025-FS	1450940000	M.6	IE-FPM502UE0001MSD0D0X	8876430400	R.12	IE-FPM2BEG-50	2781950000	R.11	IE-PHV14M-RJ	1011560000	N.7
IE-FCL025-FS	1450940000	M.8	IE-FPM502UE0001MSD0D0X	8876430400	R.12	IE-FPM2BEG-50	2781950000	R.12	IE-PHM02EG-50	1444650000	N.5
IE-FCL025-FS	1450840000	M.9	IE-FPM502UE0003MSD0D0X	8876430400	R.12	IE-FPM2BEG-50	2781950000	R.12	IE-PHM02EG-50	1444650000	N.5
IE-FCL025-FS	1450840000	M.10	IE-FPM502UE0005MSD0D0X	8876430400	R.12	IE-FPM2BEG-50	2781950000	R.12	IE-PHM02EG-50	1444650000	N.5
IE-FCL025-FS	1450840000	M.12	IE-FPM502UE0005MSD0D0X	8876430400	R.12	IE-FPM2BEG-50	2781950000	R.12	IE-PHM02EG-50	1444650000	N.5
IE-FCL025-FS	1450840000	M.15	IE-FPM502UE0005MSD0T0X	8876430400	R.12	IE-FPM2BEG-50	2781950000	R.12	IE-PHM02EG-50	1444650000	N.5
IE-FCL025-FS	1450870000	M.6	IE-FPM502UE0002MLD0D0X	8876430400	R.11	IE-FPM2ZLY0002MLD0D0X	1273430030	R.10	IE-PHM02EG-50	1444650000	N.5
IE-FCL025-FS	1450870000	M.8	IE-FPM502UE0005MSD0D0X	8876430400	R.12	IE-FPM2ZLY0002MLD0D0X	1273430030	R.10	IE-PHM02EG-50	1444650000	N.5
IE-FCL025-FS	1450870000	M.9	IE-FPM502UE0005MSD0D0X	8876430400	R.12	IE-FPM2ZLY0002MLD0D0X	1273430030	R.10	IE-PHM02EG-50	1444650000	N.5
IE-FCL025-FS	1450870000	M.10	IE-FPM502UE0005MSD0D0X	8876430400	R.12	IE-FPM2ZLY0002MLD0D0X	1273430030	R.10	IE-PHM02EG-50	1444650000	N.5
IE-FCL025-FS	1450870000	M.12	IE-FPM502UE0005MSD0D0X	8876430400	R.12	IE-FPM2ZLY0002MLD0D0X	1273430030	R.10	IE-PHM02EG-50	1444650000	N.5
IE-FCL025-FS	1450870000	M.15	IE-FPM502UE0005MSD0T0X	8876430400	R.12	IE-FPM2ZLY0002MLD0D0X	1273430030	R.10	IE-PHM02EG-50	1444650000	N.5
IE-FCL025-FS	1450390000	M.6	IE-FPM502UE0005MSD0T0X	8876430400	R.12	IE-FPM2ZLY0002MLD0D0X	1273430030	R.10	IE-PHM02EG-50		

Type	Order No.	Page	Type	Order No.	Page	Type	Order No.	Page	Type	Order No.	Page
IE-PP-RJ45	2552580000	Q.58	IE-S1DS2VE0020TM2TM2-E	2726070020	Q.63	IE-SW-IP67-5M12	1504410000	B.8	IE-WALLMOUNT-KIT-30MM	1504450000	B.6
IE-PP-V01P	1965690000	N.12	IE-S1DS2VE0030T01T01-E	2725850030	K.8	IE-SW-IP67-5M12	1504420000	B.8	IE-WALLMOUNT-KIT-30MM	1504450000	B.13
IE-PP-V01P	1965690000	N.16	IE-S1DS2VE0050T01T01-E	2725850030	Q.61	IE-SW-PL10M-3GT-7TX	1241290000	C.10	IE-WALLMOUNT-KIT-30MM	1504450000	B.15
IE-PP-V01P	1965690000	S.24	IE-S1DS2VE0050T01T01-E	2725850050	K.8	IE-SW-PL10M-3GT-7TX	1286930000	C.10	IE-WALLMOUNT-KIT-30MM	1504450000	I.10
IE-PP-V04P	1963890000	N.19	IE-S1DS2VE0050T01T01-E	2725850050	Q.61	IE-SW-PL16M-16TX	1241100000	C.8	IE-WALLMOUNT-KIT-46MM	1504440000	F.4
IE-PP-V04P	1963890000	S.24	IE-SCLRJ-P67-POF-100	1278430000	N.10	IE-SW-PL16M-16TX	1266820000	C.8	IE-WL-BLAP-CLEU	2536600000	H.5
IE-PP-V05M	1968920000	N.25	IE-SCLRJ-P67-POF-100	1278430000	N.56	IE-SW-PL18M-2GC-16TX	1241320000	C.11	IE-WL-BLAP-CL-US	2536660000	H.5
IE-PP-V05M	1968920000	S.24	IE-SCLRJ-IP20-POF-100	1278420000	L.10	IE-SW-PL18M-2GC14TX2SCS	1241350000	C.11	IE-WL-BLAP-BR-CL-EU	2536680000	H.7
IE-PP-V14P	1058280000	N.2	IE-SFP-10GE-MM-03	2779110000	I.6	IE-SW-PL18M-2GC16TX	1266970000	C.11	IE-WL-BLAP-BR-CL-EU	2536700000	H.7
IE-PP-V14P	1058280000	N.3	IE-SFP-10GE-SM-20	2779120000	I.6	IE-SW-PL18M-2GC14TX2SCS	1287010000	C.11	IE-WL-BLAP-CL-EU	2536650000	H.5
IE-PP-V14P	1058280000	N.7	IE-SFP-10GE-SM-40	2779130000	I.6	IE-SW-SL10M-7TX-3GCHV	2778950000	C.14	IE-WL-BLAP-CL-US	2536670000	H.5
IE-PP-V14P	1058280000	N.10	IE-SFP-1FE-MM-2	2682450000	I.4	IE-SW-SL10M-7TX-3GCLV	2778960000	C.14	IE-WL-BLAP-BR-CL-EU	2536690000	H.7
IE-PP-V14P	1058280000	S.24	IE-SFP-1FE-SM-60	2682470000	I.4	IE-SW-SL20M-8GT-12GESFP-HV	2778970000	C.15	IE-WL-BLAP-BR-CL-US	2536710000	H.7
IE-PS-M12X-180-P-TH	2664820000	N.43	IE-SFP-1FEMLC-T	1241450000	I.7	IE-SW-SL20M-8GT-12GESFP-LV	2778980000	C.15	IE-XM-6D-RJ45/RJ45-IP67	882945000	N.28
IE-PS-M12X-180-S-TH	2672440000	N.43	IE-SFP-1FESLC-T	1241470000	I.7	IE-SW-SL26M-24TX-2GC-HV	2778990000	C.16	IE-XM-6U-RJ45/RJ45-IP67	882944000	N.28
IE-PS-M12X-90-P-TH	2702710000	N.43	IE-SFP-1GE-MM-05	2682480000	I.5	IE-SW-SL26M-24TX-2GC-LV	2779000000	C.16	IE-XM-RJ45/IDC	8808360000	L.14
IE-PS-M12X-90-S-TH	2702720000	N.43	IE-SFP-1GE-MM-2	2682490000	I.5	IE-SW-SL28M-HV	2779010000	C.19	IE-XM-RJ45/IDC-IP67	880844000	N.28
IE-PS-M12X-P-AW-G22/27FH	2007500000	N.41	IE-SFP-1GE-MM-10	2682500000	I.5	IE-SW-SL28M-LV	2779020000	C.6	IE-XM-RJ45/RJ45	887905000	L.15
IE-PS-M12X-P-FH	1324020000	N.41	IE-SFP-1GE-SM-10-BIDI-TX1310	2682520000	I.5	IE-SW-VL05M-5TX	1504280000	C.6	IE-XM-RJ45/RJ45-IP67	880845000	N.28
IE-PS-M12X-S-FH	1516330000	N.42	IE-SFP-1GE-SM-10-BIDI-TX1550	2682530000	I.5	IE-SW-VL05M-5TX	1504310000	C.6	IE-XM-ST/ST	880834000	L.18
IE-PS-RJ45-FH-180A-1.1	1992850000	L.5	IE-SFP-1GE-SM-20-BIDI-TX1310	2682540000	I.5	IE-SW-VL08-6GT-2GS	1241280000	C.7	IE-XR-RJ45/RJ45-2	895295000	L.11
IE-PS-RJ45-FH-180A-1.1-CG	2703440000	L.5	IE-SFP-1GE-SM-20-BIDI-TX1550	2682550000	I.5	IE-SW-VL08-6GT-2GS	1286870000	B.13	IE-XR-RJ45/RJ45	895295000	N.28
IE-PS-RJ45-FH-180A-1.6	1992820000	L.5	IE-SFP-1GE-SM-40	2682560000	I.5	IE-SW-VL08-8GT	1241270000	B.13	IE-XRJ45/IDC	880833000	L.12
IE-PS-RJ45-FH-180A-1.6-CG	2703390000	L.5	IE-SFP-1GLXLKC	1241520000	I.7	IE-SW-VL08M-5TX-1SCS	1345240000	C.7	IE-XRJ45/IDC	880833000	N.28
IE-PS-RJ45-FH-180B-1.1	1992860000	L.5	IE-SFP-1GLXLKC-T	1286710000	I.7	IE-SW-VL08M-6TX-2SCS	1241020000	C.7	IOT-GW30	2682620000	G.4
IE-PS-RJ45-FH-180B-1.6	1992830000	L.5	IE-SFP-1GLXLCT	1286710000	I.7	IE-SW-VL08M-6TX-2ST	1240990000	C.7			
IE-PS-RJ45-FH-180B-1.6-CG	2703410000	L.5	IE-SFP-1GLXLCT	1286710000	I.7	IE-SW-VL08M-6TX-7TX	1240940000	C.7			
IE-PS-RJ45-FH-180B-1.8	1992840000	L.7	IE-SFP-1GLXLCT	1286720000	I.7	IE-SW-VL08M-6GT-2GS	1286870000	B.13			
IE-PS-RJ45-FH-180B-1.8-CG	2703420000	L.7	IE-SFP-1GLXLCT	1286720000	I.7	IE-SW-VL08M-6GT-2GS	1286880000	B.13			
IE-PS-RJ45-FH-90A-1.1	1518080000	L.6	IE-SFP-1GLXLCT	1286720000	I.7	IE-SW-VL16T-16TX	1241000000	C.7			
IE-PS-RJ45-FH-90A-1.6	1992870000	L.6	IE-SR-2GT-LAN	1345270000	D.5	IE-SW-VL16T-16TX	1286590000	B.7			
IE-PS-RJ45-FH-90B-1.1	1518090000	L.6	IE-SR-2GT-LAN-FN	1489940000	D.5	IE-SW-SL02-2GESFP+	2779210000	C.21			
IE-PS-RJ45-FH-90B-1.6	1992890000	L.6	IE-SR-2GT-LAN-JM	2535980000	D.5	IE-SW-SL04-4GESFP	2779200000	C.21			
IE-PS-RJ45-FH-90P-1.6	1518100000	J.10	IE-SR-2GT-LTE/4GE	2535930000	D.5	IE-SW-SL04-4GESFP+	2779220000	C.21			
IE-PS-RJ45-FH-90P-1.6-CG	2703390000	L.5	IE-SR-2GT-LTE/4GE-U	2535970000	D.5	IE-SW-SL04-4SCS	2779170000	C.20			
IE-PS-RJ45-FH-90P-1.6-S	1518100000	L.7	IE-SR-2GT-LTE/4GE-U-M	2535970000	D.5	IE-SW-SL04-4SCS	2779160000	C.20			
IE-PS-RJ45-FH-90P-1.6-TH	1518100000	L.7	IE-SR-2GT-LTE/4GE-US	2535780000	D.5	IE-SW-SL04-4ST	2779190000	C.20			
IE-PS-RJ45-FH-BK-A	1132040000	J.14	IE-SR-4TX	2751270000	D.6	IE-SW-SL04-4STS	2779180000	C.20			
IE-PS-RJ45-FH-BK-A	1132040000	L.4	IE-SR-4TX-LTE/4GE	2751280000	D.6	IE-SW-SL08-6GESESFP	2779150000	C.20			
IE-PS-RJ45-FH-BK-B	1132050000	J.14	IE-SR-4TX-LTE/4GE-USEMEA	2739630000	D.6	IE-SW-SL08-6GT	2779140000	C.20			
IE-PS-RJ45-FH-BK-B	1132050000	L.4	IE-SR-6GT-LAN	2535940000	D.5	IE-T0-LCD-MM	8947010000	L.18			
IE-PS-RJ45-FH-BK-P	1132060000	J.10	IE-SR-6GT-LTE/4GE	2535960000	D.5	IE-T0-LCD-SM	8947020000	L.18			
IE-PS-RJ45-FH-BK-P	1132060000	L.4	IE-SR-6GT-LTE/4GE-U	2535950000	D.5	IE-T0-RJ45-C	8946920000	J.10			
IE-PS-RJ45-TH-BK	1963590000	J.14	IE-SW-AL05LM-5TX	2682250000	C.4	IE-T0-RJ45-C	8946920000	J.14			
IE-PS-RJ45-TH-BK	1963590000	L.8	IE-SW-AL06LM-4GT-2SCS	2682260000	C.4	IE-T0-RJ45-F	8946930000	J.14			
IE-PS-RJ45-TH-BK-P	2584980000	L.9	IE-SW-AL06LM-4GT-2SCS	2682270000	C.4	IE-T0-RJ45-FJA	8946930000	L.13			
IE-PS-SCLRJ1-POF	1206720000	J.10	IE-SW-AL06M-4GTPOE-2GESFP	2682430000	C.13	IE-T0-RJ45-FJA	8946930000	L.13			
IE-PS-SCLRJ1-POF	1206720000	J.14	IE-SW-AL08M-6TX-2GT	2682290000	C.9	IE-T0-RJ45-FJB	8946940000	J.14			
IE-PS-SCLRJ1-POF	1206720000	L.10	IE-SW-AL08M-8GT	2682350000	C.12	IE-T0-RJ45-FJB	8946940000	J.13			
IE-PS-SCLRJ1-POF-QA	2564950000	L.10	IE-SW-AL08M-8GTPOE	2682420000	C.13	IE-T0-RJ45-FJP	8946950000	J.10			
IE-PS-SPD-S-FH-180	2726040000	K.11	IE-SW-AL08M-BTX	2682280000	C.8	IE-T0-RJ45-FJP	8946950000	J.13			
IE-PS-SPD-S-FH-180	2726040000	L.2	IE-SW-AL10M-BTX-2GC	2740420000	C.9	IE-T0-SCD-MM	8946970000	L.17			
IE-PS-V01M-2SC-POF	1963280000	J.14	IE-SW-AL12M-8GT-4GESFP	2682340000	C.12	IE-T0-SCD-SM	8946980000	L.17			
IE-PS-V01M-RJ45-FH	1963120000	J.14	IE-SW-AL14M-12GT-2GESFP	2682360000	C.12	IE-T0-SCJ-MM	8946990000	J.10			
IE-PS-V01M-RJ45-FH	1963120000	N.12	IE-SW-AL16M-16TX	2682310000	C.5	IE-T0-SCJ-MM	8946990000	J.14			
IE-PS-V01M-RJ45-FH-BP	1963130000	N.12	IE-SW-AL18M-16TX-2GC	2682330000	C.9	IE-T0-SCJ-MM	8946990000	L.17			
IE-PS-V01M-RJ45-TH	1963140000	J.14	IE-SW-AL24M-16GT-3GESFP	2682370000	C.12	IE-T0-SCJ-MM	8947000000	L.17			
IE-PS-V01M-RJ45-TH	1963140000	N.12	IE-SW-AL24M-24TX	2682320000	C.5	IE-T0-SCJ-MM	8947000000	L.17			
IE-PS-V01M-RJ45-TH-BP	1963150000	N.12	IE-SW-BL05-1GT-4GTPOE	1504320000	B.15	IE-T0-SCJ-MM	8947000000	L.17			
IE-PS-V01P-RJ45-FH	1012490000	J.14	IE-SW-BL05-46T-1GS	2435400000	B.13	IE-T0-USB	8946960000	L.16			
IE-PS-V01P-RJ45-FH	1012490000	N.16	IE-SW-BL05-46T-1GS	2435410000	B.13	IE-T0-USAB	1438180000	L.16			
IE-PS-V01P-RJ45-FH-BP	1012570000	N.16	IE-SW-BL05-47X-1SC	1240870000	B.6	IE-USB-3.0-A-0.5M	2581730005	M.14			
IE-PS-V01P-RJ45-TH	1012470000	J.14	IE-SW-BL05-47X-1ST	1240880000	B.6	IE-USB-3.0-A-0.5M	2581730005	M.32			
IE-PS-V01P-RJ45-TH	1012470000	N.16	IE-SW-BL05-5TX	1240890000	B.6	IE-USB-3.0-A-0.5M	2581730005	M.32			
IE-PS-V04P-RJ45-FH	1963160000	N.16	IE-SW-BL05-5GT-4GTPOE	1504340000	B.15	IE-USB-3.0-A-0.5M	2581730005	M.60			
IE-PS-V04P-RJ45-FH	1963160000	N.19	IE-SW-BL05-5GT-4GTPOE	1504340000	B.15	IE-USB-3.0-A-1.8M	2581730018	M.14			
IE-PS-V04P-RJ45-FH	1963160000	N.19	IE-SW-BL05-5GT-4GTPOE	1504340000	B.15	IE-USB-3.0-A-1.8M	2581730018	N.55			
IE-PS-V04P-RJ45-FH	1963170000	N.19	IE-SW-BL05-5GT-4GTPOE	1504340000	B.15	IE-USB-3.0-A-1.8M	2581730018	N.55			
IE-PS-V04P-RJ45-FH	1963170000	N.19	IE-SW-BL05-5GT-4GTPOE	1504340000	B.15	IE-USB-3.0-A-1.8M	2581730018	N.55			
IE-PS-V04P-RJ45-FH	1963170000	N.19	IE-SW-BL05-5GT-4GTPOE	1504340000	B.15	IE-USB-3.0-A-1.8M	2581730018	N.55			
IE-PS-V04P-RJ45-FH	1963170000	N.19	IE-SW-BL05-5GT-4GTPOE	1504340000	B.15	IE-USB-3.0-A-1.8M	2581730018	N.55			
IE-PS-V04P-RJ45-FH	1963170000	N.19	IE-SW-BL05-5GT-4GTPOE	1504340000	B.15	IE-USB-3.0-A-1.8M	2581730018	N.55			
IE-PS-V14M-2SC-POF	1191550000	N.10	IE-SW-BL08-2TX-2ST	1240930000	B.8	IE-USB-3.0-A-3.0M	1993500003	M.59			
IE-PS-V14M-2SC-POF	1191550000	N.10	IE-SW-BL08-2TX-1SC	1412070000	B.8	IE-USB-3.0-A-3.0M	1993500003	M.59			
IE-PS-V14M-2SC-POF-QA	2568260000	N.1									

Type	Order No.	Page	Type	Order No.	Page	Type	Order No.	Page	Type	Order No.	Page
RM-KIT	1241440000	C.12	SCREWTY-M12-DM	1900001000	0.50	TM1 12 MC NE GE	1718411687	0.38	VT SF 5/21 MC NE WS VO	1689470001	0.9
RM-KIT	1241440000	C.13	SCREWTY-M12-DM	1900001000	0.51	TM1 12 MC NE GE	1718411687	0.39	VT SF 5/21 MC NE WS VO	1689470001	0.10
RM-KIT	1241440000	C.14	SCREWTY-M12-DM	1900001000	0.52	TM1 12 MC NE GE	1718411687	0.40	VT SF 5/21 MC NE WS VO	1689470001	0.11
RM-KIT	1241440000	C.15	SEE ESD 120	9205130000	S.9	TM1 12 MC NE GE	1718411687	0.41	VT SF 5/21 MC NE WS VO	1689470001	0.12
RM-KIT	1241440000	D.5	SEE ESD 125	9204750000	S.9	TM1 12 MC NE GE	1718411687	0.42	VT SF 5/21 MC NE WS VO	1689470001	0.13
RM-KIT	1241440000	D.6	SM 27/18 K MC NE GR	1073340000	M.2	TM1 12 MC NE GE	1718411687	0.43	VT SF 5/21 MC NE WS VO	1689470001	0.14
RM-KIT	1241440000	F.4	SM 27/18 K MC NE GR	1073340000	M.3	TM1 12 MC NE GE	1718411687	0.44	VT SF 5/21 MC NE WS VO	1689470001	0.15
RM-KIT	1241440000	F.5	SM 27/18 K MC NE GR	1073340000	M.4	TM1 12 MC NE GE	1718411687	0.45	VT SF 5/21 MC NE WS VO	1689470001	0.16
RM-KIT	1241440000	F.6	SM 27/18 K MC NE SI	1713760000	M.2	TM1 12 MC NE GE	1718411687	0.46	VT SF 5/21 MC NE WS VO	1689470001	0.17
RM-KIT	1241440000	G.4	SM 27/18 K MC NE SI	1713760000	M.3	TM1 12 MC NE GE	1718411687	0.47	VT SF 5/21 MC NE WS VO	1689470001	0.27
RM-KIT	1241440000	H.5	SM 27/18 K MC NE SI	1713760000	M.4	TM1 12 MC NE GE	1718411687	0.48	VT SF 5/21 MC NE WS VO	1689470001	R.4
RM-KIT	1241440000	H.7	SM 27/18 K MC NE WS	1707270000	M.2	TM1 12 MC NE GE	1718411687	0.49	VT SF 5/21 MC NE WS VO	1689470001	R.5
RM-KIT	1241440000	I.10	SM 27/18 K MC NE WS	1707270000	M.3	TM1 12 MC NE GE	1718411687	0.50	VT SF 5/21 MC NE WS VO	1689470001	R.6
SM 27/18 K MC NE WS	1707270000	M.4	SM 27/18 K MC NE WS	1707270000	M.5	TM1 12 MC NE GE	1718411687	0.51	VT SF 5/21 MC NE WS VO	1689470001	R.7
S			SM 27/18 K MC NE WS	17099860000	M.31	TM1 12 MC NE GE	1718411687	0.52	VT SF 5/21 MC NE WS VO	1689470001	R.8
SAIM12-KBC18/20	2664860000	N.37	SM 27/18 K MC NE WS	17099860000	M.32	TM1 12 MC NE GE	1718411687	0.53	VT SF 5/21 MC NE WS VO	1689470001	R.9
SAIM12-KBC20/22	2664870000	N.37	SM-H 27/18 SW	1716630000	M.30	TM1 12 MC NE GE	1718411687	0.54	VT SF 5/21 MC NE WS VO	1689470001	R.10
SAIM12-KBC22/24	2673730000	N.37	SM-H 27/18 SW	1716630000	M.31	TM1 12 MC NE GE	1718411687	0.55	VT SF 5/21 MC NE WS VO	1689470001	R.11
SAIM12-KBC26/28	2673740000	N.37	SM-H 27/18 SW	1716630000	M.32	TM1 12 MC NE GE	1718411687	0.56	VT SF 5/21 MC NE WS VO	1689470001	R.12
SAIM12-KBC18/20	2664840000	N.37	SUPER CUT	9205150000	S.9	TM1 18 MC NE GE	1718431687	0.6	VT SF 5/21 MC NE WS VO	1689470001	R.13
SAIM12-KBC20/22	2664850000	N.37	SZE ESD 130	9205140000	S.9	TM1 18 MC NE GE	1718431687	0.7	VT SF 5/21 MC NE WS VO	1730560001	S.27
SAIM12-KBC22/24	2673710000	N.37	SZE ESD 130	9204770000	S.9	TM1 18 MC NE GE	1718431687	0.8	VT SF 6/21 MC NE WS VO	1730560001	0.6
SAIM12-KBC26/28	2673720000	N.37	TM 4/12 HF/HB	1719840000	0.6	TM1 18 MC NE GE	1718431687	0.9	VT SF 6/21 MC NE WS VO	1730560001	0.7
SAI-SKM12 BU	8425960000	S.24	TM 4/12 HF/HB	1719840000	0.7	TM1 18 MC NE GE	1718431687	0.10	VT SF 6/21 MC NE WS VO	1730560001	0.8
SAI-SKM12 UNI 2029	2330260000	S.24	TM 4/12 HF/HB	1719840000	0.8	TM1 18 MC NE GE	1718431687	0.11	VT SF 6/21 MC NE WS VO	1730560001	0.9
T			TM 4/12 HF/HB	1719840000	0.9	TM1 18 MC NE GE	1718431687	0.12	VT SF 6/21 MC NE WS VO	1730560001	0.10
SAIBCD-18/28/4/9CG	2672420000	N.35	TM 4/12 HF/HB	1719840000	0.1	TM1 18 MC NE GE	1718431687	0.13	VT SF 6/21 MC NE WS VO	1730560001	0.11
SAIBCD-WDF-D-18/28/4/9CG	2664780000	N.35	TM 4/12 HF/HB	1719840000	0.2	TM1 18 MC NE GE	1718431687	0.14	VT SF 6/21 MC NE WS VO	1730560001	0.12
SAIBM4/8S-M12 4P D-ZF	1892130001	N.32	TM 4/12 HF/HB	1719840000	0.3	TM1 18 MC NE GE	1718431687	0.15	VT SF 6/21 MC NE WS VO	1730560001	0.13
SAIBM4/8S-M12 4P C-BOD	1892130000	N.33	TM 4/12 HF/HB	1719840000	0.4	TM1 18 MC NE GE	1718431687	0.16	VT SF 6/21 MC NE WS VO	1730560001	0.14
SAIBP-M4D4/8-M12	2681700000	N.34	TM 4/12 HF/HB	1719840000	0.5	TM1 18 MC NE GE	1718431687	0.17	VT SF 6/21 MC NE WS VO	1730560001	0.15
SAIBW4/8S-M12 4P D-ZF	1139330000	N.32	TM 4/12 HF/HB	1719840000	0.6	TM1 18 MC NE GE	1718431687	0.18	VT SF 6/21 MC NE WS VO	1730560001	0.16
SAIBWC-D-18/28/4/9CG	2702700000	N.36	TM 4/12 HF/HB	1719840000	0.7	TM1 18 MC NE GE	1718431687	0.19	VT SF 6/21 MC NE WS VO	1730560001	0.17
SAIBWP-M4D4/8-M12	2681710000	N.34	TM 4/12 HF/HB	1719840000	0.8	TM1 18 MC NE GE	1718431687	0.20	VT SF 6/21 MC NE WS VO	1730560001	0.27
SAISCD-18/28/4/9CG	2664810000	N.35	TM 4/12 HF/HB	1719840000	0.9	TM1 18 MC NE GE	1718431687	0.21	VT SF 6/21 MC NE WS VO	1730560001	R.4
SAISCD-WDF-D-18/28/4/9CG	2664790000	N.35	TM 4/12 HF/HB	1719840000	0.1	TM1 18 MC NE GE	1718431687	0.22	VT SF 6/21 MC NE WS VO	1730560001	R.5
SAISM4/8S-M12 4P Z-F	1892120001	N.32	TM 4/12 HF/HB	1719840000	0.2	TM1 18 MC NE GE	1718431687	0.23	VT SF 6/21 MC NE WS VO	1730560001	R.6
SAISM4/8S-M12 4P D-COD	1892120000	N.33	TM 4/12 HF/HB	1719840000	0.3	TM1 18 MC NE GE	1718431687	0.24	VT SF 6/21 MC NE WS VO	1730560001	R.7
SAISP-M4D4/8-M12	2681680000	N.34	TM 4/12 HF/HB	1719840000	0.4	TM1 18 MC NE GE	1718431687	0.25	VT SF 6/21 MC NE WS VO	1730560001	R.8
SAISW4/8S-M12 4P D-ZF	1803930001	N.32	TM 4/12 HF/HB	1719840000	0.5	TM1 18 MC NE GE	1718431687	0.26	VT SF 6/21 MC NE WS VO	1730560001	R.9
SAISWC-D-18/28/4/9CG	2702690000	N.36	TM 4/12 HF/HB	1719840000	0.6	TM1 18 MC NE GE	1718431687	0.27	VT SF 6/21 MC NE WS VO	1730560001	R.10
SAISWP-M4D4/8-M12	2681690000	N.34	TM 4/12 HF/HB	1719840000	0.7	TM1 18 MC NE GE	1718431687	0.28	VT SF 6/21 MC NE WS VO	1730560001	R.11
SCISSORS KEVLAR	1208910000	N.10	TM 4/12 HF/HB	1719840000	0.8	TM1 18 MC NE GE	1718431687	0.29	VT SF 6/21 MC NE WS VO	1730560001	R.12
SCISSORS KEVLAR	1208910000	S.10	TM 4/12 HF/HB	1719840000	0.9	TM1 18 MC NE GE	1718431687	0.30	VT SF 6/21 MC NE WS VO	1730560001	R.13
SCREWTY SET	1910000000	N.42	TM 4/12 HF/HB	1719840000	0.1	TM1 18 MC NE GE	1718431687	0.31	VT SF 6/21 MC NE WS VO	1730560001	R.14
SCREWTY SET	1910000000	0.34	TM 4/12 HF/HB	1719840000	0.2	TM1 18 MC NE GE	1718431687	0.32	WT		
SCREWTY SET	1910000000	0.35	TM 4/12 HF/HB	1719840000	0.3	TM1 18 MC NE GE	1718431687	0.33	WFSKHV/1,5-2,5	1491970000	M.26
SCREWTY SET	1910000000	0.36	TM 4/12 HF/HB	1719840000	0.4	TM1 18 MC NE GE	1718431687	0.34			
SCREWTY SET	1910000000	0.37	TM 4/12 HF/HB	1719840000	0.5	TM1 18 MC NE GE	1718431687	0.35			
SCREWTY SET	1910000000	0.38	TM 4/12 HF/HB	1719840000	0.6	TM1 18 MC NE GE	1718431687	0.36			
SCREWTY SET	1910000000	0.39	TM 4/12 HF/HB	1719840000	0.7	TM1 18 MC NE GE	1718431687	0.37			
SCREWTY SET	1910000000	0.40	TM 4/12 HF/HB	1719840000	0.8	TM1 18 MC NE GE	1718431687	0.38			
SCREWTY SET	1910000000	0.41	TM 4/12 HF/HB	1719840000	0.9	TM1 18 MC NE GE	1718431687	0.39			
SCREWTY SET	1910000000	0.42	TM 4/12 HF/HB	1719840000	0.1	TM1 18 MC NE GE	1718431687	0.40			
SCREWTY SET	1910000000	0.43	TM 4/12 HF/HB	1719840000	0.2	TM1 18 MC NE GE	1718431687	0.41			
SCREWTY SET	1910000000	0.44	TM 4/12 HF/HB	1719840000	0.3	TM1 18 MC NE GE	1718431687	0.42			
SCREWTY SET	1910000000	0.45	TM 4/12 HF/HB	1719840000	0.4	TM1 18 MC NE GE	1718431687	0.43			
SCREWTY SET	1910000000	0.46	TM 4/12 HF/HB	1719840000	0.5	TM1 18 MC NE GE	1718431687	0.44			
SCREWTY SET	1910000000	0.47	TM 4/12 HF/HB	1719840000	0.6	TM1 18 MC NE GE	1718431687	0.45			
SCREWTY SET	1910000000	0.48	TM 4/12 HF/HB	1719840000	0.7	TM1 18 MC NE GE	1718431687	0.46			
SCREWTY SET	1910000000	0.49	TM 4/12 HF/HB	1719840000	0.8	TM1 18 MC NE GE	1718431687	0.47			
SCREWTY SET	1910000000	0.50	TM 4/12 HF/HB	1719840000	0.9	TM1 18 MC NE GE	1718431687	0.48			
SCREWTY SET	1910000000	0.51	TM 4/12 HF/HB	1719840000	0.1	TM1 18 MC NE GE	1718431687	0.49			
SCREWTY SET	1910000000	0.52	TM 4/12 HF/HB	1719840000	0.2	TM1 18 MC NE GE	1718431687	0.50			
SCREWTY SET	1910000000	0.53	TM 4/12 HF/HB	1719840000	0.3	TM1 18 MC NE GE	1718431687	0.51			
SCREWTY SET	1910000000	0.54	TM 4/12 HF/HB	1719840000	0.4	TM1 18 MC NE GE	1718431687	0.52			
SCREWTY SET	1910000000	0.55	TM 4/12 HF/HB	1719840000	0.5	TM1 18 MC NE GE	1718431687	0.53			
SCREWTY M12	1900000000	0.34	TM 4/12 HF/HB	1719840000	0.6	TM1 18 MC NE GE	1718431687	0.54			
SCREWTY M12	1900000000	0.35	TM 4/12 HF/HB	1719840000	0.7	TM1 18 MC NE GE	1718431687	0.55			
SCREWTY M12	1900000000	0.36	TM 4/12 HF/HB	1719840000	0.8	TM1 18 MC NE GE	1718431687	0.56			
SCREWTY M12	1900000000	0.37	TM 4/12 HF/HB	1719840000	0.9	TM1 18 MC NE GE	1718431687	0.57			
SCREWTY M12	1900000000	0.38	TM 4/12 HF/HB	1719840000	0.1	TM1 18 MC NE GE	1718431687	0.58			
SCREWTY M12	1900000000	0.39	TM 4/12 HF/HB	1719840000	0.2	TM1 18 MC NE GE	1718431687	0.59			
SCREWTY M12	1900000000	0.40	TM 4/12 HF/HB	1719840000	0.3	TM1 18 MC NE GE	1718431687	0.60			
SCREWTY M12	1900000000	0.41	TM 4/12 HF/HB	1719840000	0.4	TM1 18 MC NE GE	1718431687	0.61			
SCREWTY M12	1900000000	0.42	TM 4/12 HF/HB	1719840000	0.5	TM1 18 MC NE GE	1718431687	0.62			
SCREWTY M1											

Order No.	Type	Page	Order No.	Type	Page	Order No.	Type	Page	Order No.	Type	Page
1010000000											
1010840015	IE-C5D04RE0015MCSXXX-X	0.54	1058280000	IE-PP-V14P	N.2	1058280000	IE-PP-V14P	N.3	1072900000	IE-BSS-V14M-HYB-10P-FJ	J.10
1010840030	IE-C5D04RE0030MCSXXX-X	0.54	1058280000	IE-PP-V14P	N.10	1058280000	IE-PP-V14P	S.24	1072900000	IE-BSS-V14M-HYB-10P-FJ	N.8
1010840050	IE-C5D04RE0050MCSXXX-X	0.54	1058280000	IE-PP-V14P	N.4	1058310000	IE-BPV-V14P	N.5	1072910000	IE-PS-V14M-HYB-10P	J.11
1010840100	IE-C5D04RE0100MCSXXX-X	0.54	1058310000	IE-BPV-V14P	N.6	1058310000	IE-BPV-V14P	N.8	1072910000	IE-PS-V14M-HYB-10P	N.7
1010850015	IE-C5D04RE0015MCSMCS-E	0.53	1058310000	IE-BPV-V14P	N.8	1058310000	IE-BPV-V14P	N.8	1073340000	SM 27/18 K MC NE GR	M.2
1010850030	IE-C5D04RE0030MCSMCS-E	0.53	1058310000	IE-BPV-V14P	N.8	1058310000	IE-BPV-V14P	N.8	1073340000	SM 27/18 K MC NE GR	M.3
1010850050	IE-C5D04RE0050MCSMCS-E	0.53	1058310000	IE-BPV-V14P	N.8	107300000	IE-PS-V05M-A-RJ45-FH	N.25	107300000	IE-PS-V05M-A-RJ45-FH	N.25
1010850100	IE-C5D04RE0100MCSMCS-E	0.53	1058310000	IE-BPV-V14P	N.11	1058310000	IE-BPV-V14P	N.2	1085260000	IE-BSS-V14M-RJ45-FJ-P	J.10
1011540000	IE-BHS-V14M-RJA	N.4	1058310000	IE-BPV-V14P	N.4	1058310000	IE-BPV-V14P	N.5	1085260000	IE-BSS-V14M-RJ45-FJ-P	N.4
1011540000	IE-BHS-V14M-RJA	N.5	1058310000	IE-BPV-V14P	N.5	1058310000	IE-BPV-V14P	N.7	108530000	IE-BSS-V14M-RJ45-FJ-P	N.25
1011540000	IE-BHS-V14M-RJA	N.6	1058310000	IE-BPV-V14P	N.7	1058310000	IE-BPV-V14P	N.8	108530000	IE-BSS-V14M-RJ45-FJ-P	N.25
1011540000	IE-BHS-V14M-RJA	N.8	1058310000	IE-BPV-V14P	N.8	1058310000	IE-BPV-V14P	N.8	108530000	IE-BSS-V14M-RJ45-FJ-P	N.25
1011560000	IE-PH-V14M-RJ	N.2	1058310000	IE-BPV-V14P	N.8	1058310000	IE-BPV-V14P	N.8	108530000	IE-BSS-V14M-RJ45-FJ-P	N.25
1011560000	IE-PH-V14M-RJ	N.3	1058310000	IE-BPV-V14P	N.8	1059330015	IE-C5D04UG0015MSSMCS-E	0.34	108530000	IE-BSS-V14M-RJ45-FJ-P	N.25
1011560000	IE-PH-V14M-RJ	N.7	1059330015	IE-C5D04UG0015MSSMCS-E	0.34	1059330030	IE-C5D04UG0030MSSMCS-E	0.34	108530000	IE-BSS-V14M-RJ45-FJ-P	N.25
1012160000	IE-PS-V14M-RJ45-TH	N.3	1059330030	IE-C5D04UG0030MSSMCS-E	0.34	1059330050	IE-C5D04UG0050MSSMCS-E	0.34	108530000	IE-BSS-V14M-RJ45-FJ-P	N.25
1012170000	IE-PS-V14M-RJ45-FH-P	J.11	1059330050	IE-C5D04UG0050MSSMCS-E	0.34	1059330100	IE-C5D04UG0100MSSMCS-E	0.34	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1012170000	IE-PS-V14M-RJ45-FH-P	N.2	1059330100	IE-C5D04UG0100MSSMCS-E	0.34	1059340015	IE-C5D04URE0015MSMCS-E	0.53	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1012310000	IE-BSS-V14M-RJ45-C	J.10	1059340015	IE-C5D04URE0015MSMCS-E	0.53	1059340030	IE-C5D04URE0030MSMCS-E	0.53	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1012310000	IE-BSS-V14M-RJ45-C	N.5	1059340030	IE-C5D04URE0030MSMCS-E	0.53	1059340050	IE-C5D04URE0050MSMCS-E	0.53	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1012320000	IE-BSS-V14M-RJ45-FJA	N.4	1059340050	IE-C5D04URE0050MSMCS-E	0.53	1059340100	IE-C5D04URE0100MSMCS-E	0.53	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1012370000	IE-BS-V01P-RJ45-C	J.14	1059340100	IE-C5D04URE0100MSMCS-E	0.53	1059750015	IE-C5D04UG0015MCAXXX-X	0.37	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1012370000	IE-BS-V01P-RJ45-C	N.17	1059750015	IE-C5D04UG0015MCAXXX-X	0.37	1059750030	IE-C5D04UG0030MCAXXX-X	0.37	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1012380000	IE-BS-V01P-RJ45-FJA	J.14	1059750030	IE-C5D04UG0030MCAXXX-X	0.37	1059750500	IE-C5D04UG0050MCAXXX-X	0.37	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1012440000	IE-PHV01P	N.16	1059750500	IE-C5D04UG0050MCAXXX-X	0.37	1059751000	IE-C5D04UG0100MCAXXX-X	0.37	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1012460000	IE-PHV01P-BP	N.16	1059770015	IE-C5D04UG0100MCSCMA-E	0.36	1059770030	IE-C5D04UG0030MCSCMA-E	0.36	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1012470000	IE-PS-V01P-RJ45-TH	J.14	1059770030	IE-C5D04UG0030MCSCMA-E	0.36	1059770050	IE-C5D04UG0050MCSCMA-E	0.36	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1012470000	IE-PS-V01P-RJ45-TH	N.16	1059770050	IE-C5D04UG0050MCSCMA-E	0.36	1059770100	IE-C5D04UG0100MCSCMA-E	0.36	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1012490000	IE-PS-V01P-RJ45-FH	J.14	1059770100	IE-C5D04UG0100MCSCMA-E	0.36	1059890015	IE-C5D04URE0015MCAMCA-E	0.36	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1012560000	IE-PS-V01P-RJ45-TH-BP	N.16	1059890015	IE-C5D04URE0015MCAMCA-E	0.36	1059890030	IE-C5D04URE0030MCAMCA-E	0.36	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1012570000	IE-PS-V01P-RJ45-FH-BP	N.16	1059890030	IE-C5D04URE0030MCAMCA-E	0.36	1059890100	IE-C5D04URE0100MCAMCA-E	0.36	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1016960000	IE-BH-V01P	N.17	1059890100	IE-C5D04URE0100MCAMCA-E	0.36	1059900015	IE-C5D04URE0015MCAXXX-X	0.56	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1018790000	IE-FCMR-J45-C	J.10	1059900015	IE-C5D04URE0015MCAXXX-X	0.56	1059900030	IE-C5D04URE0030MCAXXX-X	0.56	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1018790000	IE-FCMR-J45-C	J.14	1059900030	IE-C5D04URE0030MCAXXX-X	0.56	105990050	IE-C5D04URE0050MCAXXX-X	0.56	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1018810000	IE-FCMR-J45-FJA	J.14	105990050	IE-C5D04URE0050MCAXXX-X	0.56	105990100	IE-C5D04URE0100MCAXXX-X	0.56	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1018810000	IE-FCMR-J45-FJA	M.30	105990100	IE-C5D04URE0100MCAXXX-X	0.56	1059940015	IE-C5D04URE0015MCSCMA-E	0.55	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1018820000	IE-FCMR-J45-FJB	J.14	1059940015	IE-C5D04URE0015MCSCMA-E	0.55	105994030	IE-C5D04URE0030MCSCMA-E	0.55	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1018820000	IE-FCMR-J45-FJB	M.30	105994030	IE-C5D04URE0030MCSCMA-E	0.55	105994050	IE-C5D04URE0050MCSCMA-E	0.55	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1018830000	IE-FCMR-J45-FJP	J.10	105994050	IE-C5D04URE0050MCSCMA-E	0.55	1059970015	IE-C5D04URE0015MCAMCA-E	0.55	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1018840000	IE-FCMU-USA	M.32	1059970015	IE-C5D04URE0015MCAMCA-E	0.55	1059970030	IE-C5D04URE0030MCAMCA-E	0.55	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1019570000	IE-BH-USB-A	M.5	1059970030	IE-C5D04URE0030MCAMCA-E	0.55	1059970050	IE-C5D04URE0050MCAMCA-E	0.55	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1019570000	IE-BH-USB-A	M.6	1059970050	IE-C5D04URE0050MCAMCA-E	0.55	1059970100	IE-C5D04URE0100MCAMCA-E	0.55	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1019570000	IE-BH-USB-A	M.8	1059970100	IE-C5D04URE0100MCAMCA-E	0.55	1059980000	IE-C5D04URE0050MCAXXX-X	0.56	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1019570000	IE-BH-USB-A	M.9	1059980000	IE-C5D04URE0050MCAXXX-X	0.56	1059980050	IE-C5D04URE0015MCAMCA-E	0.55	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1019570000	IE-BH-USB-A	M.10	1059980050	IE-C5D04URE0015MCAMCA-E	0.55	1059990000	IE-C5D04URE0030MCAMCA-E	0.55	108530000	IE-BSS-V14M-RJ45-FH-P	N.25
1019570000	IE-BH-USB-A	M.11	1059990000	IE-C5D04URE0030MCAMCA-E	0.55	1061820000	IE-CC-V01P	J.15	1059990000	IE-C5D04URE0050MCAMCA-E	0.55
1019570000	IE-BH-USB-A	M.12	1061820000	IE-CC-V01P	N.18	1061830000	IE-OP-V01P-1S	J.15	1059990000	IE-C5D04URE0050MCAMCA-E	0.55
1019570000	IE-BH-USB-A	M.14	1061830000	IE-OP-V01P-1S	J.15	1061830000	IE-OP-V01P-1S	J.12	1062550000	IE-FM52V00005MLDLD0X	R.9
1019570000	IE-BH-USB-A	M.55	1061830000	IE-OP-V01P-1S	J.12	1062570000	IE-FM52ZV00002MLDLD0X	R.9	1062570000	IE-FM52ZV00002MLDLD0X	R.9
1020000000											
1025940010	IE-C5D04UG0010MCSXXX-X	0.35	1062580000	IE-OP-V01P-1S	J.15	1062580000	IE-OP-V01P-1S	J.15	1062580000	IE-OP-V01P-1S	J.15
1025940010	IE-C5D04UG0015MCSXXX-X	0.35	1062580000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	J.15	1062600000	IE-OP-V01P-1S	N.18
1025940030	IE-C5D04UG0030MCSXXX-X	0.35	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18
1025940050	IE-C5D04UG0050MCSXXX-X	0.35	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18
1025940100	IE-C5D04UG00100MCSXXX-X	0.35	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18
1025950005	IE-C5D04UG00050MCSMCS-E	0.34	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18
1025950015	IE-C5D04UG0015MCSMCS-E	0.34	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18
1025950030	IE-C5D04UG0030MCSMCS-E	0.34	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18
1025950050	IE-C5D04UG0050MCSMCS-E	0.34	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18
1025950100	IE-C5D04UG0100MCSMCS-E	0.34	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18	1062600000	IE-OP-V01P-1S	N.18
1040000000											
1044470010	IE-C5D04UG0010MCSCA20-E	0.35	1062600000	IE-OP-V01P-1S	N.18	1067410000	IE-PS-SCRJ-POF	N.10	1067410000	IE-PS-SCRJ-POF	N.10
1044470015	IE-C5D04UG0015MCSCA20-E	0.35	1067410000	IE-PS-SCRJ-POF	N.10	1067410000	IE-PS-SCRJ-POF	N.10	1067410000	IE-PS-SCRJ-POF	N.10
1044470030	IE-C5D04UG0030MCSCA20-E	0.35	1067410000	IE-PS-SCRJ-POF	N.10	1068820000	IE-CV14MRJ/VAPM24V-CMA	J.11	1068820000	IE-CV14MRJ/VAPM24V-CMA	J.11
1044470050	IE-C5D04UG0050MCSCA20-E	0.35	1068820000	IE-CV14MRJ/VAPM24V-CMA	J.11	1068830000	IE-CV14MRJ/VAPM24V-FJ	J.11	1068830000	IE-CV14MRJ/VAPM24V-FJ	J.11

Order No.	Type	Page	Order No.	Type	Page	Order No.	Type	Page	Order No.	Type	Page
1208930000	TOOL SET IE-POF	N.56	1241440000	RM-KIT	H.5	1286560000	IE-SW-BL08T-8TX	B.6	1350120030	IE-CSPS5VS0030VAPVAP-X	Q.32
1208930000	TOOL SET IE-POF	R.4	1241440000	RM-KIT	H.7	1286570000	IE-SW-BL08T-6TX-2ST	B.6	1350120050	IE-CSPS5VS0050VAPVAP-X	Q.32
1208930000	TOOL SET IE-POF	S.10	1241440000	RM-KIT	L.10	1286590000	IE-SW-BL16T-16TX	B.7	1350120100	IE-CSPS5VS0110VAPVAP-X	Q.32
12100000000			1241450000	IE-SFP-1FEMLC-T	L.7	1286700000	IE-SFP-1GSXLCT	L.7	1350120150	IE-CSPS5VS0150VAPVAP-X	Q.32
1212770000	AIE MULTI-STRIPAX POF	S.10	1241470000	IE-SFP-1FESLC-T	L.7	1286710000	IE-SFP-1GLSLC-T	L.7	1350120200	IE-CSPS5VS0200VAPVAP-X	Q.32
12200000000			1241500000	IE-SFP-1GLSLC	L.7	1286730000	IE-SFP-1GLHXLCT	L.7	13700000000		
1220310040	IE-C5D4BWE0040MCSA20-E	0.57	1241510000	IE-SFP-1GLXLCT	L.7	1286820000	IE-SW-PL16MT-16TX	C.8	1376510005	IE-C5D4U4G0050VAPD2D-E	Q.28
1220930000	IE-FMG62UE005MLD0LDOX	R.11	1241520000	IE-SFP-1GLXLCL	L.7	1286860000	IE-SW-VL08T-8GT	B.13	1376510010	IE-C5D4U4G0010A2DA2D-E	Q.28
1221010000	IE-BS-V01M-SCRJ-MM	J.14	1242080000	IE-CS-2TX-1RS232/485	F.5	1286870000	IE-SW-VL08T-6GT-2GS	B.13	1376510020	IE-C5D4U4G0020A2DA2D-E	Q.28
1221010000	IE-BS-V01M-SCRJ-MM	N.14	1242090000	IE-CS-2TX-2RS232/485	F.5	1286880000	IE-MC-VLT-1TX-1SC	F.4	1376510030	IE-C5D4U4G0030A2DA2D-E	Q.28
1221020000	IE-BS-V01M-SCRJ-MM	J.14	1244130005	IE-C5D4AU0010MBSMCS-E	0.38	1286890000	IE-MC-VLT-1TX-1ST	F.4	1376510050	IE-C5D4U4G0050VAPD2D-E	Q.28
1221020000	IE-BS-V01M-SCRJ-MM	N.14	1244130010	IE-C5D4AU0015MBSMCS-E	0.38	1286920000	IE-MC-VLT-1TX-1SCS	F.4	1376510100	IE-C5D4U4G0100A2DA2D-E	Q.28
1221030000	IE-BHD-V01M-SCA	N.14	1244130020	IE-C5D4AU0012MBSMCS-E	0.38	1286930000	IE-SW-BL06T-2TX-4POE	B.10	1376510150	IE-C5D4U4G0150A2DA2D-E	Q.28
1222560000	IE-FCM-USB-AB	M.32	1244130050	IE-C5D4AU0015MBSMCS-E	0.38	1286970000	IE-SW-PL10MT-3GT-TX	C.10	1376510200	IE-C5D4U4G0200A2DA2D-E	Q.28
12300000000			1248280002	IE-C5FP8LD0001M40V40D	0.23	1287010000	IE-SW-PL18MT-2GC14T2SCS	C.11			
1233160005	IE-CFP8LD0005M40W40D	0.23	1248280012	IE-C5FP8LD00012M40V40D	0.23	1287910000	IE-C7FSBLR-305M	0.5			
1233160010	IE-CFP8LD0010M40W40D	0.23	1248280015	IE-C5FP8LD0015M40W40D	0.23	1287910000	IE-C7FSBLR-305M	0.11			
1233160012	IE-CFP8LD0012M40W40D	0.23	1248280020	IE-CFP8LD0020M40W40D	0.23						
1233160015	IE-CFP8LD0015M40W40D	0.23									
1233160020	IE-CFP8LD0020M40W40D	0.23									
1233160030	IE-CFP8LD0030M40W40D	0.23									
1233160050	IE-CFP8LD0050M40W40D	0.23									
1233160100	IE-CFP8LD0100M40W40D	0.23									
1234750005	IE-C5D4U0005MBSA20-E	0.38									
1234750010	IE-C5D4U0010MBSA20-E	0.38									
1234750015	IE-C5D4U0015MBSA20-E	0.38									
1234750020	IE-C5D4U0020MBSA20-E	0.38									
1234750020	IE-C5D4U0020MBSA20-E	0.38									
1234750030	IE-C5D4U0030M40W40D	0.38									
1234750050	IE-C5D4U0050MBSA20-E	0.38									
1234770005	IE-C5D4U0005MBSXXX-E	0.39									
1234770010	IE-C5D4U0010MBSXXX-E	0.39									
1234770015	IE-C5D4U0015MBSXXX-E	0.39									
1234770020	IE-C5D4U0020MBSXXX-E	0.39									
1234770050	IE-C5D4U0050MBSXXX-E	0.39									
12400000000											
1240840000	IE-SW-BL05-5TX	B.6									
1240850000	IE-SW-BL05-5TX	B.6									
1240870000	IE-SW-BL05-4TX-1SC	B.6									
1240880000	IE-SW-BL05-4TX-1ST	B.6									
1240890000	IE-SW-BL05-4TX-1SC	B.6									
1240900000	IE-SW-BL08-8TX	B.6									
1240910000	IE-SW-BL08-6TX-2SC	B.6									
1240920000	IE-SW-BL08T-6TX-2SC	B.6									
1240930000	IE-SW-BL08-6TX-2ST	B.6									
1240940000	IE-SW-VL08-6GT-2GS	B.13									
1240990000	IE-SW-VL08M-3GT-7TX	C.10									
1241320000	IE-SW-VL18M-2GC16TX	C.11									
1241350000	IE-SW-VL18M-2GC14T2SCS	C.11									
1241380000	IE-SW-BL06-2TX-4POE	B.10									
1241400000	IE-MC-VL17X-1SC	F.4									
1241410000	IE-MC-VL17X-1ST	F.4									
1241420000	IE-MC-VLT-1X-1SC	F.4									
1241430000	EBR-MODULE RS232	C.6									
1241430000	EVR-MODULE RS232	C.7									
1241430000	EVR-MODULE RS232	C.10									
1241430000	EVR-MODULE RS232	H.5									
1241430000	EVR-MODULE RS232	H.7									
1241430000	EVR-MODULE RS232	I.8									
1241440000	RM-KIT	B.4									
1241440000	RM-KIT	B.5									
1241440000	RM-KIT	B.6									
1241440000	RM-KIT	B.7									
1241440000	RM-KIT	B.9									
1241440000	RM-KIT	B.10									
1241440000	RM-KIT	B.11									
1241440000	RM-KIT	B.12									
1241440000	RM-KIT	B.13									
1241440000	RM-KIT	B.14									
1241440000	RM-KIT	B.15									
1241440000	RM-KIT	B.16									
1241440000	RM-KIT	C.4									
1241440000	RM-KIT	C.5									
1241440000	RM-KIT	C.6									
1241440000	RM-KIT	C.7									
1241440000	RM-KIT	C.9									
1241440000	RM-KIT	C.10									
1241440000	RM-KIT	C.12									
1241440000	RM-KIT	C.13									
1241440000	RM-KIT	C.14									
1241440000	RM-KIT	C.15									
1241440000	RM-KIT	D.5									
1241440000	RM-KIT	D.6									
1241440000	RM-KIT	F.4									
1241440000	RM-KIT	F.5									
1241440000	RM-KIT	F.6									
1241440000	RM-KIT	G.4									
1241440000	IE-PS-V04P-RJ45-FH-B	N.19									
1271250000	IE-PS-V05M-RJ45-FH-B	N.25									
1273900000	IE-C7FSBLD-305M	0.5									
1273980000	IE-C7FSBLD-305M	0.10									
1273430010	IE-POZ2EE0001MS-JOSJ0-X	J.10									
1273430010	IE-POZ2EE0001MS-JOSJ0-X	J.14									
1273430010	IE-POZ2EE0001MS-JOSJ0-X	R.10									
1273430030	IE-POZ2EE0003MS-JOSJ0-X	J.10									
1273430030	IE-POZ2EE0003MS-JOSJ0-X	J.14									
1273430030	IE-POZ2EE0003MS-JOSJ0-X	R.10									
1273430050	IE-POZ2EE0005MS-JOSJ0-X	J.10									
1273430050	IE-POZ2EE0005MS-JOSJ0-X	J.14									
1273430050	IE-POZ2EE0005MS-JOSJ0-X	R.10									
1273430050	IE-POZ2EE0005MS-JOSJ0-X	R.14									
1273430050	IE-POZ2EE0005MS-JOSJ0-X	R.19									
1278420000	IE-SCRJ-IP20-P0F-100	L.10									
1278430000	IE-SCRJ-IP67-P0F-100	N.10									
1278430000	IE-SCRJ-IP67-P0F-100	N.56									
1273430100	IE-POZ2EE0001MS-JOSJ0-X	R.10									
1273430100	IE-POZ2EE0001MS-JOSJ0-X	R.14									
1273430100	IE-POZ2EE0001MS-JOSJ0-X	R.19									
1273430100	IE-POZ2EE0001MS-JOSJ0-X	R.25									
1278420000	IE-SCRJ-IP20-P0F-100	L.10									
1278430000	IE-SCRJ-IP67-P0F-100	N.10									
1278430000	IE-SCRJ-IP67-P0F-100	N.56									
1285830000	IE-CST-2TX-1RS232/485	F.5									
1285840000	IE-CST-2TX-2RS232/485	F.5									
1286530000	IE-SW-BL05T-4TX-1SCS	B.6									
1286540000	IE-SW-BL05T-4TX-1ST	B.6									
1286540000	IE-SW-BL05T-4TX-1SC	B.6									
1286550000	IE-SW-BL05T-4TX-1SC	B.6									

Order No.	Type	Page	Order No.	Type	Page	Order No.	Type	Page	Order No.	Type	Page
1433990100	IE-FM5Z2L00010MST0ST0-X	R.5	1457580050	IE-C6EL8UG0050U40XCS-E	0.42	1689470001	VT SF 5/21 MC NE WS VO	0.6	1718431044	TM+18 MC NE WS	S.27
1438180000	IE-TO-USB-AB	L.16	1457580100	IE-C6EL8UG0100U40XCS-E	0.42	1689470001	VT SF 5/21 MC NE WS VO	0.7	1718431687	TM+18 MC NE GE	0.6
14400000000											
1444650000	IE-PCBR2-M12X-S-180	N.47	1457580120	IE-C6EL8UG0120U40XCS-E	0.42	1689470001	VT SF 5/21 MC NE WS VO	0.8	1718431687	TM+18 MC NE GE	0.7
1449420050	IE-FSM02UE0005MSD0SDEX	R.14	1487920000	IE-BI-USB-3.0-A	M.5	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.9
1449420200	IE-FSM02UE0020MSD0SDEX	R.14	1487920000	IE-BI-USB-3.0-A	M.6	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.10
1449420250	IE-FSM02UE0025MSD0SDEX	R.14	1487920000	IE-BI-USB-3.0-A	M.8	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.11
1449420400	IE-FSM02UE0040MSD0SDEX	R.14	1487920000	IE-BI-USB-3.0-A	M.9	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.12
1449470005	IE-C6KS8VG0005XCSCXXX-E	0.40	1487920000	IE-BI-USB-3.0-A	M.10	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.13
1449470015	IE-C6KS8VG0015XCSCXXX-E	0.40	1487920000	IE-BI-USB-3.0-A	M.11	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.14
1449470030	IE-C6KS8VG0030XCSCXXX-E	0.40	1487920000	IE-BI-USB-3.0-A	M.12	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.15
1449470050	IE-C6KS8VG0050XCSCXXX-E	0.40	1487920000	IE-BI-USB-3.0-A	M.14	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.16
1449470100	IE-C6KS8VG0100XCSCXXX-E	0.40	1487920000	IE-BI-USB-3.0-A	M.55	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.17
14500000000											
1450510000	IE-FC-SFP-KNOB	M.3	1487980000	IE-US-B-A-MICRO-1.8M	0.59	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.18
1450520000	IE-FC-SFP-KEY2	M.3	1489940000	IE-SR-2GT-LAN-FN	D.5	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.19
1450530000	IE-FC-SFM-KNOB	M.3	1491920000	VFSKHV/1.5-2.5/485	M.22	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.20
1450540000	IE-FC-SFM-KEY2	M.3	1491940000	VFSKHV/1.5-2.5/638	M.26	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.21
1450550000	IE-FC-SP-PWB/2ST	M.8	1491970000	WFSKHV/1.5-2.5	M.26	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.22
1450570000	IE-FC-SP-PWS/4ST	M.10	1499940000	IE-CC-8W-FA-IP67	S.3	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.23
1450580000	IE-FC-SP-1ST/1D9/1D25	M.12	1504280000	IE-SW-VL05M-5TX	C.6	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.24
1450590000	IE-FC-SP-2ST/2D9	M.12	1504310000	IE-SW-VL05MT-5TX	C.6	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.25
1450600000	IE-FC-SP-PWS/2ST/1D9	M.9	1504320000	IE-SW-BL05-1GT-4GTP0E	B.15	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.26
1450610000	IE-FC-SP-PWS/2D9	M.10	1504340000	IE-SW-BL05T-1GT-4GTP0E	B.15	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.27
1450620000	IE-FC-SP-PWU/2ST	M.11	1504410000	IE-SW-IP67-5M12	B.8	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.28
1450630000	IE-FC-SP-PWB/2ST	M.8	1504420000	IE-SW-IP67-5M12	B.8	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.29
1450640000	IE-FC-SP-PWS/4ST	M.10	1504440000	IE-WALLMOUNT-KIT-46MM	F.4	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.30
1450650000	IE-FC-IP-1ST/1D9/1D25	M.12	1504450000	IE-WALLMOUNT-KIT-30MM	B.6	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.31
1450670000	IE-FC-IP-2ST/2D9	M.12	1504460000	IE-WALLMOUNT-KIT-30MM	B.13	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.32
1450680000	IE-FC-IP-PWS/2D9	M.10	1504470000	IE-WALLMOUNT-KIT-30MM	B.15	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.33
1450690000	IE-FC-IP-PWS/2ST/1D9	M.9	1504480000	IE-WALLMOUNT-KIT-30MM	I.10	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.34
1450700000	IE-FC-IP-PWU/2ST	M.11	1504490000	IE-WALLMOUNT-KIT-30MM	I.10	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.35
1450710000	IE-FC-IP-BP	M.7	1504500000	IE-WALLMOUNT-KIT-30MM	I.10	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.36
1450730000	IE-FCI-PWB-DE	L.19	1504510000	IE-FCI-PWB-DE	M.17	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.37
1450730000	IE-FCI-PWB-DE	M.17	1504520000	IE-FCI-PWB-FR	M.19	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.38
1450740000	IE-FCI-PWB-FR	M.18	1504530000	IE-FCI-PWB-FR	M.19	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.39
1450750000	IE-FCI-PWB-FR	M.19	1504540000	IE-FCI-PWB-FR	M.20	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.40
1450770000	IE-FCI-PWB-GB	L.19	1504550000	IE-FCI-PWB-GB	M.17	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.41
1450770000	IE-FCI-PWB-GB	M.17	1504560000	IE-FCI-PWB-GB	M.20	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.42
1450780000	IE-FCI-PWB-GB	M.19	1504570000	IE-FCI-PWB-GB	M.19	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.43
1450780000	IE-FCI-PWB-GB	M.19	1504580000	IE-FCI-PWB-GB	M.19	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.44
1450790000	IE-FCI-PWB-CN	M.17	1504590000	IE-FCI-PWB-CN	M.22	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.45
1450790000	IE-FCI-PWB-CN	M.22	1504600000	IE-FCI-PWB-US	M.11	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.46
1450800000	IE-FCI-PWB-US	M.11	1504610000	IE-FCI-PWB-US	M.17	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.47
1450800000	IE-FCI-PWB-US	M.17	1504620000	IE-FCI-PWB-US	M.20	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.48
1450800000	IE-FCI-PWB-US	M.22	1504630000	IE-FCI-PWB-US	M.19	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.49
1450810000	IE-FCI-PWS-IT	L.19	1504640000	IE-FCI-PWS-IT	M.17	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.50
1450810000	IE-FCI-PWS-IT	M.10	1504650000	IE-FCI-PWS-IT	M.17	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.51
1450810000	IE-FCI-PWS-IT	M.17	1504660000	IE-FCI-PWS-IT	M.20	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.52
1450810000	IE-FCI-PWPC	M.20	1504670000	IE-FCI-PWPC	M.20	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.53
1450820000	IE-FCI-PWPC	M.3	1504680000	IE-FCI-PWPC	M.4	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.54
1450820000	IE-FCI-PWPC	M.4	1504690000	IE-FCI-PWPC	M.5	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.55
1450820000	IE-FCI-PWPC	M.5	1504700000	IE-FCI-PWPC	M.8	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.56
1450820000	IE-FCI-PWPC	M.8	1504710000	IE-FCI-PWPC	M.9	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.57
1450820000	IE-FCI-PWPC	M.9	1504720000	IE-FCI-PWPC	M.10	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.58
1450820000	IE-FCI-PWPC	M.10	1504730000	IE-FCI-PWPC	M.10	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.59
1450820000	IE-FCI-PWPC	M.11	1504740000	IE-FCI-PWPC	M.12	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.60
1450830000	IE-FCI-PWB-AU	L.19	1504750000	IE-FCI-PWB-AU	M.27	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.61
1450830000	IE-FCI-PWB-AU	M.17	1504760000	IE-FCI-PWB-AU	M.21	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.62
1450840000	IE-FCI-D9-F9	M.6	1504770000	IE-FCI-D9-F9	M.6	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.63
1450840000	IE-FCI-D9-F9	M.10	1504780000	IE-FCI-D9-F9	M.12	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.64
1450840000	IE-FCI-D9-F9	M.12	1504790000	IE-FCI-D9-F9	M.12	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.65
1450840000	IE-FCI-D9-F9	M.15	1504800000	IE-FCI-D9-F9	M.15	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.66
1450850000	IE-FCI-D9-FM	M.6	1504810000	IE-FCI-D9-FM	M.8	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.67
1450850000	IE-FCI-D9-FM	M.8	1504820000	IE-FCI-D9-FM	M.11	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.68
1450850000	IE-FCI-D9-FM	M.9	1504830000	IE-FCI-D9-FM	M.10	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.69
1450850000	IE-FCI-D9-FM	M.10	1504840000	IE-FCI-D9-FM	M.12	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.70
1450850000	IE-FCI-D9-FM	M.12	1504850000	IE-FCI-D9-FM	M.15	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.71
1450850000	IE-FCI-D9-FS	M.6	1504860000	IE-FCI-D9-FS	M.6	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.72
1450860000	IE-FCI-D9-FS	M.8	1504870000	IE-FCI-D9-FS	M.8	1689470001	VT SF 5/21 MC NE WS VO	0.9	1718431687	TM+18 MC NE GE	0.73
1450860000	IE-FCI-D9-FS	M.9	1504880000	IE-FCI-D9-FS</td							

Order No.	Type	Page	Order No.	Type	Page	Order No.	Type	Page	Order No.	Type	Page
1730560001	VT SF 6/21 MC NE WS VO	0.7	1900001000	SCREWTY-M12-DM	0.46	1963140000	IE-PS-V01M-RJ45-TH	J.14	1968920000	IE-PP-V05M	N.25
1730560001	VT SF 6/21 MC NE WS VO	0.8	1900001000	SCREWTY-M12-DM	0.47	1963140000	IE-PS-V01M-RJ45-TH	N.12	1968920000	IE-PP-V05M	S.24
1730560001	VT SF 6/21 MC NE WS VO	0.9	1900001000	SCREWTY-M12-DM	0.48	1963150000	IE-PS-V01M-RJ45-TH-BP	N.12	1968930000	IE-BP-V05M	N.26
1730560001	VT SF 6/21 MC NE WS VO	0.10	1900001000	SCREWTY-M12-DM	0.49	1963160000	IE-PS-V04P-RJ45-FH	N.19	1968930000	IE-BP-V05M	S.24
1730560001	VT SF 6/21 MC NE WS VO	0.11	1900001000	SCREWTY-M12-DM	0.50	1963170000	IE-PS-V04P-RJ45-FH-BP	N.19			
1730560001	VT SF 6/21 MC NE WS VO	0.12	1900001000	SCREWTY-M12-DM	0.51	1963180000	IE-PS-V04P-RJ45-TH	N.19			
1730560001	VT SF 6/21 MC NE WS VO	0.13	1900001000	SCREWTY-M12-DM	0.52	1963190000	IE-PS-V04P-RJ45-TH-BP	N.19			
1730560001	VT SF 6/21 MC NE WS VO	0.14	1900020000	SCREWTY-M12 F	N.42	1963200000	IE-PS-V05M-RJ45-FH	N.25			
1730560001	VT SF 6/21 MC NE WS VO	0.15	1900021000	SCREWTY-M12 F-DM	N.42	1963280000	IE-PS-V01M-ZSC-POF	J.14			
1730560001	VT SF 6/21 MC NE WS VO	0.16	1905490000	M-PRINT PRO	S.26	1963420000	IE-BS-V04P-SCRJ2SC-SMC	N.23			
1730560001	VT SF 6/21 MC NE WS VO	0.17				1963430000	IE-BS-V01M-LCD-SMC	N.15			
1730560001	VT SF 6/21 MC NE WS VO	0.27				1963450000	IE-BS-V04P-LCD-SMC	N.24			
1730560001	VT SF 6/21 MC NE WS VO	R.4				1963460000	IE-BS-V05M-RJ45-FJ-A	N.26			
1730560001	VT SF 6/21 MC NE WS VO	R.5	1910000000	SCREWTY SET	N.42	1963470000	IE-BS-V01M-RJ45C	J.14			
1730560001	VT SF 6/21 MC NE WS VO	R.6	1910000000	SCREWTY SET	0.34	1963470000	IE-BS-V01M-RJ45C	N.13			
1730560001	VT SF 6/21 MC NE WS VO	R.7	1910000000	SCREWTY SET	0.35	1963480000	IE-BS-V01M-RJ45-FJ-A	J.14			
1730560001	VT SF 6/21 MC NE WS VO	R.8	1910000000	SCREWTY SET	0.38	1963480000	IE-BS-V01M-RJ45-FJ-A	N.13			
1730560001	VT SF 6/21 MC NE WS VO	R.9	1910000000	SCREWTY SET	0.39	1963490000	IE-BS-V04P-RJ45-C	N.20			
1730560001	VT SF 6/21 MC NE WS VO	R.10	1910000000	SCREWTY SET	0.44	1963500000	IE-BS-V04P-RJ45-FJ-A	N.20			
1730560001	VT SF 6/21 MC NE WS VO	R.11	1910000000	SCREWTY SET	0.45	1963510000	IE-BS-V05M-RJ45C	N.26			
1730560001	VT SF 6/21 MC NE WS VO	R.12	1910000000	SCREWTY SET	0.46	1963520000	IE-BH-V04P	N.20			
1730560001	VT SF 6/21 MC NE WS VO	R.13	1910000000	SCREWTY SET	0.47	1963520000	IE-BH-V04P	N.22			
1730560001	VT SF 6/21 MC NE WS VO	R.14	1910000000	SCREWTY SET	0.48	1963520000	IE-BH-V04P	N.23			
1730560001	VT SF 6/21 MC NE WS VO	S.27	1910000000	SCREWTY SET	0.49	1963520000	IE-BH-V04P	N.24			
1736181044	ESG 7/20 SIRIUS MC NE WS	M.2	1910000000	SCREWTY SET	0.50	1963530000	IE-BH-V05M	N.26	1992800000	IE-PIRJ45-FH-A-1.6	L.5
1736181044	ESG 7/20 SIRIUS MC NE WS	M.3	1910000000	SCREWTY SET	0.51	1963540000	IE-BH-V01M	N.13	1992800000	IE-PIRJ45-FH-A-1.6	L.5
1736181044	ESG 7/20 SIRIUS MC NE WS	M.4	1910000000	SCREWTY SET	0.52	1963540000	IE-BH-V01M	N.15	1992800000	IE-PIRJ45-FH-9.0-B-1.6	L.6
1736181044	ESG 7/20 SIRIUS MC NE WS	M.5				1963580000	IE-PJ-RJ45-TH	L.8	1992900000	IE-PIRJ45-FH-B-1.6	L.5
1736181044	ESG 7/20 SIRIUS MC NE WS	M.6				1963580000	IE-PJ-RJ45-TH	N.27	1992900000	IE-PIRJ45-FH-B-1.6	L.6
1736181044	ESG 7/20 SIRIUS MC NE WS	M.8				1963590000	IE-PS-RJ45-TH-BK	J.14	1992910000	IE-PIRJ45-FP1-1.6	L.7
1736181044	ESG 7/20 SIRIUS MC NE WS	M.9				1963590000	IE-PS-RJ45-TH-BK	L.8	1992920000	IE-PIRJ45-FHA-1.1	L.5
1736181044	ESG 7/20 SIRIUS MC NE WS	M.10				1963600000	IE-PS-RJ45-FH-BK	L.4	1992920000	IE-PIRJ45-FHA-1.1	L.6
1736181044	ESG 7/20 SIRIUS MC NE WS	M.11				1963700000	IE-BS-V05M-RJ45-FJ-P	N.26	1992930000	IE-PIRJ45-FH-B-1.1	L.5
1736181044	ESG 7/20 SIRIUS MC NE WS	M.12				1963730000	IE-BI-RJ45-FJ-P	M.20	1992930000	IE-PIRJ45-FH-B-1.1	L.6
18000000000											
1803930001	SAISW4-8S-M12 4P D-ZF	N.32				1963800000	IE-BI-RJ45-FJ-P	M.5	1993540000	IE-PH-AD-V05M-RJ45	N.25
18500000000											
1857440000	ESG 9/11 K MC NE WS	L.13				1963830000	IE-BI-RJ45-FJ-P	M.6	1993550005	IE-USB-AA-0.5M	M.32
1857440000	ESG 9/11 K MC NE WS	L.15				1963830000	IE-BI-RJ45-FJ-P	M.7	1993550005	IE-USB-AA-0.5M	N.55
1857440000	ESG 9/11 K MC NE WS	L.16				1963830000	IE-BI-RJ45-FJ-P	M.8	1993550005	IE-USB-AA-0.5M	N.59
1857440000	ESG 9/11 K MC NE WS	L.17				1963830000	IE-BI-RJ45-FJ-P	M.9	1993550005	IE-USB-AA-0.5M	M.14
1857440000	ESG 9/11 K MC NE WS	L.18				1963830000	IE-BI-RJ45-FJ-P	M.10	1993550005	IE-USB-AA-0.5M	N.55
1857440000	ESG 9/11 K MC NE WS	M.30				1963830000	IE-BI-RJ45-FJ-P	M.11	1993550005	IE-USB-AA-0.5M	N.59
1857440000	ESG 9/11 K MC NE WS	M.32				1963830000	IE-BI-RJ45-FJ-P	M.12	1993550005	IE-USB-AA-0.5M	M.59
1857440000	ESG 9/11 K MC NE WS	N.2				1963830000	IE-BI-RJ45-FJ-P	M.13	1993550010	IE-USB-AA-1.0M	M.14
1857440000	ESG 9/11 K MC NE WS	N.3				1963830000	IE-BI-RJ45-FJ-P	M.14	1993550010	IE-USB-AA-1.0M	M.32
1857440000	ESG 9/11 K MC NE WS	N.7				1963830000	IE-BI-RJ45-FJ-P	N.21	1993550010	IE-USB-AA-1.0M	N.55
1857440000	ESG 9/11 K MC NE WS	N.10				1963830000	IE-BI-RJ45-FJ-P	N.51	1993550015	IE-USB-AA-1.5M	M.14
1857440000	ESG 9/11 K MC NE WS	N.12				1963830000	IE-BI-RJ45-FJ-P	N.52	1993550015	IE-USB-AA-1.5M	M.32
1857440000	ESG 9/11 K MC NE WS	N.16				1963830000	IE-BI-RJ45-FJ-P	N.53	1993550015	IE-USB-AA-1.5M	N.55
1857440000	ESG 9/11 K MC NE WS	N.19				1963830000	IE-BI-RJ45-FJ-P	N.54	1993550018	IE-USB-AA-1.8M	M.32
1857440000	ESG 9/11 K MC NE WS	N.20				1963830000	IE-BI-RJ45-FJ-P	N.55	1993550018	IE-USB-AA-1.8M	N.55
1857440000	ESG 9/11 K MC NE WS	N.21				1963830000	IE-BI-RJ45-FJ-P	N.56	1993550018	IE-USB-AA-1.8M	N.59
1857440000	ESG 9/11 K MC NE WS	N.22				1963830000	IE-BI-RJ45-FJ-P	N.57	1993550018	IE-USB-AA-1.8M	M.32
1857440000	ESG 9/11 K MC NE WS	N.23				1963830000	IE-BI-RJ45-FJ-P	N.58	1993550018	IE-USB-AA-1.8M	N.55
1857440000	ESG 9/11 K MC NE WS	N.24				1963830000	IE-BI-RJ45-FJ-P	N.59	1993550030	IE-USB-AA-3.0M	M.14
1857440000	ESG 9/11 K MC NE WS	S.27				1962400000	IE-BH-V01M	N.12	1993550030	IE-USB-AA-3.0M	M.32
18600000000											
1866730000	REMOVAL TOOL HD	L.10				1962440000	IE-BH-V04P	N.20	2003140000	IE-FC-SFP-CAB	M.3
18800000000											
1880120000	ESG 6/17 K MC NEW	P.5				1962440000	IE-BH-V04P	N.22	2003150000	IE-FC-DFM-CAB-DB	M.2
1880120000	ESG 6/17 K MC NEW	P.6				1962450000	IE-BH-V04P	N.23	2003160000	IE-FC-SFM-CAB	M.3
18900000000											
1892120000	SAISM4-8S-M12 4P D-COD	N.33				1962470000	IE-BH-V04P	N.24	2003170000	IE-FC-DFM-KN0B	M.2
1892120001	SAISM4-8S-M12 4P D-ZF	N.32				1962480000	IE-BH-V04P	N.25	2003180000	IE-FC-DFM-KEY	M.2
1892130000	SAIBM4-8S/M12 4P D-COD	N.33				1962490000	IE-BH-V04P	N.26	2003190000	IE-FC-DFM-CAB	M.2
1892130001	SAIBM4-8S/M12 4P D-ZF	N.32				1962720000	IE-BH-V04P	N.27	2003340000	IE-FC-DF-IPH	M.2
19000000000											
1900000000	SCREWTY-M12	0.34				1962840000	IE-BH-V04P	N.28	2003350000	IE-FC-IP-PWB/109	M.8
1900000000	SCREWTY-M12	0.35				1962850000	IE-BH-V04P	N.29	2003370000	IE-FC-DIP-CL3/A/2ST/109	M.6
1900000000	SCREWTY-M12	0.38				1962850000	IE-BH-V04P	N.30	2003390000	IE-FCH1HDMI-FF	M.6
1900000000	SCREWTY-M12	0.39				1962850000	IE-BH-V04P	N.31	2003390000	IE-FCH1HDMI-FF	M.9
1900000000	SCREWTY-M12	0.44				1962850000	IE-BH-V04P	N.32	2003390000	IE-FCH1HDMI-FF	M.10
1900000000	SCREWTY-M12	0.45				1962850000	IE-BH-V04P	N.33	2003390000	IE-FCH1HDMI-FF	M.12
1900000000	SCREWTY-M12	0.46				1962850000	IE-BH-V04P	N.34	2003390000	IE-FCH1HDMI-FF	M.16
1900000000	SCREWTY-M12	0.47				1962870000	IE-BH-V04P	N.35	2004810000	IE-FC-DSP-CL3/A/2ST/109	M.6
1900000000	SCREWTY-M12	0.48				1962880000	IE-BH-V04P	N.36	2004890000	IE-FC-DIP-BP	M.7
1900000000	SCREWTY-M12	0.49				1962890000	IE-BH-V04P	N.37	2007230000	IE-FC1PWB-FR-OR	L.19
1900000000	SCREWTY-M12	0.50				1962890000	IE-BH-V04P	N.38	2007230000	IE-FC1PWB-FR-OR	M.19
1900000000	SCREWTY-M12	0.51				1962900000	IE-BH-V04P	N.39	2007500000	IE-PS-M12X-P-AWG22/27FH	N.41
1900000000	SCREWTY-M12	0.52				1962900000	IE-BH-V04P	N.40	2008410000	KOK52 X 91	M.3
1900000000	SCREWTY-M12	0.53				1962900000	IE-BH-V04P	N.41	2008410000	KOK52 X 91	M.4
1900000000	SCREWTY-M12	0.55				1962900000	IE-BH-V04P	N.42	2027660000	IE-BHD-V04P	N.20
1900											

Order No.	Type	Page
2047310100	IE-C5DD4UG0100A60A60-E	0.29
2047310150	IE-C5DD4UG0150A60A60-E	0.29
2047310200	IE-C5DD4UG0200A60A60-E	0.29

20600000000

2066650000	IE-FC-KEY2	M.2
2066650000	IE-FC-KEY2	M.3
2067070000	IE-FC-DIP-PWB/2ST/FILS	M.5
2067080000	IE-FC-DSP-PWB/2ST/FILS	M.5

21600000000

2168220000	IE-PCB-M12X-S-90	N.48
230260000	SAI-SK-M12-UNI 2029	S.24

24200000000

2426700000	IE-FCI-PWB-CZ	L.19
2426700000	IE-FCI-PWB-CZ	M.17
2426700000	IE-FCI-PWB-CZ	M.21

24300000000

2435400000	IE-SW-BL05-4GT-1GS	B.13
2435410000	IE-SW-BL05T-4GT-1GS	B.13

24400000000

2447050000	U-LINK-LIC-STD-150-1Y	E.6
2447060000	U-LINK-LIC-VPN-1Y	E.6

24500000000

2455360000	IE-CDR-V14MSCPOF/VAPM-C II	J.11
2455360000	IE-CDR-V14MSCPOF/VAPM-C II	0.9
2457840000	U-LINK-LIC-STD-300-1Y	E.6
2457850000	U-LINK-LIC-STD-500-1Y	E.6

24600000000

2465440000	IE-PS-VAPM-5.2-P	J.10
2465440000	IE-PS-VAPM-5.2-P	N.60
2465440000	IE-PS-VAPM-5P-2.5	P.5
2465440000	IE-PS-VAPM-5P-2.5	P.6

24900000000

2493480000	IE-BSS-VAPM-24V	J.10
2493480000	IE-BSS-VAPM-24V	N.61
2493490000	IE-BHD-VAPM	J.10
2493490000	IE-BHD-VAPM	N.61
2494060000	IE-BP-VAPP-DC	N.61

25000000000

2500710000	IE-FCI-PWB-IND	L.19
2500710000	IE-FCI-PWB-IND	M.17
2500710000	IE-FCI-PWB-IND	M.23
2505070000	IE-FCI-PWB-2USB-A-5V	M.25

25300000000

2531060000	IE-FCI-PWB-ISR	L.19
2531060000	IE-FCI-PWB-ISR	M.17
2531060000	IE-FCI-PWB-ISR	M.23
2531330000	IE-REDU-6.8-PS-VAPM	N.60
2534680000	IE-DINRAIL-AD-PWB	L.19
2534680000	IE-DINRAIL-AD-PWB	M.18
2534680000	IE-DINRAIL-AD-PWB	M.19
2534680000	IE-DINRAIL-AD-PWB	M.20
2534680000	IE-DINRAIL-AD-PWB	M.21
2534680000	IE-DINRAIL-AD-PWB	M.22
2534680000	IE-DINRAIL-AD-PWB	M.23
2534680000	IE-DINRAIL-AD-PWB	M.24
2534680000	IE-DINRAIL-AD-PWB	M.25
2535780000	IE-SR-2G7-LTE/4G-US	D.5
2535930000	IE-SR-2G7-LTE/4G-EU	D.5
2535940000	IE-SR-6GT-LAN	D.5
2535950000	IE-SR-6GT-LTE/4G-US	D.5
2535960000	IE-SR-6GT-LTE/4G-EU	D.5
2535970000	IE-SR-2G7-LTE/4G-EU-M	D.5
2535980000	IE-SR-2G7-LAN-M	D.5
2536060000	IE-WL-BL-AP-CL-EU	H.5
2536650000	IE-WL-BL-AP-CL-EU	H.5
2536660000	IE-WL-BL-AP-CL-US	H.5
2536670000	IE-WL-BL-AP-CL-US	H.5
2536890000	IE-WL-VL-AP-BR-CLEU	H.7
2536900000	IE-WL-VL-AP-BR-CLEU	H.7
2536710000	IE-WL-VL-AP-BR-CL-US	H.7
2536710000	IE-WL-VL-AP-BR-CL-US	H.7

25400000000

2548060000	IE-FCI-P-PWB	M.9
------------	--------------	-----

25500000000

2552580000	IE-PP-RJ45	Q.18
2552580000	IE-PP-RJ45	Q.19
2552580000	IE-PP-RJ45	Q.20
2552580000	IE-PP-RJ45	Q.21
2552580000	IE-PP-RJ45	Q.22
2552580000	IE-PP-RJ45	Q.23
2552580000	IE-PP-RJ45	Q.24
2552580000	IE-PP-RJ45	Q.25
2552580000	IE-PP-RJ45	Q.26
2552580000	IE-PP-RJ45	Q.27
2552580000	IE-PP-RJ45	Q.28
2552580000	IE-PP-RJ45	Q.29
2552580000	IE-PP-RJ45	Q.35
2552580000	IE-PP-RJ45	Q.38
2552580000	IE-PP-RJ45	Q.42
2552580000	IE-PP-RJ45	Q.57
2552580000	IE-PP-RJ45	Q.58

2583830000	CABITTE SE 18-19 LRG BK	S.18
2583840000	CABITTE SE 17-18 LRG BK	S.18
2583860000	CABITTE SE 15-16 LRG BK	S.18
2583880000	CABITTE SE 14-15 LRG BK	S.18
2583890000	CABITTE CR 24/10 EMV	S.22
2583900000	CABITTE BSE LRG BK	S.18
2583910000	CABITTE CR 16/8 EMV	S.22
2583920000	CABITTE CR 10/6 EMV	S.22
2583930000	CABITTE CR 12-13 SML BK	S.18
2583940000	CABITTE CGS M50 BK	S.21
2583950000	CABITTE CGS M40 BK	S.21
2583960000	CABITTE CGS M32 BK	S.21
2583970000	CABITTE CGS M25 BK	S.21
2583980000	CABITTE CGS M20 BK	S.21
2583990000	CABITTE FRL 24/10 BK	S.20
2584000000	CABITTE FRL 16/8 BK	S.20
2584010000	CABITTE FRL 10/6 BK	S.19
2584020000	CABITTE FRL 12-13 SML BK	S.18
2584030000	CABITTE FRL 24/10 SML BK	S.18
2584040000	CABITTE FRL 11-12 SML BK	S.18
2584050000	CABITTE FRL 9-10 SML BK	S.18
2584060000	CABITTE FRL 25-26 SML BK	S.18
2584070000	CABITTE G1H BK	S.21
2584200000	CABITTE G1X BK	S.21
2584300000	CABITTE G1T BK	S.21
2584320000	CABITTE G11 BK	S.21
2584330000	CABITTE SE 8-9 SML BK	S.18
2584340000	CABITTE SE 31-32 LRG BK	S.18
2584350000	CABITTE SE 30-31 LRG BK	S.18
2584360000	CABITTE SE 29-30 LRG BK	S.18
2584370000	CABITTE SE 28-29 LRG BK	S.18
2584380000	CABITTE SE 27-28 LRG BK	S.18
2584390000	CABITTE SE 26-27 LRG BK	S.18
2584400000	CABITTE SE 25-26 LRG BK	S.18
2584410000	CABITTE SE 24-25 LRG BK	S.18
2584420000	CABITTE SE 23-24 LRG BK	S.18
2584430000	CABITTE SE 22-23 LRG BK	S.18
2584440000	CABITTE SE 21-22 LRG BK	S.18
2584450000	CABITTE SE 20-21 LRG BK	S.18
2584460000	CABITTE SE 19-20 LRG BK	S.18
2584470000	CABITTE SE 18-19 LRG BK	S.18
2584480000	CABITTE SE 17-18 LRG BK	S.18
2584490000	CABITTE SE 16-17 LRG BK	S.18
2584500000	CABITTE SE 15-16 LRG BK	S.18
2584510000	CABITTE SE 14-15 LRG BK	S.18
2584520000	CABITTE BSE LRG Y	S.18
2584530000	CABITTE SE 19-20 LRG Y	S.18
2584540000	CABITTE SE 18-19 SML Y	S.18
2584550000	CABITTE SE 17-18 SML Y	S.18
2584560000	CABITTE SE 16-17 SML Y	S.18
2584570000	CABITTE SE 15-16 SML Y	S.18
2584580000	CABITTE SE 14-15 SML Y	S.18
2584590000	CABITTE SE 13-14 SML Y	S.18
2584600000	CABITTE SE 12-13 SML Y	S.18
2584610000	CABITTE SE 11-12 SML Y	S.18
2584620000	CABITTE SE 10-11 SML Y	S.18
2584630000	CABITTE SE 9-10 SML Y	S.18
2584640000	CABITTE SE 8-9 SML Y	S.18
2584650000	CABITTE SE 7-8 SML Y	S.18
2584660000	CABITTE SE 6-7 SML Y	S.18
2584670000	CABITTE SE 5-6 SML Y	S.18
2584680000	CABITTE SE 4-5 SML Y	S.18
2584690000	CABITTE SE 3-4 SML Y	S.18
2584700000	CABITTE SE 2-3 SML Y	S.18
2584710000	CABITTE SE 1-2 SML Y	S.18
2584720000	CABITTE SE 2/3 SML BK	S.18
2584730000	CABITTE SE 2-1 SML BK	S.18
2584740000	CABITTE SE 2/1 SML BK	S.18
2584750000	CABITTE SE 2/1 SML BK	S.18
2584760000	CABITTE SE 2/1 SML BK	S.18
2584770000	CABITTE SE 2/1 SML BK	S.18
2584780000	CABITTE SE 2/1 SML BK	S.18
2584790000	CABITTE SE 2/1 SML BK	S.18
2584800000	CABITTE SE 2/1 SML BK	S.18
2584810000	CABITTE SE 2/1 SML BK	S.18
2584820000	CABITTE SE 2/1 SML BK	S.18
2584830000	CABITTE SE 2/1 SML BK	S.18
2584840000	CABITTE SE 2/1 SML BK	S.18
2584850000	CABITTE SE 2/1 SML BK	S.18
2584860000	CABITTE SE 2/1 SML BK	S.18
2584870000	CABITTE SE 2/1 SML BK	S.18
2584880000	CABITTE SE 2/1 SML BK	S.18
2584890000	CABITTE SE 2/1 SML BK	S.18
2584900000	CABITTE SE 2/1 SML BK	S.18
2584910000	CABITTE SE 2/1 SML BK	S.18
2584920000	CABITTE SE 2/1 SML BK	S.18
2584930000	CABITTE SE 2/1 SML BK	S.18
2584940000	CABITTE SE 2/1 SML BK	S.18
2584950000	CABITTE SE 2/1 SML BK	S.18
2584960000	CABITTE SE 2/1 SML BK	S.18
2584970000	CABITTE SE 2/1 SML BK	S.18
2584980000	CABITTE SE 2/1 SML BK	S.18
2584990000	CABITTE SE 2/1 SML BK	S.18
2585000000	CABITTE SE 2/1 SML BK	S.18
2585010000	CABITTE SE 2/1 SML BK	S.18
2585020000	CABITTE SE 2/1 SML BK	S.18
2585030000	CABITTE SE 2/1 SML BK	

Order No.	Type	Page	Order No.	Type	Page	Order No.	Type	Page	Order No.	Type	Page
2682260000	IE-SW-AL06LM-4TX-2SC	C.4	2706190050	IE-C5D04U0G0050DCAXXX-E	0.49	2717810015	IE-C5D04U0P015PCAPSA-E	0.47	2763510000	IE-C5ES8VG-500	Q.8
2682270000	IE-SW-AL06LM-4TX-2SCS	C.4	2706190075	IE-C5D04U0G0075DCAXXX-E	0.49	2717810030	IE-C5D04U0P0030PCAPSA-E	0.47	2763520000	IE-C5IT4UG-500	J.11
2682280000	IE-SW-AL08M-8TX	C.5	2706190100	IE-C5D04U0G0100DCAXXX-E	0.49	2717810050	IE-C5D04U0P0050PCAPSA-E	0.47	2763520000	IE-C5IT4UG-500	0.5
2682290000	IE-SW-AL08M-6TX-2GT	C.9	2706200015	IE-C5D04U0G0015DCSDCS-E	0.50	2717810075	IE-C5D04U0P0075PCAPSA-E	0.47	2763520000	IE-C5IT4UG-500	0.16
2682310000	IE-SW-AL16M-16TX	C.5	2706200030	IE-C5D04U0G0030DCSDCS-E	0.50	2717810100	IE-C5D04U0P0100PCAPSA-E	0.47	2763530000	IE-C7BS8UG-500	0.5
2682320000	IE-SW-AL24M-24TX	C.5	2706200050	IE-C5D04U0G0050DCSDCS-E	0.50				2763530000	IE-C7BS8UG-500	0.7
2682330000	IE-SW-AL18M-16TX-2SC	C.9	2706200075	IE-C5D04U0G0075DCSDCS-E	0.50				2763540000	IE-C7BS8VG-500	0.5
2682340000	IE-SW-AL12M-8GT-4GESFP	C.12	2706200100	IE-C5D04U0G0100DCSDCS-E	0.50				2763550000	IE-C7ES8UG-500	0.7
2682350000	IE-SW-AL08M-8GT	C.12	2706200200	IE-C5D04U0G0200DCSDCS-E	0.50				2763560000	IE-C7ES8VG-500	0.9
2682360000	IE-SW-AL14M-12GT-2GESFP	C.12	2706200300	IE-C5D04U0G0300DCSDCS-E	0.50				2763560000	IE-C7ES8VG-500	0.9
2682370000	IE-SW-AL24M-16GT-8GESFP	C.12	2706210015	IE-C5D04U0G0150DCSDSS-E	0.50				2763640000	IE-FPOD2UG-500	J.11
2682380000	IE-SW-EL08-8PQE	B.9	2706210030	IE-C5D04U0G0030DCSDSS-E	0.50				2763640000	IE-FPOD2UG-500	J.15
2682390000	IE-SW-EL06-4PQE-2SC	B.9	2706210050	IE-C5D04U0G0050DCSDSS-E	0.50				2763640000	IE-FPOD2UG-500	R.4
2682400000	IE-SW-EL08-8GTPQE	B.14	2706210075	IE-C5D04U0G0075DCSDSS-E	0.50				2763660000	IE-C5DHAG-100	N.7
2682410000	IE-SW-EL10-8GTPQE-2GESFP	B.14	2706211000	IE-C5D04U0G0100DCSDSS-E	0.50				2763660000	IE-C5DHAG-100	0.5
2682420000	IE-SW-AL08M-8GTPQE	C.13	2706212000	IE-C5D04U0G0200DCSDSS-E	0.50				2763660000	IE-C5DHAG-100	0.17
2682430000	IE-SW-AL06M-4GTPQE-2GESFP	C.13	2706213000	IE-C5D04U0G0300DCSDSS-E	0.50				2764770000	IE-C5IT4UG-100	0.5
2682440000	IE-INJ-EL02-2GTPQE	B.16	2706220015	IE-C5D04U0G0150DCADCA-E	0.51				2764770000	IE-C5IT4UG-100	0.16
2682450000	IE-SFP-1FE-MM-2	I.4	2706220030	IE-C5D04U0G0300DCADCA-E	0.51				2768720000	IE-PIRJ45-TH-P	N.2
2682470000	IE-SFP-1FE-SM-60	I.4	2706220050	IE-C5D04U0G0050DCADCA-E	0.51				2768740000	IE-PSV14M-RJ45-THP	J.11
2682480000	IE-SFP-1GE-MM-00	I.5	2706220075	IE-C5D04U0G0075DCADCA-E	0.51				2768740000	IE-PSV14M-RJ45-THP	N.2
2682490000	IE-SFP-1GE-MM-2	I.5	2706221000	IE-C5D04U0G0100DCADCA-E	0.51						
2682500000	IE-SFP-1GE-SM-10	I.5	2706230015	IE-C5D04U0G0150CDAOSA-E	0.51						
2682510000	IE-SFP-1GE-SM-40	I.5	2706230030	IE-C5D04U0G0300CDAOSA-E	0.51						
2682520000	IE-SFP-1GE-5M-10-BIDI-TX1310	I.5	2706230050	IE-C5D04U0G0050CDAOSA-E	0.51						
2682530000	IE-SFP-1GE-SM-10-BIDI-TX1550	I.5	2706230075	IE-C5D04U0G0075CDAOSA-E	0.51						
2682540000	IE-SFP-1GE-SM-20-BIDI-TX1310	I.5	2706231000	IE-C5D04U0G0100CDAOSA-E	0.51						
2682550000	IE-SFP-1GE-SM-20-BIDI-TX1550	I.5	2706250015	IE-C5D04U0G0150CSE40-E	0.52						
2682600000	IE-CS-MBGW-2TX-1COM	F.6	2706250030	IE-C5D04U0G0300CSE40-E	0.52						
2682610000	IE-EBR-MODULE-RS232-ALM	C.12	2706250050	IE-C5D04U0G0500CSE40-E	0.52						
2682610000	IE-EBR-MODULE-RS232-ALM	C.13	2706250075	IE-C5D04U0G075CSE40-E	0.52						
2682610000	IE-EBR-MODULE-RS232-ALM	C.15	2706250100	IE-C5D04U0G0100CSE40-E	0.52						
2682610000	IE-EBR-MODULE-RS232-ALM	C.19	2706250200	IE-C5D04U0G0200CSE40-E	0.52						
2682610000	IE-EBR-MODULE-RS232-ALM	I.9	2706250300	IE-C5D04U0G0300CSE40-E	0.52						
2682620000	IOT-GW30	G.4	2706260015	IE-C5D04U0G0015M40M40-V	0.21						
2701550002	IE-CFPBLV0002M40M40-V	Q.21	2706260030	IE-C5D04U0G0050M40M40-V	0.21						
2701550005	IE-CFPBLV0005M40M40-V	Q.21	2706260050	IE-C5D04U0G0100M40M40-V	0.21						
2701550010	IE-CFPBLV0010M40M40-V	Q.21	2706260075	IE-C5D04U0G0075M40M40-V	0.21						
2701550015	IE-CFPBLV0015M40M40-V	Q.21	2706261000	IE-C5D04U0G0100M40M40-V	0.21						
2701550020	IE-CFPBLV0020M40M40-V	Q.21	2706262000	IE-C5D04U0G0030M40M40-V	0.21						
2701550020	IE-CFPBLV0030M40M40-V	Q.21	2706263000	IE-C5D04U0G0050M40M40-V	0.21						
2701550030	IE-CFPBLV0030M40M40-V	Q.21	2706265000	IE-C5D04U0G0075M40M40-V	0.21						
2701550050	PRINT/ET CONNECT	S.26	2715590000	PJ CON JET CONNECT	S.26						
2701560000	PJ CON INK SET	S.26	2715600000	PJ CON INK SET	S.26						
2701561000	PJ CON INK C	S.26	2715610000	PJ CON INK C	S.26						
2701562000	PJ CON INK M	S.26	2715620000	PJ CON INK M	S.26						
2702690000	SAISWC-D-18/28/4/9CG	N.36	2715630000	PJ CON INK Y	S.26						
2702700000	SAIBWC-D-18/28/4/9CG	N.36	2715640000	PJ CON INK K	S.26						
2702710000	IE-PS-M12X-90-P-TH	N.43	2715650000	PJ CON FLUID SET	S.26						
2702720000	IE-PS-M12X-90-S-TH	N.43	2715660000	PJ CON WASTE PAD	S.26						
2703320005	IE-CFPPL8LD0005M40L40-D	Q.24	2715670000	PJ CON TEXTILE COVER	S.26						
2703320010	IE-CFPPL8LD00010M40L40-D	Q.24	2715680000	PJ CON FI STICK	S.26						
2703320012	IE-CFPPL8LD0012M40L40-D	Q.24	2717740015	IE-C5D04UP0015PSSXXX-E	0.44						
2703320015	IE-CFPPL8LD0015M40L40-D	Q.24	2717740030	IE-C5D04UP0030PSSXXX-E	0.44						
2703320020	IE-CFPPL8LD0020M40L40-D	Q.24	2717740050	IE-C5D04UP0050PSSXXX-E	0.44						
2703320030	IE-CFPPL8LD0030M40L40-D	Q.24	2717740075	IE-C5D04UP0075PSSXXX-E	0.44						
2703330012	IE-CFPPL8LD00012M40R40-D	Q.24	2717750010	IE-C5D04UP0100PSSXXX-E	0.44						
2703330015	IE-CFPPL8LD0015M40R40-D	Q.24	2717750030	IE-C5D04UP0300PSSXXX-E	0.44						
2703330020	IE-CFPPL8LD0020M40R40-D	Q.24	2717750050	IE-C5D04UP0305PSSXXX-E	0.44						
2703330030	IE-CFPPL8LD0030M40R40-D	Q.24	2717750075	IE-C5D04UP075PSSXXX-E	0.44						
2703330050	IE-CFPPL8LD0050M40R40-D	Q.24	2717752000	IE-C5D04UP0200PSSXXX-E	0.44						
2703330100	IE-CFPPL8LD0100M40R40-D	Q.24	2717753000	IE-C5D04UP0300PSSXXX-E	0.44						
2703390000	IE-PSRJ45FH-180A-1.6CG	L.5	2717760015	IE-C5D04UP0105PSSXXX-E	0.45						
2703410000	IE-PSRJ45FH-180B-1.6CG	L.5	2717760030	IE-C5D04UP0303PSSXXX-E	0.45						
2703420000	IE-PSRJ45FH-180B-1.6CG	L.7	2717760050	IE-C5D04UP050PSAXXX-E	0.45						
2703440000	IE-PSRJ45FH-180A-1.1CG	L.5	2717760075	IE-C5D04UP075PSAXXX-E	0.45						
2703460000	IE-PSRJ45FH-180B-1.1CG	L.5	2717761000	IE-C5D04UP0100PSAXXX-E	0.45						
2704480000	IE-CABLE-BENDER-90	0.18	2717762000	IE-C5D04UP0200PSAXXX-E	0.45						
2704480000	IE-CABLE-BENDER-90	0.19	2717763000	IE-C5D04UP0300PSAXXX-E	0.45						
2704480000	IE-CABLE-BENDER-90	0.20	2717770015	IE-C5D04UP0105PCAXXX-E	0.45						
2704480000	IE-CABLE-BENDER-90	0.21	2717770030	IE-C5D04UP0303PCAXXX-E	0.45						
2704480000	IE-CABLE-BENDER-90	0.22	2717770050	IE-C5D04UP0505PCAXXX-E	0.45						
2704480000	IE-CABLE-BENDER-90	0.25	2717770075	IE-C5D04UP0075PCAXXX-E	0.45						
2704480000	IE-CABLE-BENDER-90	0.26	2717771010	IE-C5D04UP0100PCAXXX-E	0.45						
2704480000	IE-CABLE-BENDER-90	0.27	2717778015	IE-C5D04UP0115PCSPCS-E	0.46						
2704480000	IE-CABLE-BENDER-90	S.23	2717780030	IE-C5D04UP0303PCSPCS-E	0.46						
2705000000	IE-SW-EL08-8GT-MINI	B.12	2717780050	IE-C5D04UP0050PCSPCS-E	0.46						
2706150015	IE-C5D04U0G0015DCSXSS-E	Q.48	2717780075	IE-C5D04UP075PCSPCS-E	0.46						
2706150030	IE-C5D04U0G0030DCSXSS-E	Q.48	2717780100	IE-C5D04UP0100PCSPCS-E	0.46						
2706160015	IE-C5D04U0G0015DSAXXX-E	Q.49	2717780120	IE-C5D04UP0200PCSPCS-E	0.46						
2706160030	IE-C5D04U0G0030DSAXXX-E	Q.49	2717780140	IE-C5D04UP0300PCSPCS-E	0.46						
2706160050	IE-C5D04U0G0050DCSXSS-E	Q.48	2717780160	IE-C5D04UP0200PCSPCS-E	0.46						
2706160075	IE-C5D04U0G0075DSAXXX-E	Q.48	2717780180	IE-C5D04UP0303PCSPCS-E	0.46						
2706160100	IE-C5D04U0G0100DSAXXX-E	Q.49	2717800015	IE-C5D04UP0015PCAPCA-E	0.47						
2706160200	IE-C5D04U0G0200DSAXXX-E	Q.49	2717800030	IE-C5D04UP0303PCAPCA-E	0.47						
2706160300	IE-C5D04U0G0300DSAXXX-E	Q.49	2717800050	IE-C5D04UP0050PCAPCA-E	0.47						
2706160300	IE-C5D04U0G0400DSAXXX-E	Q.49	2717800075	IE-C5D04UP0075PCAPCA-E	0.47						
2706160500	IE-C5D04U0G0150DCAXXX-E	Q.49	2717800100	IE-C5D04UP0100PCAPCA-E	0.47						
27061607											

Order No.	Type	Page
8813160000	IE-C5CS8UG-100	0.6
8813170000	IE-C7ES8VG-100	0.5
8813170000	IE-C7ES8VG-100	0.9
8813180000	IE-C7ES8UG-100	0.5
8813180000	IE-C7ES8UG-100	0.9
8813190000	IE-C5ES8VG-100	J.15
8813190000	IE-C5ES8VG-100	0.5
8813190000	IE-C5ES8VG-100	0.8
8813200000	IE-C5ES8UG-100	J.15
8813200000	IE-C5ES8UG-100	0.5
8813200000	IE-C5ES8UG-100	0.8
8813210000	IE-C5ED8UG-100	0.5
8813210000	IE-C5ED8UG-100	0.14
8813270000	IE-FM62ZV00001MSTOSOX	R.8
8813280000	IE-FM62ZV00002MSTOSOX	R.8
8813290000	IE-FM62ZV00003MSTOSOX	R.8
8813300000	IE-FM52ZV00001MSDOSOX	R.8
8813310000	IE-FM52ZV00002MSDOSOX	R.8
8813320000	IE-FM52ZV00003MSDOSOX	R.8
8813330000	IE-FM62ZV00001MSDOSOX	R.8
8813340000	IE-FM62ZV00002MSDOSOX	R.8
8813350000	IE-FM62ZV00003MSDOSOX	R.8
8813390000	IE-FM52ZV00002MSTOSOX	R.9
8813400000	IE-FM62ZV00002MSTOSOX	R.9
8813490000	IE-DPC	S.24
8813500000	IE-DM	L.14
8813500000	IE-DM	L.15
8813500000	IE-DM	L.18

8820000000

8829440000	IE-XM-6U-RJ45/RJ45-IP67	N.28
8829450000	IE-XM-6D-RJ45/RJ45-IP67	N.28

8870000000

8876350050	IE-FM52ZV00005MSDOSOX	R.8
8876350100	IE-FM52ZV00010MSDOSOX	R.8
8876360050	IE-FM52ZV00005MSDOSOX	R.8
8876361000	IE-FM52ZV00010MSDOSOX	R.8
8876370010	IE-FM52ZV0001MSTOSOX	R.8
8876370020	IE-FM52ZV00002MSTOSOX	R.8
8876370030	IE-FM52ZV00003MSTOSOX	R.8
8876370050	IE-FM52ZV00005MSTOSOX	R.8
8876370100	IE-FM52ZV00010MSTOSOX	R.8
8876380050	IE-FM52ZV00005MSTOSOX	R.8
8876380100	IE-FM62ZV00010MSTOSOX	R.8
8876430010	IE-FM52ZV00001MSDOSOX	R.12
8876430030	IE-FM52ZV00003MSDOSOX	R.12
8876430050	IE-FM52ZV00005MSDOSOX	R.12
8876430100	IE-FM52ZV00010MSDOSOX	R.12
8876430500	IE-FM52ZV00005MSDOSOX	R.12
8876431000	IE-FM52ZV000100MSDOSOX	R.12
8876440010	IE-FM52ZV00001MSDOSOX	R.12
8876440010	IE-FM52ZV00001MSDOSOX	R.12
8876440030	IE-FM52ZV00003MSDOSOX	R.12
8876440050	IE-FM52ZV00005MSDOSOX	R.12
8876450010	IE-FM52ZV00010MSTOSOX	R.12
8876450050	IE-FM52ZV00005MSDOSOX	R.12
8876451000	IE-FM52ZV000100MSTOSOX	R.12
8876460010	IE-FM52ZV00001MSDOSOX	R.12
8876460030	IE-FM52ZV00003MSTOSOX	R.12
8876460050	IE-FM52ZV00005MSTOSOX	R.12
8876461000	IE-FM52ZV000100MSTOSOX	R.12
8876450010	IE-FM52ZV00001MSTOSOX	R.12
8876450030	IE-FM52ZV00003MSTOSOX	R.12
8876450050	IE-FM52ZV00005MSTOSOX	R.12
8876451000	IE-FM52ZV000100MSTOSOX	R.12
8876454000	IE-FM52ZV00005MSDOSOX	R.12
8876460050	IE-FM52ZV00005MSDOSOX	R.12
8876461000	IE-FM62ZV000100MSDOSOX	R.12
8876461000	IE-FM62ZV000100MSTOSOX	R.12
8879050000	IE-XM-RJ45/RJ45	L.15

8890000000

8898990000	IE-C5DS4VG-100	J.11
8898990000	IE-C5DS4VG-100	0.5
8898990000	IE-C5DS4VG-100	0.15
8899000000	IE-C5AS4VG-100	J.11
8899000000	IE-C5AS4VG-100	0.5
8899000000	IE-C5AS4VG-100	0.15
8899010000	IE-C5D04UG-100	J.11
8899010000	IE-C5D04UG-100	0.5
8899010000	IE-C5D04UG-100	0.16

8900000000

8901620000	IE-M12-ADAP S	N.38
8901630000	IE-M12-ADAP A	N.38
8901640000	IE-M12-COUP	N.39
8902810000	IE-M12-PCBCE	N.40
8902820000	IE-M12-PCBCE-PANEL	N.40

8940000000

8941350003	IE-C6FS8UG0003A40A40-G	0.27
8941350005	IE-C6FS8UG0005A40A40-G	0.27
8941350010	IE-C6FS8UG0010A40A40-G	0.27
8941350015	IE-C6FS8UG0015A40A40-G	0.27
8941350020	IE-C6FS8UG0020A40A40-G	0.27


Order No.	Type	Page
8941350030	IE-C6FS8UG0030A40A40-G	0.27
8941350050	IE-C6FS8UG0050A40A40-G	0.27
8941350100	IE-C6FS8UG0100A40A40-G	0.27
8941350150	IE-C6FS8UG0150A40A40-G	0.27
8941350200	IE-C6FS8UG0200A40A40-G	0.27
8946920000	IE-T0-RJ45-C	J.10
8946920000	IE-T0-RJ45-C	J.14
8946920000	IE-T0-RJ45-C	L.15
8946930000	IE-T0-RJ45-FJA	J.14
8946930000	IE-T0-RJ45-FJA	L.13
8946940000	IE-T0-RJ45-FJB	J.14
8946940000	IE-T0-RJ45-FJB	L.13
8946950000	IE-T0-RJ45-FJP	J.10
8946950000	IE-T0-RJ45-FJP	L.13
8946960000	IE-T0-USB	L.16
8946970000	IE-T0-SCD-MM	L.17
8946980000	IE-T0-SCD-SM	L.17
8946990000	IE-T0-SCRJ-MM	J.10
8946990000	IE-T0-SCRJ-MM	J.14
8946990000	IE-T0-SCRJ-MM	L.17
8947000000	IE-T0-SCRJ-SM	J.10
8947000000	IE-T0-SCRJ-SM	J.14
8947000000	IE-T0-SCRJ-SM	L.17
8947010000	IE-T0-LCD-MM	L.18
8947020000	IE-T0-LCD-SM	L.18


Order No.	Type	Page
9200000000		
9202800000	TT 8 RS MP 8	L.8
9202800000	TT 8 RS MP 8	N.3
9202800000	TT 8 RS MP 8	N.50
9202800000	TT 8 RS MP 8	0.17
9202800000	ERME MULTI-STRIPAX	S.10
9203100000	ERAN MULTI-STRIPAX	S.10
9204350000	IE-CST	0.6
9204350000	IE-CST	0.7
9204350000	IE-CST	0.8
9204350000	IE-CST	0.9
9204350000	IE-CST	0.10
9204350000	IE-CST	0.11
9204350000	IE-CST	0.12
9204350000	IE-CST	0.13
9204350000	IE-CST	0.14
9204350000	IE-CST	0.15
9204350000	IE-CST	0.16
9204350000	IE-CST	0.17
9204350000	IE-CST	0.18
9204350000	IE-CST	0.19
9204350000	IE-CST	0.20
9204350000	IE-CST	0.21
9204350000	IE-CST	0.22
9204350000	IE-CST	0.23
9204350000	IE-CST	0.24
9204350000	IE-CST	0.25
9204350000	IE-CST	0.26
9204350000	IE-CST	0.27
9204350000	IE-CST	0.28
9204350000	IE-CST	0.29
9204350000	IE-CST	0.30
9204350000	IE-CST	0.31
9204350000	IE-CST	0.32
9204350000	IE-CST	0.33
9204350000	IE-CST	0.35
9204350000	IE-CST	0.54
9204350000	IE-CST	0.57
9204350000	IE-CST	S.4
9204370000	IE-FISP-V4	M.30
9204370000	IE-FISP-V4	M.31
9204370000	IE-FISP-V4	M.32
9204370000	IE-FISP-V4	N.20
9204370000	IE-FISP-V4	N.22
9204370000	IE-FISP-V4	N.23
9204370000	IE-FISP-V4	N.24
9204370000	IE-FISP-V4	S.15
9204372000	IE-FM6D2UE0050MLDOLDOX	R.11
9207902000	IE-FM5D2UE0010MLDOLDOX	R.11
9207903000	IE-FM5D2UE0010MLDOLDOX	R.11
9207904000	IE-FM5D2UE0050MLDOLDOX	R.11
9204370000	SEE ESD 125	S.9
9204760000	FZE ESD 130	S.9
9204770000	SZE ESD 130	S.9
9204790000	IE-KOK-V5	S.16
9205000000	KOHS 9.5+19	S.16
9205010000	KOHS 19	S.16
9205020000	KOPD 10.0	S.16
9205130000	SEE ESD 120	S.9
9205140000	SVSE ESD 130	S.9
9205150000	SUPER CUT	S.9
9205210000	KOF SET ESD	S.9
9205300000	IE-CTFL-GOF	N.58
9204500000	LAN USB TESTER	S.7

9030060000	AM 12	0.6
9030060000	AM 12	0.7
9030060000	AM 12	0.8
9030060000	AM 12	0.9
9030060000	AM 12	0.10
9030060000	AM 12	0.11
9030060000	AM 12	0.12
9030060000	AM 12	0.13
9030060000	AM 12	0.14
9030060000	AM 12	0.15
9030060000	AM 12	0.16
9030060000	AM 12	0.17
9030060000	AM 12	0.18
9030060000	AM 12	0.19
9030060000	AM 12	0.20
9030060000	AM 12	0.21
9030060000	AM 12	0.22
9030060000	AM 12	0.23
9030060000	AM 12	0.24
9030060000	AM 12	0.25
9030060000	AM 12	0.26
9030060000	AM 12	0.27
9030060000	AM 12	0.28
9030060000	AM 12	0.30
9030060000	AM 12	0.31
9030060000	AM 12	0.32
9030060000	AM 12	0.33
9030060000	AM 12	0.35
9030060000	AM 12	0.54
9030060000	AM 12	0.57
9030060000	AM 12	S.4
9032020000	MEKA BL CST	S.4

Addresses worldwide

Let's connect.





We cannot guarantee that there are no mistakes in the publications or software provided by us to the customer for the purpose of making orders. We try our best to quickly correct errors in our printed media.

All orders are based on our general terms of delivery, which can be reviewed on the websites of our group companies where you place your order. On demand we can also send the general terms of delivery to you.

Weidmüller – Your partner in Industrial Connectivity

As experienced experts we support our customers and partners around the world with products, solutions and services in the industrial environment of power, signal and data. We are at home in their industries and markets and know the technological challenges of tomorrow. We are therefore continuously developing innovative, sustainable and useful solutions for their individual needs. Together we set standards in Industrial Connectivity.

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 16
32758 Detmold, Germany
T +49 5231 14-0
F +49 5231 14-292083
www.weidmueller.com

Personal support can
be found on our website:
www.weidmueller.com/contact

Made in Germany



4 064675 051817

Order number: 2780490000/05/2021/SMR