


# PCB terminals and connectors

## High-quality components and unique design-in services

OMNIMATE® device connectivity

Product  
catalog with  
webcodes



**Weidmüller** 

# Device developments designed with unique efficiency

## OMNIMATE® during a typical device development phase

**24/7 Online-Services**  
 The right know-how at any time, helpful support  
 and reliable services for your device development.  
[www.weidmueller.com/omnimate-services](http://www.weidmueller.com/omnimate-services)



Efficient planning and design-in processes save you valuable time in product development. In addition to our PCB components, we offer a wide range of support tools and services.



### Information

We support you with specialist expertise and detailed information. Do you have any questions about device development in accordance with UL 600 V or would you like to find out about the benefits of PUSH IN technology? Our white papers and webinars provide you with comprehensive, compact and useful information.

**Webcode #11359**



### Product selection

Precise product recommendations just one click away: Our AppGuide supports you in a simple and targeted way. Simply select the required device application and the AppGuide recommends to you the suitable connection solutions for the different functions of your device.

**Webcode #01171**



### Use

Your information edge: Our handling videos provide you step by step with useful information and important details on handling the various products. This makes the design-in process and installation even easier, safer and more pleasant for you.


**Webcode #11535**



### Design-in support

You can adapt PCB terminals, connectors and electronics housings to your application, as required, using our online configurators. With the sample service, your personal design-in sample is in your hands within just 72 hours. Free of charge and worldwide.

**Webcode #01163**






# Many ways lead to the right product

## Our online services as process-optimisation tools

There is more than one route to the final layout. Our support concept will assist you in all of your search and selection options.

Weidmüller has fundamentally re-designed the selection and ordering process for device connectivity in a way that better suits your application. In the future, there'll no longer be just the one path to the right product; there'll just be the right path: yours.



### Webcode selection

For an application, you need certain specifications for certain products. Our new webcode allows you to go directly to the relevant products: simply choose the required product from the following pages and enter the hashtag with five-digit code on our website, and you'll be directed to the relevant details.


[www.weidmueller.com](http://www.weidmueller.com)



### The AppGuide

When working with applications, you'll need to find ways of successfully implementing your ideas. Simply select your device application in our AppGuide, and we will recommend a range of products for all the different functions of your device.

Webcode #01171



### Specification filters

In our online catalog in the area of device connectivity, you filter the right product in seconds using your product and application requirements.

Webcode #11534



## Webcode: the hashtag for easy product searching

A hashtag followed by five digits – that's all you need to find out detailed information about the products in our wide-ranging portfolio. Entering the sequence of characters activates certain product groups or an individual product.

### Where can I find the webcode?

Next to the product, either in this brochure or online.

### Where do I enter the webcode?

Just enter the code into the search screen on our website. \*

### Where will I be directed to once I've entered the webcode?

You'll be taken to the product specifications and technical details, as well as additional info and downloads.

\* Note: Make sure that the pop-up blocker settings are disabled

# Your device application


## Our AppGuide for device developers

Based on your application, the AppGuide will show you a representative range of products for the different functions of your device.

The overview will show you the application as you know it. Move the cursor over the markings to find out information on the connection technology for sub-assemblies and components. And it's just a few more clicks from here to your desired product.




**AppGuide**  
Simply select your device application in our AppGuide, and we will recommend a range of products for all the different functions of your device.  
[www.weidmueller.com/appguide](http://www.weidmueller.com/appguide)




**1. Open the AppGuide**  
Go to: [www.weidmueller.com/appguide](http://www.weidmueller.com/appguide) or use the **Webcode #01171**



**2. Select the application**  
Hotspots will show you the way to our recommended products



**3. Select product group**  
Use the hotspots to find the perfect products for your applications



**4. Receive the product**  
Configure your selection and use the available functions of our online catalogue

Go directly to your application with the webcode



Industrial controls



Drive controllers and regulators



Devices of machine safety



Analogue signal converter



Photovoltaic inverter



Power supply



Radio base stations



Heating electronics



Building security equipment



LED lighting systems



Elevator electronics devices



Webcode  
#01171




# OMNIMATE® 4.0 – Fast. Flexible. Digital.

## SNAP IN connectivity solutions for pioneers


The demands on the development of electrical devices are constantly increasing. This leads to higher complexity and challenges device developers. OMNIMATE® 4.0 is the efficient solution for a continuous, digitalised device development process for the connected world of tomorrow.

OMNIMATE® 4.0 combines three innovations in one: super-fast wire connection technology, modular product design and a fastest possible delivery. The innovative SNAP IN connection technology allows even flexible conductors without ferrules to be connected easily without tools. An indicator signals the secure connection both acoustically and visually. The modular product concept of OMNIMATE® 4.0 enables flexible configuration via the Weidmüller Configurator (WMC) for the design of your next generation devices with reduced engineering efforts and all relevant digital data. Through this combination of modularity and a digital value chain even highly individual products are ready to be shipped within 3 days – from samples to product series.




### Maximum wiring speed

The innovative SNAP IN connection enables secure wiring in record time. With SNAP IN even flexible conductors without ferrules can be connected intuitively and completely tool-free - even in fully automated wiring processes.



### Hearable and visible feedback

OMNIMATE® 4.0 with the visual safety indicator gives you direct feedback of the clamping situation. Beside a hearable "click" the green visual safety indicator increase the security of the proper wiring of the connector.



### Easy and intuitive handling

The easy and one-hand usable topflange fixes the product and prevents undesired disconnection. The tool-less re-wiring with the lever function brings the handling to a new level.

Learn more about the the game changer  
in the connector market.  
[www.weidmueller.com/omnimate40](http://www.weidmueller.com/omnimate40)




# OMNIMATE® 4.0 in the Weidmüller Configurator

## Create your own configuration


Your are looking for a specific solution perfectly fitting to your individual devices and their requirements.

The modular product concept of OMNIMATE® 4.0 enables flexible configuration and request via the Weidmüller Configurator (WMC). The software tool significantly reduces your efforts and speeds up your engineering processes from product specification to the individual offer within minutes. Digital engineering can be as simple as that.



### Integrated future-proof technologies

The modular design of OMNIMATE® 4.0 provides a flexible product portfolio with unlimited variations. The individual configuration in the Weidmüller Configurator realized hybrid connectors with the next generation technology Single Pair Ethernet (SPE).



### Highest flexibility for your application

The Weidmüller Configurator (WMC) reduce your engineering efforts with the intuitive usability as well as the realtime feedback of your configuration. The configured product can be requested directly and the offer preperation will be automatically done within minutes.




### Full Design-in support

OMNIMATE® 4.0 brings the full design-in support for device manufacturer. That covers the reasy configuration according to the requirements of your application as well as the provision of all digital engineering data. The availability of free samples within 3 days and the support with handling videos fullfills the OMNIMATE® services.

## OMNIMATE® 4.0– SNAP IN PCB connectors

Pitch 5.00 mm




### Webcode #11530

#### MHS 5

Highly reliable male header for reflow and wave soldering methods.

- Male header
- Pitch: 5.00 mm
- Number of poles: 2-12
- IEC: 400 V / 26.8 A
- UL: 300 V / 18.5 A




### Webcode # 11531

#### MPS 5

Female plug with 180° outlet direction, SNAP IN connection technology and optional self-locking top flange.

- SNAP IN connection
- Pitch: 5.00 mm
- Number of poles: 2-12
- IEC: 400 V / 26.8 A / 0.5-2.5 mm²
- UL: 300 V / 18.5 A / AWG 20-12/7/9




### Webcode # 11532

#### MHS 5 D11

Hybrid male header with integrated Single Pair Ethernet (SPE) data connection for reflow soldering.

- Male header
- Pitch: 5.00 mm
- Number of poles: 2-12
- IEC: 400 V / 26.8 A
- UL: 300 V / 18.5 A



### Webcode # 11533

#### MPS 5 D11

Hybrid female plug with SNAP IN connection technology and field attachable Single Pair Ethernet data connector.

- SNAP IN connection
- Pitch: 5.00 mm
- Number of poles: 2-12
- IEC: 400 V / 26.8 A / 0.5-2.5 mm²
- UL: 300 V / 18.5 A / AWG 20-12/7/9



Learn more about our digital engineering possibilities with unique services over the Weidmüller Configurator (WMC).  
[www.weidmueller.com/configurator](http://www.weidmueller.com/configurator)



# Single Pair Ethernet

## Data connection for the factory of the future

In the factory of the future, machines and systems will be connected to each other consistently via a data infrastructure. These cyber-physical systems can act independently in the Industrial Internet of Things (IIoT), communicate in real time, and control production processes. In order to enable this, a continuous network with high-performance data connections from the sensor to the cloud is required. This pushes conventional Ethernet systems to their limits.

Single Pair Ethernet (SPE) facilitates the extension of the Ethernet to the sensor. It is compact, flexible, and enables high ranges. SPE provides for the extension of existing installations and supports consistent communication. Indeed, SPE is considered by Weidmüller as the missing component needed to close the current gap in the supply of standard Ethernet at field level.

SPE runs at the same transmission speeds as conventional Ethernet but with data lines up to 1,000 m in length. Together with other new technologies like 5G, SPE enables both continuous IP communication between the server and the cloud, as well as supplying up to 60 Watts of power in complex IIoT solutions through PoDL (Power over Data Line).




Learn more about our next generation of IIoT-oriented Ethernet within the connected world of today and tomorrow.  
[www.weidmueller.com/spe](http://www.weidmueller.com/spe)



# OMNIMATE® Data


## Single Pair Ethernet Connectors

- Devices can become significantly smaller - Most compact design for implementing IIoT devices (saving of > 50 %)
- Vibration-proof and insensitive to electromagnetic influences - Particularly robust, industry-compatible construction
- The colour-coded two-wire connection technology saves installation time and avoids connection errors - User-friendly structure for safe and quick installation
- Suitable for IIoT, corresponds to the latest IEEE / IEC standards for data rates from 10Mbit/s to 1Gbit/s. - High future security through compliance with international standards
- Safe locking - Even in the smallest installation space, a robust locking mechanism up to 50N is ensured (acoustic feedback during the mating process)
- Reliable process - Troublefree assembly due to sharpened pin geometry, guide posts and Tape on Reel packaging



Webcode # 11523  
**IE-PCB-SP0**  
Angled (90°) Single-Pair PCB male header for IP20

- Reflow-soldering (THR)
- Robust housing with metal snap-in mechanism
- Shielded and reinforced contacts (PdNi)
- Performance Category: up to 1Gbit/s
- Plugging cycles: 750
- Packaging in ToR



Webcode # 11524  
**IE-PCB-SPM (circular connector M8)**  
Staight (180°) Single-Pair PCB male header for IP67

- Reflow-soldering (THR)
- Front and rear wll mounting possible
- Performance Category: up to 1Gbit/s
- Packaging in ToR



Webcode # 11525  
**IE-S1DS2VE00 and IE-PS-SP0**  
Single-Pair female plugs for IP20

- Pre-assembled patch cables
- Industrial design metal snap-in locking hook
- Shielded and reinforced contacts
- Performance Category: up to 1Gbit/s
- Plugging cycles: 750
- Packaging in bag



Webcode # 11526  
**IE-PCB-SPM (M8)**  
Staight (180°) Single-Pair PCB male and female header for IP67

- Inverse M8 System possible (PoDL coding)
- Performance Category: up to 1Gbit/s
- Packaging in bag

# OMNIMATE® Data

## Reliable data interfaces for your device

Plug-in connectors and jacks for data transmission are already an integral part of the future-proof device design. In the industrial environment, they have to stand up to exacting requirements and the ever-increasing data transmission rates demand high-quality on individual components.


The Weidmüller data connectors provide convincing solutions. RJ45, USB and D-SUB PCB connectors ensure a safe and efficient interface to your device.

The fully shielded product range boasts high levels of electromagnetic compatibility, caters to all established outlet angles, and includes latching hooks on the top and bottom as well as an innovative **STEADYTEC®** connection system for an industry-standard design.



### OMNIMATE® Data RJ45 modular and transformer jacks

- Future-proof transmission characteristics up to Cat 6 standard for a data rate of up to 1 Gbit/s
- Electromagnetic compatibility and protection through 360° shielding
- RJ45 transformer jacks with integrated "magnetics" actively counteract faults and save space on the board
- Reinforced gold layer improves corrosion protection, reduces contact problems and guarantees a long service life



### OMNIMATE® Data USB PCB jacks

- Robust plug & play operation - connect and disconnect without shutting down or restarting the system
- Reinforced gold surface - up to 1,500 plugging cycles meet the requirements for high resistance
- High rated current of up to 1.5 A provides sufficient safety reserves with a maximum charging current of 0.9 A
- Flexible deployment thanks to the compatibility of USB 3.0 hosts and devices with version 2.0



### OMNIMATE® Data D-SUB PCB connectors

- Simple installation - Due to the straight and angled designs, the sockets integrate into any installation situation.
- High performance – Established locking systems in combination with polarisation and protection of the contacts fulfil standards in electronical applications.
- Broad range of applications – In compliance with the dimensions according to IEC 60807-3 (IEC 807-3) and DIN 41652, a wide variety of applications, such as measuring devices, interfaces and electronic devices, are covered.



Learn more about our plug-in jack  
for data transmission in  
Industrial Ethernet environment.


[www.weidmueller.com/omnimate-data](http://www.weidmueller.com/omnimate-data)






OMNIMATE® Data – PCB jacks and plug-in connectors

PCB modular jack




Webcode #11413  
RJ45 solder connection for (THT)  
PCB jack for wave soldering process

- Outlet direction: 90° and 180°
- Catch mechanism: up and down
- Performance Category: up to Cat 6
- Plugging cycles: 750
- With / without LEDs



Webcode #11414  
RJ45 solder connection (THR)  
PCB jack for reflow and wave soldering process


- Outlet direction: 90° and 180°
- Catch mechanism: up and down
- Performance Category: up to Cat 6
- Plugging cycles: 750
- With / without LEDs



Webcode #11415  
RJ45 solder connection for (SMT)  
PCB jack for reflow soldering process


- Outlet direction: 90° and 180°
- Catch mechanism: up and down
- Performance Category: up to Cat 5
- Plugging cycles: 750
- With / without LEDs

RJ45 transformer jacks




Webcode #11416  
RJ45 solder connection for (THT)  
PCB jack for wave soldering process

- Integrated magnetics
- Outlet direction: 90°
- Catch mechanism: up and down
- Performance Category: up to 1Gbit/s
- Plugging cycles: 750




Webcode #11417  
RJ45 solder connection (THR)  
PCB jack for reflow and wave soldering process

- Integrated magnetics
- Outlet direction: 90° and 180°
- Catch mechanism: up and down
- Performance Category: up to 1Gbit/s
- Plugging cycles: 750
- With / without LEDs



Webcode #11418  
RJ45 solder connection (THT) multiport  
PCB jack for wave soldering process


- Integrated magnetics
- Outlet direction: 90°
- Catch mechanism: up and down
- Performance Category: up to 1Gbit/s
- Plugging cycles: 750
- With / without LEDs



Webcode #11419  
RJ45 solder connection (THR) multiport  
PCB jack for wave soldering process

- Integrated magnetics
- Outlet direction: 90°
- Catch mechanism: up and down
- Performance Category: up to 1Gbit/s
- Plugging cycles: 750
- With / without LEDs

Plug-in connectors



Webcode #11312  
RJ45 connector „steadytec“  
Tool-free and field-attachable plug for Industrial Ethernet

- IDC connection, 4-8-core
- Outlet direction: 180°
- Category: Cat.5 and Cat.6<sub>A</sub>
- AWG 26...AWG 22 / 0.48...0.76 mm²


Patch cable



Webcode #11313  
RJ45 patch cable  
Freely configurable RJ45 cable in a wide range of colours


- Protected latching hook, 8-core
- Outlet direction: 90°, 180° and 270°
- Category: Cat.6<sub>A</sub>

D-SUB connectors



Webcode #11528  
High-Density D-SUB solder connection for (THT)  
PCB connectors for wave soldering process

- Outlet direction: 90°
- Gender: femal, male
- Side termination: threaded nut
- Packed in tray




Webcode #11462  
D-SUB solder connection for (THT)  
PCB connectors for wave soldering process

- Outlet direction: 90° and 180°
- Gender: femal, male
- Side termination: hole, nut, bold
- Packed in tray


OMNIMATE® Data – PCB jacks and plug-in connectors

USB jacks




Webcode #11420  
USB 3.0/2.0 solder connection (THT)  
PCB jack for wave soldering process

- Outlet direction: 90° and 180°
- Performance Category: up to 5 Gbit/s
- Plugging cycles: ≥1.500
- Packed in tray



Webcode #11421  
USB 3.0 solder connection (THR)  
PCB jack for reflow and wave soldering process


- Outlet direction: 180°
- Performance Category: up to 5 Gbit/s
- Plugging cycles: ≥1.500
- Packed in tray or ToR



Webcode #11422  
USB 2.0 solder connection for (SMT)  
PCB jack for reflow soldering process (SMT)

- Outlet direction: 90°
- Performance Category: up to 5 Gbit/s
- Plugging cycles: ≥1.500
- Packed in ToR

Ethernet terminal




Webcode #11527  
LSF-SMT and LMF  
PCB terminal for Ethernet-compliant data transmission e.g. for PROFINET (up to 100Mbps)

- PUSH IN spring connection
- Pitch: 3.50, 3.81 and 5.08 mm
- Number of poles: 4
- For all IIoT devices


OMNIMATE® Data – M8 and M12 PCB jacks

M8




Webcode #11364  
M8 Dome (individual part)  
PCB circular connector for automatic assembly and M8 threads.

- Number of poles: 3, 4, 8
- Female and male contact
- SMT, THR
- Shielded and unshielded



Webcode #11366  
M8 Front mounting  
PCB circular connector with M8 thread for front mounting.


- Number of poles: 3, 4, 8
- Female and male contact
- Outlet direction: 180°
- Shielded and unshielded



Webcode #11368  
M8 Rear panel mounting  
PCB circular connector with M8 thread for rear panel mounting.


- Number of poles: 3, 4, 8
- Female and male contact
- Outlet direction: 90°, 180°
- Shielded and unshielded

M12




Webcode #11352  
M12 Dome (individual part)  
PCB circular connector for automatic assembly and M12 threads.

- Number of poles: 4, 5, 8
- Female and male contact
- SMT
- Shielded and unshielded
- Coding: A, B, D



Webcode #11354  
M12 Front mounting  
PCB circular connector with M12 thread for front mounting.

- Number of poles: 4, 5, 8
- Female and male contact
- Outlet direction: 90°, 180°
- Shielded and unshielded
- Coding: A, B, D, X



Webcode #11356  
M12 Front mounting  
PCB circular connector with M12 thread for front mounting.

- Number of poles: 4, 5, 8
- Female and male contact
- Outlet direction: 90°, 180°
- Shielded and unshielded
- Coding: A, B, D, X

SAI plugs and cables



Webcode #11529  
SAI round plug-in connectors and cables  
High IP rated connectivity range of M5, M8, M12, M16 and M23

- Different codings like A, B and D
- Up to protection degree IP 69K
- For mechanically and chemically stressed applications

## OMNIMATE® Signal


### Transmit numerous signals in the smallest possible space

A reliable device connection is an absolute must for your customised applications. With OMNIMATE® Signal, we can now offer you the right PCB-connection to meet your exact requirements.

You can choose from a product range that includes compact PCB terminals and connectors, which, thanks to intelligent locking concepts and high-performance connection systems, provides your design-in process with a wide range of application-specific solutions.


We have also not forgotten about your production processes when formulating our product range, as our THR and SMD components ensure the highest productivity levels during the reflow soldering process.

#### OMNIMATE® Signal PCB terminals



- Application-oriented connection systems ranging from clamping yoke screw connections to PUSH IN spring connections in all relevant cross-section ranges up to 6 mm<sup>2</sup>
- Can be used universally in all standard pitches from 3.50 mm to 7.62 mm
- A wide range of reflow-compatible products for automated SMT processes
- Compact, multi-layer designs up to 72-pole


#### OMNIMATE® Signal PCB plug-in connectors



- Compact at 2.50 mm pitch  
36 connections at 3.50 mm pitch, highest level of power reserves at 3.81 mm pitch and largest application area at 5.08 mm pitch
- Application-oriented connection systems ranging from clamping yoke screw connections to PUSH IN spring connections.
- A wide range of reflow-compatible products for automated SMT processes
- Multi-row and multi-layer designs up to 48-pole

#### OMNIMATE® Signal Board-to-Board connectors

- Industrial suitable density combined with high flexible connection combinations (mezzanine, mother-to-daughter, extended-board and Board-to-wire)
- Pitch 1,27mm from 12 – 80 poles in different outlet-directions and heights
- Developed for automatic assembly with high precise pin coplanarity and SMT-fixation
- Reliable contact surface (PdNi-Au) equipped in high-performance material LCP and packed in Tape on reel for automatic assembly




Learn more about our full-range signal solutions that includes extremely compact PCB terminals and connectors.  
[www.weidmueller.com/omnimate-signal](http://www.weidmueller.com/omnimate-signal)






OMNIMATE® Signal – PCB terminals

Clamping yoke screw connection




**Webcode #01010**  
**LM 3.50 / LM1N / LM2N**  
Small, compact PCB terminal with conductor outlet direction of 90° or 135°.

- Clamping yoke screw connection
- Pitch: 3.50 mm
- Number of poles: 2-12
- IEC: 320 V / 16 A / 0.2-1.5 mm²
- UL: 300 V / 10 A / AWG 28-14




**Webcode #01012**  
**LM 5.00/5.08**  
Single-row PCB terminal with conductor outlet direction of 90°, 135° and 180°.

- Clamping yoke screw connection
- Pitch: 5.00 mm / 5.08 mm
- Number of poles: 2-24
- IEC: 630 V / 17.5 A / 0.2-2.5 mm²
- UL: 300 V / 15 A / AWG 24-14



**Webcode #01014**  
**LS 5.08**  
Small, compact PCB terminal with conductor outlet direction of 90°.


- Clamping yoke screw connection
- Pitch: 5.08 mm
- Number of poles: 2-12
- IEC: 630 V / 17.5 A / 0.08-1.5 mm²
- UL: 300 V / 15 A / AWG 28-14



**Webcode #01016**  
**LL 5.00/5.08**  
Single-row PCB terminal with conductor outlet direction of 90° and 180°.

- Clamping yoke screw connection
- Pitch: 5.00 mm / 5.08 mm
- Number of poles: 2-24
- IEC: 500 V / 32.5 A / 0.5-6 mm²
- UL: 300 V / 20 A / AWG 28-12


Clamping yoke screw connection



**Webcode #01018**  
**LL 9.52**  
Single-row PCB terminal with conductor outlet direction of 90°.

- Clamping yoke screw connection
- Pitch: 9.52 mm
- Number of poles: 2-3
- IEC: 1,000 V / 32 A / 0.18-6 mm²
- UL: 300 V / 30 A / AWG 26-10


TOP - screw connection



**Webcode #01024**  
**TOP**  
PCB terminal with conductor insertion and contact point actuation from the same direction.


- TOP screw connection
- Pitch: 5.08 mm / 6.35 mm / 7.62 mm
- Number of poles: 2-24
- IEC: 630 V / 24 A / 0.2-2.5 mm²
- UL: 300 V / 10 A / AWG 26-14

Leaf - spring screw connection



**Webcode #01020**  
**PS 3.5**  
Very small and compact PCB terminal with conductor outlet direction of 90°.


- Leaf-spring screw connection
- Pitch: 3.50 mm
- Number of poles: 2-12
- IEC: 320 V / 17.5 A / 0.2-1.5 mm²
- UL: 300 V / 10 A / AWG 28-16



**Webcode #01022**  
**PM 5.00/5.08**  
PCB terminal with conductor inlet direction of 90°.


- Leaf-spring screw connection
- Pitch: 5.00 mm / 5.08 mm
- Number of poles: 2-12
- IEC: 600 V / 24 A / 0.13-2.5 mm²
- UL: 300 V / 15 A / AWG 26-14

PUSH IN - spring connection




**Webcode #01028**  
**LSF-SMT 3.5 / 3.81**  
PCB terminal for fully automatic assembly for THR reflow soldering (SMT) and wave soldering.

- PUSH IN spring connection
- Pitch: 3.50 mm / 3.81 mm
- Number of poles: 2-24
- IEC: 320 V / 17.5 A / 0.2-1.5 mm²
- UL: 300 V / 12 A / AWG 24-16




**Webcode #01030**  
**LSF-SMT 5.00 / 5.08**  
PCB terminal for fully automatic assembly for THR reflow soldering (SMT) and wave soldering.

- PUSH IN spring connection
- Pitch: 5.00 mm / 5.08 mm
- Number of poles: 2-8
- IEC: 500 V / 17.5 A / 0.2-1.5 mm²
- UL: 300 V / 12 A / AWG 24-16



**Webcode #01032**  
**LSF-SMT 7.50 / 7.62**  
PCB terminal for fully automatic assembly for THR reflow soldering (SMT) and wave soldering.

- PUSH IN spring connection
- Pitch: 7.50 mm / 7.62 mm
- Number of poles: 2-8
- IEC: 800 V / 17.5 A / 0.2-1.5 mm²
- UL: 300 V / 12 A / AWG 24-16




**Webcode #01034**  
**LSF-SMD 3.5**  
PCB terminal for fully automatic assembly for reflow soldering (SMT).

- PUSH IN spring connection
- Pitch: 3.50 mm
- Number of poles: 2-12
- IEC: 320 V / 17.5 A / 0.2-1.5 mm²
- UL: 300 V / 12 A / AWG 24-16


OMNIMATE® Signal – PCB terminals

PUSH IN - spring connection




**Webcode #01036**  
**LSF-SMD 5.00**  
PCB terminal for fully automatic assembly for reflow soldering (SMT).

- PUSH IN spring connection
- Pitch: 5.00 mm
- Number of poles: 2-8
- IEC: 500 V / 17.5 A / 0.2-1.5 mm²
- UL: 300 V / 12 A / AWG 24-16



**Webcode #01038**  
**LSF-SMD 7.50**  
PCB terminal for fully automatic assembly for reflow soldering (SMT).


- PUSH IN spring connection
- Pitch: 7.50 mm
- Number of poles: 2-6
- IEC: 800 V / 17.5 A / 0.2-1.5 mm²
- UL: 300 V / 12 A / AWG 24-16



**Webcode #01040**  
**LMF 5.00/5.08**  
PCB terminal with pusher for opening the contact point and an integrated test point.


- PUSH IN spring connection
- Pitch: 5.00 mm / 5.08 mm
- Number of poles: 2-24
- IEC: 400 V / 24 A / 0.2-2.5 mm²
- UL: 300 V / 10 A / AWG 26-12

PUSH IN - spring connection




**Webcode #01042**  
**LMFS 5.00/5.08**  
PCB terminal without pusher; contact point can be opened using a screwdriver and integrated test point.

- PUSH IN spring connection
- Pitch: 5.00 mm / 5.08 mm
- Number of poles: 2-24
- IEC: 400 V / 24 A / 0.2-2.5 mm²
- UL: 300 V / 10 A / AWG 26-12




**Webcode #01026**  
**LS2HF 3.50**  
Double-storey PCB terminal for wave soldering processes, with conductor insertion and slider operation from the same direction (TOP).

- PUSH IN spring connection
- Pitch: 3.50 mm
- Number of poles: 4-24
- IEC: 400 V / 10 A / 0.14-1.5 mm²
- UL: 150 V / 12.5 A / AWG 26-16



**Webcode #11514**  
**LMF 7.50**  
PCB terminal with pusher for opening the contact point and an integrated test point.


- PUSH IN spring connection
- Pitch: 7.50 mm
- Number of poles: 2-24
- IEC: 1000 V / 24 A / 0.2-2.5 mm²
- UL: 300 V / 20 A / AWG 26-12



**Webcode #11515**  
**LMFS 7.50**  
PCB terminal without pusher; contact point can be opened using a screwdriver and integrated test point.

- PUSH IN spring connection
- Pitch: 7.50 mm
- Number of poles: 2-24
- IEC: 1000 V / 24 A / 0.2-2.5 mm²
- UL: 300 V / 20 A / AWG 26-12


PUSH IN - spring connection



**Webcode #11448**  
**LMZF**  
Single-row PCB terminal with maintenance-free tension clamp connection and with conductor outlet direction of 135°.

- Tension clamp connection
- Pitch: 5, 7 & 10 mm
- Number of poles: 2-24
- IEC: 630 V/24 A / 0.13 - 2.5 mm²
- UL: 300 V/15 A / AWG 26-AWG 14

Tension clamp connection




**Webcode #11447**  
**LM2NZF & LM3RZF**  
Multi-level PCB terminal with conductor outlet direction of 135°.

- Tension clamp connection
- Pitch: 5.08 mm
- Number of poles: 2-24
- IEC: 630 V/24 A / 0.13 - 2.5 mm²
- UL: 300 V/15 A / AWG 26-AWG 14




OMNIMATE® Board-to-Board connectors

Pitch 1.27 mm




Webcode #11516  
**FMH1**  
Male header with stack hight 1.75 mm

- Reflow-soldering (SMT) -Pitch: 1.27 mm
- Number of poles: 12-80
- Clear. and creepage distance: min. 0.4 mm
- IEC: 2.8 A (20°C, 12 pole)
- UL: 150 V / 1.7 A (12 pole)



Webcode #11517  
**FMH3**  
Male header with stack hight 3.25 mm


- Reflow-soldering (SMT) -Pitch: 1.27 mm
- Number of poles: 12-80
- Clear. and creepage distance: min. 0.4 mm
- IEC: 2.8 A (20°C, 12 pole)
- UL: 150 V / 1.7 A (12 pole)



Webcode #11518  
**FMH**  
Male header, angled


- Reflow-soldering (SMT) -Pitch: 1.27 mm
- Number of poles: 12-80
- Clear. and creepage distance: min. 0.4 mm
- IEC: 2.8 A (20°C, 12 pole)
- UL: 150 V / 1.7 A (12 pole)

Pitch 1.27 mm




Webcode #11519  
**FFH6**  
Female header with stack hight 6.25 mm

- Reflow-soldering (SMT) -Pitch: 1.27 mm
- Number of poles: 12-80
- Clear. and creepage distance: min. 0.4 mm
- IEC: 2.8 A (20°C, 12 pole)
- UL: 150 V / 1.7 A (12 pole)




Webcode #11520  
**FFH9**  
Female header with stack hight 9.05 mm

- Reflow-soldering (SMT) -Pitch: 1.27 mm
- Number of poles: 12-80
- Clear. and creepage distance: min. 0.4 mm
- IEC: 2.8 A (20°C, 12 pole)
- UL: 150 V / 1.7 A (12 pole)



Webcode #11521  
**FFH**  
Female header, angled

- Reflow-soldering (SMT) -Pitch: 1.27 mm
- Number of poles: 12-80
- Clear. and creepage distance: min. 0.4 mm
- IEC: 2.8 A (20°C, 12 pole)
- UL: 150 V / 1.7 A (12 pole)




Webcode #11522  
**FFP**  
Female plug

- IDC-Connection
- Pitch: 1.27 mm -Number of poles: 12-80
- Clear. and creepage distance: min. 0.4 mm
- IEC: 2.8 A (20°C, 12 pole)
- UL: 150 V / 1.0 A (12 pole) / AWG 30


OMNIMATE® Signal – PCB connectors

Pitch 2.50 mm



Webcode #11323  
**BLF 2.50**  
Female plug for conductor connection with PUSH IN spring connection.


- PUSH IN spring connection
- Pitch: 2.50 mm
- Number of poles: 2-12
- IEC: 320 V / 6 A / 0.08 – 0.5 mm²
- UL: 150 V / 5 A / AWG 28 - 20



Webcode #11324  
**SL 2.50**  
Male header for wave soldering methods for 2.50 mm pitch.


- Male header
- Pitch: 2.50 mm
- Number of poles: 2-12
- IEC: 320 V / 6 A
- UL: 320 V / 6 A

Pitch 3.50 mm double - row design



Webcode #01060  
**S2C 3.50**  
High-temperature-resistant, double-row male header for reflow and wave soldering methods.


- Male header
- Pitch: 3.50 mm
- Number of poles: 4-36
- IEC: 200 V / 13.4 A
- UL: 150 V / 10 A



Webcode #01058  
**B2CF 3.50**  
Compact double-row female plug with maximum connection density within an extremely small space.


- PUSH IN spring connection
- Pitch: 3.50 mm
- Number of poles: 4-46
- IEC: 320 V / 13.4 A / 0.14-1.5 mm²
- UL: 300 V / 9.5 A / AWG 26-16

Pitch 3.50 mm




Webcode #01068  
**SL-SMT 3.50**  
High-temperature-resistant male header for reflow and wave soldering methods.

- Male header
- Pitch: 3.50 mm
- Number of poles: 2-24
- IEC: 320 V / 15 A
- UL: 300 V / 10 A




Webcode #01072  
**SL 3.50**  
Male header for wave soldering methods.

- Male header
- Pitch: 3.50 mm
- Number of poles: 2-24
- IEC: 320 V / 17 A
- UL: 300 V / 10 A



Webcode #01066  
**BL 3.50**  
Female plug for conductor connection with clamping yoke screw connection.


- Clamping yoke screw connection
- Pitch: 3.50 mm
- Number of poles: 2-24
- IEC: 320 V / 17 A / 0.2-1.5 mm²
- UL: 300 V / 10 A / AWG 28-14



Webcode #11410  
**BLF 3.5**  
Female plug with PUSH IN spring connection


- PUSH IN spring connection
- Pitch: 3.50 mm
- Number of poles: 2-24
- IEC: 320 V / 14.5 A / 0.2 – 1.5 mm²
- UL: 300 V / 9.5 A / AWG 28-16

Pitch 3.50 mm




Webcode #01064  
**BL-I/O 3.5**  
Extremely compact female plug in one or three-row design and with an integrated LED display.

- PUSH IN spring connection
- Pitch: 3.50 mm
- Number of poles: 10 & 30
- IEC: 200 V / 2.2 A / 0.2-1 mm²
- UL: 50 V / 5 A / AWG 24-16




Webcode #11445  
**BL-I/O CJC**  
Compact female plug with integrated cold junction compensation.

- PUSH IN spring connection
- Pitch: 3.50 mm
- Number of poles: 10
- IEC: 50 -V / 2.2 A / 0.2 – 1.5 mm²
- UL: 50 V / 5 A / AWG 24 – 16



Webcode #01076  
**SC-SMT 3.81**  
High-temperature-resistant male header with a very low profile for reflow and wave soldering methods.

- Male header
- Pitch: 3.81 mm
- Number of poles: 2-16
- IEC: 320 V / 17.5 A
- UL: 300 V / 10 A




Webcode #01080  
**SC 3.81**  
Male header with a very low profile for wave soldering methods.

- Male header
- Pitch: 3.81 mm
- Number of poles: 2-20
- IEC: 320 V / 17.5 A
- UL: 300 V / 10 A


OMNIMATE® Signal – PCB connectors

Pitch 3.81 mm




Webcode #11316  
**SCZ 3.81**  
Compact male plug for conductor connection with clamping yoke screw connection.

- Clamping yoke screw connection
- Pitch: 3.81 mm
- Number of poles: 2-12
- IEC: 320 V / 17.5 A / 0.14-1.5 mm²
- UL: 300 V / 10 A / AWG 28-16




Webcode #01074  
**BCZ 3.81**  
Compact female plug for conductor connection with clamping yoke screw connection.

- Clamping yoke screw connection
- Pitch: 3.81 mm
- Number of poles: 2-20
- IEC: 320 V / 17.5 A / 0.14-1.5 mm²
- UL: 300 V / 10 A / AWG 28-16



Webcode #01078  
**BCF 3.81**  
Female plug with very low profile for conductor connection with PUSH IN spring connection.

- PUSH IN spring connection
- Pitch: 3.81 mm
- Number of poles: 2-18
- IEC: 320 V / 17.5 A / 0.2-1.5 mm²
- UL: 300 V / 10 A / AWG 28-16




Webcode #01082  
**BCL-SMT 3.81**  
High-temperature-resistant female header with a very low profile for reflow soldering methods.

- Female header
- Pitch: 3.81 mm
- Number of poles: 2-12
- IEC: 320 V / 17.5 A
- UL: 300 V / 10 A




OMNIMATE® Signal – PCB connectors

Pitch 5.00 mm




**Webcode #11444**  
**SL-SMT 5.00HC**  
High-temperature-resistant, bent pin header, optimized for automatic assembly and reflow and wave soldering.

- Male header
- Pitch: 5.00 mm
- Number of poles: 2-24
- IEC: 400 V / 27.5 A
- UL: 300 V / 18.5 A




**Webcode #11443**  
**SL-SMaT 5.0xHC**  
High-temperature-resistant, modular pin header.

- High-current male header
- Pitch: 5.0x mm
- Number of poles: 2 & 3
- IEC: 400 V / 27.5 A
- UL: 300 V / 15 A



**Webcode #01095**  
**SL 5.00**  
Pin headers with solder pin length optimized for wave flow soldering.


- Male header
- Pitch: 5.00 mm
- Number of poles: 2-24
- IEC: 400 V / 24 A
- UL: 300 V / 18.5 A



**Webcode #11461**  
**SLD 5.00**  
2-tier male header with parallel pin arrangement with outlet direction of 90° & 180°, optimized for wave soldering methods.


- Male header
- Pitch: 5.00 mm
- Number of poles: 4-48
- IEC: 400 V / 15 A
- UL: 300 V / 10 A

Pitch 5.00 mm



**Webcode #01165**  
**BLZP 5.00HC**  
High-current-female-plug for outlet direction of 90°, 180° or 270°.


- Clamping yoke screw connection
- Pitch: 5.00 mm
- Number of poles: 2-24
- IEC: 400 V / 23 A / 0.2-4 mm²
- UL: 300 V / 20 A / AWG 30-12



**Webcode #11442**  
**BLF 5.00HC**  
Compact high-current-female-plug for outlet direction of 90°, 180° or 270°.


- PUSH IN spring connection
- Pitch: 5.00 mm
- Number of poles: 2-24
- IEC: 400 V / 24 A / 0.2-2.5 mm²
- UL: 300 V / 18.5 A / AWG 26-12

Pitch 5.08 mm




**Webcode #01090**  
**SL-SMT 5.08HC**  
Highly temperature-resistant angled male header optimised for automatic assembly and for reflow and wave soldering methods.

- Male header
- Pitch: 5.08 mm
- Number of poles: 2-24
- IEC: 400 V / 27.5 A
- UL: 300 V / 18.5 A




**Webcode #11441**  
**SLDV-THR 5.08**  
High-temperature resistant, double level, laterally offset, male connector with flange or solder flange.

- Male header
- Pitch: 5.08 mm
- Number of poles: 4-48
- IEC: 400 V / 15 A
- UL: 300 V / 10 A



**Webcode #01094**  
**SL 5.08HC**  
Male headers in glass-fibre-reinforced plastic, optimised for wave soldering methods.


- Male header
- Pitch: 5.08 mm
- Number of poles: 2-24
- IEC: 400 V / 24 A
- UL: 300 V / 18.5 A



**Webcode #11440**  
**SLD 5.08**  
2-tier male header with parallel or laterally offset pin arrangement with with outlet direction of 90° & 180°, optimized for wave solving methods.


- Male header, parallel or laterally offset
- Pitch: 5.08 mm
- Number of poles: 4-48
- IEC: 400 V / 15 A
- UL: 300 V / 10 A

Pitch 5.08 mm




**Webcode #01098**  
**SLF 5.08**  
Male plugs with straight outlet direction provide space for labelling and can be coded.

- PUSH IN spring connection
- Pitch: 5.08 mm
- Number of poles: 2-12
- IEC: 400 V / 25.9 A / 0.2-2.5 mm²
- UL: 300 V / 14 A / AWG 26-12




**Webcode #01087**  
**SLS 5.08**  
Male plug with clamping-yoke screw wire-connect system. Clamping yoke screw connection

- Pitch: 5.08 mm
- Number of poles: 2-24
- IEC: 400 V/21.5 A / 0.2-2.5 mm²
- UL: 300 V/14 A / AWG 26-AWG 12



**Webcode #01102**  
**SLT 5.08**  
Male plugs with straight outlet direction provide space for labelling and can be coded.


- TOP screw connection system
- Pitch: 5.08 mm
- Number of poles: 2-16
- IEC: 400 V / 16 A / 0.2-2.5 mm²
- UL: 300 V / 15 A / AWG 26-14



**Webcode #01084**  
**BLZP 5.08HC**  
High-current female plug for conductor connection with 90°, 180° to 225° and 270° outlet direction.


- Clamping yoke screw connection
- Pitch: 5.08 mm
- Number of poles: 2-24
- IEC: 400 V / 23 A / 0.2-4 mm²
- UL: 300 V / 20 A / AWG 30-12

Pitch 5.08 mm




**Webcode #01092**  
**BLT 5.08HC**  
High-current female plug for conductor connection with a straight 180° outlet direction and space for labelling.

- TOP screw connection
- Pitch: 5.08 mm
- Number of poles: 2-24
- IEC: 400 V / 27 A / 0.2-2.5 mm²
- UL: 300 V / 17 A / AWG 26-14




**Webcode #01088**  
**BLF 5.08HC**  
Compact high-current female plug for conductor outlet directions of 90° to 180° and 270°.

- PUSH IN spring connection
- Pitch: 5.08 mm
- Number of poles: 2-24
- IEC: 400 V / 24 A / 0.2-2.5 mm²
- UL: 300 V / 18.5 A / AWG 26-12



**Webcode #01096**  
**BLC 5.08**  
Female plug to allow for the pre-assembly of wiring harnesses in large quantities.


- Crimp connection system
- Pitch: 5.08 mm
- Number of poles: 2-16
- IEC: 400 V / 21 A
- UL: 300 V / 10 A / AWG 26-14



**Webcode #01100**  
**BLL 5.08**  
Female header for PCB assembly with 90° and 180° outlet direction and optimised solder pin length for wave soldering methods.


- Female header
- Pitch: 5.08 mm
- Number of poles: 2-24
- IEC: 400 V / 23 A
- UL: 300 V / 15 A

Rectangular connector



**Webcode #11360**  
**RSV 1.6 C**  
Rectangular connector for a high component density, for use as a free coupling or a PCB variant.


- Crimp connection system
- Pitch: 5.00 mm
- Number of poles: 4-36
- IEC: 630 V / 17 A
- UL: 600 V / 10 A / AWG 26-12




**Webcode #01106**  
**RSV 1.6 L**  
Rectangular connector with solder pin and solder jack contacts for PCB applications.

- Solder pin contacts
- Pitch: 5.00 mm
- Number of poles: 4-36
- IEC: 500 V / 14 A
- UL: 300 V / 10 A


Accessories



**Webcode #11439**  
**Accessories**  
For signal PCB terminals



**Webcode #11438**  
**Accessories**  
For signal PCB connectors




# OMNIMATE® Power

## Powerful connections with maximum security

New products and innovations help to shake up the market. Many power electronics applications are constantly evolving at a rapid pace, causing the requirements placed on connection systems to increase as well.

As specialists with a great deal of experience, we know the maximum power and security requirements that you place on your electronic devices. Our high-performance PCB terminals, PCB connectors and panel feedthrough terminal blocks therefore also comply with applicable device standards such standard for speed-controlled drive technology.


Our Power products also fully achieve 600 volts in accordance with UL standards. PCB terminal blocks with PUSH IN wire connection and application-specific plug-in connectors for motor connection with shield support complete the range.



### OMNIMATE® Power PCB terminals




- High-power to 150 A / 1000 V (IEC) or 127 A / 600 V (UL)
- Application-oriented scalability with connection cross-sections from 16 mm<sup>2</sup> to 50 mm<sup>2</sup>
- Simple UL device approval up to 600 V
- PUSH IN wire connection up to 16 mm<sup>2</sup>
- Maintenance-free steel clamping yoke for vibration-resistant screw connections



### OMNIMATE® Power PCB plug-in connectors



- Application-oriented scalability: from the compact 4 mm<sup>2</sup> connector for 29 A (IEC) or 20 A (UL) up to the sturdy 16 mm<sup>2</sup> connector for 76 A (IEC) or 60 A (UL)
- Unlimited usage up to 1000 V (IEC) or 600 V (UL)
- A variety of application-optimised mounting options



### OMNIMATE® Power Panel feedthrough terminal blocks



- Clamping yoke screw connection
- PUSH IN wire connection
- Wall and housing feedthrough
- Simple, flexible and cost-saving assembly and connection of conductors
- Cable lug
- Solder connection




Learn more about our application-oriented connection solutions for your power electronics devices at:  
[www.weidmueller.com/omnimate-power](http://www.weidmueller.com/omnimate-power)




OMNIMATE® Power – PCB terminals

Clamping yoke screw connection




**Webcode #01044**  
**LL 6.35**  
High-performance PCB terminal with offset solder pins and conductor outlet direction of 90°.

- Clamping yoke screw connection
- Pitch: 6.35 mm
- Number of poles: 2–12
- IEC: 1.000 V / 32 A / 0.18–6 mm<sup>2</sup>
- UL: 600 V / 30 A / AWG 26–10




**Webcode #01048**  
**LU 10.16**  
High-performance PCB terminal with offset solder pins and conductor outlet direction of 90°.

- Clamping yoke screw connection
- Pitch: 10.16 mm
- Number of poles: 2–10
- IEC: 1.000 V / 76 A / 0.5–16 mm<sup>2</sup>
- UL: 300 V / 65 A / AWG 26–6



**Webcode #01050**  
**LUP 10.16 V with test point**  
High-performance PCB terminal with integrated test point and conductor outlet direction of 90°.


- Clamping yoke screw connection
- Pitch: 10.16 mm
- Number of poles: 2–9
- IEC: 1.000 V / 76 A / 0.5–16 mm<sup>2</sup>
- UL: 600 V / 51 A / AWG 26–6



**Webcode #01052**  
**LUP 12.70 with test point**  
High-performance PCB terminal with integrated test point and conductor outlet direction of 90°.


- Clamping yoke screw connection
- Pitch: 12.70 mm
- Number of poles: 2–9
- IEC: 1.000 V / 76 A / 0.5–16 mm<sup>2</sup>
- UL: 600 V / 58 A / AWG 26–6

Clamping yoke screw connection



**Webcode #01054**  
**LX 15.00 with test point**  
High-performance PCB terminal with integrated test point and conductor outlet direction of 90°.


- Clamping yoke screw connection
- Pitch: 15.00 mm
- Number of poles: 1–9
- IEC: 1.000 V / 101 A / 1.5–25 mm<sup>2</sup>
- UL: 600 V / 85 A / AWG 16–4



**Webcode #01056**  
**LXXX 15.00 with test point**  
High-performance PCB terminal with integrated test point and conductor outlet direction of 90°.


- Clamping yoke screw connection
- Pitch: 15.00 mm
- Number of poles: 1–9
- IEC: 1.000 V / 150 A / 0.5–50 mm<sup>2</sup>
- UL: 600 V / 127 A / AWG 20–1

PUSH IN spring connection




**Webcode #11408**  
**LLF / LLFS 7.5**  
Highly reliable PCB terminals with integrated test point and conductor outlet direction of 90° and 180°.

- PUSH IN spring connection
- Fast wiring without tool (LLF 7.50)
- Pitch: 7.5 mm
- Number of poles: 1–12
- IEC: 1.000 V / 41 A / 0.5–6 mm<sup>2</sup>
- UL: 600 V / 35 A / AWG 24–8



**Webcode #01046**  
**LUF / LUFS 10**  
Highly reliable PCB terminals with integrated test point and conductor outlet direction of 90° and 180°.

- PUSH IN spring connection
- Fast wiring without tool (LUF10)
- Pitch: 10.00 mm
- Number of poles: 1–12
- IEC: 1.000 V / 76 A / 0.5–16 mm<sup>2</sup>
- UL: 600 V / 61 A / AWG 18–6




**Webcode #11409**  
**LUF / LUFS 15**  
Highly reliable PCB terminals with integrated test point and conductor outlet direction of 90° and 180°.

- PUSH IN spring connection
- Fast wiring without tool (LUF 15)
- Pitch: 15.00 mm
- Number of poles: 2–8
- IEC: 1.000 V / 76 A / 0.5–16 mm<sup>2</sup>
- UL: 1.000 V / 57 A / AWG 18–6


OMNIMATE® Power – PCB connectors

OMNIMATE® Power Hybrid




**Webcode #11437**  
**SV-SMT 7.62 hybrid**  
High-temperature-resistant hybrid male header with energy and signal contacts.

- Male header
- Pitch: 7.62 mm
- Pole count: 2/4–5/8
- IEC: 1.000 V / 41 A
- UL: 300 V / 35 A




**Webcode #01112**  
**SV 7.62 hybrid**  
Hybrid male header with energy and signal contacts.

- Male header
- Pitch: 7.62 mm
- Pole count: 2/4–5/8
- IEC: 1.000 V / 41 A
- UL: 300 V / 35 A



**Webcode #11465**  
**BVF 7.62HP hybrid**  
Hybrid female plug - the perfect 2-in-1 solution for the simultaneous combination of energy and signals. Available with plug-in EMC shield support on request.


- PUSH IN spring connection
- Pitch: 7.62 mm
- Pole count: 2/4–5/8
- IEC: 1.000 V / 38 A / 0.5–10 mm<sup>2</sup>
- UL: 600 V / 35 A / AWG 24–8



**Webcode #11466**  
**BVFL 7.62 hybrid**  
Hybrid female plug with Wire-Ready PUSH IN the perfect 2-in-1 solution for the simultaneous combination of energy and signals.


- Wire-Ready PUSH-IN spring connection
- Pitch: 7.62 mm
- Pole count: 2 / 4–5 / 8
- IEC: 1.000 V / 38 A / 0.5–6 mm
- UL: 600 V / 35 A / AWG 24–8

OMNIMATE® Power Hybrid




**Webcode #11467**  
**BVF 7.62 hybrid with pluggable shield connection**  
Hybrid female plug with pluggable shield connection to printed circuit board.

- PUSH IN spring connection
- Pitch: 7.62 mm
- Pole count: 4–4
- IEC: 1.000 V / 38 A / 0.5–10 mm
- UL: 600 V / 35 A / AWG 24–8




**Webcode #11468**  
**BVLF 7.62 hybrid with pluggable shield connection**  
Hybrid female plug with Wire-Ready PUSH IN and pluggable shield connection to printed circuit board.

- Wire-Ready PUSH IN spring connection
- Pitch: 7.62 mm
- Pole count: 4–4
- IEC: 1.000 V / 38 A / 0.5–6 mm
- UL: 600 V / 35 A / AWG 24–8



**Webcode #11481**  
**BVF 7.62 hybrid with pluggable shield connection**  
Hybrid female plug with pluggable shield connection to the device metall housing.


- PUSH IN spring connection
- Pitch: 7.62 mm
- Pole count: 4–4
- IEC: 1.000 V / 38 A / 0.5–10 mm
- UL: 600 V / 35 A / AWG 24–8



**Webcode #11480**  
**BVFL 7.62 hybrid with pluggable shield connection**  
Hybrid female plug with Wire-Ready PUSH-IN and pluggable shield connection to the device metall housing.


- Wire-Ready PUSH IN spring connection
- Pitch: 7.62 mm
- Pole count: 4–4
- IEC: 1.000 V / 38 A / 0.5–6 mm
- UL: 600 V / 35 A / AWG 24–8

OMNIMATE® Power IT




**Webcode #01116**  
**SL 7.62IT**  
Male header with optional solder flange attachment and with leading contact for IT networks.

- Male header
- Pitch: 7.62 mm
- Number of poles: 2–6
- IEC: 630 V / 29 A
- UL: 300 V / 20 A




**Webcode #01114**  
**BLZ 7.62IT**  
Female plug with 180° outlet direction and touch safety for IT networks with self-locking centre flange.

- Clamping yoke screw connection
- Pitch: 7.62 mm
- Number of poles: 2–6
- IEC: 1.000 V / 41 A / 0.2–6 mm<sup>2</sup>
- UL: 600 V / 40.5 A / AWG 24–8



**Webcode #11469**  
**SV-SMT 7.62IT**  
High temperature-resistant male haeder with leading contact for IT-networks.

- Male header
- Pitch: 7.62 mm
- Number of poles: 2–5
- IEC: 1.000 V / 41 A
- UL: 300 V / 40.5 A




**Webcode #01120**  
**SV 7.62IT**  
Male header with optional solder flange attachment and with leading contact for IT networks.

- Male header
- Pitch: 7.62 mm
- Number of poles: 2–4
- IEC: 1.000 V / 41 A
- UL: 300 V / 40.5 A

OMNIMATE® Power – PCB connectors

OMNIMATE® Power IT




Webcode #01118

**BVZ 7.62IT**

Female plug with 180° outlet direction and touch safety for IT networks with self-locking centre flange.

- Clamping yoke screw connection
- Pitch: 7.62 mm
- Number of poles: 2-4
- IEC: 1,000 V / 41 A / 0.2-6 mm²
- UL: 600 V / 40.5 A / AWG 24-8




Webcode #01124

**SU 10.16IT**

Male header with optional solder flange attachment and with leading contact for computer networks.

- Male header
- Pitch: 10.16 mm
- Number of poles: 2-4
- IEC: 1,000 V / 76 A
- UL: 300 V / 60 A




Webcode #01122

**BUZ 10.16IT**

Female plug with 180° outlet direction and touch safety for IT networks with self-locking centre flange.

- Clamping yoke screw connection
- Pitch: 10.16 mm
- Number of poles: 2-4
- IEC: 1,000 V / 78 A / 0.2-16 mm²
- UL: 300 V / 60 A / AWG 22-4




Webcode #11479

**BUZ 10.16IT SH**

Female plug with 180° outlet direction and touch safety for IT networks with self-locking centre flange and pluggable shield connection to the device metall housing.

- Clamping yoke screw connection
- Pitch: 10.16 mm
- Number of poles: 3-4
- IEC: 1,000 V / 76 A / 2.5-16 mm²
- UL: 600 V / 55 A / AWG 22-4

OMNIMATE® Power IT




Webcode #11407

**BUF 10.16IT**

Female plug with 180° outlet direction for IT networks with self-locking centre flange.

- PUSH IN spring connection
- Pitch: 10.16 mm
- Number of poles: 2-5
- IEC: 1,000 V / 76 A / 2.5 - 16 mm²
- UL: 600 V / 55 A / AWG 12 - AWG 4




Webcode #11471

**BUF 10.16IT SH**

Female plug with 180° outlet direction and touch safety for IT networks with self-locking centre flange and pluggable shield connection to the device metall housing.

- PUSH IN spring connection
- Pitch: 10.16 mm
- Number of poles: 3-4
- IEC: 1,000 V / 76 A / 2.5-16 mm²
- UL: 600 V / 55 A / AWG 12-4

OMNIMATE® Power HP pitch 4 mm²




Webcode #01130

**SL 7.62HP**

Male header with single compartment mating profile and touch protection.

- Male header
- Pitch: 7.62 mm
- Number of poles: 2-12
- IEC: 630 V / 29 A
- UL: 300 V / 20 A




Webcode #01132

**SLZ 7.62HP**

Male plug with single compartment mating profile with 180° outlet direction as touch-safe solution for the reverse voltage in HP networks.

- Clamping yoke screw connection
- Pitch: 7.62 mm
- Number of poles: 2-5
- IEC: 1,000 V / 20 A / 0.5-2.5 mm²
- UL: 600 V / 17 A / AWG 20-12




Webcode #01134

**SLF 7.62HP**

Male plug with single compartment mating profile with 180° outlet direction as touch-safe solution for the reverse voltage in HP networks.

- PUSH IN spring connection
- Pitch: 7.62 mm
- Number of poles: 2-5
- IEC: 1,000 V / 24 A / 0.5-2.5 mm²
- UL: 600 V / 20 A / AWG 20-12




Webcode #11472

**SLF 7.62HP SH**

Male plug with single compartment mating profile with 180° outlet direction as touch-safe solution for the reverse voltage in HP networks, with pluggable shield connection to the device metall housing.

- PUSH IN spring connection
- Pitch: 7.62 mm
- Number of poles: 4
- IEC: 1,000 V / 24 A / 0.5-2.5 mm²
- UL: 600 V / 20 A / AWG 20-12

OMNIMATE® Power HP pitch 4 mm²




Webcode #01126

**BLZ 7.62HP**

Female plug with single compartment mating profile with 180° outlet direction and touch protection for HP networks.

- Clamping yoke screw connection
- Pitch: 7.62 mm
- Number of poles: 2-12
- IEC: 630 V / 29 A / 0.2-4 mm²
- UL: 600 V / 20 A / AWG 20-12




Webcode #01128

**BLF 7.62HP**

Female plug with single compartment mating profile with 180° outlet direction and touch protection for HP networks.

- PUSH IN spring connection
- Pitch: 7.62 mm
- Number of poles: 2-12
- IEC: 1,000 V / 24 A / 0.5-2.5 mm²
- UL: 600 V / 20 A / AWG 20-12




Webcode #01136

**BLL 7.62HP**

Touch-safe female header with single compartment mating profile for the PCB with one-hand safety interlock.

- Female header
- Pitch: 7.62 mm
- Number of poles: 2-5
- IEC: 630 V / 24 A
- UL: 300 V / 20 A

OMNIMATE® Power HP pitch 10 mm²




Webcode #11473

**SV-SMT 7.62HP**

High temperature-resistant single-row male header for pole-loss-safe attachment or for use with patented multi-function flanges for TNC(S) networks.

- Male header
- Pitch: 7.62 mm
- Number of poles: 2-5
- IEC: 1,000 V / 41 A
- UL: 300 V / 40.5 A




Webcode #01142

**SV 7.62HP**

High-performance single-row male header for pole-loss-safe attachment or for use with patented multi-function flanges for TNC(S) networks.

- Male header
- Pitch: 7.62 mm
- Number of poles: 2-12
- IEC: 1,000 V / 41 A
- UL: 300 V / 40.5 A




Webcode #11474

**SVD 7.62HP**

Double-row high-current, high-performance pin headers for pole-loss-safe attachment or for use with patented multi-function flanges for TNC(S) networks.

- Male header
- Pitch: 7.62 mm
- Number of poles: 4-12
- IEC: 1,000 V / 47 A
- UL: 300 V / 30 A




Webcode #01144

**SVZ 7.62HP**

High-performance male plug for pole-loss-safe attachment or for use with patented multi-function flanges for TNC(S) networks.

- Clamping yoke screw connection
- Pitch: 7.62 mm
- Number of poles: 2-7
- IEC: 1,000 V / 41 A / 0.2-6 mm²
- UL: 600 V / 35 A / AWG 24-10

OMNIMATE® Power HP pitch 10 mm²




Webcode #11475

**SVF 7.62HP**

High-performance male plug with 180° outlet direction as a three-flange version for the housing feedthrough for TNC(S) networks.

- PUSH IN spring connection
- Pitch: 7.62 mm
- Number of poles: 2-6
- IEC: 1,000 V / 41 A / 0.5-10 mm²
- UL: 600 V / 35 A / AWG 24-10




Webcode #11476

**SVFL 7.62HP**

High-performance male plug with 180° outlet direction as a three-flange version for the housing feedthrough for TNC(S) networks.

- Wire-Ready PUSH IN spring connection
- Pitch: 7.62 mm
- Number of poles: 2-6
- IEC: 1,000 V / 41 A / 0.5-6 mm²
- UL: 600 V / 35 A / AWG 24-10



Webcode #01138

**BVZ 7.62HP**


High-performance female plug for pole-loss-safe attachment or for use with patented multi-function flanges for TNC(S) networks.

- Clamping yoke screw connection
- Pitch: 7.62 mm
- Number of poles: 2-12
- IEC: 1,000 V / 41 A / 0.2-6 mm²
- UL: 600 V / 40.5 A / AWG 24-8




OMNIMATE® Power – PCB connectors

OMNIMATE® Power HP pitch 10 mm²




**Webcode #11477**  
**BVF 7.62HP**  
High-performance female plug with 180° outlet direction as a touch-safe solution for the power output for TNC(S) networks.

- PUSH IN spring connection
- Pitch: 7.62 mm
- Number of poles: 2-7
- IEC: 1.000 V / 41 A / 0.5-10 mm²
- UL: 600 V / 35 A / AWG 24-8




**Webcode #11478**  
**BVFL 7.62HP**  
High-performance female plug with 180° outlet direction as a touch-safe solution for the power output for TNC(S) networks.

- Wire-Ready PUSH-IN spring connection
- Pitch: 7.62 mm
- Number of poles: 2-5
- IEC: 1.000 V / 41 A / 0.5-6 mm²
- UL: 600 V / 35 A / AWG 24-8



**Webcode #11512**  
**BVDF 7.62HP**  
Bus connector with two connections per pole with the time-saving 6mm² PUSH IN connection system


- Female header
- Pitch: 7.62 mm
- Number of Poles: 2-8
- IEC: 600 V / 46 A / 0.5 - 10 mm²
- UL: 600 V / 35 A / AWG 24 - AWG 8



**Webcode #01148**  
**BVL 7.62HP**  
High-performance female header for pole-loss-safe attachment or for use with patented multi-function flanges for TNC(S) networks.


- Female header
- Pitch: 7.62 mm
- Number of poles: 2-7
- IEC: 1.000 V / 41 A
- UL: 300 V / 35 A

OMNIMATE® Power HP pitch 10.16 mm²




**Webcode #01152**  
**SU 10.16HP**  
High-performance single-row male header for pole-loss-safe attachment or for use with patented multi-function flanges for TNC(S) networks.

- Male header
- Pitch: 10.16 mm
- Number of poles: 2-9
- IEC: 1.000 V / 76 A
- UL: 300 V / 60 A




**Webcode #01154**  
**SUZ 10.16HP**  
High-performance male plug with 180° outlet direction and high-strength contact system for TNC(S) networks.

- Clamping yoke screw connection
- Pitch: 10.16 mm
- Number of poles: 2-9
- IEC: 1.000 V / 78 A / 0.2-16 mm²
- UL: 600 V / 54 A / AWG 24-6



**Webcode #01150**  
**BUZ 10.16HP**  
High-performance female plug with 180° outlet direction for pole-loss-safe attachment or for use with patented multi-function flanges for TNC(S) networks.


- Clamping yoke screw connection
- Pitch: 10.16 mm
- Number of poles: 2-9
- IEC: 1.000 V / 78 A / 0.2-16 mm²
- UL: 600 V / 60 A / AWG 22-4



**Webcode #01156**  
**BUL 10.16HP**  
High-performance female header with 180° outlet direction and high-strength contact system for TNC(S) networks.

- Female header
- Pitch: 10.16 mm
- Number of poles: 2-4
- IEC: 1.000 V / 76 A
- UL: 300 V / 57 A


PUSH IN spring connection



**Webcode #01158**  
**PGK**  
Device feedthrough terminal blocks with disc design and intuitive locking for a quick and compact solution.

- PUSH IN spring connection
- Connection cross-section: up to 4 mm²
- IEC: 500 V / 32 A / 0.5-4 mm²
- UL: 300 V / 30 A / AWG 24-10


Clamping yoke screw connection



**Webcode #01160**  
**WGK**  
High-current feed-through terminals as a universal solution to guide currents of various scales through the device wall.

- Clamping yoke screw connection
- Connection cross-section: 6 to 95 mm²
- IEC: 1.000 V / 232 A / 0.5-95 mm²
- UL: 600 V / 230 A / AWG 24-4/0


Accessories



**Webcode #11463**  
**Accessories**  
For Power feed-through terminals


OMNIMATE® Power – PCB- connector cross connection / DC - link

OMNIMATE® Power- Powerbus and T-connector



**Webcode #11513**  
**PB 160**  
Modular current bar solution, for multi-axis servo amplifiers intermediate circuit and 24 V control voltage supply.

- Modular SNAP-IN bus system
- Tool less connection
- Number of poles: 2
- IEC: 1000 V / 160 A
- UL: 750 V dc / 160 A



**Webcode #11512**  
**BVDF 7.62HP**  
Bus connector with two connections per pole with the time-saving 6 mm² PUSH IN connection system.

- Female header
- Pitch: 7.62 mm
- Number of Poles: 2-8
- IEC: 600 V / 46 A / 0.5 -10 mm²
- UL: 600 V / 35 A / AWG 24 - AWG 8

# Shape design-in processes in a uniquely efficient way

## Our services make sure you get perfect results


They develop connection systems for PCBs and devices based on the final application. Our specialists will gladly provide you with really concrete support with your design-in process, with expertise, advice and a range of useful services.

Our design-in application specialists know your working environment intimately and will support you from the specifications stage right through to series production of your individual solution. Not only will you benefit from our OMNIMATE® services such as the product configurator with 3D models available for download, or the unparalleled 72-hour sample service for your free design-in samples; you'll also have access to a wide range of additional services designed to make your day-to-day work quicker, easier and more professional.



**Webcode #01163**  
**72-hour sample service**

Just order your design-in samples, quickly and easily. Make the most of the free 72-hour sample service for OMNIMATE®. Wherever you're situated, we always keep our word and deliver your samples to the desired location within 72 hours.



**Webcode #01201**  
**Webinars on practical issues**

Exciting online seminars on relevant issues relating to device connection systems will help you with the practical aspects of your project. All webinar services are free of charge. You can find out dates, topics and presenters quickly and easily using the corresponding webcode.



**Webcode #11359**  
**Whitepaper**

We share our expertise: Find out detailed information and interesting facts about trend topics in the field of device connectivity in our Whitepaper section.



**Safe and easy product handling**

A QR code on the product and the outer packaging leads directly to the corresponding handling video. The individual installation steps can be followed directly during processing.




**On-site advice by application specialists**

We develop connection systems for PCBs and devices based on the application. And if you can involve us in your development at an early stage – even better. As part of our personal on-site customer consultancy service, our application specialists will meet with your technicians to discuss questions and problems relating to your project.




**Ready-to-connect cables for every requirement**

From pre-assembled cabling solutions to bespoke special cables, ensuring reliable and efficient connections is a challenging task. We support you with our demand-oriented assembly services to handle even the most complex of cabling tasks.




**Webcode #01203**  
**Component library for electronic PCB design**

Switching symbols and the painstaking creation of footprints are now things of the past. We offer extensive component libraries of OMNIMATE® PCB terminals and PCB connectors for a wide range of different EDA systems. Simply download and import the data set and you're ready to go.



**b2b.partcommunity.com**  
**CAD models in the Part Community**

CAD models for our OMNIMATE® PCB connection systems can be found in one of the industry's most important online forums. The "Part Community" allows engineers and technicians to trade knowledge on technical topics in all fields. The Community's online catalogue contains the exact dimensions and all other relevant data for our products.



**Webcode #11347**  
**Technical information**

The OMNIMATE® device connection methodology is highly flexible, ensuring your application requirements are met. The more familiar you are with it, the easier it is to find the optimum component.



**Online and personal support**

From planning through installation to operation, we can provide exactly the right help and information for each step of your application based on our solutions and products: up-to-date, uncomplicated and comprehensive, around the clock, online or in person.



Visit our website  
for more information  
**[www.weidmuller.com/service](http://www.weidmuller.com/service)**



## **Weidmüller – Your partner in Industrial Connectivity**

As experienced experts we support our customers and partners around the world with products, solutions and services in the industrial environment of power, signal and data. We are at home in their industries and markets and know the technological challenges of tomorrow. We are therefore continuously developing innovative, sustainable and useful solutions for their individual needs. Together we set standards in Industrial Connectivity.

We cannot guarantee that there are no mistakes in the publications or software provided by us to the customer for the purpose of making orders. We try our best to quickly correct errors in our printed media.

All orders are based on our general terms of delivery, which can be reviewed on the websites of our group companies where you place your order. On demand we can also send the general terms of delivery to you.

Weidmüller Interface GmbH & Co. KG  
Klingenbergstraße 16  
32758 Detmold, Germany  
T +49 5231 14-0  
F +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

Personal support can  
be found on our website:  
[www.weidmueller.com/contact](http://www.weidmueller.com/contact)

Made in Germany



Order number: 2811880000/03/2021/SMM